

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: **P093**
Version: **GHS 1.0 en**

date of compilation: 2021-08-11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance **Ammonia solution 30-33 %, extra pure**
Article number **P093**
CAS number **[1336-21-6]**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: **Laboratory chemical
Laboratory and analytical use**

Uses advised against: **Do not use for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).**

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: **Department Health, Safety and Environment**

e-mail (competent person): **sicherheit@carlroth.de**

1.4 Emergency telephone number

| Name | Street | Postal code/city | Telephone | Website |
|--|-----------------|--------------------|-----------|---------|
| NSW Poisons Information Centre Childrens Hospital | Hawkesbury Road | 2145 Westmead, NSW | 131126 | |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

| Section | Hazard class | Category | Hazard class and category | Hazard statement |
|---------|---|----------|---------------------------|------------------|
| 2.16 | Substance or mixture corrosive to metals | 1 | Met. Corr. 1 | H290 |
| 3.2 | Skin corrosion/irritation | 1C | Skin Corr. 1C | H314 |
| 3.3 | Serious eye damage/eye irritation | 1 | Eye Dam. 1 | H318 |
| 3.8R | Specific target organ toxicity - single exposure (respiratory tract irritation) | 3 | STOT SE 3 | H335 |

For full text of abbreviations: see SECTION 16

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS05, GHS07



Hazard statements

H290 May be corrosive to metals
H314 Causes severe skin burns and eye damage
H335 May cause respiratory irritation

Precautionary statements

Precautionary statements - prevention

P260 Do not breathe dusts or mists
P280 Wear eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P390 Absorb spillage to prevent material damage

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Hazardous ingredients for labelling: Ammonia ...%

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

| Name of substance | Identifier | Wt% | Classification acc. to GHS | Pictograms | Notes |
|-------------------|---------------------|-----------|---|------------|-------|
| Ammonia ...% | CAS No 1336-21-6 | 30 - < 35 | Skin Corr. 1C / H314 Eye Dam. 1 / H318 STOT SE 3 / H335 | | B(a) |

Notes

B(a): The classification refers to an aqueous solution

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Risk of blindness, Gastric perforation, Risk of serious damage to eyes, Irritation, Cough, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

Ammonia solution 30-33 %, extra pure

article number: P093

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. The product itself does not burn.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO_x)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use extractor hood (laboratory). Handle and open container with care. Provision of sufficient ventilation. Clear contaminated areas thoroughly.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

| Country | Name of agent | CAS No | Identifier | TWA [ppm] | TWA [mg/m ³] | STEL [ppm] | STEL [mg/m ³] | Ceiling-C [ppm] | Ceiling-C [mg/m ³] | Notation | Source |
|---------|---------------|-----------|------------|-----------|--------------------------|------------|---------------------------|-----------------|--------------------------------|----------|--------|
| AU | ammonia | 7664-41-7 | WES | 25 | 17 | 35 | 24 | | | | WES |

Notation

Ceiling-C
STEL

Ceiling value is a limit value above which exposure should not occur
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

| Relevant DNELs of components of the mixture | | | | | | |
|---|-----------|-----------|------------------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | End-point | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| Ammonia ...% | 1336-21-6 | DNEL | 47.6 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| Ammonia ...% | 1336-21-6 | DNEL | 47.6 mg/m ³ | human, inhalatory | worker (industry) | acute - systemic effects |
| Ammonia ...% | 1336-21-6 | DNEL | 14 mg/m ³ | human, inhalatory | worker (industry) | chronic - local effects |
| Ammonia ...% | 1336-21-6 | DNEL | 36 mg/m ³ | human, inhalatory | worker (industry) | acute - local effects |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

| Relevant DNELs of components of the mixture | | | | | | |
|---|-----------|-----------|------------------|------------------------------------|-------------------|----------------------------|
| Name of substance | CAS No | End-point | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| Ammonia ...% | 1336-21-6 | DNEL | 6.8 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |
| Ammonia ...% | 1336-21-6 | DNEL | 6.8 mg/kg bw/day | human, dermal | worker (industry) | acute - systemic effects |

| Relevant PNECs of components of the mixture | | | | | | |
|---|-----------|-----------|-----------------|-------------------|---------------------------|------------------------------|
| Name of substance | CAS No | End-point | Threshold level | Organism | Environmental compartment | Exposure time |
| Ammonia ...% | 1336-21-6 | PNEC | 0.001 mg/l | aquatic organisms | freshwater | short-term (single instance) |
| Ammonia ...% | 1336-21-6 | PNEC | 0.001 mg/l | aquatic organisms | marine water | short-term (single instance) |

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection. Wear face protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

• material thickness

>0,3 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: **P093**

- **Splash protection - Protective gloves**
- type of material: NBR (Nitrile rubber)
- material thickness: >0,11 mm
- breakthrough times of the glove material: >240 minutes (permeation: level 5)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: K (against ammonia and organic ammonia derivatives, colour code: Green).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---|
| Physical state | liquid |
| Colour | colourless - light yellow |
| Odour | stinging - like ammonia |
| Melting point/freezing point | -92 °C |
| Boiling point or initial boiling point and boiling range | 24 °C at 1,013 hPa |
| Flammability | non-combustible |
| Lower and upper explosion limit | 16 vol% - 30 vol% |
| Flash point | not determined |
| Auto-ignition temperature | 630 °C |
| Decomposition temperature | not relevant |
| pH (value) | >12 |
| Kinematic viscosity | not determined |
| <u>Solubility(ies)</u> | |
| Water solubility | miscible in any proportion |
| <u>Partition coefficient</u> | |
| Partition coefficient n-octanol/water (log value): | -1.38 (calculated value) not relevant (inorganic) |
| Vapour pressure | 837 hPa at 20 °C |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: **P093**

| | |
|--------------------------------|---|
| Density | 0.88 g/cm ³ at 20 °C |
| Relative vapour density | information on this property is not available |
| Particle characteristics | not relevant (liquid) |
| <u>Other safety parameters</u> | |
| Oxidising properties | none |

9.2 Other information

Information with regard to physical hazard classes:

Corrosive to metals category 1: corrosive to metals

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: Aldehydes, Chlorine, Chlorates, Fluorine, Halogenated hydrocarbons, Oxidisers, Perchlorates, Phosphorus oxides (e.g. P₂O₅), Mercury, Nitric acid, Acid chlorides, inorganic, Oxygen, Strong acid, Chromium(VI) oxide, Hydrogen peroxide,
=> Explosive properties

10.4 Conditions to avoid

Keep away from heat.

10.5 Incompatible materials

different metals, copper, iron, zinc

Release of flammable materials with

Metals, Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: **P093**

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea

• If on skin

causes severe burns, causes poorly healing wounds

• Other information

none

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

| Aquatic toxicity (chronic) of components of the mixture | | | | | |
|---|-----------|----------|------------|---------|---------------|
| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
| Ammonia ...% | 1336-21-6 | EC50 | 2,700 mg/l | algae | 18 d |

Biodegradation

Not readily biodegradable. The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

Properties of waste which render it hazardous

H8 Corrosives
H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

| | |
|----------------|------------|
| UN RTDG | UN 2672 |
| IMDG-Code | UN 2672 |
| ICAO-TI | UN 2672 |

14.2 UN proper shipping name

| | |
|----------------|------------------|
| UN RTDG | AMMONIA SOLUTION |
| IMDG-Code | AMMONIA SOLUTION |
| ICAO-TI | Ammonia solution |

14.3 Transport hazard class(es)

| | |
|----------------|---|
| UN RTDG | 8 |
| IMDG-Code | 8 |
| ICAO-TI | 8 |

14.4 Packing group

| | |
|----------------|-----|
| UN RTDG | III |
| IMDG-Code | III |
| ICAO-TI | III |

14.5 Environmental hazards

| | |
|--|--------------------------------------|
| | hazardous to the aquatic environment |
| Environmentally hazardous substance (aquatic environment): | Ammonia ...% |

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport information National regulations Additional information (UN RTDG)

| | |
|------------------------------|---|
| UN number | 2672 |
| Class | 8 |
| Environmental hazards | Yes Hazardous to the aquatic environment |
| Packing group | III |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

Danger label(s)

8
Fish and tree



Special provisions (SP)

-
UN RTDG

Excepted quantities (EQ)

E1
UN RTDG

Limited quantities (LQ)

5 L
UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name

AMMONIA SOLUTION

Particulars in the shipper's declaration

UN2672, AMMONIA SOLUTION, 8, III, MARINE POLLUTANT

Marine pollutant

yes (P) (hazardous to the aquatic environment), (Ammonia ...%)

Danger label(s)

8, "Fish and tree"



Special provisions (SP)

-

Excepted quantities (EQ)

E1

Limited quantities (LQ)

5 L

EmS

F-A, S-B

Stowage category

A

Segregation group

18 - Alkalis

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name

Ammonia solution

Particulars in the shipper's declaration

UN2672, Ammonia solution, 8, III

Environmental hazards

yes (hazardous to the aquatic environment)

Danger label(s)

8



Special provisions (SP)

A64

Excepted quantities (EQ)

E1

Limited quantities (LQ)

1 L

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

National inventories

| Country | Inventory | Status |
|---------|------------|--------------------------------|
| AU | AICS | all ingredients are listed |
| CA | DSL | all ingredients are listed |
| CN | IECSC | all ingredients are listed |
| EU | ECSI | all ingredients are listed |
| EU | REACH Reg. | all ingredients are listed |
| JP | CSCL-ENCS | all ingredients are listed |
| KR | KECI | all ingredients are listed |
| MX | INSQ | all ingredients are listed |
| NZ | NZIoC | all ingredients are listed |
| PH | PICCS | all ingredients are listed |
| TR | CICR | not all ingredients are listed |
| TW | TCSI | all ingredients are listed |
| US | TSCA | all ingredients are listed |

Legend

| | |
|------------|---|
| AICS | Australian Inventory of Chemical Substances |
| CICR | Chemical Inventory and Control Regulation |
| CSCL-ENCS | List of Existing and New Chemical Substances (CSCL-ENCS) |
| DSL | Domestic Substances List (DSL) |
| ECSI | EC Substance Inventory (EINECS, ELINCS, NLP) |
| IECSC | Inventory of Existing Chemical Substances Produced or Imported in China |
| INSQ | National Inventory of Chemical Substances |
| KECI | Korea Existing Chemicals Inventory |
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances (PICCS) |
| REACH Reg. | REACH registered substances |
| TCSI | Taiwan Chemical Substance Inventory |
| TSCA | Toxic Substance Control Act |

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: P093

SECTION 16: Other information

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|-------------|--|
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| Ceiling-C | Ceiling value |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| ELINCS | European List of Notified Chemical Substances |
| EmS | Emergency Schedule |
| Eye Dam. | Seriously damaging to the eye |
| Eye Irrit. | Irritant to the eye |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| MARPOL | International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant") |
| NLP | No-Longer Polymer |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| Skin Corr. | Corrosive to skin |
| Skin Irrit. | Irritant to skin |
| STEL | Short-term exposure limit |
| STOT SE | Specific target organ toxicity - single exposure |
| TWA | Time-weighted average |
| UN RTDG | UN Recommendations on the Transport of Dangerous Good |
| vPvB | Very Persistent and very Bioaccumulative |
| WES | Safe Work Australia: Workplace exposure standards for airborne conatminants |

Key literature references and sources for data

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ammonia solution 30-33 %, extra pure

article number: **P093**

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

| Code | Text |
|------|--|
| H290 | May be corrosive to metals. |
| H314 | Causes severe skin burns and eye damage. |
| H318 | Causes serious eye damage. |
| H335 | May cause respiratory irritation. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.