

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: **0840**  
Version: **GHS 3.0 en**  
Replaces version of: 2020-09-01  
Version: (GHS 2)

date of compilation: 2018-09-06  
Revision: 2022-01-27

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance **n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH**  
Article number 0840  
CAS number 110-54-3

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical  
Laboratory and analytical use  
Uses advised against: Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0  
**Telefax:** +49 (0) 721 - 56 06 149  
**e-mail:** sicherheit@carlroth.de  
**Website:** www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** **sicherheit@carlroth.de**

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.7	Reproductive toxicity	2	Repr. 2	H361f
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labelling

#### Signal word

**Danger**

#### Pictograms

GHS02, GHS07,  
GHS08



#### Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361f	Suspected of damaging fertility
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled)

#### Precautionary statements

##### **Precautionary statements - prevention**

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P260	Do not breathe dust/fume/gas/mist/vapours/spray

##### **Precautionary statements - response**

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of soap and water
P331	Do NOT induce vomiting
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

##### **Precautionary statements - storage**

P403+P233	Store in a well-ventilated place. Keep container tightly closed
P403+P235	Store in a well-ventilated place. Keep cool

For professional users only

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

## 2.3 Other hazards

### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Name of substance	n-Hexane
Molecular formula	C <sub>6</sub> H <sub>14</sub>
Molar mass	86.18 g/mol
CAS No	110-54-3

## SECTION 4: First aid measures

### 4.1 Description of first aid measures



#### General notes

Take off contaminated clothing.

#### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

#### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

### 4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis

### 4.3 Indication of any immediate medical attention and special treatment needed

none

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### Ventilation requirements

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
AU	n-hexane	110-54-3	WES	20	72						WES

#### Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	75 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

## 8.2 Exposure controls

### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

#### Skin protection



#### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

NBR (Nitrile rubber)

#### • material thickness

≥0,4 mm

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	like: - Gasoline
Melting point/freezing point	-95 °C at 1,013 hPa (ECHA)
Boiling point or initial boiling point and boiling range	68 – 69 °C at 1,013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1.1 vol% (LEL) - 7.5 vol% (UEL)
Flash point	-22 °C at 1,013 hPa (ECHA)
Auto-ignition temperature	225 °C (ECHA)
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	0.5 mm <sup>2</sup> /s at 20 °C
<u>Solubility(ies)</u>	
Water solubility	<0.1 g/l at 20 °C
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	4 (pH value: 7, 20 °C) (ECHA)
Soil organic carbon/water (log KOC)	3.34 (ECHA)
Vapour pressure	160 hPa at 20 °C

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

### Density and/or relative density

Density 0.66 g/cm<sup>3</sup> at 20 °C

Relative vapour density 2.79 (air = 1)

Particle characteristics not relevant (liquid)

### Other safety parameters

Oxidising properties none

## 9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics: There is no additional information.

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

#### **If heated**

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Chlorine, Iodine, Peroxides, Nitrogen oxides (NO<sub>x</sub>),  
=> Explosive properties

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

Rubber articles, different plastics

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### **Classification acc. to GHS**

#### **Acute toxicity**

Shall not be classified as acutely toxic.



# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
inhalation: vapour	LC50	185 mg/l/4h	rat		TOXNET
oral	LD50	25,000 mg/kg	rat		TOXNET
dermal	LD50	>2,000 mg/kg	rabbit		ECHA

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Suspected of damaging fertility.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).

Hazard category	Target organ	Exposure route
2	nervous system	if inhaled

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

nausea, vomiting, aspiration hazard

#### • If in eyes

slightly irritant but not relevant for classification

#### • If inhaled

irritant effects, headache, vertigo, fatigue, dizziness, narcosis

#### • If on skin

causes skin irritation

#### • Other information

none

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

## 11.2 Endocrine disrupting properties

Not listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LL50	12.51 mg/l	fish	ECHA	96 h
EL50	21.85 mg/l	aquatic invertebrates	ECHA	48 h

### Biodegradation

The substance is readily biodegradable.

### 12.2 Process of degradability

Theoretical Oxygen Demand: 3.527 mg/mg  
Theoretical Carbon Dioxide: 3.064 mg/mg

Process of degradability		
Process	Degradation rate	Time
oxygen depletion	83 %	10 d

### 12.3 Bioaccumulative potential

The substance fulfils the very bioaccumulative criterion.

n-octanol/water (log KOW)	4 (pH value: 7, 20 °C) (ECHA)
BCF	501.2 (ECHA)

### 12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	3.34 (ECHA)
--	-------------

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Not listed.

### 12.7 Other adverse effects

Data are not available.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### Relevant provisions relating to waste(Basel Convention)

#### Properties of waste which render it hazardous

H3 Flammable liquids  
H11 Toxic (Delayed or chronic)

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## SECTION 14: Transport information

### 14.1 UN number

UN RTDG	UN 1208
IMDG-Code	UN 1208
ICAO-TI	UN 1208

### 14.2 UN proper shipping name

UN RTDG	HEXANES
IMDG-Code	HEXANES
ICAO-TI	Hexanes

### 14.3 Transport hazard class(es)

UN RTDG	3
IMDG-Code	3
ICAO-TI	3

### 14.4 Packing group

UN RTDG	II
IMDG-Code	II
ICAO-TI	II

### 14.5 Environmental hazards

hazardous to the aquatic environment

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

#### Transport information National regulations Additional information (UN RTDG)

UN number	1208
Class	3
Environmental hazards	Yes Hazardous to the aquatic environment
Packing group	II
Danger label(s)	3 Fish and tree



Special provisions (SP)	- UN RTDG
Excepted quantities (EQ)	E2 UN RTDG
Limited quantities (LQ)	1 L UN RTDG

#### International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	HEXANES
Particulars in the shipper's declaration	UN1208, HEXANES, 3, II, -22°C c.c., MARINE POLLUTANT
Marine pollutant	yes (P) (hazardous to the aquatic environment)
Danger label(s)	3, "Fish and tree"



Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	E

# Safety data sheet Safety data sheet


acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Hexanes
Particulars in the shipper's declaration	UN1208, Hexanes, 3, II
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	3
	
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

#### National regulations(Australia)

##### Australian Inventory of Chemical Substances(AICS)

Substance is listed.

#### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

#### Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

### Legend

ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Narcotic effects.	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

### Abbreviations and acronyms

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: 0840

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## n-Hexane ROTISOLV® ≥99 %, MOSH/MOAH

article number: **0840**

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.