

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: **1652**

Version: **GHS 3.0 en**

Replaces version of: 2018-11-27

Version: (GHS 2)

date of compilation: 2017-06-23

Revision: 2022-10-10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance

Liquid butane UNIVERSAL REFILL GAS

Article number

1652

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Laboratory chemical
Laboratory and analytical use

Uses advised against:

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.2	Flammable gas	1A	Flam. Gas 1A	H220
2.5	Gas under pressure	L	Press. Gas L	H280

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Contains gas under pressure; may explode if heated.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS02, GHS04



Hazard statements

H220

Extremely flammable gas

H280

Contains gas under pressure; may explode if heated

Precautionary statements

Precautionary statements - prevention

P210

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary statements - response

P377

Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381

Eliminate all ignition sources if safe to do so

Precautionary statements - storage

P410+P403

Protect from sunlight. Store in a well-ventilated place

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub-stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
butane	CAS No 106-97-8	40	Flam. Gas 1A / H220		C(a) U
Propane	CAS No 74-98-6	30	Flam. Gas 1A / H220		U(a)
isobutane	CAS No 75-28-5	30	Flam. Gas 1A / H220		C(a) U

Notes

C(a): Mixture of isomers

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Notes

- U(a): The allocation to the group 'gases under pressure' of the hazard class is based on the physical state in which the gas is packaged
- U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, dry extinguishing powder, BC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. Contact with the product can cause burns and/or frostbite. Risk of vapour cloud explosion in case of evaporation or release. Contains gas under pressure; may explode if heated.

Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

No special measures are necessary.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

Liquid butane UNIVERSAL REFILL GAS

article number: 1652

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun-try	Name of agent	CAS No	Identifi-er	TWA [mg/m ³]	STEL [mg/m ³]	Ceil-ing-C [mg/m ³]	Nota-tion	Source
AU	butane	106-97-8	WES	1,900				WES

Notation

Ceiling-C
STEL Ceiling value is a limit value above which exposure should not occur
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

• material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)


• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Respiratory protection



Respiratory protection necessary at:

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	gaseous
Form	liquefied
Colour	colourless
Odour	characteristic
Melting point/freezing point	-187.6 °C at 1,013 hPa
Boiling point or initial boiling point and boiling range	not determined
Flammability	flammable gas in accordance with GHS criteria
Lower and upper explosion limit	31 g/m ³ (LEL) - 210 g/m ³ (UEL) / 5 vol% (LEL) - 15 vol% (UEL)
Flash point	not determined
Auto-ignition temperature	537 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not relevant
<u>Solubility(ies)</u>	
Water solubility	not determined
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	this information is not available
Vapour pressure	2.73 bar at 20 °C
<u>Density and/or relative density</u>	
Density	0.56 g/cm ³
Relative vapour density	not relevant Gaseous
Particle characteristics	not relevant (gaseous)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes:

Flammable gases

Explosion limits 5 vol% - 15 vol%

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

If heated

Danger of explosion. Gas under pressure. Danger of bursting container.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Liquid butane UNIVERSAL REFILL GASarticle number: **1652****Respiratory or skin sensitisation**

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics**• If swallowed**

Data are not available.

• If in eyes

Data are not available.

• If inhaled

headache, vertigo, drowsiness, dizziness

• If on skin

Data are not available.

• Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information**12.1 Toxicity**

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture					
Name of sub-stance	CAS No	Endpoint	Value	Species	Exposure time
butane	106-97-8	LC50	49.9 mg/l	fish	96 h
butane	106-97-8	EC50	19.37 mg/l	algae	96 h
isobutane	75-28-5	LC50	49.9 mg/l	fish	96 h
isobutane	75-28-5	EC50	19.37 mg/l	algae	96 h

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Propane	74-98-6	LC50	49.9 mg/l	fish	96 h
Propane	74-98-6	EC50	19.37 mg/l	algae	96 h

Biodegradation

The relevant substances of the mixture are readily biodegradable.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1.09 (pH value: 7, 20 °C)	
isobutane	75-28-5		1.09 (pH value: 7, 20 °C)	
Propane	74-98-6		1.09 (pH value: 7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 2037
IMDG-Code	UN 2037
ICAO-TI	UN 2037

14.2 UN proper shipping name

UN RTDG	RECEPTACLES, SMALL, CONTAINING GAS
IMDG-Code	RECEPTACLES, SMALL, CONTAINING GAS
ICAO-TI	Receptacles, small, containing gas

14.3 Transport hazard class(es)

UN RTDG	2.1
IMDG-Code	2.1
ICAO-TI	2.1

14.4 Packing group

not assigned

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number	2037
Class	2.1
Danger label(s)	2.1



Special provisions (SP)	191, 277, 303, 344 UN RTDG
Excepted quantities (EQ)	E0 UN RTDG
Limited quantities (LQ)	1 L UN RTDG

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	RECEPTACLES, SMALL, CONTAINING GAS
Particulars in the shipper's declaration	UN2037, RECEPTACLES, SMALL, CONTAINING GAS, 2.1
Marine pollutant	-
Danger label(s)	2.1



Special provisions (SP)	191, 277, 303, 344
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Receptacles, small, containing gas
Particulars in the shipper's declaration	UN2037, Receptacles, small, containing gas, 2.1
Danger label(s)	2.1



Special provisions (SP)	A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Contains gas under pressure; may explode if heated.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Precautionary statements - storage: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Gas	Flammable gas
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Abbr.	Descriptions of used abbreviations
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.