

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: **1652**

Version: **3.0 en**

Replaces version of: 2018-11-27

Version: (2)

date of compilation: 2017-06-23

Revision: 2022-10-10

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance **Liquid butane UNIVERSAL REFILL GAS**

Article number 1652

Registration number (REACH) not relevant (mixture)

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical  
Laboratory and analytical use

Uses advised against: Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:** +49 (0) 721 - 56 06 0

**Telefax:** +49 (0) 721 - 56 06 149

**e-mail:** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

**Website:** [www.carlroth.de](http://www.carlroth.de)

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

**e-mail (competent person):** [sicherheit@carlroth.de](mailto:sicherheit@carlroth.de)

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Centre Beaumont Hospital	Beaumont Road	Dublin 9	01 809 2166	<a href="https://www.poisons.ie/">https://www.poisons.ie/</a>

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.2	Flammable gas	1A	Flam. Gas 1A	H220
2.5	Gas under pressure	C	Press. Gas C	H280

For full text of abbreviations: see SECTION 16

**The most important adverse physicochemical, human health and environmental effects**

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Contains gas under pressure; may explode if heated.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008 (CLP)

##### Signal word

**Danger**

##### Pictograms

GHS02, GHS04



##### Hazard statements

H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated

##### Precautionary statements

###### Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
------	---

###### Precautionary statements - response

P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely
P381	In case of leakage, eliminate all ignition sources

###### Precautionary statements - storage

P403	Store in a well-ventilated place
P410+P403	Protect from sunlight. Store in a well-ventilated place

#### Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)



H220	Extremely flammable gas.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P377	Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381	In case of leakage, eliminate all ignition sources.
P403	Store in a well-ventilated place.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

not relevant (mixture)

#### 3.2 Mixtures

##### Description of the mixture

Name of sub-stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
butane	CAS No 106-97-8  EC No 203-448-7  Index No 601-004-00-0	40	Flam. Gas 1A / H220		C(a) GHS-HC U
Propane	CAS No 74-98-6  EC No 200-827-9  Index No 601-003-00-5	30	Flam. Gas 1A / H220		GHS-HC U(a)
isobutane	CAS No 75-28-5  EC No 200-857-2  Index No 601-004-00-0	30	Flam. Gas 1A / H220		C(a) GHS-HC U

##### Notes

C(a): Mixture of isomers

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

U(a): The allocation to the group 'gases under pressure' of the hazard class is based on the physical state in which the gas is packaged

U: When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

For full text of abbreviations: see SECTION 16

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures



##### General notes

Take off contaminated clothing.

##### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

### Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, dry extinguishing powder, BC-powder

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. Contact with the product can cause burns and/or frostbite. Risk of vapour cloud explosion in case of evaporation or release. Contains gas under pressure; may explode if heated.

#### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), May produce toxic fumes of carbon monoxide if burning.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

No special measures are necessary.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [mg/m <sup>3</sup> ]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
IE	n-butane	106-97-8	OELV					S.I. No. 619 of 2001
IE	propane	74-98-6	OELV				asphyx	S.I. No. 619 of 2001
IE	isobutane	75-28-5	OELV					S.I. No. 619 of 2001

#### Notation

asphyx  
Ceiling-C  
STEL

Simple asphyxiants

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### 8.2 Exposure controls

#### Individual protection measures (personal protective equipment)

##### Eye/face protection



Use safety goggle with side protection.

##### Skin protection



##### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

##### • type of material

NBR (Nitrile rubber)

##### • material thickness

>0,11 mm


##### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

##### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

##### Respiratory protection



Respiratory protection necessary at:

##### Environmental exposure controls

Keep away from drains, surface and ground water.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	gaseous
Form	liquefied
Colour	colourless
Odour	characteristic
Melting point/freezing point	-187,6 °C at 1.013 hPa
Boiling point or initial boiling point and boiling range	not determined
Flammability	flammable gas in accordance with GHS criteria
Lower and upper explosion limit	31 g/m <sup>3</sup> (LEL) - 210 g/m <sup>3</sup> (UEL) / 5 vol% (LEL) - 15 vol% (UEL)
Flash point	not determined
Auto-ignition temperature	537 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not relevant

#### Solubility(ies)

Water solubility	not determined
------------------	----------------

#### Partition coefficient

Partition coefficient n-octanol/water (log value):	this information is not available
--	-----------------------------------

Vapour pressure	2,73 bar at 20 °C
-----------------	-------------------

#### Density and/or relative density

Density	0,56 g/cm <sup>3</sup>
Relative vapour density	not relevant Gaseous

Particle characteristics	not relevant (gaseous)
--------------------------	------------------------

#### Other safety parameters

Oxidising properties	none
----------------------	------

#### 9.2 Other information

Information with regard to physical hazard classes:

Flammable gases

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: **1652**

Explosion limits	5 vol% - 15 vol%
Other safety characteristics:	
Temperature class (EU, acc. to ATEX)	T1 Maximum permissible surface temperature on the equipment: 450°C

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

#### If heated

Danger of explosion. Gas under pressure. Danger of bursting container.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

There is no additional information.

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification according to GHS (1272/2008/EC, CLP)

##### Acute toxicity

Shall not be classified as acutely toxic.

##### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

##### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

##### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

##### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

Data are not available.

#### • If in eyes

Data are not available.

#### • If inhaled

headache, vertigo, drowsiness, dizziness

#### • If on skin

Data are not available.

#### • Other information

none

### 11.2 Endocrine disrupting properties

None of the ingredients are listed.

### 11.3 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
butane	106-97-8	LC50	49,9 mg/l	fish	96 h
butane	106-97-8	EC50	19,37 mg/l	algae	96 h
isobutane	75-28-5	LC50	49,9 mg/l	fish	96 h
isobutane	75-28-5	EC50	19,37 mg/l	algae	96 h
Propane	74-98-6	LC50	49,9 mg/l	fish	96 h

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Propane	74-98-6	EC50	19,37 mg/l	algae	96 h

### Biodegradation

The relevant substances of the mixture are readily biodegradable.

### 12.2 Process of degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
butane	106-97-8		1,09 (pH value: 7, 20 °C)	
isobutane	75-28-5		1,09 (pH value: 7, 20 °C)	
Propane	74-98-6		1,09 (pH value: 7, 20 °C)	

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

None of the ingredients are listed.

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

### Sewage disposal-relevant information

Do not empty into drains.

### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: **1652**

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADRRID	UN 2037
IMDG-Code	UN 2037
ICAO-TI	UN 2037

### 14.2 UN proper shipping name

ADRRID	RECEPTACLES, SMALL, CONTAINING GAS
IMDG-Code	RECEPTACLES, SMALL, CONTAINING GAS
ICAO-TI	Receptacles, small, containing gas

### 14.3 Transport hazard class(es)

ADRRID	2 (2.1)
IMDG-Code	2.1
ICAO-TI	2.1

### 14.4 Packing group

not assigned

### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name	RECEPTACLES, SMALL, CONTAINING GAS
Particulars in the transport document	UN2037, RECEPTACLES, SMALL, CONTAINING GAS, 2.1, (D)
Classification code	5F
Danger label(s)	2.1



Special provisions (SP)	191, 303, 344
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2




# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Tunnel restriction code (TRC)	D
<b>Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) Additional information</b>	
Classification code	5F
Danger label(s)	2.1
	
Special provisions (SP)	191, 303, 344
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
Transport category (TC)	2
Hazard identification No	23
<b>International Maritime Dangerous Goods Code (IMDG) - Additional information</b>	
Proper shipping name	RECEPTACLES, SMALL, CONTAINING GAS
Particulars in the shipper's declaration	UN2037, RECEPTACLES, SMALL, CONTAINING GAS, 2.1
Marine pollutant	-
Danger label(s)	2.1
	
Special provisions (SP)	191, 277, 303, 344
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 L
EmS	F-D, S-U
Stowage category	B
<b>International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information</b>	
Proper shipping name	Receptacles, small, containing gas
Particulars in the shipper's declaration	UN2037, Receptacles, small, containing gas, 2.1
Danger label(s)	2.1
	
Special provisions (SP)	A167
Excepted quantities (EQ)	E0
Limited quantities (LQ)	1 kg

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### Relevant provisions of the European Union (EU)

##### Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
butane	flammable / pyrophoric		R40	40
Propane	flammable / pyrophoric		R40	40
isobutane	flammable / pyrophoric		R40	40

##### Legend

- R40
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
    - metallic glitter intended mainly for decoration,
    - artificial snow and frost,
    - 'whoopie' cushions,
    - silly string aerosols,
    - imitation excrement,
    - horns for parties,
    - decorative flakes and foams,
    - artificial cobwebs,
    - stink bombs.
  2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:  
'For professional users only'.
  3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
  4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

#### List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

None of the ingredients are listed.

#### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P2	flammable gases	10 50	45)

##### Notation

45) Flammable gases, category 1 or 2

#### Deco-Paint Directive

VOC content	100 %
-------------	-------

#### Industrial Emissions Directive (IED)

VOC content	100 %
-------------	-------

#### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

### Water Framework Directive (WFD)

none of the ingredients are listed

### Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

### Regulation on drug precursors

none of the ingredients are listed

### Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

### Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

### Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

### National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

### Legend

TCSI Taiwan Chemical Substance Inventory  
TSCA Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Contains gas under pressure; may explode if heated.	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: 1652

Abbr.	Descriptions of used abbreviations
EmS	Emergency Schedule
Flam. Gas	Flammable gas
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
S.I. No. 619 of 2001	Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Liquid butane UNIVERSAL REFILL GAS

article number: **1652**

---

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.