according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773 date of compilation: 2016-01-12 Version: 3.0 en

Revision: 2022-04-13

Replaces version of: 2017-02-28

Version: (2)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Standard mixture of mineral oils 5 000 mg/l

Mineral oil and diesel in n-hexane

Article number 1773

Registration number (REACH) not relevant (mixture)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr, 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.6	Carcinogenicity	1B	Carc. 1B	H350

United Kingdom (en) Page 1 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.7	Reproductive toxicity	2	Repr. 2	H361f
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

Pictograms

GHS02, GHS07, GHS08, GHS09









Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H350	May cause cancer
H361f	Suspected of damaging fertility
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled)
H411	Toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, sparks, open flames, hot surfaces. No smoking
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection/hear-ing protection

Precautionary statements - response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor
P308+P313	IF exposed or concerned: Get medical advice/attention
P331	Do NOT induce vomiting

United Kingdom (en) Page 2 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773

For professional users only

Hazardous ingredients for labelling: n-Hexane, Lubricating oils

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Symbol(s)







H304 May be fatal if swallowed and enters airways.

May cause cancer. H350

H361f Suspected of damaging fertility.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting. contains: n-Hexane, Lubricating oils

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 **Substances**

not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
n-Hexane	CAS No 110-54-3 EC No 203-777-6 Index No 601-037-00-0 REACH Reg. No 01-2119480412- 44-xxxx	≥ 50	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361f STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411		GHS-HC IOELV
Lubricating oils	CAS No 74869-22-0 EC No 278-012-2 Index No 649-484-00-0	0,3 - < 1	Carc. 1B / H350		GHS-HC L(a)

Notes

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/

2008/EC, Annex VI)
Substance with a community indicative occupational exposure limit value IOELV:

The classification as a carcinogen is mandatory. The substance contains at least 3 % DMSO extract L(a):

United Kingdom (en) Page 3 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

Name of sub- stance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
n-Hexane	CAS No 110-54-3	STOT RE 2; H373: C ≥ 5 %	-	-	
	EC No 203-777-6				
	Index No 601-037-00-0				
Lubricating oils	CAS No 74869-22-0	-	-	2,18 ^{mg} / _l /4h	inhalation: dust/ mist
	EC No 278-012-2				
	Index No 649-484-00-0				

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

United Kingdom (en) Page 4 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

United Kingdom (en) Page 5 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 2 - 8 °C

7.3 Specific end use(s)

No information available.

United Kingdom (en) Page 6 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	n-hexane	110-54-3	IOELV	20	72						2006/15/ EC
GB	n-hexane	110-54-3	WEL	20	72						EH40/ 2005

Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time
n-Hexane	110-54-3	DNEL	75 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
n-Hexane	110-54-3	DNEL	11 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Lubricating oils	74869-22-0	PNEC	9,33 ^{mg} / _{kg}	aquatic organ- isms	water	short-term (single instance)

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection



United Kingdom (en) Page 7 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773

hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a quide.

• type of material

NBR (Nitrile rubber)

material thickness

≥0,4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid
Colour colourless

Odour characteristic

Melting point/freezing point -95 °C at 1.013 hPa

Boiling point or initial boiling point and boiling

range

69 °C

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 1,1 vol% (LEL) - 7,5 vol% (UEL)

Flash point -26 °C Auto-ignition temperature 240 °C

Decomposition temperature not relevant

United Kingdom (en) Page 8 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

pH (value) not determined

Kinematic viscosity not determined

Solubility(ies)

Water solubility not determined

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 160 hPa at 20 °C

Density and/or relative density

Density 0,6547 ^g/_{cm³} at 20 °C

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Other safety characteristics:

Temperature class (EU, acc. to ATEX)

Maximum permissible surface temperature on

There is no additional information.

the equipment: 200°C

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Chlorine, Iodine, Peroxides, Nitrogen oxides (NOx), => Explosive properties

10.4 Conditions to avoid

United Kingdom (en) Page 9 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Lubricating oils	74869-22-0	inhalation: dust/mist	2,18 ^{mg} / _l /4h

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
n-Hexane	110-54-3	inhalation: va- pour	LC50	185 ^{mg} / _l /4h	rat
n-Hexane	110-54-3	oral	LD50	25.000 ^{mg} / _{kg}	rat
n-Hexane	110-54-3	dermal	LD50	>2.000 ^{mg} / _{kg}	rabbit
Lubricating oils	74869-22-0	oral	LD50	>5.000 ^{mg} / _{kg}	rat
Lubricating oils	74869-22-0	inhalation: dust/mist	LC50	2,18 ^{mg} / _l /4h	rat
Lubricating oils	74869-22-0	dermal	LD50	>2.000 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

United Kingdom (en) Page 10 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

Carcinogenicity

May cause cancer.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).

Hazard category	Target organ	Exposure route
2	nervous system	if inhaled

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

nausea, vomiting, aspiration hazard

• If in eyes

slightly irritant but not relevant for classification

• If inhaled

irritant effects, headache, vertigo, fatigue, dizziness, narcosis

• If on skin

causes skin irritation

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
n-Hexane	110-54-3	LL50	12,51 ^{mg} / _l	fish	96 h
n-Hexane	110-54-3	EL50	21,85 ^{mg} / _l	aquatic invertebrates	48 h

United Kingdom (en) Page 11 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

Aquatic toxicity (acute) of components of the mixture					
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Lubricating oils	74869-22-0	LL50	>100 ^{mg} / _l	fish	96 h
Lubricating oils	74869-22-0	EL50	>10.000 ^{mg} / _l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture						
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time	
Lubricating oils	74869-22-0	LL50	>10.000 ^{mg} / _l	aquatic invertebrates	24 h	
Lubricating oils	74869-22-0	EL50	>10.000 ^{mg} / _l	aquatic invertebrates	24 h	

Biodegradation

Data are not available.

12.2 Process of degradability

Degradabilit	Degradability of components of the mixture					
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
n-Hexane	110-54-3	oxygen deple- tion	83 %	10 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture					
Name of substance	CAS No	BCF	Log KOW	BOD5/COD	
n-Hexane	110-54-3	501,2	4 (pH value: 7, 20 °C)		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

United Kingdom (en) Page 12 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

IIN number or ID number

14.1	UN number or ID number	
	ADRRID	UN 1208
	IMDG-Code	UN 1208
	ICAO-TI	UN 1208
14.2	UN proper shipping name	
	ADRRID	HEXANES
	IMDG-Code	HEXANES
	ICAO-TI	Hexanes
14.3	Transport hazard class(es)	
	ADRRID	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	ADRRID	II
	IMDG-Code	II
	ICAO-TI	II
14.5	Environmental hazards	hazardous to the aquatic environment

Environmentally hazardous substance (aquatic

environment):

United Kingdom (en) Page 13 / 23

n-Hexane

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name HEXANES

Particulars in the transport document UN1208, HEXANES, 3, II, (D/E), environmentally

hazardous

Classification code F1

Danger label(s) 3, "Fish and tree"



Environmental hazards yes (hazardous to the aquatic environment)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E
Hazard identification No 33

Emergency Action Code 3YE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information

Classification code 3

Danger label(s) 3
Fish and tree



Environmental hazards Yes

Hazardous to water

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Hazard identification No 33

United Kingdom (en) Page 14 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name HEXANES

Particulars in the shipper's declaration UN1208, HEXANES, 3, II, -26°C c.c., MARINE POL-

LUTANT

Marine pollutant yes (P) (hazardous to the aquatic environment)

Danger label(s) 3, "Fish and tree"





Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category E

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Hexanes

Particulars in the shipper's declaration UN1208, Hexanes, 3, II

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)

Name of substance	Name acc. to inventory	CAS No	Restriction	No
Standard mixture of mineral oils	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3
Lubricating oils	carcinogenic		R28-30	28
n-Hexane	flammable / pyrophoric		R40	40
n-Hexane	substances in tattoo inks and perman- ent make-up		R75	75

Legend

R28-30 1. Shall not be placed on the market, or used,

- as substances,

- as constituents of other substances, or,

United Kingdom (en) Page 15 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773

Legend

for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than:

- either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, - the relevant concentration specified in Directive 1999/45/EC where no specific concentration limit is set out in Part 3 of Annex VI to Regulation (EC) No 1272/2008.

Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows:

'Restricted to professional users'.

2. By way of derogation, paragraph 1 shall not apply to:
(a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC;
(b) cosmetic products as defined by Directive 76/768/EEC;

(c) the following fuels and oil products:
- motor fuels which are covered by Directive 98/70/EC

- mineral oil products intended for use as fuel in mobile or fixed combustion plants,
- fuels sold in closed systems (e.g. liquid gas bottles);
(d) artists' paints covered by Directive 1999/45/EC;
(e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date;
(f) devices covered by Regulation (EU) 2017/745.

1 Shall not be used in:

R3 1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in orna-

mental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
2. Articles not complying with paragraph 1 shall not be placed on the market.
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they

— can be used as fuel in decorative oil lamps for supply to the general public, and
— present an aspiration hazard and are labelled with H304.

4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation

(CEN).

5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met

ments are met:

(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";

(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';

(c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.';

1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for extent signed and supply to the general public for extent signed and supply to the general public are packaged in black opaque to the general public for extent signed and supply to the general public are packaged in black opaque to the general public for extent and description purposes such as the following:

R40 for supply to the general public for entertainment and decorative purposes such as the following: - metallic glitter intended mainly for decoration,

- artificial snow and frost,

- 'whoopee' cushions,

- silly string aerosols, - imitation excrement, - horns for parties, - decorative flakes and foams,

- artificial cobwebs,

2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'.

3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).

4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

Page 16 / 23 United Kingdom (en)

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773

Legend

R75

1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:
(a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
(b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant

category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;

(c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitiser category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;

(d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:

(i) 0,1 % by weight, if the substance is used solely as a pH regulator;
(ii) 0,01 % by weight, in all other cases;
(e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
(f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:

(i) "Pierse off products":

(ii) "Rinse-off products";
(iii) "Not to be used in products applied on mucous membranes";
(iii) "Not to be used in eye products";
(g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column; (h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.

2. For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of

making a mark or design on his or her body

making a mark or design on his or her body.

3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.

4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:

(a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);

(b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).

5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such

stance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, para-

plication of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.

6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.

7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:

7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:

(a) the statement "Mixture for use in tattoos or permanent make-up";

(b) a reference number to uniquely identify the batch;

(c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;

(d) the additional statement "PH regulator" for substances falling under point (d)(i) of paragraph 1;

(e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;

(f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below the concentration limit specified in Appendix 13;

(g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No

(g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.

The information shall be clearly visible, easily legible and marked in a way that is indelible.
The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise.

Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use.

Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph. graph.

Page 17 / 23 United Kingdom (en)

according to Regulation (EC) No. 1907/2006 (REACH)

Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: **1773**

Legend

8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

None of the ingredients are listed.

Seveso Directive

2012/	2012/18/EU (Seveso III)					
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes			
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200 500	57)			

Notation

57) Hazardous to the Aquatic Environment in category Chronic 2

Deco-Paint Directive

VOC content	0,3 - <1 % 6,547 ⁹ / _l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	654,7 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Lubricating oils	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrinerelated functions in or via the aquatic environment		a)	

United Kingdom (en) Page 18 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
n-Hexane	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AICS	not all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	all ingredients are listed

United Kingdom (en) Page 19 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in nhexane

article number: 1773

Country	Inventory	Status
TW	TCSI	all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AICS CICR CSCL-ENCS DSL ECSI IECSC Australian Inventory of Chemical Substances Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS)

List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)
Korea Existing Chemicals Inventory
New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)

INSQ ISHA-ENCS KECI

NZIoC

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Narcotic effects.	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

United Kingdom (en) Page 20 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l $\,$ Mineral oil and diesel in n-hexane

article number: 1773

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code

United Kingdom (en) Page 21 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

Abbr.	Descriptions of used abbreviations
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
Repr.	Reproductive toxicity
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

United Kingdom (en) Page 22 / 23

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 5 000 mg/l Mineral oil and diesel in n-hexane

article number: 1773

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H350	May cause cancer.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 23 / 23