acc. to Safe Work Australia - Code of Practice

Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

article number: **1CYY** Version: **GHS 2.0 en** Replaces version of: 2020-07-29 Version: (GHS 1)

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### 1.1 Product identifier

Identification of the substance

Article number

## lute 2-propanol

Chrome azurol S indicator solution 0,5 % in di-

1CYY

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory and analytical use Laboratory chemical

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

#### **1.3** Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

**Telephone:**+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

#### e-mail (competent person):

#### sicherheit@carlroth.de

#### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

### Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16



date of compilation: 2020-07-29 Revision: 2022-04-11

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

#### article number: **1CYY**

### **The most important adverse physicochemical, human health and environmental effects** The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Warning

#### Pictograms

GHS02, GHS07



#### **Hazard statements**

H226	Flammable liquid and vapour
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

#### Precautionary statements

#### **Precautionary statements - prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

#### **Precautionary statements - response**

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
P312 P370+P378	lenses, if present and easy to do. Continue rinsing Call a POISON CENTER or doctor/physician if you feel unwell In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

#### **Precautionary statements - storage**

P403+P233	Store in a well-ventilated place. Keep container tightly closed
P403+P235	Store in a well-ventilated place. Keep cool

#### Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Hazardous ingredients for labelling: 2-Propanol

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

not relevant (mixture)

#### 3.2 Mixtures

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

#### article number: 1CYY

Description of the mixture									
Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes				
2-Propanol	CAS No 67-63-0	25 - 50	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336						

For full text of abbreviations: see SECTION 16

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures



#### **General notes**

Take off contaminated clothing.

#### **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

#### **Following ingestion**

Rinse mouth. Call a doctor if you feel unwell.

#### 4.2 Most important symptoms and effects, both acute and delayed

Vomiting, Irritation, Dizziness, Drowsiness, Narcosis

### 4.3 Indication of any immediate medical attention and special treatment needed

none

### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

#### article number: 1CYY

#### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO $_2$ ), May produce toxic fumes of carbon monoxide if burning.

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

#### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Provision of sufficient ventilation.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

acc. to Safe Work Australia - Code of Practice



#### article number: 1CYY

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

Conditions for safe storage, including any incompatibilities 7.2 Keep container tightly closed. Protect from sunlight.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### **Consideration of other advice:**

Ground/bond container and receiving equipment.

#### **Ventilation requirements**

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

#### 7.3 Specific end use(s)

No information available.

#### SECTION 8: Exposure controls/personal protection

#### 8.1 **Control parameters**

#### **National limit values**

#### **Occupational exposure limit values (Workplace Exposure Limits)**

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	isopropyl alcohol (propan-2-ol)	67-63-0	WES	400	983	500	1,230				WES

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur STEL

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture										
Name of sub- stanceCAS NoEnd- pointThreshol d levelProtection goal, route of exposureUsed inExposure										
2-Propanol	anol 67-63-0		500 mg/m <sup>3</sup>	human, inhalat- ory	worker (industry)	chronic - systemic effects				
2-Propanol	67-63-0	DNEL	888 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects				



acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

#### article number: 1CYY

Relevant PNECs of components of the mixture										
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time				
2-Propanol	67-63-0	PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	freshwater	short-term (single instance)				
2-Propanol	67-63-0	PNEC	140.9 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	marine water	short-term (single instance)				
2-Propanol	67-63-0	PNEC	2,251 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)				
2-Propanol	67-63-0	PNEC	552 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)				
2-Propanol	67-63-0	PNEC	552 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	marine sediment	short-term (single instance)				
2-Propanol	67-63-0	PNEC	28 <sup>mg</sup> / <sub>kg</sub>	terrestrial organ- isms	soil	short-term (single instance)				

#### 8.2 Exposure controls

#### Individual protection measures (personal protective equipment)

#### Eye/face protection



Use safety goggle with side protection.

#### **Skin protection**



#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

NBR (Nitrile rubber)

#### material thickness

0,4 mm

#### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

article number: 1CYY

#### other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

#### **Respiratory protection**



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65  $^{\circ}$ C, colour code: Brown).

#### **Environmental exposure controls**

Keep away from drains, surface and ground water.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	dark brown
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	82 °C at 1,013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	not determined
Flash point	30 °C
Auto-ignition temperature	425 °C
Decomposition temperature	not relevant
pH (value)	7
Kinematic viscosity	not determined
Solubility(ies)	
Water solubility	miscible in any proportion
Partition coefficient	
Partition coefficient n-octanol/water (log value):	
	this information is not available
	this information is not available
Vapour pressure	43 hPa at 20 °C
Vapour pressure Density and/or relative density	
Density and/or relative density	43 hPa at 20 °C

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

article number: 1CYY

Particle characteristics	not relevant (liquid)
Other safety parameters	
Oxidising properties	none
Other information	
Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	
Miscibility	completely miscible with water

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

9.2

The mixture contains reactive substance(s). Risk of ignition.

#### If heated

Risk of ignition. Vapours may form explosive mixtures with air.

#### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

#### **10.3** Possibility of hazardous reactions

**Exothermic reaction with:** strong oxidiser, Iron, Nitric acid, Strong acid, Aldehydes, Aluminium, Amines,

Danger of explosion: Chlorates, Nitro compound, Hydrogen peroxide, Phosgene

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### **10.5** Incompatible materials

plastic and rubber

#### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### **Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

#### Acute toxicity

Shall not be classified as acutely toxic.

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

article number: 1CYY

cute toxicity of components of the mixture										
Name of substance	CAS No	Exposure route	Endpoint	Value	Species					
2-Propanol	67-63-0	inhalation: va- pour	LC50	37.5 <sup>mg</sup> / <sub>l</sub> /4h	rat					
2-Propanol	67-63-0	oral	LD50	5,045 <sup>mg</sup> / <sub>kg</sub>	rat					
2-Propanol	67-63-0	dermal	LD50	12,800 <sup>mg</sup> / <sub>kg</sub>	rabbit					

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### **Respiratory or skin sensitisation**

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

#### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

vomiting, nausea

#### • If in eyes

Causes serious eye irritation

#### • If inhaled

dizziness, fatigue, narcosis

#### • If on skin

repeated exposure may cause skin dryness or cracking

#### Other information

Other adverse effects: Headache, Vertigo

### **11.2** Endocrine disrupting properties

None of the ingredients are listed.

acc. to Safe Work Australia - Code of Practice

#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol



#### article number: **1CYY**

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture					
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
2-Propanol	67-63-0	LC50	9,640 <sup>mg</sup> / <sub>l</sub>	Pimephales promelas	96 h

#### Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
2-Propanol	67-63-0	LC50	>10,000 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	24 h

#### Biodegradation

Data are not available.

#### 12.2 Process of degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
2-Propanol	67-63-0	biotic/abiotic	95 %	21 d	modifizierter OECD Screen- ing Test	
2-Propanol	67-63-0	oxygen deple- tion	53 %	5 d		ECHA

#### 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
2-Propanol	67-63-0		0.05	

#### 12.4 Mobility in soil

Data are not available.

## 12.5 Results of PBT and vPvB assessment

Data are not available.

**12.6 Endocrine disrupting properties** None of the ingredients are listed.

#### 12.7 Other adverse effects

Data are not available.

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

article number: **1CYY** 

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### Relevant provisions relating to waste(Basel Convention)

#### Properties of waste which render it hazardous

H3 Flammable liquids

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

### **SECTION 14: Transport information**

#### 14.1 UN number

1-1.1	ort number	
	UN RTDG	UN 1987
	IMDG-Code	UN 1987
	ICAO-TI	UN 1987
14.2	UN proper shipping name	
	UN RTDG	ALCOHOLS, N.O.S.
	IMDG-Code	ALCOHOLS, N.O.S.
	ICAO-TI	Alcohols, n.o.s.
	Technical name (hazardous ingredients)	2-Propanol
14.3	Transport hazard class(es)	
	UN RTDG	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	UN RTDG	III
	IMDG-Code	III
	ICAO-TI	III
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

article number: **1CYY** 

14.6	Special precautions for user			
	There is no additional information.			
14.7	Transport in bulk according to Annex II of M			
	The cargo is not intended to be carried in bulk.			
14.8 Information for each of the UN Model Regulations		ations		
	Transport informationNational regulationsAdditional information(UN RTDG)			
	UN number	1987		
	Class	3		
	Packing group	III		
	Danger label(s)	3		
	Special provisions (SP)	223, 274 UN RTDG		
	Excepted quantities (EQ)	E1 UN RTDG		
	Limited quantities (LQ)	5 L UN RTDG		
	International Maritime Dangerous Goods Code (IMDG) - Additional information			
	Proper shipping name	ALCOHOLS, N.O.S.		
	Particulars in the shipper's declaration	UN1987, ALCOHOLS, N.O.S., (contains: 2-Propan- ol), 3, III, 30°C c.c.		
	Marine pollutant	-		
	Danger label(s)	3		
	Special provisions (SP)	223, 274		
	Excepted quantities (EQ)	E1		
	Limited quantities (LQ)	5 L		
	EmS	F-E, S-D		
	Stowage category	A		
	International Civil Aviation Organization (IC	AO-IATA/DGR) - Additional information		
	Proper shipping name	Alcohols, n.o.s.		
	Particulars in the shipper's declaration	UN1987, Alcohols, n.o.s., (contains: 2-Propanol), 3, III		
	Danger label(s)	3		
	Special provisions (SP)	A3 A180		

Special provisions (SP)

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

article number: **1CYY** 

Excepted quantities (EQ)	E1	
Limited quantities (LQ)	10 L	

### **SECTION 15: Regulatory information**

**15.1** Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

#### National regulations(Australia)

#### Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

#### **Other information**

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### **National inventories**

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

#### Legend

AICS CICR	Australian Inventory of Chemical Substances Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL ECSI	Domestic Substances List (DSL) EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIOC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

acc. to Safe Work Australia - Code of Practice

# ® Foth

#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

#### article number: **1CYY**

### **SECTION 16: Other information**

#### Indication of changes (revised safety data sheet)

# Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Narcotic effects.	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: 2-Propanol		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

#### article number: **1CYY**

Abbr.	Descriptions of used abbreviations
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

#### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### **Classification procedure**

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### List of relevant phrases (code and full text as stated in section 2 and 3)

acc. to Safe Work Australia - Code of Practice



#### Chrome azurol S indicator solution 0,5 % in dilute 2-propanol

#### article number: **1CYY**

Code	Text
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.