according to Regulation (EC) No. 1907/2006 (REACH)

Methylamine 40 % in water, for synthesis

article number: 1E51 date of compilation: 18.08.2020 Version: 2.0 en Revision: 18.02.2022

Replaces version of: 18.08.2020

Version: (1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Methylamine** 40 % in water, for synthesis

Article number 1E51

Registration number (REACH) not relevant (mixture)

Index number in CLP Annex VI [612-001-01-6] EC number [200-820-0] CAS number [74-89-5]

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for squirting or spraying. Do not use

for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private

purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

sicherheit@carlroth.de e-mail (competent person):

1.4 **Emergency telephone number**

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	Skin corrosion/irritation	1	Skin Corr. 1	H314

Page 1 / 18 Malta (en)

according to Regulation (EC) No. 1907/2006 (REACH)



Methylamine 40 % in water, for synthesis

article number: 1E51

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

Pictograms

GHS02, GHS05, GHS07



Hazard statements

H225 Highly flammable liquid and vapour H302+H332 Harmful if swallowed or if inhaled

H314 Causes severe skin burns and eye damage

H335 May cause respiratory irritation

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking

P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower]

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 Immediately call a POISON CENTER/doctor

Hazardous ingredients for labelling: Monomethylamine ... %

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger

Symbol(s)







H314 Causes severe skin burns and eye damage.

Malta (en) Page 2 / 18

according to Regulation (EC) No. 1907/2006 (REACH)



Methylamine 40 % in water, for synthesis

article number: 1E51

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

contains: Monomethylamine ... %

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Monomethylamine %	CAS No 74-89-5 EC No 200-820-0 Index No 612-001-01-6	40	Flam. Liq. 1 / H224 Acute Tox. 4 / H302 Acute Tox. 4 / H332 Skin Corr. 1B / H314 Eye Dam. 1 / H318 STOT SE 3 / H335		B(a) GHS-HC

Notes

B(a): The classification refers to an aqueous solution

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/FC. Annex VI)

Name of sub- stance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
Monomethylam- ine %	CAS No 74-89-5 EC No 200-820-0 Index No 612-001-01-6	STOT SE 3; H335: C ≥ 5 %	-	698 ^{mg} / _{kg} 3.555 ^{ppmv} / _{4h} 11 ^{mg} / _l /4h	oral inhalation: gas inhalation: va- pour

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Malta (en) Page 3 / 18

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Methylamine 40 % in water, for synthesis

article number: 1E51

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Rinse mouth with water (only if the person is conscious). Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Vomiting, Risk of blindness, Gastric perforation, Risk of serious damage to eyes, Irritation, Cough, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO_2), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

Malta (en) Page 4 / 18

according to Regulation (EC) No. 1907/2006 (REACH)

Methylamine 40 % in water, for synthesis

article number: 1E51



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Handle and open container with care. Clear contaminated areas thoroughly.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Malta (en) Page 5 / 18

according to Regulation (EC) No. 1907/2006 (REACH)

Methylamine 40 % in water, for synthesis

article number: 1E51



Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time
Monomethylamine %	74-89-5	DNEL	0,72 mg/ m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
Monomethylamine %	74-89-5	DNEL	0,427 mg/ m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects
Monomethylamine %	74-89-5	DNEL	0,1 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Monomethylamine %	74-89-5	PNEC	0,016 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
Monomethylamine %	74-89-5	PNEC	0,002 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
Monomethylamine %	74-89-5	PNEC	0,126 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Monomethylamine %	74-89-5	PNEC	0,776 ^{mg} / kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Monomethylamine %	74-89-5	PNEC	0,078 ^{mg} / kg	aquatic organ- isms	marine sediment	short-term (single instance)
Monomethylamine %	74-89-5	PNEC	0,126 ^{mg} / kg	terrestrial organ- isms	soil	short-term (single instance)

Malta (en) Page 6 / 18



according to Regulation (EC) No. 1907/2006 (REACH)

Methylamine 40 % in water, for synthesis

article number: 1E51



Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection. Wear face protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a quide.

type of material

Butyl caoutchouc (butyl rubber)

material thickness

>0,5 mm

· breakthrough times of the glove material

>480 minutes (permeation: level 6)

Splash protection - Protective gloves

• type of material: NBR (Nitrile rubber)

material thickness: >0,3 mm

• breakthrough times of the glove material: >120 minutes (permeation: level 4)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection






Respiratory protection necessary at: Aerosol or mist formation. Type: K (against ammonia and organic ammonia derivatives, colour code: Green).

Environmental exposure controls

Keep away from drains, surface and ground water.

Malta (en) Page 7 / 18





according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Methylamine 40 % in water, for synthesis

article number: 1E51

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour clear - colourless
Odour like ammonia

Melting point/freezing point $-40 \, ^{\circ}\text{C}$ Boiling point or initial boiling point and boiling $48 \, ^{\circ}\text{C}$

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 4,9 vol% (LEL) - 20,7 vol% (UEL)

Flash point -18 °C
Auto-ignition temperature 430 °C

Decomposition temperature not relevant pH (value) 14 (20 °C)

Kinematic viscosity not determined

Solubility(ies)

Water solubility (soluble)

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 370 hPa at 20 °C

Density and/or relative density

Density $0.9 \, \mathrm{g}_{\mathrm{cm}^3}$ at 20 °C

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard There is no additional information.

classes:

Other safety characteristics:

Temperature class (EU, acc. to ATEX)

T2

Maximum permissible surface temperature on

the equipment: 300°C

Malta (en) Page 8 / 18

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Methylamine 40 % in water, for synthesis

article number: 1E51

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Acetylene, Aldehydes, Alcohols, Chlorine, Fluorine, Halogenated hydrocarbons, Mercury, Strong acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

copper, zinc, tin

Release of flammable materials with

Metals, Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if swallowed. Harmful if inhaled.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Monomethylamine %	74-89-5	oral	698 ^{mg} / _{kg}
Monomethylamine %	74-89-5	inhalation: gas	3.555 ^{ppmV} / _{4h}
Monomethylamine %	74-89-5	inhalation: vapour	11 ^{mg} / _l /4h

Malta (en) Page 9 / 18

according to Regulation (EC) No. 1907/2006 (REACH)



Methylamine 40 % in water, for synthesis

article number: 1E51

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Monomethylamine %	74-89-5	oral	LD50	698 ^{mg} / _{kg}	rat
Monomethylamine %	74-89-5	inhalation: gas	LC50	7.110 ppmV/ 1h	rat

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea

• If on skin

causes severe burns, causes poorly healing wounds

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.

Malta (en) Page 10 / 18

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Methylamine 40 % in water, for synthesis

article number: 1E51

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture Name of substance CAS No Endpoint Value Species Exposure time Monomethylamine ... 74-89-5 EC50 163 mg/_I aquatic invertebrates 48 h

Biodegradation

Data are not available.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture					
Name of substance	CAS No	BCF	Log KOW	BOD5/COD	
Monomethylamine %	74-89-5		-0,713 (25 °C)		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

Malta (en) Page 11 / 18

according to Regulation (EC) No. 1907/2006 (REACH)

ROTH

Methylamine 40 % in water, for synthesis

article number: 1E51

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADR UN 1235 IMDG-Code UN 1235 ICAO-TI UN 1235

14.2 UN proper shipping name

ADR METHYLAMINE, AQUEOUS SOLUTION IMDG-Code METHYLAMINE, AQUEOUS SOLUTION ICAO-TI Methylamine, aqueous solution

14.3 Transport hazard class(es)

 ADR
 3 (8)

 IMDG-Code
 3 (8)

 ICAO-TI
 3 (8)

14.4 Packing group

ADR II IMDG-Code II ICAO-TI II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name METHYLAMINE, AQUEOUS SOLUTION

Particulars in the transport document UN1235, METHYLAMINE, AQUEOUS SOLUTION, 3

(8), II, (D/E)

Classification code FC
Danger label(s) 3+8

Malta (en) Page 12 / 18

according to Regulation (EC) No. 1907/2006 (REACH)



Methylamine 40 % in water, for synthesis

article number: 1E51





Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E
Hazard identification No 338

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name METHYLAMINE, AQUEOUS SOLUTION

Particulars in the shipper's declaration UN1235, METHYLAMINE, AQUEOUS SOLUTION, 3

(8), II, -18°C c.c.

Marine pollutant -

Danger label(s) 3+8





Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-C

Stowage category E

Segregation group 18 - Alkalis

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Methylamine, aqueous solution

Particulars in the shipper's declaration UN1235, Methylamine, aqueous solution, 3 (8), II

Danger label(s) 3+8





Excepted quantities (EQ) E2
Limited quantities (LQ) 0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Malta (en) Page 13 / 18

according to Regulation (EC) No. 1907/2006 (REACH)

Methylamine 40 % in water, for synthesis

article number: 1E51



Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)

Name of substance	Name acc. to inventory	CAS No	Restriction	No
Methylamine	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3
Monomethylamine %	flammable / pyrophoric		R40	40

Legend

R40

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

tricks and jokes,

agames for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 Articles not complying with paragraph 1 shall not be placed on the market.
 Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume,

– can be used as fuel in decorative oil lamps for supply to the general public, and

present an aspiration hazard and are labelled with H304

- Decent an aspiration flazard and are fabrilled with Flower.
 Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation
- (CEN).

 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met

(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage"; (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage'; (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.";

Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following: - metallic glitter intended mainly for decoration,

- artificial snow and frost,
- 'whoopee' cushions, silly string aerosols
- imitation excrement,
- horns for parties,
 decorative flakes and foams,
- artificial cobwebs,
- stink bombs
- 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'.
- 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
- The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

None of the ingredients are listed.

Seveso Directive

2012/18/EU (Seveso III)					
No	Dangerous substance/hazard categories		(tonnes) for the ap- and upper-tier re- ments	Notes	
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)	

Notation

Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Page 14 / 18 Malta (en)

according to Regulation (EC) No. 1907/2006 (REACH)



Methylamine 40 % in water, for synthesis

article number: 1E51

Deco-Paint Directive

VOC content	40 % 784,9 ^g / _I

Industrial Emissions Directive (IED)

VOC content	40 %
VOC content (Water content was discounted)	784,9 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed

Malta (en) Page 15 / 18

according to Regulation (EC) No. 1907/2006 (REACH)



Methylamine 40 % in water, for synthesis

article number: 1E51

Country	Inventory	Status
PH	PICCS	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS CSCL-ENCS

Australian Inventory of Chemical Substances List of Existing and New Chemical Substances (CSCL-ENCS) Domestic Substances List (DSL)

DSL ECSI IECSC INSQ ECSI EC Substances List (DSL)
ECSI EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC Inventory of Existing Chemical Substances Produced or Imported in China INSQ National Inventory of Chemical Substances
KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate

Malta (en) Page 16 / 18

according to Regulation (EC) No. 1907/2006 (REACH)



Methylamine 40 % in water, for synthesis

article number: 1E51

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)

Malta (en) Page 17 / 18

according to Regulation (EC) No. 1907/2006 (REACH)



Methylamine 40 % in water, for synthesis

article number: 1E51

Abbr.	Descriptions of used abbreviations
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STOT SE	Specific target organ toxicity - single exposure
SVHC	Substance of Very High Concern
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Malta (en) Page 18 / 18