acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen



article number: **1EET** Version: **GHS 1.0 en**

date of compilation: 2021-02-18

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Article number

Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

1EET

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory and analytical use Laboratory chemical

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name Street		Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.6	Carcinogenicity	1B	Carc. 1B	H350

For full text of abbreviations: see SECTION 16

2.2 Label elements

acc. to Safe Work Australia - Code of Practice

® §ROTH

Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

Danger

article number: **1EET**

Labelling

Signal word

Pictograms

GHS05, GHS08

Hazard statements

H290	May be corrosive to metals
H315	Causes skin irritation
H318	Causes serious eye damage
H350	May cause cancer

Precautionary statements

Precautionary statements - prevention

P280 Wear protective gloves

Precautionary statements - response

P302+P352 P305+P351+P338	IF ON SKIN: Wash with plenty of soap and water IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing
P321	Specific treatment (see on this label)
P390	Absorb spillage to prevent material damage

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

For professional users only

Hazardous ingredients for labelling:

Cobalt(II) chloride, Hydrochloric acid %

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Hydrochloric acid %	CAS No 7647-01-0	3-<5	Met. Corr. 1 / H290 Skin Corr. 1A / H314 Eye Dam. 1 / H318 STOT SE 3 / H335		B(a) IOELV

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: 1EET

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Cobalt(II) chloride	CAS No 7646-79-9	< 0.05	Acute Tox. 4 / H302 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Muta. 2 / H341 Carc. 1B / H350i Repr. 1B / H360F	! *	1(a) IARC: 2B

Notes

1(a): The concentration stated is the percentage by weight of the metallic element calculated with reference to the total weight of the mixture

- B(a): IARC: The classification refers to an aqueous solution
- IARC group 2B: possibly carcinogenic to humans (International Agency for Research on Cancer)

2B: IOELV: Substance with a community indicative occupational exposure limit value

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 **Description of first aid measures**



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Risk of blindness, Risk of serious damage to eyes, Irritation

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 **Extinguishing media**



acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: 1EET

Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Avoid exposure.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: 1EET

Consideration of other advice

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

Control parameters 8.1

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Co nt y		Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
A	U	hydrogen chloride (hydrochloric acid)	7647-01- 0	WES					5	7.5		WES

Notation

STEL

ſ

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time			
Hydrochloric acid %	7647-01-0	DNEL	8 mg/m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects			
Hydrochloric acid %	7647-01-0	DNEL	15 mg/m ³	human, inhalat- ory	worker (industry)	acute - local ef- fects			
Cobalt(II) chloride	7646-79-9	DNEL	88.1 µg/m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects			

Relevant PNECs	Relevant PNECs of components of the mixture										
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time					
Cobalt(II) chloride	7646-79-9	PNEC	0.62 ^{µg} / _l	aquatic organ- isms	freshwater	short-term (single instance)					
Cobalt(II) chloride	7646-79-9	PNEC	2.36 ^{µg} / _l	aquatic organ- isms	marine water	short-term (single instance)					
Cobalt(II) chloride	7646-79-9	PNEC	0.37 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)					
Cobalt(II) chloride	7646-79-9	PNEC	53.8 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)					
Cobalt(II) chloride	7646-79-9	PNEC	69.8 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)					



Ceiling-C

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: 1EET

Relevant PNECs of components of the mixture									
Name of sub- stance CAS No End- point		Threshol d level	Organism	Environmental compartment	Exposure time				
Cobalt(II) chloride	7646-79-9	PNEC	10.9 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)			

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. P2 (filters at least 94 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen



article number: **1EET**

SECTION 9: Physical and chemical properties

9.1	Information on basic physical and chemical properties								
	Physical state	liquid							
	Colour	acc. to product description							
	Odour	characteristic							
	Melting point/freezing point	not determined							
	Boiling point or initial boiling point and boiling range	100 °C at 1,013 hPa							
	Flammability	non-combustible							
	Lower and upper explosion limit	not determined							
	Flash point	not determined							
	Auto-ignition temperature	not determined							
	Decomposition temperature	not relevant							
	pH (value)	not determined (acidic)							
	Kinematic viscosity	not determined							
	Solubility(ies)								
	Water solubility	miscible in any proportion							
	water solubility								
	Partition coefficient								
	Partition coefficient n-octanol/water (log value):	not relevant (inorganic)							
	Vapour pressure	23 hPa at 20 °C							
	Density	1.017 ^g / _{cm³} at 20 °C							
	Particle characteristics	no data available							
	Other safety parameters								
0.2	Oxidising properties	none							
9.2	Other information								
	Information with regard to physical hazard classes:								
	Corrosive to metals	category 1: corrosive to metals							
	Other safety characteristics:								
	Miscibility	completely miscible with water							

acc. to Safe Work Australia - Code of Practice

® §ROTH

Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: **1EET**

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: Alkali metals, Strong alkali

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

- **10.5 Incompatible materials** different metals
- 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture							
Name of substance	CAS No	Exposure route	ATE				
Cobalt(II) chloride	7646-79-9	oral	418 ^{mg} / _{kg}				

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Cobalt(II) chloride	7646-79-9	oral	LD50	418 ^{mg} / _{kg}	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: 1EET

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

gastrointestinal complaints

• If in eyes

Causes serious eye damage, risk of blindness

If inhaled

Data are not available.

• If on skin

causes skin irritation, slightly irritant but not relevant for classification

Other information

none

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Cobalt(II) chloride	7646-79-9	LC50	1.512 ^{mg} / _l	fish	96 h
Cobalt(II) chloride	7646-79-9	EC50	2,618 ^{µg} / _l	aquatic invertebrates	48 h
Cobalt(II) chloride	7646-79-9	ErC50	71,314 ^{µg} / _l	algae	96 h

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Cobalt(II) chloride	7646-79-9	EC50	82.2 ^{µg} / _l	aquatic invertebrates	21 d

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: **1EET**

Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Cobalt(II) chloride	7646-79-9	23		

12.4 Mobility in soil

Data are not available.

- **12.5 Results of PBT and vPvB assessment** Data are not available.
- **12.6 Endocrine disrupting properties** None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H8 Corrosives

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

	r Standard Pt/Co (Hazen) ROTI®Calipure 2 e number: 1EET	.50 Hazen			
	TION 14: Transport information				
14.1	UN number				
	UN RTDG	UN 3264			
	IMDG-Code	UN 3264			
	ICAO-TI	UN 3264			
4.2	UN proper shipping name				
	UN RTDG	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.			
	IMDG-Code	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.			
	ICAO-TI	Corrosive liquid, acidic, inorganic, n.o.s.			
	Technical name (hazardous ingredients)	Hydrochloric acid %			
4.3	Transport hazard class(es)				
	UN RTDG	8			
	IMDG-Code	8			
	ICAO-TI	8			
4.4	Packing group				
	UN RTDG	III			
	IMDG-Code	III			
	ICAO-TI	III			
4.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations			
4.6	Special precautions for user There is no additional information.				
4.7	Transport in bulk according to Annex II o	f MARPOL and the IBC Code			
	The cargo is not intended to be carried in bu	ulk.			
	Information for each of the UN Model Re	gulations			
	Transport informationNational regulatio	nsAdditional information(UN RTDG)			
	UN number	3264			
	Proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.			
	Class	8			
	Packing group	III			
	Danger label(s)	8			
	Special provisions (SP)	223, 274 UN RTDG			

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: 1EET

Excepted quantities (EQ)	E1 UN RTDG
Limited quantities (LQ)	5 L UN RTDG
International Maritime Dangerous Goods Code	(IMDG) - Additional information
Marine pollutant	-
Danger label(s)	8
Special provisions (SP)	223, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	A
Segregation group	1 - Acids
International Civil Aviation Organization (ICAO	-IATA/DGR) - Additional information
Danger label(s)	8
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Hydrochloric acid %	7647-01-0	Table II	2806.10

National inventories

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen



article number: 1EET

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EÌNEĆS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chémicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: 1EET

Abbr.	Descriptions of used abbreviations
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
Muta.	Germ cell mutagenicity
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
Resp. Sens.	Respiratory sensitisation
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 250 Hazen

article number: **1EET**

Abbr.	Descriptions of used abbreviations
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne conatminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H350i	May cause cancer by inhalation.
H360F	May damage fertility.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.