acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen



date of compilation: 2021-02-18 article number: 1EEX Version: GHS 1.0 en

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Colour Standard Pt/Co (Hazen) ROTI®Calipure

400 Hazen

1EEX Article number

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

sicherheit@carlroth.de e-mail (competent person):

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	3.3 Serious eye damage/eye irritation		Eye Dam. 1	H318
3.6	Carcinogenicity	1B	Carc. 1B	H350

For full text of abbreviations: see SECTION 16

2.2 **Label elements**

Page 1 / 16 Australia (en)

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

Labelling

Signal word Danger

Pictograms

GHS05, GHS08



Hazard statements

H290	May be corrosive to metals
H315	Causes skin irritation
H318	Causes serious eye damage
H350	May cause cancer

Precautionary statements

Precautionary statements - prevention

P280 Wear protective gloves

Precautionary statements - response

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P321 Specific treatment (see on this label)

P390 Absorb spillage to prevent material damage

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

For professional users only

Hazardous ingredients for labelling: Cobalt(II) chloride, Hydrochloric acid %, Po-

tassium hexachloroplatinate(IV)

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Hydrochloric acid %	CAS No 7647-01-0	3-<5	Met. Corr. 1 / H290 Skin Corr. 1A / H314 Eye Dam. 1 / H318 STOT SE 3 / H335		B(a) IOELV

Australia (en) Page 2 / 16

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Potassium hexa- chloroplatinate(IV)	CAS No 16921-30-5	0.1 - < 1	Met. Corr. 1 / H290 Acute Tox. 3 / H301 Eye Dam. 1 / H318 Resp. Sens. 1 / H334 Skin Sens. 1 / H317		
Cobalt(II) chloride	CAS No 7646-79-9	< 0.1	Acute Tox. 4 / H302 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Muta. 2 / H341 Carc. 1B / H350i Repr. 1B / H360F	<u>(!)</u>	1(a) IARC: 2B

Notes

1(a): The concentration stated is the percentage by weight of the metallic element calculated with reference to the total

weight of the mixture

B(a): The classification refers to an aqueous solution

IÀRC: IARC group 2B: possibly carcinogenic to humans (International Agency for Research on Cancer) 2B:

IOELV: Substance with a community indicative occupational exposure limit value

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Risk of blindness, Risk of serious damage to eyes, Irritation

4.3 Indication of any immediate medical attention and special treatment needed

none

Australia (en) Page 3 / 16

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX



SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Australia (en) Page 4 / 16

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX



SECTION 7: Handling and storage

Precautions for safe handling

Avoid exposure.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	hydrogen chloride (hydrochloric acid)	7647-01- 0	WES					5	7.5		WES

Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time	
Hydrochloric acid %	7647-01-0	DNEL	8 mg/m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects	
Hydrochloric acid %	7647-01-0	DNEL	15 mg/m³	human, inhalat- ory	worker (industry)	acute - local ef- fects	
Cobalt(II) chloride	7646-79-9	DNEL	88.1 μg/m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects	

Australia (en) Page 5 / 16

acc. to Safe Work Australia - Code of Practice



article number: **1EEX**



Relevant PNECs	Relevant PNECs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time				
Potassium hexa- chloroplatinate(IV)	16921-30-5	PNEC	0.14 ^{µg} / _l	aquatic organ- isms	freshwater	short-term (single instance)				
Potassium hexa- chloroplatinate(IV)	16921-30-5	PNEC	0.017 ^{µg} / _l	aquatic organ- isms	marine water	short-term (single instance)				
Potassium hexa- chloroplatinate(IV)	16921-30-5	PNEC	0.125 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)				
Potassium hexa- chloroplatinate(IV)	16921-30-5	PNEC	0.261 ^{mg} / kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)				
Potassium hexa- chloroplatinate(IV)	16921-30-5	PNEC	0.026 ^{mg} / kg	aquatic organ- isms	marine sediment	short-term (single instance)				
Potassium hexa- chloroplatinate(IV)	16921-30-5	PNEC	0.005 ^{mg} / kg	terrestrial organ- isms	soil	short-term (single instance)				
Cobalt(II) chloride	7646-79-9	PNEC	0.62 ^{µg} / _l	aquatic organ- isms	freshwater	short-term (single instance)				
Cobalt(II) chloride	7646-79-9	PNEC	2.36 ^{µg} / _l	aquatic organ- isms	marine water	short-term (single instance)				
Cobalt(II) chloride	7646-79-9	PNEC	0.37 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)				
Cobalt(II) chloride	7646-79-9	PNEC	53.8 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)				
Cobalt(II) chloride	7646-79-9	PNEC	69.8 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)				
Cobalt(II) chloride	7646-79-9	PNEC	10.9 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)				

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection






Australia (en) Page 6 / 16

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI® Calipure 400 Hazen

article number: 1EEX





type of material

NBR (Nitrile rubber)

material thickness

>0.11 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. P2 (filters at least 94 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour acc. to product description

Odour characteristic Melting point/freezing point not determined

100 °C Boiling point or initial boiling point and boiling

range

Flammability

non-combustible

Lower and upper explosion limit not determined not determined Flash point Auto-ignition temperature not determined

not relevant Decomposition temperature

pH (value) not determined (acidic)

Kinematic viscosity not determined

Page 7 / 16 Australia (en)



acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure 23 hPa at 20 °C

Density $1.003 \, {}^{9}/_{cm^3}$ at 20 ${}^{\circ}\text{C}$

Particle characteristics no data available

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Corrosive to metals category 1: corrosive to metals

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: Alkali metals, Strong alkali

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

different metals

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Australia (en) Page 8 / 16

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Potassium hexachloroplatinate(IV)	16921-30-5	oral	195 ^{mg} / _{kg}
Cobalt(II) chloride	7646-79-9	oral	418 ^{mg} / _{kg}

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Potassium hexachloroplatinate(IV)	16921-30-5	oral	LD50	195 ^{mg} / _{kg}	rat
Cobalt(II) chloride	7646-79-9	oral	LD50	418 ^{mg} / _{kg}	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Australia (en) Page 9 / 16

acc. to Safe Work Australia - Code of Practice

Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX



Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

gastrointestinal complaints

• If in eyes

Causes serious eye damage, risk of blindness

• If inhaled

Data are not available.

• If on skin

causes skin irritation, slightly irritant but not relevant for classification

Other information

none

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture											
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time						
Potassium hexa- chloroplatinate(IV)	16921-30-5	LC50	25.78 ^{mg} / _l	fish	96 h						
Potassium hexa- chloroplatinate(IV)	16921-30-5	ErC50	2.4 ^{mg} / _l	algae	72 h						
Cobalt(II) chloride	7646-79-9	LC50	1.512 ^{mg} / _l	fish	96 h						
Cobalt(II) chloride	7646-79-9	EC50	2,618 ^{µg} / _l	aquatic invertebrates	48 h						
Cobalt(II) chloride	7646-79-9	ErC50	71,314 ^{µg} / _l	algae	96 h						

Aquatic toxicity (chronic) of components of the mixture Name of substance CAS No Endpoint Value Species

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Potassium hexa- chloroplatinate(IV)	16921-30-5	EC50	103 ^{mg} / _l	microorganisms	3 h
Cobalt(II) chloride	7646-79-9	EC50	82.2 ^{µg} / _l	aquatic invertebrates	21 d

Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Australia (en) Page 10 / 16

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Cobalt(II) chloride	7646-79-9	23		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H8 Corrosives

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG UN 3264

IMDG-Code UN 3264 ICAO-TI UN 3264

14.2 UN proper shipping name

UN RTDG CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

IMDG-Code CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

ICAO-TI Corrosive liquid, acidic, inorganic, n.o.s.

Australia (en) Page 11 / 16

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

	Technical name (hazardous ingredients)	Hydrochloric acid %, Potassium hexachloro- platinate(IV)
14.3	Transport hazard class(es)	
	UN RTDG	8
	IMDG-Code	8
	ICAO-TI	8
14.4	Packing group	
	UN RTDG	III
	IMDG-Code	III
	ICAO-TI	III
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number	3264
Proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Class	8
Packing group	III
Danger label(s)	8



Special provisions (SP)	223, 274 UN RTDG
Excepted quantities (EQ)	E1 UN RTDG
Limited quantities (LO)	51

Limited quantities (LQ) 5 L UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant Danger label(s) 8



Special provisions (SP) 223, 274

Excepted quantities (EQ) E1

Australia (en) Page 12 / 16

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

Limited quantities (LQ) 5 L

EmS F-A, S-B

Stowage category A

Segregation group 1 - Acids

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 8



Special provisions (SP) A3
Excepted quantities (EQ) E1
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Hydrochloric acid %	7647-01-0	Table II	2806.10

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Australia (en) Page 13 / 16

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

Legend

AICS CICR CSCL-ENCS Australian Inventory of Chemical Substances Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS)

CSCL-ENCS
DSL Domestic Substances List (DSL)
ECSI ECSI EC Substance Linventory (EINECS, ELINCS, NLP)
IECSC Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances
KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory
TSCA Toxic Substance Control Act

TCSI TSCA

Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)

Australia (en) Page 14 / 16

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

	International Civil Aviation Organization Technical instructions for the safe transport of dangerous goods by air International Maritime Dangerous Goods Code International Maritime Dangerous Goods Code Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval n-Octanol/water
IMDG IMDG-Code LC50 LD50 L	International Maritime Dangerous Goods Code International Maritime Dangerous Goods Code Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
IMDG-Code LC50 L LD50 L	International Maritime Dangerous Goods Code Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LC50 L	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LD50 L	lethality during a specified time interval Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
	specified time interval
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
Muta.	Germ cell mutagenicity
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
Resp. Sens.	Respiratory sensitisation
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne conatminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Australia (en) Page 15 / 16

acc. to Safe Work Australia - Code of Practice



Colour Standard Pt/Co (Hazen) ROTI®Calipure 400 Hazen

article number: 1EEX

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H350i	May cause cancer by inhalation.
H360F	May damage fertility.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 16 / 16