according to Regulation (EC) No. 1907/2006 (REACH)



Colour Standard ROTI®Calipure ASTM A1

article number: **1H63** Version: **1.0 en** date of compilation: 2021-03-18

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Article number

Registration number (REACH)

Colour Standard ROTI®Calipure ASTM A1

1H63

not relevant (mixture)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory and analytical use Laboratory chemical

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

according to Regulation (EC) No. 1907/2006 (REACH)



Colour Standard ROTI®Calipure ASTM A1

article number: 1H63

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word	Danger	
Pictograms		
GHS08		
Hazard statem	ents	
H304	May be fatal if swallow	ed and enters airways
Precautionary	statements	
Precautionary	statements - response	
P301+P310 P331	IF SWALLOWED: Immedia Do NOT induce vomiting	ately call a POISON CENTER/doctor
Supplemental l	hazard information	
EUH066	Repeated exposure may	cause skin dryness or cracking.
Hazardous ingi	redients for labelling:	n-Dodecane, Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1-methylethyl)-1,1'-biphenyl
Labelling of package Signal word: Dange	ges where the contents do not exce r	eed 125 ml

Symbol(s)



H304	May be fatal if swallowed and enters airways.
P301+P310 P331	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.
EUH066 contains:	Repeated exposure may cause skin dryness or cracking. n-Dodecane Reaction mass of diisopropyl-1,1'-biphenyl and tris(1-methylethyl)-1,1'-biphenyl

2.3 **Other hazards**

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

according to Regulation (EC) No. 1907/2006 (REACH)



Colour Standard ROTI®Calipure ASTM A1

article number: 1H63

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
n-Dodecane	CAS No 112-40-3 EC No 203-967-9	≥ 50	Asp. Tox. 1 / H304 EUH066		
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl	EC No 915-589-8	≤ 2,5	STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 4 / H413		

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed none

according to Regulation (EC) No. 1907/2006 (REACH)





article number: 1H63

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO $_2$), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

according to Regulation (EC) No. 1907/2006 (REACH)



Colour Standard ROTI®Calipure ASTM A1

article number: 1H63

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

Specific designs for storage rooms or vessels Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Data are not available.

Relevant DNELs	Relevant DNELs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time				
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl		DNEL	0,192 mg/ m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects				
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl		DNEL	0,54 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects				

according to Regulation (EC) No. 1907/2006 (REACH)

Colour Standard ROTI®Calipure ASTM A1



article number: 1H63

Relevant PNECs	Relevant PNECs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time				
n-Dodecane	112-40-3	PNEC	0,96 ^{µg} / _l	aquatic organ- isms	freshwater	short-term (single instance)				
n-Dodecane	112-40-3	PNEC	0,93 ^{µg} / _l	aquatic organ- isms	marine water	short-term (single instance)				
n-Dodecane	112-40-3	PNEC	14 ^{µg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)				
n-Dodecane	112-40-3	PNEC	2 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)				
n-Dodecane	112-40-3	PNEC	2 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)				
n-Dodecane	112-40-3	PNEC	0,81 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)				
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl		PNEC	0,126 ^{µg} / _l	aquatic organ- isms	freshwater	short-term (single instance)				
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl		PNEC	0,013 ^{µg} / _l	aquatic organ- isms	marine water	short-term (single instance)				
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl		PNEC	1 ^{mg} /l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)				
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl		PNEC	1.481 ^{µg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)				
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl		PNEC	148,1 ^{µg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)				
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1- methylethyl)-1,1'-bi- phenyl		PNEC	295,3 ^{µg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)				

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

according to Regulation (EC) No. 1907/2006 (REACH)

Colour Standard ROTI®Calipure ASTM A1

® ROTH

article number: 1H63

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	acc. to product description
Odour	characteristic
Melting point/freezing point	-10 °C at 1 atm
Boiling point or initial boiling point and boiling range	≥205,5 °C at 1 atm
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	0,6 vol% - 6,5 vol%

according to Regulation (EC) No. 1907/2006 (REACH)

Colour Standard ROTI®Calipure ASTM A1



article number: 1H63

	Flash point	71 °C
	Auto-ignition temperature	200 °C
	Decomposition temperature	not relevant
	pH (value)	not determined
	Kinematic viscosity	not determined
	Solubility(ies)	
	Water solubility	not determined
	Partition coefficient	
	Partition coefficient n-octanol/water (log value):	this information is not available
	Vapour pressure	0,02 kPa at 25 °C
	Density	~0,757 ^g / _{cm³} at 15 °C
	Particle characteristics	No data available.
	Other safety parameters	
	Oxidising properties	none
9.2	Other information	
	Information with regard to physical hazard classes:	hazard classes acc. to GHS (physical hazards): not relevant
	Other safety characteristics:	
	Temperature class (EU, acc. to ATEX)	T4 Maximum permissible surface temperature on the equipment: 135°C

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

according to Regulation (EC) No. 1907/2006 (REACH)

Colour Standard ROTI®Calipure ASTM A1

article number: 1H63

10.5 Incompatible materials There is no additional information.

10.6 Hazardous decomposition products Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species		
n-Dodecane	112-40-3	oral	LD50	>5.000 ^{mg} / _{kg}	rat		
n-Dodecane	112-40-3	inhalation: dust/mist	LC50	≥6.100 ^{mg} / _{m³} / 4h	rat		
n-Dodecane	112-40-3	dermal	LD50	>2.000 ^{mg} / _{kg}	rat		
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1-methylethyl)-1,1'- biphenyl		oral	LD50	>5.000 ^{mg} / _{kg}	rat		
Reaction mass of diisopropyl-1,1'-bi- phenyl and tris(1-methylethyl)-1,1'- biphenyl		dermal	LD50	>5.000 ^{mg} / _{kg}	rabbit		

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).



according to Regulation (EC) No. 1907/2006 (REACH)



Colour Standard ROTI®Calipure ASTM A1

article number: 1H63

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

aspiration hazard

• If in eyes

Data are not available.

• If inhaled

Data are not available.

• If on skin

repeated exposure may cause skin dryness or cracking

• Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Biodegradation

Data are not available.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture									
Name of substance	CAS No	BCF	Log KOW	BOD5/COD					
n-Dodecane	112-40-3		6,98 (pH value: 7, 25 °C)						
Reaction mass of diisopropyl-1,1'- biphenyl and tris(1-methylethyl)- 1,1'-biphenyl			6,67						

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

according to Regulation (EC) No. 1907/2006 (REACH)



Colour Standard ROTI®Calipure ASTM A1

article number: 1H63

12.6 Endocrine disrupting properties None of the ingredients are listed.

12.7 Other adverse effects Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

- 14.2 UN proper shipping name
- 14.3 Transport hazard class(es)
- 14.4 Packing group
- 14.5 Environmental hazards

not subject to transport regulations

not assigned

none

not assigned

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

not assigned

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

according to Regulation (EC) No. 1907/2006 (REACH)





article number: 1H63

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	Νο
Colour Standard ROTI®Calipure ASTM	this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC		R3	3

Legend R3

1. Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

- tricks and jokes,

games for one or more participants, or any article intended to be used as such, even with ornamental aspects,

 Articles not complying with paragraph 1 shall not be placed on the market.
 Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they

can be used as fuel in decorative oil lamps for supply to the general public, and,
 present an aspiration hazard and are labelled with R65 or H304,

4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation

(CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:

(a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: 'Keep lamps filled with this liquid out of the reach of children'; and, by 1 December 2010, 'Just a sip of lamp oil - or even sucking the wick of lamps - may lead to life-threatening lung damage';
(b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter may lead to life threatening lung damage';
(c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black or parts are packaged in liters but 1 December 2010.

(c) lamp oils and grill lighters, labelled with R65 of H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.
6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.
7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids.

fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

None of the ingredients are listed. (Or Concentration of the substance in a mixture: <0.1 % Mass concentration)

Seveso Directive

2012/18/EU (Seveso III)			
Νο	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the ap- plication of lower and upper-tier re- quirements	Notes
	not assigned		

Deco-Paint Directive (2004/42/EC)

VOC content 97,5	%
734,	2 ^g /l

according to Regulation (EC) No. 1907/2006 (REACH)



Colour Standard ROTI®Calipure ASTM A1

article number: 1H63

Directive on industrial emissions (VOCs, 2010/75/EU)		
VOC content	97,5 %	
VOC content	734,2 ^g / _l	

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS) - Annex II

none of the ingredients are listed

Regulation 166/2006/EC concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

none of the ingredients are listed

Regulation 98/2013/EU on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation 111/2005/EC laying down rules for the monitoring of trade between the Community and third countries in drug precursors

none of the ingredients are listed

Regulation 1005/2009/EC on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation 649/2012/EU concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

National inventories

Country	Inventory	Status
AU	AICS	not all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AICSAustralian Inventory of Chemical SubstancesCSCL-ENCSList of Existing and New Chemical Substances (CSCL-ENCS)DSLDomestic Substances List (DSL)ECSIEC Substance Inventory (EINECS, ELINCS, NLP)IECSCInventory of Existing Chemical Substances Produced or Imported in ChinaINSQNational Inventory of Chemical SubstancesKECIKorea Existing Chemicals InventoryNZIOCNew Zealand Inventory of ChemicalsPICCSPhilippine Inventory of Chemicals and Chemical Substances (PICCS)

according to Regulation (EC) No. 1907/2006 (REACH)

Colour Standard ROTI®Calipure ASTM A1



article number: 1H63

Legend

REACH Reg. REACH registered substances TCSI Taiwan Chemical Substance Inventory TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways)	
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)	
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard	
Asp. Tox.	Aspiration hazard	
BCF	Bioconcentration factor	
BOD	Biochemical Oxygen Demand	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures	
COD	Chemical oxygen demand	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union)	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
IMDG	International Maritime Dangerous Goods Code	
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
log KOW	n-Octanol/water	
NLP	No-Longer Polymer	

according to Regulation (EC) No. 1907/2006 (REACH)



Colour Standard ROTI®Calipure ASTM A1

article number: 1H63

Abbr.	Descriptions of used abbreviations	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals	
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)	
STOT RE	Specific target organ toxicity - repeated exposure	
SVHC	Substance of Very High Concern	
VOC	Volatile Organic Compounds	
vPvB	Very Persistent and very Bioaccumulative	

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text	
H304	May be fatal if swallowed and enters airways.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H413	May cause long lasting harmful effects to aquatic life.	

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.