acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X date of compilation: 2021-08-04 Version: **3.0 en** Revision: 2024-03-02

Replaces version of: 2023-10-16

Version: (2)



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Lithium hydroxide ROTI®METIC 99,995 % (4N5)**

Article number 1L5X

EC number 215-183-4 CAS number 1310-65-2

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for squirting or spraying. Do not use

for products which come into direct contact with the skin. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de Website: www.carlroth.de

sheet:

sicherheit@carlroth.de e-mail (competent person):

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.2	Skin corrosion/irritation	1	Skin Corr. 1	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

United Kingdom (en) Page 1 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS05, GHS07



Hazard statements

H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage

Precautionary statements

Precautionary statements - prevention

P280 Wear protective gloves/eye protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water [or shower]

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P310 Immediately call a POISON CENTER/doctor

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Lithium hydroxide

Molecular formula LiOH

Molar mass 23,95 ^g/_{mol}
CAS No 1310-65-2
EC No 215-183-4

United Kingdom (en) Page 2 / 16



acc. to Regulation (EC) No. 1907/2006 (REACH)



article number: 1L5X



Substance, Specific Conc. Limits, M-factors, ATE				
Specific Conc. Limits	M-Factors	ATE	Exposure route	
-	-	363 ^{mg} / _{kg}	oral	

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Rinse mouth with water (only if the person is conscious). Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Vomiting, Risk of blindness, Gastric perforation, Risk of serious damage to eyes

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water, foam, alcohol resistant foam, dry extinguishing powder, ABC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture


Non-combustible.

United Kingdom (en) Page 3 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe dust.

6.2 **Environmental precautions**

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains. Take up mechanically.

Advice on how to clean up a spill

Take up mechanically. Control of dust.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

Precautions for safe handling 7.1

Handle and open container with care. Avoid dust formation. Clear contaminated areas thoroughly.

Measures to prevent fire as well as aerosol and dust generation

Removal of dust deposits.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place. Hygroscopic solid.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

humidity, UV-radiation/sunlight

Consideration of other advice:

Ventilation requirements

Use local and general ventilation.

United Kingdom (en) Page 4 / 16




5.3 **Advice for firefighters**

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
GB	dust		WEL	10			i	EH40/2005
GB	dust		WEL	4			r	EH40/2005
GB	lithium hydroxide	1310-65-2	WEL		1			EH40/2005

Notation

Ceiling value is a limit value above which exposure should not occur Inhalable fraction Ceiling-C

Respirable fraction

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)
Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

Human health values

Relevant DNELs and other threshold levels Threshold **Endpoint** Protection goal, **Used in Exposure time** level route of exposure DNEL 10 mg/m³ human, inhalatory worker (industry) chronic - systemic effects DNEL 30 mg/m³ human, inhalatory worker (industry) acute - systemic effects **DNEL** 41,35 mg/kg human, dermal worker (industry) chronic - systemic effects bw/day DNEL 100 mg/kg bw/ human, dermal worker (industry) acute - systemic effects day

Environmental values

Relevant PNECs and other threshold levels

End- point	Threshold level	Organism	Environmental com- partment	Exposure time
PNEC	2,3 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,23 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
PNEC	79,2 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	153 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)

United Kingdom (en) Page 5 / 16



acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



Relevant	PNECs and ot	her threshold levels		
End- point	Threshold level	Organism	Environmental com- partment	Exposure time
PNEC	15,3 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
PNEC	28,22 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection. Wear face protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection






Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P2 (filters at least 94 % of airborne particles, colour code: White).

United Kingdom (en) Page 6 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state solid
Form powder
Colour white

Odour odourless

Melting point/freezing point 423,9 °C at 1.013 hPa (ECHA)

Boiling point or initial boiling point and boiling

range

Flammability

non-combustible

not determined

Lower and upper explosion limit not determined

Flash point not applicable

Auto-ignition temperature not determined

Decomposition temperature 924 °C

pH (value) \sim 12 (in aqueous solution: 50 $^{\rm g}$ / $_{\rm l}$, 50 $^{\rm o}$ C)

Kinematic viscosity not relevant

Solubility(ies)

Water solubility $110 \, {}^{9}/_{1}$ at 20 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure not determined

Density and/or relative density

Density $1,54 \, \mathrm{g/_{cm^3}}$

Relative vapour density Information on this property is not available.

Bulk density $\sim 550 \, \mathrm{kg/m^3}$

Particle characteristics No data available.

Other safety parameters

Oxidising properties none

United Kingdom (en) Page 7 / 16



acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



Information with regard to physical hazard

(physical hazards): not relevant

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

10.2 Chemical stability

Hygroscopic solid.

10.3 Possibility of hazardous reactions

Violent reaction with: Acids,

Dangerous/dangerous reactions with: Ammonium compounds

10.4 Conditions to avoid

UV-radiation/sunlight. Protect from moisture. Keep away from heat. Decompostion takes place from temperatures above: 924 °C.

10.5 Incompatible materials

aluminium, lead, zinc, tin

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4. May be harmful in contact with skin or if inhaled.

Acute toxicity

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	363 ^{mg} / _{kg}	mouse		ECHA
inhalation: dust/ mist	LC50	>6,15 ^{mg} / _l /4h	rat		ECHA
dermal	LD50	>2.000 ^{mg} / _{kg}	rat		ECHA

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

United Kingdom (en) Page 8 / 16



classes:

hazard classes acc. to GHS

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

If inhaled

Data are not available.

• If on skin

causes severe burns, causes poorly healing wounds

Other information

Agitation, Irreversible damage to internal organs, Poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)					
Endpoint	Value	Species	Source	Exposure time	
LC50	62,2 ^{mg} / _l	fish	ECHA	96 h	
EC50	19,1 ^{mg} / _l	aquatic invertebrates	ECHA	48 h	
ErC50	87,57 ^{mg} / _l	algae	ECHA	72 h	

United Kingdom (en) Page 9 / 16



acc. to Regulation (EC) No. 1907/2006 (REACH)



article number: 1L5X



Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	180,8 ^{mg} / _l	microorganisms	ECHA	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP 4 irritant - skin irritation and eye damage

HP 6 acute toxicity

HP 8 corrosive

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

United Kingdom (en) Page 10 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



SECTION 14: Transport information

14.1 UN number or ID number

ADRRID UN 2680 IMDG-Code UN 2680 ICAO-TI **UN 2680**

14.2 UN proper shipping name

ADRRID LITHIUM HYDROXIDE IMDG-Code LITHIUM HYDROXIDE ICAO-TI Lithium hydroxide

14.3 Transport hazard class(es)

ADRRID 8 **IMDG-Code** 8 ICAO-TI 8

14.4 Packing group

ADRRID II **IMDG-Code** II ICAO-TI II

14.5 Environmental hazards

non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information

Proper shipping name LITHIUM HYDROXIDE

Particulars in the transport document UN2680, LITHIUM HYDROXIDE, 8, II, (E)

Classification code C6 Danger label(s) 8



Excepted quantities (EQ) E2 Limited quantities (LQ) 1 kg Transport category (TC) 2 Ε Tunnel restriction code (TRC)

United Kingdom (en) Page 11 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X

Hazard identification No 80
Emergency Action Code 2X

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional

information

Classification code C6

Danger label(s) 8

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 kg
Transport category (TC) 2
Hazard identification No 80

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name LITHIUM HYDROXIDE

Particulars in the shipper's declaration UN2680, LITHIUM HYDROXIDE, 8, II

Marine pollutant Danger label(s) 8



Special provisions (SP) - Excepted quantities (EQ) E2
Limited quantities (LQ) 1 kg
EmS F-A, S-B

Stowage category A

Segregation group 18 - Alkalis

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Lithium hydroxide

Particulars in the shipper's declaration UN2680, Lithium hydroxide, 8, II

Danger label(s) 8



Excepted quantities (EQ) E2
Limited quantities (LQ) 5 kg

United Kingdom (en) Page 12 / 16



acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	18/EU (Seveso III)		
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

Deco-Paint Directive

VOC content	0 %
-------------	-----

Industrial Emissions Directive (IED)

VOC content 0 %	
-----------------	--

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Lithium hydroxide	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	
Lithium hydroxide	Metals and their compounds		a)	

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

United Kingdom (en) Page 13 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



Regulation concerning the export and import of hazardous chemicals (PIC)

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

Restrictions according to GB REACH, Annex 17

not listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC CICR Australian Inventory of Industrial Chemicals

CSCL-ENCS DSL ECSI IECSC

Australian Inventory of Industrial Chemicals
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances

Korea Existing Chemicals Inventory

NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

Toxic Substance Control Act

Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

United Kingdom (en) Page 14 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval

United Kingdom (en) Page 15 / 16

acc. to Regulation (EC) No. 1907/2006 (REACH)

Lithium hydroxide ROTI®METIC 99,995 % (4N5)

article number: 1L5X



Abbr.	Descriptions of used abbreviations
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 16 / 16