acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

date of compilation: 2021-08-13 article number: 1LAE Version: GHS 1.0 en

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

o-Cresolphthaleine indicator solution 0,1 % in Identification of the substance

ethanol, denatured

Article number 1LAE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

sicherheit@carlroth.de e-mail (competent person):

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.3	Serious eye damage/eye irritation	2A	Eye Irrit. 2A	H319

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 **Label elements**

Australia (en) Page 1 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Labelling

Signal word Danger

Pictograms

GHS02, GHS07



Hazard statements

H225 Highly flammable liquid and vapour H319 Causes serious eye irritation

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 Keep container tightly closed

Precautionary statements - response

P337+P313 If eye irritation persists: Get medical advice/attention

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Ethanol	CAS No 64-17-5	25 – 50	Flam. Liq. 2 / H225 Eye Irrit. 2A / H319		IARC: 1
2-Propanol	CAS No 67-63-0	≤ 2.5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336	(1)	

Australia (en) Page 2 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
2-Butanone	CAS No 78-93-3	≤ 2.5	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336 EUH066		IOELV

Notes

IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)

IOELV: Substance with a community indicative occupational exposure limit value

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Nausea, Vomiting, Abdominal pain, Breathing difficulties, Vertigo, Drowsiness, Narcosis, Loss of righting reflex, and ataxia

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

Australia (en) Page 3 / 17

acc. to Safe Work Australia - Code of Practice

ROTH

o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Australia (en) Page 4 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	ethyl alcohol (ethan- ol)	64-17-5	WES	1,00 0	1,880						WES
AU	isopropyl alcohol (propan-2-ol)	67-63-0	WES	400	983	500	1,230				WES
AU	methyl ethyl ketone (MEK) (2-butanone)	78-93-3	WES	150	445	300	890				WES

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) STEL

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Australia (en) Page 5 / 17

acc. to Safe Work Australia - Code of Practice

2-Propanol

2-Propanol



chronic - systemic

effects

chronic - systemic

effects

o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Relevant DNELs of components of the mixture Name of sub-**CAS No** End-**Threshol Protection Used** in **Exposure time** goal, route of exposure d level stance point 1,900 mg/ human, inhalatacute - systemic effects Ethanol 64-17-5 **DNEL** worker (industry) m³ orv Ethanol 64-17-5 DNEL 343 mg/kg human, dermal worker (industry) chronic - systemic effects 64-17-5 chronic - systemic Ethanol DNEL human, inhalat-950 mg/m³ worker (industry) effects ory 600 mg/m³ 2-Butanone 78-93-3 DNEL human, inhalatworker (industry) chronic - systemic effects ory **DNEL** 1,161 mg/ human, dermal 2-Butanone 78-93-3 worker (industry) chronic - systemic kg bw/day effects

human, inhalat-

ory

human, dermal

worker (industry)

worker (industry)

500 mg/m³

888 mg/kg

bw/day

DNEL

DNEL

Relevant PNECs of components of the mixture

67-63-0

67-63-0

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Ethanol	64-17-5	PNEC	0.79 ^{mg} / _{cm³}	unknown	marine water	intermittent re- lease
Ethanol	64-17-5	PNEC	2.75 ^{mg} / _{cm³}	unknown	air	intermittent re- lease
Ethanol	64-17-5	PNEC	3.6 ^{mg} / _{cm³}	unknown	freshwater sedi- ment	intermittent re- lease
Ethanol	64-17-5	PNEC	580 ^{mg} / _{cm³}	unknown	sewage treatment plant (STP)	intermittent re- lease
Ethanol	64-17-5	PNEC	0.63 ^{mg} / _{cm³}	unknown	soil	intermittent re- lease
Ethanol	64-17-5	PNEC	0.96 ^{mg} / _{cm³}	unknown	freshwater	intermittent re- lease
2-Butanone	78-93-3	PNEC	55.8 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
2-Butanone	78-93-3	PNEC	55.8 ^{mg} / _I	aquatic organ- isms	marine water	short-term (single instance)
2-Butanone	78-93-3	PNEC	709 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
2-Butanone	78-93-3	PNEC	284.7 ^{mg} / kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
2-Butanone	78-93-3	PNEC	284.7 ^{mg} / kg	aquatic organ- isms	marine sediment	short-term (single instance)
2-Butanone	78-93-3	PNEC	22.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
2-Propanol	67-63-0	PNEC	140.9 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)

Australia (en) Page 6 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
2-Propanol	67-63-0	PNEC	140.9 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
2-Propanol	67-63-0	PNEC	2,251 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
2-Propanol	67-63-0	PNEC	552 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
2-Propanol	67-63-0	PNEC	552 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
2-Propanol	67-63-0	PNEC	28 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,5 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Australia (en) Page 7 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour acc. to product description

Odour like: - alcohol
Melting point/freezing point not determined

Boiling point or initial boiling point and boiling

range

78 °C at 1,013 hPa

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 3.5 vol% - 15 vol%

Flash point 13 °C (data apply to the main component)

Auto-ignition temperature 455 °C (data apply to the main component)

Decomposition temperature not relevant pH (value) 7 (20 °C)

Kinematic viscosity not determined

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 59 hPa at 20 °C

Density $0.88 \, \mathrm{g}/_{\mathrm{cm}^3}$

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Australia (en) Page 8 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

There is no additional information.

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Alkali metals, Alkaline earth metal, Acetic anhydride, Peroxides, Phosphorus oxides (e.g. P2O5), Nitric acid, Nitrate, Perchlorates, => Explosive properties

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Australia (en) Page 9 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Ethanol	64-17-5	inhalation: va- pour	LC50	95.6 ^{mg} / _l /4h	rat
Ethanol	64-17-5	oral	LD50	7,060 ^{mg} / _{kg}	rat
2-Butanone	78-93-3	dermal	LD50	6,480 ^{mg} / _{kg}	rabbit
2-Butanone	78-93-3	oral	LD50	2,054 ^{mg} / _{kg}	rat
2-Propanol	67-63-0	inhalation: va- pour	LC50	37.5 ^{mg} / _l /4h	rat
2-Propanol	67-63-0	oral	LD50	5,045 ^{mg} / _{kg}	rat
2-Propanol	67-63-0	dermal	LD50	12,800 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, abdominal pain, nausea, Causes damage to liver through prolonged or repeated exposure if swallowed, loss of righting reflex, and ataxia

• If in eyes

Causes serious eye irritation

• If inhaled

drowsiness, narcosis, vertigo, breathing difficulties, Inebriation

Australia (en) Page 10 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

• If on skin

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation)

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Ethanol	64-17-5	LC50	8,140 ^{mg} / _l	orfe (Leuciscus idus)	96 h
Ethanol	64-17-5	EC50	9,000 – 14,000 ^{mg} / _l	daphnia magna	48 h
2-Butanone	78-93-3	LC50	2,993 ^{mg} / _l	fish	96 h
2-Butanone	78-93-3	EC50	308 ^{mg} / _l	aquatic invertebrates	48 h
2-Butanone	78-93-3	ErC50	1,972 ^{mg} / _l	algae	72 h
2-Propanol	67-63-0	LC50	9,640 ^{mg} / _l	Pimephales promelas	96 h

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
2-Propanol	67-63-0	LC50	>10,000 ^{mg} / _l	aquatic invertebrates	24 h

Biodegradation

Data are not available.

12.2 Process of degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Ethanol	64-17-5	biotic/abiotic	94 %	d		
2-Butanone	78-93-3	oxygen deple- tion	98 %	28 d		ECHA
2-Propanol	67-63-0	biotic/abiotic	95 %	21 d	modifizierter OECD Screen- ing Test	
2-Propanol	67-63-0	oxygen deple- tion	53 %	5 d		ECHA

Australia (en) Page 11 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Ethanol	64-17-5		-0.31	
2-Butanone 78-93-3			0.3 (pH value: 7, 40 °C)	
2-Propanol 67-63-0			0.05	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

Australia (en) Page 12 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

SECTION 14: Transport information

14.1 UN number

UN RTDG UN 1170

IMDG-Code UN 1170

ICAO-TI **UN 1170**

14.2 UN proper shipping name

UN RTDG ETHANOL IMDG-Code ETHANOL ICAO-TI

14.3 Transport hazard class(es)

3 **UN RTDG IMDG-Code** 3 ICAO-TI 3

14.4 Packing group

UN RTDG II IMDG-Code II ICAO-TI II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

Ethanol

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 1170 **Class** 3 **Packing group** II Danger label(s) 3



Special provisions (SP) 144

UN RTDG

Excepted quantities (EQ)

E2 UN RTDG

Limited quantities (LQ)

UN RTDG

Australia (en) Page 13 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ETHANOL

Particulars in the shipper's declaration UN1170, ETHANOL, 3, II, 13°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP) 144

Excepted quantities (EQ) E2

Limited quantities (LQ) 1 L

EmS F-E. S

EmS F-E, S-D

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Ethanol

Particulars in the shipper's declaration UN1170, Ethanol, 3, II

Danger label(s) 3



Special provisions (SP) A3, A58, A180

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
2-Butanone	78-93-3	Table II	2914.12

National inventories

Australia (en) Page 14 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS CICR CSCL-ENCS

Australian Inventory of Chemical Substances
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)
Korea Existing Chemicals Inventory
New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH registered substances

DSL ECSI IECSC INSQ ISHA-ENCS KECI

NZIoC

REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations		
BCF	Bioconcentration factor		
BOD	Biochemical Oxygen Demand		
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)		
Ceiling-C	Ceiling value		
COD	Chemical oxygen demand		
DGR	Dangerous Goods Regulations (see IATA/DGR)		
DNEL	Derived No-Effect Level		
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval		

Australia (en) Page 15 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

Abbr.	Descriptions of used abbreviations	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control	
Eye Dam.	Seriously damaging to the eye	
Eye Irrit.	Irritant to the eye	
Flam. Liq.	Flammable liquid	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
log KOW	n-Octanol/water	
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
ppm	Parts per million	
STEL	Short-term exposure limit	
STOT SE	Specific target organ toxicity - single exposure	
TWA	Time-weighted average	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	
WES	Safe Work Australia: Workplace exposure standards for airborne conatminants	

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

Australia (en) Page 16 / 17

acc. to Safe Work Australia - Code of Practice



o-Cresolphthaleine indicator solution 0,1 % in ethanol, denatured

article number: 1LAE

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 17 / 17