acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: **1P44** Version: **GHS 1.0 en**

date of compilation: 2022-04-06

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Article number

(20°C)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory and analytical use Laboratory chemical

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

Viscosity standard N7.5 ROTI®Calipure 14 cSt

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)

2.2	Label elements							
	Labelling							
	Signal word	Danger						
	Pictograms	Pictograms						
	GHS08							
	Hazard statements							
	H304	May be fatal if swallowe	d and enters airways					
	Precautionary	statements						
	Precautionary statements - response							
	P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician P331 Do NOT induce vomiting							
	Precautionary statements - storage							
	P405 Store locked up							
	Precautionary statements - disposal							
	P501	Dispose of contents/cont	ainer to industrial combustion plant					
	Hazardous ingredients for labelling: Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics							
2.3	Other hazards							

Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Hydrocarbons, C14- C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		≥ 50	Asp. Tox. 1 / H304 EUH066		

For full text of abbreviations: see SECTION 16

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: 1P44

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO $_2$), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: 1P44

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: 1P44

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: 1P44

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties Physical state liquid Colour acc. to product description Odour characteristic - like: - Gasoline Melting point/freezing point not determined Boiling point or initial boiling point and boiling 261 °C at 1,013 hPa range Flammability this material is combustible, but will not ignite readily Lower and upper explosion limit 0.6 vol% (LEL) - 7 vol% (UEL) 113 °C Flash point Auto-ignition temperature 210 °C (auto-ignition temperature (liquids and gases)) not relevant Decomposition temperature not determined pH (value) not determined Kinematic viscosity Solubility(ies) Water solubility (practically insoluble) Partition coefficient this information is not available Partition coefficient n-octanol/water (log value): 0.001 kPa at 20 °C Vapour pressure Density and/or relative density 0.85 ^g/_{cm³} at 20 °C Density information on this property is not available Relative vapour density Particle characteristics not relevant (liquid) Other safety parameters Oxidising properties none 9.2 Other information hazard classes acc. to GHS Information with regard to physical hazard

classes:

(physical hazards): not relevant

acc. to Safe Work Australia - Code of Practice



Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)

article number: 1P44

Other safety characteristics:

There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		oral	LD50	>5,000 ^{mg} / _{kg}	rat
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		inhalation: dust/mist	LC50	>5,266 ^{mg} / _{m³} / 4h	rat
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		dermal	LD50	>3,160 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: 1P44

Respiratory or skin sensitisation Shall not be classified as a respiratory or skin sensitiser. Germ cell mutagenicity Shall not be classified as germ cell mutagenic. Carcinogenicity Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

aspiration hazard

• If in eyes

Data are not available.

• If inhaled

Data are not available.

• If on skin

Data are not available.

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture					
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C14- C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		LL50	>1,028 ^{mg} / _l	fish	96 h

acc. to Safe Work Australia - Code of Practice



Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)

article number: 1P44

Aquatic toxicity (acute) of components of the mixture					
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C14- C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		EL50	>1,000 ^{mg} / _l	aquatic invertebrates	24 h

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Hydrocarbons, C14- C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		EL50	>5 ^{mg} /I	aquatic invertebrates	21 d
Hydrocarbons, C14- C18, n-alkanes, isoalkanes, cyclics, <2% aromatics		EC50	>100 ^{mg} / _l	microorganisms	3 h

Biodegradation

Data are not available.

12.2 Process of degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Hydrocarbons, C14-C18, n-al- kanes, isoalkanes, cyc- lics, <2% aro- matics		oxygen deple- tion	74 %	28 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: **1P44**

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

- 14.1 UN number
- 14.2 UN proper shipping name
- 14.3 Transport hazard class(es)
- 14.4 Packing group
- 14.5 Environmental hazards

not assigned

not subject to transport regulations

not assigned

not assigned

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

- **14.7** Transport in bulk according to Annex II of MARPOL and the IBC Code The cargo is not intended to be carried in bulk.
- 14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG) Not subject to transport regulations. UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: **1P44**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
EU	REACH Reg.	all ingredients are listed

Legend

REACH Reg. REACH registered substances

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Asp. Tox.	Aspiration hazard
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
PBT	Persistent, Bioaccumulative and Toxic
UEL	Upper explosion limit (UEL)

acc. to Safe Work Australia - Code of Practice

Viscosity standard N7.5 ROTI®Calipure 14 cSt (20°C)



article number: **1P44**

Abbr.	Descriptions of used abbreviations
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H304	May be fatal if swallowed and enters airways.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.