acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50 date of compilation: 2022-04-05 Version: GHS 2.0 en Revision: 2024-03-02

Replaces version of: 2022-04-05

Version: (GHS 1)

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### **Product identifier** 1.1

Identification of the substance Viscosity standard N15000 ROTI®Calipure

77000 cŠt (20°C)

Article number 1P50

CAS number 9003-29-6

Alternative name(s) Polybutylene (isobutylene/butene copolymer)

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for private purposes (household).

Food, drink and animal feedingstuffs.

#### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

sheet:

e-mail (competent person): sicherheit@carlroth.de

#### 1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16

#### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

Australia (en) Page 1 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

#### 2.2 Label elements

#### Labelling

Signal word Warning

Not required

**Pictograms** 

**Hazard statements** 

H227 Combustible liquid

#### **Precautionary statements**

#### **Precautionary statements - prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking P280 Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary statements - response**

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

#### Precautionary statements - storage

P403 Store in a well-ventilated place

# **Precautionary statements - disposal**

P501 Dispose of contents/container to industrial combustion plant

#### 2.3 Other hazards

This material is combustible, but will not ignite readily.

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

# **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

"UVCB substance" (substance of unknown or variable composition).

Name of substance Viscosity standard

CAS No 9003-29-6

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures



#### **General notes**

Take off contaminated clothing.

Australia (en) Page 2 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

#### **Following inhalation**

Provide fresh air.

#### Following skin contact

Rinse skin with water/shower.

#### Following eye contact

Rinse cautiously with water for several minutes.

#### Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

#### **Hazardous combustion products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), May produce toxic fumes of carbon monoxide if burning.

#### **5.3** Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

Australia (en) Page 3 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

# **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Provision of sufficient ventilation.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

#### **Incompatible substances or mixtures**

Observe hints for combined storage.

#### Consideration of other advice:

#### **Ventilation requirements**

Use local and general ventilation.

Australia (en) Page 4 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

#### 7.3 Specific end use(s)

No information available.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

**National limit values** 

**Occupational exposure limit values (Workplace Exposure Limits)** 

This information is not available.

#### 8.2 Exposure controls

Individual protection measures (personal protective equipment)

#### **Eye/face protection**





Use safety goggle with side protection.

#### Skin protection





#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

#### breakthrough times of the glove material

>480 minutes (permeation: level 6)

### other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Australia (en) Page 5 / 12

acc. to Safe Work Australia - Code of Practice

# ROTH

#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

#### **Respiratory protection**





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

#### **Environmental exposure controls**

Keep away from drains, surface and ground water.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state liquid
Colour clear

Odour odourless

Melting point/freezing point <-57 °C at 1,013 hPa (ECHA)

Boiling point or initial boiling point and boiling

range

202 °C (ECHA)

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 0.3 vol% (LEL) - 7.5 vol% (UEL)

Flash point 71 °C (ECHA)

Auto-ignition temperature 215 °C at 1,013 hPa (ECHA) (auto-ignition temper-

ature (liquids and gases))

Decomposition temperature not relevant
pH (value) not determined
Kinematic viscosity not determined
Dynamic viscosity 1.486 cP at 20 °C

Solubility(ies)

Water solubility  $<2.4 \,\mathrm{mg/l}$  at 20 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): 7.6 – 7.8 (pH value: 7, 20 °C) (ECHA)

Soil organic carbon/water (log KOC) 3.44 – 8.13 (ECHA)

Vapour pressure 0.11 bar at 37.8 °C

Density and/or relative density

Density  $0.895 \, {}^{\rm g}/{}_{\rm cm^3}$  at 20  ${}^{\rm o}{\rm C}$ 

Relative vapour density Information on this property is not available.

Australia (en) Page 6 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

There is no additional information.

Other safety characteristics: There is no additional information.

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

It's a reactive substance. Risk of ignition.

Risk of ignition. Vapours may form explosive mixtures with air.

#### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

#### 10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### 10.5 Incompatible materials

There is no additional information.

## 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

# **SECTION 11: Toxicological information**

# 11.1 Information on toxicological effects

#### Classification acc. to GHS

#### **Acute toxicity**

**Acute toxicity** 

Shall not be classified as acutely toxic.

Exposure route	Endpoint	Value	Species	Method	Source
inhalation: dust/ mist	LC50	<4,800 <sup>mg</sup> / <sub>m³</sub> /4h	rat		ECHA
oral	LD50	>10,000 <sup>mg</sup> / <sub>kg</sub>	rat		ECHA
dermal	LD50	>2,000 <sup>mg</sup> / <sub>kg</sub>	rat		ECHA

Australia (en) Page 7 / 12

acc. to Safe Work Australia - Code of Practice

# ROTH

#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### **Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### **Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

## **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

#### Symptoms related to the physical, chemical and toxicological characteristics

#### If swallowed

Data are not available.

#### • If in eyes

Data are not available.

#### • If inhaled

Data are not available.

#### • If on skin

Data are not available.

#### Other information

Health effects are not known.

#### 11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Toxic to aquatic life.

Australia (en) Page 8 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

Aquatic	toxicity	(acute)
---------	----------	---------

Endpoint	Value	Species	Source	Exposure time
EC50	>3.1 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	48 h

#### **Aquatic toxicity (chronic)**

Endpoint	Value	Species	Source	Exposure time
EC50	>10 <sup>g</sup> / <sub>l</sub>	microorganisms	ECHA	16 h

#### 12.2 Persistence and degradability

#### **Process of degradability**

Process	Degradation rate	Time
oxygen depletion	3 %	28 d
carbon dioxide generation	93.9 %	28 d

#### 12.3 Bioaccumulative potential

The substance fulfils the very bioaccumulative criterion.

n-octanol/water (log KOW)	7.6 – 7.8 (pH value: 7, 20 °C) (ECHA)
in octained traces (log trott)	7.6 7.6 (p. 1.6.6.7, 2.6 -c) (2.6.1.7)

## 12.4 Mobility in soil

Henry's law constant	701.4 <sup>Pa m³</sup> / <sub>mol</sub> at 20 °C (ECHA)
The Organic Carbon normalised adsorption coefficient	3.44 – 8.13 (ECHA)

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

#### 12.7 Other adverse effects

Data are not available.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

Australia (en) Page 9 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

#### Waste treatment of containers/packagings

Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

# **SECTION 14: Transport information**

17.1 ON HUILDEL	14.1	UN number	not subject to transport regulation
-----------------	------	-----------	-------------------------------------

14.2 UN proper shipping name not assigned
 14.3 Transport hazard class(es) not assigned
 14.4 Packing group not assigned

**14.5** Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulátions

#### 14.6 Special precautions for user

There is no additional information.

#### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

#### 14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

Not subject to transport regulations. UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

## National regulations(Australia)

#### Australian Inventory of Chemical Substances(AICS)

Substance is listed.

#### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Australia (en) Page 10 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

#### **National inventories**

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC Australian Inventory of Industrial Chemicals
CICR Chemical Inventory and Control Regulation
CSCL-ENCS
DSL Domestic Substances List (DSL)
ECSI EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC Inventory of Existing Chemical Substances Produced or Imported in China INSQ National Inventory of Chemical Substances
KECI Korea Existing Chemicals Inventory
NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.
REACH registered substances
TCSI Taiwan Chemical Substance Inventory
TSCA Toxic Substance Control Act

**TSCA** Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

## **SECTION 16: Other information**

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1		National inventories: change in the listing (table)	yes

Australia (en) Page 11 / 12

acc. to Safe Work Australia - Code of Practice



#### Viscosity standard N15000 ROTI®Calipure 77000 cSt (20°C)

article number: 1P50

# **Abbreviations and acronyms**

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

#### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.

#### **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 12 / 12