acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt **Hydrocarbon Oil**

date of compilation: 2022-09-28 article number: 1PL8 Version: GHS 1.0 en

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 **Product identifier**

Identification of the substance Single-Element Standard Solution ROTI®Star

1000 mg/l Sc in 75 cSt Hydrocarbon Oil

Article number 1PL8

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

Emergency telephone number 1.4

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

2.2 **Label elements**

Labelling

Signal	word	Danger

Page 1 / 12 Australia (en)

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

Pictograms

GHS08



Hazard statements

H304 May be fatal if swallowed and enters airways

Precautionary statements

Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P331 Do NOT induce vomiting

Precautionary statements - storage

P405 Store locked up

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Hazardous ingredients for labelling: Hydrocarbon Oil

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Hydrocarbon Oil	CAS No 8042-47-5	≥80	Asp. Tox. 1 / H304	\$	

For full text of abbreviations: see SECTION 16

Australia (en) Page 2 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

Australia (en) Page 3 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

Australia (en) Page 4 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Relevant DNELs of components of the mixture **CAS No Threshol Used** in **Exposure time** Name of sub-End-**Protection** goal, route of stance point d level exposure 164.6 mg/ 8042-47-5 DNEL human, inhalat-Hydrocarbon Oil chronic - systemic worker (industry) m^3 effects 8042-47-5 **DNEL** Hydrocarbon Oil 217.1 mg/ human, dermal worker (industry) chronic - systemic kg bw/day effects

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

≥0,3 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

Australia (en) Page 5 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt **Hydrocarbon Oil**

article number: 1PL8

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties 9.1

Physical state liquid Form viscous Colour brown

Odour characteristic Melting point/freezing point not determined Boiling point or initial boiling point and boiling

range

>218 °C at 1,013 hPa

Flammability this material is combustible, but will not ignite

readily

Lower and upper explosion limit not determined

115 °C Flash point

>325 °C (auto-ignition temperature (liquids and Auto-ignition temperature

gases))

Decomposition temperature not relevant pH (value) not determined not determined Kinematic viscosity

Solubility(ies)

Water solubility (practically insoluble)

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

not determined Vapour pressure

Australia (en) Page 6 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

Density and/or relative density

Density 0.862 ^g/_{cm³} at 20 °C

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

hazard classes acc. to GHS (physical hazards): not relevant

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Australia (en) Page 7 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

Acute toxicity estimate (A	ATE) of components	of the mixture
----------------------------	--------------------	----------------

Name of substance	CAS No	Exposure route	ATE
Hydrocarbon Oil	8042-47-5	inhalation: dust/mist	

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Hydrocarbon Oil	8042-47-5	oral	LD50	>5,000 ^{mg} / _{kg}	rat
Hydrocarbon Oil	8042-47-5	inhalation: dust/mist	LC50	>5 ^{mg} / _l /4h	rat
Hydrocarbon Oil	8042-47-5	dermal	LD50	>2,000 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

aspiration hazard

• If in eyes

Data are not available.

• If inhaled

Data are not available.

• If on skin

Data are not available.

Australia (en) Page 8 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Biodegradation

Data are not available.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

Australia (en) Page 9 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

SECTION 14: Transport information

14.1 UN number not subject to transport regulations

14.2 UN proper shipping name not assigned
 14.3 Transport hazard class(es) not assigned
 14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

Not subject to transport regulations. UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
KR	KECI	all ingredients are listed

Australia (en) Page 10 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt **Hydrocarbon Oil**

article number: 1PL8

Country	Inventory	Status
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals
CICR Chemical Inventory and Control Regulation
DSL Domestic Substances List (DSL)
ECSI EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC Inventory of Existing Chemical Substances Produced or Imported in China
INSQ National Inventory of Chemical Substances
KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

TCSI TSCA Taiwan Chemical Substance Inventory Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
Asp. Tox.	Aspiration hazard	
ATE	Acute Toxicity Estimate	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
IMDG	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
NLP	No-Longer Polymer	

Australia (en) Page 11 / 12

acc. to Safe Work Australia - Code of Practice



Single-Element Standard Solution ROTI®Star 1000 mg/l Sc in 75 cSt Hydrocarbon Oil

article number: 1PL8

Abbr.	Descriptions of used abbreviations	
PBT	Persistent, Bioaccumulative and Toxic	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H304	May be fatal if swallowed and enters airways.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 12 / 12