Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: **1XX9** Version: **1.0 en**

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Article number

Registration number (REACH)

Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in n-hexane

1XX9

not relevant (mixture)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

| Section | Hazard class | Cat- egory | Hazard class and category | Hazard statement |
|---------|---|---------------|---------------------------|---------------------|
| 2.6 | Flammable liquid | 2 | Flam. Liq. 2 | H225 |
| 3.2 | Skin corrosion/irritation | 2 | Skin Irrit. 2 | H315 |
| 3.6 | Carcinogenicity | 1B | Carc. 1B | H350 |
| 3.7 | Reproductive toxicity | 2 | Repr. 2 | H361f |
| 3.8D | Specific target organ toxicity - single exposure (narcotic effects, drowsiness) | 3 | STOT SE 3 | H336 |
| 3.9 | Specific target organ toxicity - repeated exposure | 2 | STOT RE 2 | H373 |
| 3.10 | Aspiration hazard | 1 | Asp. Tox. 1 | H304 |
| 4.1C | Hazardous to the aquatic environment - chronic hazard | 2 | Aquatic Chronic 2 | H411 |



date of compilation: 28.09.2022

® ROTH

Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word Danger

Pictograms

GHS02, GHS07, GHS08, GHS09



Hazard statements

| H225 H304 | Highly flammable liquid and vapour May be fatal if swallowed and enters airways |
|--------------|---|
| H315 | Causes skin irritation |
| H336 | May cause drowsiness or dizziness |
| H350 | May cause cancer |
| H361f | Suspected of damaging fertility |
| H373 | May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled) |
| H411 | Toxic to aquatic life with long lasting effects |

Precautionary statements

Precautionary statements - prevention

P280

Wear protective gloves/protective clothing/eye protection/face protection

For professional users only

Hazardous ingredients for labelling:

n-Hexane, Lubricating oils

Labelling of packages where the contents do not exceed 125 ml

Signal word: Danger



| H304 | May be fatal if swallowed and enters airways. |
|-----------|--|
| H350 | May cause cancer. |
| H361f | Suspected of damaging fertility. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| contains: | n-Hexane, Lubricating oils |

according to Regulation (EC) No. 1907/2006 (REACH)

Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

2.3 **Other hazards**

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 **Substances**

not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

| Name of sub- stance | Identifier | Wt% | Classification acc. to GHS | Pictograms | Notes |
|------------------------|--|------|--|------------|-----------------|
| n-Hexane | CAS No 110-54-3 EC No 203-777-6 Index No 601-037-00-0 REACH Reg. No 01-2119480412- 44-xxxx | ≥ 50 | Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361f STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411 | | GHS-HC IOELV |
| Lubricating oils | CAS No 74869-22-0 EC No 278-012-2 Index No 649-484-00-0 | 1 | Carc. 1B / H350 | | GHS-HC L(a) |
| Fuels, diesel | CAS No 68334-30-5 EC No 269-822-7 Index No 649-224-00-6 | 1 | Carc. 2 / H351 | | GHS-HC N(a) |

Notes

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/

IOELV:

2008/EC, Annex VI) Substance with a community indicative occupational exposure limit value The classification as a carcinogen is mandatory. The substance contains at least 3 % DMSO extract The classification as a carcinogen is mandatory. The full refining history is not known and the substance from which it L(a): N(a): is produced is a carcinogen

| Name of sub- stance | Identifier | Specific Conc. Limits | M-Factors | ATE | Exposure route |
|------------------------|--|--------------------------|------------------|-----|-------------------|
| n-Hexane | CAS No 110-54-3 EC No 203-777-6 Index No 601-037-00-0 | STOT RE 2; H373: C ≥ 5 % | - | - | |



according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: **1XX9**

| | me of sub- stance | Identifier | Specific Conc. Limits | M-Factors | ATE | Exposure route |
|------|----------------------|--|-----------------------|------------------|---------------------------------------|---------------------------|
| Lubr | ricating oils | CAS No 74869-22-0 EC No 278-012-2 Index No 649-484-00-0 | - | - | 2,18 ^{mg} / _l /4h | inhalation: dust/ mist |

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Do not induce vomiting. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Dizziness, Nausea, Fatigue, Varying degrees of pulmonary injury, Irritation, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: **1XX9**

Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.



according to Regulation (EC) No. 1907/2006 (REACH)

Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 2 – 8 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters National limit values



according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

Occupational exposure limit values (Workplace Exposure Limits)

| - | - | | | - | - | | | | - | | |
|-----------------|---------------|----------|-----------------|----------------------|--------------------|-----------------------|---------------------|--------------------------------|-------------------------------|---------------|----------------|
| Cou ntr y | Name of agent | CAS No | Identi- fier | TW A [pp m] | TWA [mg/ m³] | STE L [pp m] | STEL [mg/ m³] | Ceil ing- C [pp m] | Ceil- ing-C [mg/ m³] | Nota- tion | Source |
| EU | n-hexane | 110-54-3 | IOELV | 20 | 72 | | | | | | 2006/15/ EC |
| MT | n-hexane | 110-54-3 | OELV | 20 | 72 | | | | | | CAP. 424 |

Notation

Ceiling-C STEL

TWA

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

| Relevant DNELs of components of the mixture | | | | | | | | |
|---|------------|---------------|-----------------------------|--|-------------------|-------------------------------|--|--|
| Name of sub- stance | CAS No | End- point | Threshol d level | Protection goal, route of exposure | Used in | Exposure time | | |
| n-Hexane | 110-54-3 | DNEL | 75 mg/m³ | human, inhalat- ory | worker (industry) | chronic - systemic effects | | |
| n-Hexane | 110-54-3 | DNEL | 11 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects | | |
| Fuels, diesel | 68334-30-5 | DNEL | 68,34 mg/ m ³ | human, inhalat- ory | worker (industry) | chronic - systemic effects | | |
| Fuels, diesel | 68334-30-5 | DNEL | 4.288 mg/ m ³ | human, inhalat- ory | worker (industry) | acute - systemic effects | | |
| Fuels, diesel | 68334-30-5 | DNEL | 2,91 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects | | |

Relevant PNECs of components of the mixture Name of sub-**CAS No** Threshol Environmental End-Organism **Exposure time** stance point d level compartment 9,33 ^{mg}/_{kg} Lubricating oils 74869-22-0 PNEC aquatic organshort-term (single water isms instance)

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

according to Regulation (EC) No. 1907/2006 (REACH)

Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

• material thickness

≥0,4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 $^{\circ}$ C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| Physical state | liquid |
|--|--|
| Colour | colourless |
| Odour | characteristic |
| Melting point/freezing point | -95 °C at 1.013 hPa |
| Boiling point or initial boiling point and boiling range | 69 °C |
| Flammability | flammable liquid in accordance with GHS criteria |
| Lower and upper explosion limit | 1,1 vol% (LEL) - 7,5 vol% (UEL) |



according to Regulation (EC) No. 1907/2006 (REACH)

Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane



article number: 1XX9

| | Flash point | -26 °C |
|-----|---|--|
| | Auto-ignition temperature | 240 °C |
| | Decomposition temperature | not relevant |
| | pH (value) | not determined |
| | Kinematic viscosity | not determined |
| | Solubility(ies) | |
| | Water solubility | 0,1 ^g / _l at 20 °C |
| | Partition coefficient | |
| | Partition coefficient n-octanol/water (log value): | this information is not available |
| | Vapour pressure | 160 hPa at 20 °C |
| | Density and/or relative density | |
| | Density | ~ 0,66 ^g / _{cm³} at 20 °C |
| | Relative vapour density | information on this property is not available |
| | Particle characteristics | not relevant (liquid) |
| | Other safety parameters | |
| | Oxidising properties | none |
| 9.2 | Other information | |
| | Information with regard to physical hazard classes: | There is no additional information. |
| | Other safety characteristics: | |
| | Temperature class (EU, acc. to ATEX) | T3 Maximum permissible surface temperature on the equipment: 200°C |

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Chlorine, Iodine, Peroxides, Nitrogen oxides (NOx), => Explosive properties

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

| Acute toxicity estimate (ATE) of components of the mixture | | | | | |
|---|------------|-----------------------|---------------------------------------|--|--|
| Name of substance CAS No Exposure route ATE | | | | | |
| Lubricating oils | 74869-22-0 | inhalation: dust/mist | 2,18 ^{mg} / _l /4h | | |

Acute toxicity of components of the mixture

| Name of substance | CAS No | Exposure route | Endpoint | Value | Species |
|-------------------|------------|--------------------------|----------|---------------------------------------|---------|
| n-Hexane | 110-54-3 | inhalation: va- pour | LC50 | 185 ^{mg} / _l /4h | rat |
| n-Hexane | 110-54-3 | oral | LD50 | 25.000 ^{mg} / _{kg} | rat |
| n-Hexane | 110-54-3 | dermal | LD50 | >2.000 ^{mg} / _{kg} | rabbit |
| Lubricating oils | 74869-22-0 | oral | LD50 | >5.000 ^{mg} / _{kg} | rat |
| Lubricating oils | 74869-22-0 | inhalation: dust/mist | LC50 | 2,18 ^{mg} / _l /4h | rat |
| Lubricating oils | 74869-22-0 | dermal | LD50 | >2.000 ^{mg} / _{kg} | rabbit |

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

according to Regulation (EC) No. 1907/2006 (REACH)



article number: 1XX9

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).

| Hazard category | Target organ | Exposure route |
|-----------------|----------------|----------------|
| 2 | nervous system | if inhaled |

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, nausea, aspiration hazard

• If in eyes

corneal opacity

• If inhaled

vertigo, dizziness, fatigue, headache, irritant effects, fatigue, narcosis

• If on skin

risk of absorption via the skin, causes skin irritation, repeated exposure may cause skin dryness or cracking

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

11.3 Information on other hazards

There is no additional information.



according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in n-hexane

article number: 1XX9

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

| quatic toxicity (acute) of components of the mixture | | | | | | |
|--|------------|----------|--------------------------------------|-----------------------|------------------|--|
| Name of sub- stanceCAS Non-Hexane110-54-3 | | Endpoint | Value | Species | Exposure time | |
| | | LL50 | 12,51 ^{mg} / _l | fish | 96 h | |
| n-Hexane | 110-54-3 | EL50 | 21,85 ^{mg} / _l | aquatic invertebrates | 48 h | |
| Lubricating oils 74869-22-0 | | LL50 | >100 ^{mg} / _l | fish | 96 h | |
| Lubricating oils | 74869-22-0 | EL50 | >10.000 ^{mg} / _l | aquatic invertebrates | 48 h | |

Aquatic toxicity (chronic) of components of the mixture

| Name of sub- stance | CAS No | Endpoint | Value | Species | Exposure time |
|------------------------|------------|----------|--------------------------------------|-----------------------|------------------|
| Lubricating oils | 74869-22-0 | LL50 | >10.000 ^{mg} / _l | aquatic invertebrates | 24 h |
| Lubricating oils | 74869-22-0 | EL50 | >10.000 ^{mg} / _l | aquatic invertebrates | 24 h |

Biodegradation

Data are not available.

12.2 Process of degradability

Degradability of components of the mixture

| Name of substance | CAS No | Process | Degrada- tion rate | Time | Method | Source |
|-------------------|------------|-----------------------|-----------------------|------|--------|--------|
| n-Hexane | 110-54-3 | oxygen deple- tion | 83 % | 10 d | | ECHA |
| Fuels, diesel | 68334-30-5 | oxygen deple- tion | 57,5 % | 28 d | | ECHA |

12.3 Bioaccumulative potential

Data are not available.

| Bioaccumulative potential of components of the mixture | | | | | | |
|--|----------|-------|------------------------|----------|--|--|
| Name of substance | CAS No | BCF | Log KOW | BOD5/COD | | |
| n-Hexane | 110-54-3 | 501,2 | 4 (pH value: 7, 20 °C) | | | |

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

- HP 3 flammable
- HP 5 specific target organ toxicity (STOT)/aspiration toxicity
- HP7 carcinogenic
- **HP 10** toxic for reproduction **HP 14** ecotoxic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number ADR UN 1208 IMDG-Code UN 1208 ICAO-TI UN 1208 14.2 UN proper shipping name ADR HEXANES IMDG-Code **HEXANES** ICAO-TI Hexanes 14.3 Transport hazard class(es) ADR 3 3 IMDG-Code

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: **1XX9**

| | ICAO-TI | 3 |
|------|--|--------------------------------------|
| 14.4 | Packing group | |
| | ADR | II |
| | IMDG-Code | II |
| | ICAO-TI | II |
| 14.5 | Environmental hazards | hazardous to the aquatic environment |
| | Environmentally hazardous substance (aquatic environment): | n-Hexane |

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

| Proper shipping name | HEXANES |
|---|---|
| Particulars in the transport document | UN1208, HEXANES, 3, II, (D/E), environmentally hazardous |
| Classification code | F1 |
| Danger label(s) | 3, "Fish and tree" |
| | |
| Environmental hazards | Yes (hazardous to the aquatic environment) |
| Excepted quantities (EQ) | E2 |
| Limited quantities (LQ) | 1 L |
| Transport category (TC) | 2 |
| Tunnel restriction code (TRC) | D/E |
| Hazard identification No | 33 |
| International Maritime Dangerous Goods Code | (IMDG) - Additional information |
| Proper shipping name | HEXANES |
| Particulars in the shipper's declaration | UN1208, HEXANES, 3, II, -26°C c.c., MARINE POL- LUTANT |
| Marine pollutant | yes (P) (hazardous to the aquatic environment) |
| Danger label(s) | 3, "Fish and tree" |
| | |
| Special provisions (SP) | - |

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

| Excepted quantities (EQ) | E2 |
|--|---|
| Limited quantities (LQ) | 1 L |
| EmS | F-E, S-D |
| Stowage category | E |
| International Civil Aviation Organization (ICA | O-IATA/DGR) - Additional information |
| Proper shipping name | Hexanes |
| Particulars in the shipper's declaration | UN1208, Hexanes, 3, II |
| Environmental hazards | Yes (hazardous to the aquatic environment) |
| Danger label(s) | 3 |
| | |
| Excepted quantities (EQ) | E2 |
| Limited quantities (LQ) | 1 L |
| | |

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1 **Relevant provisions of the European Union (EU)**

Restrictions according to REACH, Annex XVII

| Dangerous substances with restrictions (REACH, Annex XVII) | | | | | | |
|--|--|--------|-------------|----|--|--|
| Name of substance | Name acc. to inventory | CAS No | Restriction | No | | |
| Standard mixture of mineral oils | this product meets the criteria for classification in accordance with Reg- ulation No 1272/2008/EC | | R3 | 3 | | |
| Lubricating oils | carcinogenic | | R28-30 | 28 | | |
| Fuels, diesel | carcinogenic | | R28-30 | 28 | | |
| Fuels, diesel | substances in tattoo inks and perman- ent make-up | | R75 | 75 | | |
| n-Hexane | flammable / pyrophoric | | R40 | 40 | | |
| n-Hexane | substances in tattoo inks and perman- ent make-up | | R75 | 75 | | |

Legend

R28-30 1. Shall not be placed on the market, or used,

- as substances. - as constituents of other substances, or,

- in mixtures,

for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than:

- either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or, - the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of

such substances and mixtures is marked visibly, legibly and indelibly as follows:

Restricted to professional users'. 2. By way of derogation, paragraph 1 shall not apply to:

(a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC;
(b) cosmetic products as defined by Directive 76/768/EEC;
(c) the following fuels and oil products:
motor fuels which are covered by Directive 98/70/EC,

Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

| Leger | nd |
|-------|--|
| - 5 - | - mineral oil products intended for use as fuel in mobile or fixed combustion plants, |
| | - fuels sold in closed systems (e.g. liquid gas bottles); |
| | (d) artists' paints covered by Regulation (EC) No 1272/2008; |
| | (e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. When |
| | a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date; |
| | (f) devices covered by Regulation (EU) 2017/745. |
| R3 | 1. Shall not be used in: |
| КЭ | |
| | - ornamental articles intended to produce light or colour effects by means of different phases, for example in orna- |
| | mental lamps and ashtrays, |
| | - tricks and jokes, |
| | - games for one or more participants, or any article intended to be used as such, even with ornamental aspects, |
| | 2. Articles not complying with paragraph 1 shall not be placed on the market. |
| | 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume |
| | or both, if they: |
| | — can be used as fuel in decorative oil lamps for supply to the general public, and |
| | — present an aspiration hazard and are labelled with H304. |
| | 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the |
| | European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation |
| | (CEN). |
| | 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and pac |
| | aging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requi |
| | ments are met: |
| | (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked a |
| | follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp |
| | – or even sucking the wick of lamps – may lead to life-threatening lung damage"; |
| | (b) grill lighter fluids, Jabelled with H304, intended for supply to the general public are legibly and indelibly marked l |
| | 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage'; |
| | (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black |
| | opaque containers not exceeding 1 litre by 1 December 2010.; |
| R40 | 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intende |
| | for supply to the general public for entertainment and decorative purposes such as the following: |
| | - metallic glitter intended mainly for decoration, |
| | - artificial snow and frost, |
| | - 'whoopee' cushions, |
| | - silly string aerosols, |
| | - imitation excrement, |
| | - horns for parties, |
| | - decorative flakes and foams, |
| | - artificial cobwebs, |
| | - stink bombs. |
| | 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling |
| | substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referre |

Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with: 'For professional users only'.
 By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
 The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

R75



graph.





Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in n-hexane

article number: 1XX9

Legend

8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

None of the ingredients are listed.

Seveso Directive

| 2012/ | 2012/18/EU (Seveso III) | | | | | | |
|---|--|--|-------|--|--|--|--|
| No Dangerous substance/hazard categories Qualifying quantity (tonnes) for the application of lower and upper-tier re- quirements | | | Notes | | | | |
| E2 | E2 environmental hazards (hazardous to the aquatic en- vironment, cat. 2) 200 500 | | 57) | | | | |

Notation

57) Hazardous to the Aquatic Environment in category Chronic 2

Deco-Paint Directive

| VOC content | 0,3 – <1 % 6,6 ^g / _l |
|-------------|---|
|-------------|---|

Industrial Emissions Directive (IED)

| VOC content | 100 % |
|-------------|---------------------|
| VOC content | 660 ^g /l |

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

| Name of substance | Name acc. to inventory | CAS No | Listed in | Remarks |
|-------------------|--|--------|-----------|---------|
| Lubricating oils | Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment | | a) | |

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: **1XX9**

| List of pollutants (WFD) | | | | |
|--------------------------|--|--------|-----------|---------|
| Name of substance | Name acc. to inventory | CAS No | Listed in | Remarks |
| Fuels, diesel | Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment | | a) | |
| n-Hexane | Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment | | a) | |

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

| Country | Inventory | Status |
|---------|------------|--------------------------------|
| AU | AIIC | not all ingredients are listed |
| CA | DSL | all ingredients are listed |
| CN | IECSC | all ingredients are listed |
| EU | ECSI | all ingredients are listed |
| EU | REACH Reg. | all ingredients are listed |
| JP | CSCL-ENCS | not all ingredients are listed |
| JP | ISHA-ENCS | not all ingredients are listed |
| | | |

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in n-hexane

article number: 1XX9

| Country | Inventory | Status |
|---------|-----------|--------------------------------|
| KR | KECI | all ingredients are listed |
| MX | INSQ | not all ingredients are listed |
| NZ | NZIoC | all ingredients are listed |
| РН | PICCS | not all ingredients are listed |
| TR | CICR | all ingredients are listed |
| TW | TCSI | all ingredients are listed |
| US | TSCA | not all ingredients are listed |

Legend

| Legena | |
|------------|---|
| AIIC | Australian Inventory of Industrial Chemicals |
| CICR | Chemical Inventory and Control Regulation |
| CSCL-ENCS | List of Existing and New Chemical Substances (CSCL-ENCS) |
| DSL | Domestic Substances List (DSL) |
| ECSI | EC Substance Inventory (EINECS, ELINCS, NLP) |
| IECSC | Inventory of Existing Chemical Substances Produced or Imported in China |
| INSQ | National Inventory of Chemical Substances |
| ISHA-ENCS | Inventory of Existing and New Chemical Substances (ISHA-ENCS) |
| KECI | Korea Existing Chemicals Inventory |
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances (PICCS) |
| REACH Reg. | REACH registered substances |
| TCSI | Taiwan Chemical Substance Inventory |
| TSCA | Toxic Substance Control Act |
| | |

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations | | |
|-----------------|---|--|--|
| 2006/15/EC | Commission Directive establishing a second list of indicative occupational exposure limit values in imple- mentation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC | | |
| ADN | Accord européen relatif au transport international des marchandises dangereuses par voies de naviga- tion intérieures (European Agreement concerning the International Carriage of Dangerous Goods by In- land Waterways) | | |
| ADR | Accord relatif au transport international des marchandises dangereuses par route (Agreement concern- ing the International Carriage of Dangerous Goods by Road) | | |
| Aquatic Chronic | Hazardous to the aquatic environment - chronic hazard | | |
| Asp. Tox. | Aspiration hazard | | |
| ATE | Acute Toxicity Estimate | | |
| BCF | Bioconcentration factor | | |
| BOD | Biochemical Oxygen Demand | | |
| CAP. 424 | Occupational Health and Safety Authority Act (CAP. 424) | | |
| Carc. | Carcinogenicity | | |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) | | |
| Ceiling-C | Ceiling value | | |

according to Regulation (EC) No. 1907/2006 (REACH)

Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in n-hexane



article number: 1XX9

| Abbr. | Descriptions of used abbreviations |
|------------|--|
| CLP | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures |
| COD | Chemical oxygen demand |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC No | The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identi- fier of substances commercially available within the EU (European Union) |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| EL50 | Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms |
| ELINCS | European List of Notified Chemical Substances |
| EmS | Emergency Schedule |
| Flam. Liq. | Flammable liquid |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions |
| ΙΑΤΑ | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| index No | The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 |
| IOELV | Indicative occupational exposure limit value |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |
| LD50 | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval |
| LEL | Lower explosion limit (LEL) |
| LL50 | Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality |
| log KOW | n-Octanol/water |
| NLP | No-Longer Polymer |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals |
| Repr. | Reproductive toxicity |
| RID | Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail) |

according to Regulation (EC) No. 1907/2006 (REACH)



Standard mixture of mineral oils 10 000 mg/l Mineral oil and diesel in nhexane

article number: 1XX9

| Abbr. | Descriptions of used abbreviations |
|-------------|--|
| Skin Corr. | Corrosive to skin |
| Skin Irrit. | Irritant to skin |
| STEL | Short-term exposure limit |
| STOT RE | Specific target organ toxicity - repeated exposure |
| STOT SE | Specific target organ toxicity - single exposure |
| SVHC | Substance of Very High Concern |
| TWA | Time-weighted average |
| UEL | Upper explosion limit (UEL) |
| VOC | Volatile Organic Compounds |
| vPvB | Very Persistent and very Bioaccumulative |

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|-------|--|
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H350 | May cause cancer. |
| H351 | Suspected of causing cancer. |
| H361f | Suspected of damaging fertility. |
| H373 | May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled). |
| H411 | Toxic to aquatic life with long lasting effects. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.