acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: **1YP2** date of compilation: 2023-01-05 Version: **GHS 1.0 en**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance Multi-Element MISA ICP-OES-Standard Solution 1

ROTI®Star 18 elements in 5 % HNO₃

Article number 1YP2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for squirting or spraying. Do not use

for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private

purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	3.2 Skin corrosion/irritation		Skin Corr. 1B	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

Australia (en) Page 1 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

Supplemental hazard information

Code	Supplemental hazard information
EUH071	corrosive to the respiratory tract

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS05



Hazard statements

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

Precautionary statements

Precautionary statements - prevention

P260 Do not breathe dusts or mists P280 Wear eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P390 Absorb spillage to prevent material damage

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Hazardous ingredients for labelling: Nitric acid ...% [C ≤ 70 %]

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Australia (en) Page 2 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Nitric acid% [C ≤ 70 %]	CAS No 7697-37-2	5	Ox. Liq. 3 / H272 Met. Corr. 1 / H290 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 EUH071		B(a)

Notes

B(a): The classification refers to an aqueous solution

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Gastric perforation, Risk of serious damage to eyes, Risk of blindness, Cough, Dyspnoea, Pulmonary oedema

4.3 Indication of any immediate medical attention and special treatment needed

none

Australia (en) Page 3 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Australia (en) Page 4 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provide adequate ventilation as well as local exhaustion at critical locations. Handle and open container with care. Clear contaminated areas thoroughly.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

Conditions for safe storage, including any incompatibilities 7.2

Store in a well-ventilated place. Keep container tightly closed. Keep only in original container. May cause decomposition by long-term light influence.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

UV-radiation/sunlight, contact with air/oxygen

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	nitric acid	7697-37- 2	WES	2	5.2	4	10				WES

Notation

Ceiling-C STEL

TWA

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)
Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection. Wear face protection.

Page 5 / 14 Australia (en)

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

FKM (fluoro rubber), Butyl caoutchouc (butyl rubber)

material thickness

0,5 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: NO-P3 (against nitrous gases and particles, colour code: Blue/White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid Colour clear

Odour characteristic Melting point/freezing point not determined Boiling point or initial boiling point and boiling

range

83 °C at 1,013 hPa

non-combustible Flammability Lower and upper explosion limit not determined

Australia (en) Page 6 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

Flash point not determined
Auto-ignition temperature not determined
Decomposition temperature not relevant
pH (value) <2 (20 °C)

Kinematic viscosity not determined

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure 23 hPa at 20 °C

Density and/or relative density

Density $\sim 1 \, {\rm g/_{cm^3}}$ at 20 °C

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Corrosive to metals category 1: corrosive to metals

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Australia (en) Page 7 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

10.3 Possibility of hazardous reactions

Violent reaction with: Acetone, Aldehydes, Alkali (lye), Alkali metals, Alcohols, Formic acid, Amines, Ammonia (NH3), Aniline, Combustible materials, Dichloromethane, Alkaline earth metal, Acetic anhydride, Hydrozarbons, Metal powder, Nitriles, Reducing agents, Strong alkali, Hydrogen peroxide,

=> Explosive properties

10.4 Conditions to avoid

UV-radiation/sunlight. Keep away from heat.

10.5 Incompatible materials

different metals

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: vapour	>2.65 ^{mg} / _l /4h

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: va- pour	LC50	>2.65 ^{mg} / _l /4h	rat

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Australia (en) Page 8 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

If inhaled

corrosive to the respiratory tract, cough, Dyspnoea, pulmonary oedema

• If on skin

causes severe burns, causes poorly healing wounds

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

Australia (en) Page 9 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H8 Corrosives

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 2031
IMDG-Code	UN 2031
ICAO-TI	UN 2031

14.2 UN proper shipping name

UN RTDG	NITRIC ACID
IMDG-Code	NITRIC ACID
ICAO-TI	Nitric acid

14.3 Transport hazard class(es)

UN RTDG	8
IMDG-Code	8
ICAO-TI	8

14.4 Packing group

UN RTDG	II
IMDG-Code	II
ICAO-TI	II

Australia (en) Page 10 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 2031
Class 8
Packing group II
Danger label(s) 8



Special provisions (SP)

UN RTDG

Excepted quantities (EQ) E2 UN RTDG

Limited quantities (LQ) 1 L

1 L UN RTDG

Emergency Action Code 2R

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name NITRIC ACID

Particulars in the shipper's declaration UN2031, NITRIC ACID, 8, II

Marine pollutant Danger label(s) 8



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-A, S-B

Stowage category D

Segregation group 1 - Acids

Australia (en) Page 11 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Nitric acid

Particulars in the shipper's declaration UN2031, Nitric acid, 8, II

Danger label(s)



Excepted quantities (EQ) E2 0,5 L Limited quantities (LQ)

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AIIC CICR

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) CSCL-ENCS

DSL ECSI

List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Korea Existing Chemicals Inventory
Non-domestic Substances List (NDSL)
New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)

Australia (en) Page 12 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 $\%~\text{HNO}_3$

article number: 1YP2

Legend

REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 get lethality during a specified time interval
Met. Corr.	Substance or mixture corrosive to metals
NLP	No-Longer Polymer
Ox. Liq.	Oxidising liquid
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit

Australia (en) Page 13 / 14

acc. to Safe Work Australia - Code of Practice



Multi-Element MISA ICP-OES-Standard Solution 1 ROTI®Star 18 elements in 5 % HNO₃

article number: 1YP2

Abbr.	Descriptions of used abbreviations
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 14 / 14