

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: **1YXX**  
Version: **GHS 1.0 en**

date of compilation: 2023-02-28

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Identification of the substance **PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml**

Article number 1YXX

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use  
Laboratory chemical

Uses advised against: Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

#### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0  
**Telefax:** +49 (0) 721 - 56 06 149  
**e-mail:** sicherheit@carlroth.de  
**Website:** www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** sicherheit@carlroth.de

#### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labelling

#### Signal word

**Danger**

#### Pictograms

GHS02, GHS07,  
GHS08



#### Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H373	May cause damage to organs through prolonged or repeated exposure

#### Precautionary statements

##### Precautionary statements - prevention

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P260	Do not breathe dust/fume/gas/mist/vapours/spray

##### Precautionary statements - response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of soap and water
P331	Do NOT induce vomiting
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

##### Precautionary statements - storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed
P403+P235	Store in a well-ventilated place. Keep cool

**Hazardous ingredients for labelling:** Isooctane, Polychlorobiphenyls (PCB)

## 2.3 Other hazards

### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

### Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

not relevant (mixture)

#### 3.2 Mixtures

##### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Isooctane	CAS No 540-84-1	99 - < 100	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304		
Polychlorobiphenyls (PCB)	CAS No 1336-36-3	< 0.01	STOT RE 2 / H373		

For full text of abbreviations: see SECTION 16

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures



##### General notes

Take off contaminated clothing.

##### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

##### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

##### Following ingestion

Rinse mouth. Do not induce vomiting. Observe aspiration hazard if vomiting occurs. Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Drowsiness, Dizziness, Narcosis,  
Following skin contact: Irritation,  
After eye contact: Irritant effects,  
Following ingestion: Aspiration hazard

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), May produce toxic fumes of carbon monoxide if burning.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep in a cool place.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### Ventilation requirements

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 2 – 8 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Isooctane	540-84-1	DNEL	2,035 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Isooctane	540-84-1	DNEL	773 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

### 8.2 Exposure controls

#### Individual protection measures (personal protective equipment)

##### Eye/face protection



Use safety goggles with side protection.

##### Skin protection



##### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

##### • type of material

NBR (Nitrile rubber)

##### • material thickness

>0,3 mm

##### • breakthrough times of the glove material


>480 minutes (permeation: level 6)

##### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

##### Respiratory protection



# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	like: - Gasoline
Melting point/freezing point	-107 °C
Boiling point or initial boiling point and boiling range	99.2 °C at 1,013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	45 g/m <sup>3</sup> (LEL) - 290 g/m <sup>3</sup> (UEL) / 1 vol% (LEL) - 6 vol% (UEL)
Flash point	-12 °C
Auto-ignition temperature	418 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Dynamic viscosity	0.5 mPa s at 20 °C
<u>Solubility(ies)</u>	
Water solubility	(poorly soluble (1 till < 10 mg/l))
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	this information is not available
Vapour pressure	28 hPa at 20 °C
<u>Density and/or relative density</u>	
Density	0.69 g/cm <sup>3</sup> at 15 °C
Relative vapour density	3.9 (air = 1)
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

### 9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Maximum explosion pressure 9 bar

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

#### If heated

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

different plastics

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

#### Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful in contact with skin or if inhaled.

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Isooctane	540-84-1	oral	LD50	>5,000 mg/kg	rat
Isooctane	540-84-1	inhalation: vapour	LC50	>33.52 mg/l/4h	rat



# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Isooctane	540-84-1	dermal	LD50	>2,000 mg/kg	rabbit

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

vomiting, aspiration hazard

#### • If in eyes

causes slight to moderate irritation

#### • If inhaled

drowsiness, dizziness, fatigue, narcosis

#### • If on skin

causes skin irritation

#### • Other information

none

## 11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

### SECTION 12: Ecological information

#### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Isooctane	540-84-1	LL50	18.4 mg/l	fish	96 h
Isooctane	540-84-1	LC50	0.11 mg/l	fish	96 h
Isooctane	540-84-1	EC50	0.4 mg/l	aquatic invertebrates	48 h
Isooctane	540-84-1	EL50	2.4 mg/l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Isooctane	540-84-1	EL50	1.6 mg/l	aquatic invertebrates	21 d
Isooctane	540-84-1	EC50	0.23 mg/l	aquatic invertebrates	21 d

#### 12.2 Persistence and degradability

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
Isooctane	540-84-1	oxygen depletion	61.81 %	70 d		ECHA

#### 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Isooctane	540-84-1	231	4.08	

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0,1\%$ .

#### 12.7 Other adverse effects

Data are not available.

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### Relevant provisions relating to waste(Basel Convention)

#### Properties of waste which render it hazardous

H3 Flammable liquids  
H11 Toxic (Delayed or chronic)

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## SECTION 14: Transport information

### 14.1 UN number

UN RTDG	UN 1262
IMDG-Code	UN 1262
ICAO-TI	UN 1262

### 14.2 UN proper shipping name

UN RTDG	OCTANES
IMDG-Code	OCTANES
ICAO-TI	Octanes

### 14.3 Transport hazard class(es)

UN RTDG	3
IMDG-Code	3
ICAO-TI	3

### 14.4 Packing group

UN RTDG	II
IMDG-Code	II
ICAO-TI	II

### 14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment):	Isooctane

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

### 14.6 Special precautions for user

There is no additional information.

### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

#### Transport information National regulations Additional information (UN RTDG)

UN number	1262
Class	3
Environmental hazards	Yes Hazardous to the aquatic environment
Packing group	II
Danger label(s)	3 Fish and tree



Special provisions (SP)	- UN RTDG
Excepted quantities (EQ)	E2 UN RTDG
Limited quantities (LQ)	1 L UN RTDG
Emergency Action Code	3YE

#### International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	OCTANES
Particulars in the shipper's declaration	UN1262, OCTANES, 3, II, -12°C c.c., MARINE POLLUTANT
Marine pollutant	yes (P) (hazardous to the aquatic environment)
Danger label(s)	3, "Fish and tree"



Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-E
Stowage category	B

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Octanes
Particulars in the shipper's declaration	UN1262, Octanes, 3, II
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	3



Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

#### National regulations(Australia)

##### Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

#### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed as "ACTIVE"

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

### Legend

INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality

# Safety data sheet

acc. to Safe Work Australia - Code of Practice



## PCBs Standard Solution ROTI®Star 7 PCBs in isooctane, 10 µg/ml

article number: 1YXX

Abbr.	Descriptions of used abbreviations
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.