acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 µg/ml



date of compilation: 2023-02-28 article number: 1YY2 Version: 1.0 en

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance PCBs Standard Solution ROTI®Star 8 PCBs in n-

hexane, 100 µg/ml

Article number **1YY2**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.7	Reproductive toxicity	2	Repr. 2	H361f
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373

United Kingdom (en) Page 1 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 µg/ml

article number: 1YY2

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07, GHS08, GHS09









Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361f	Suspected of damaging fertility
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled)
H411	Toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P280 Wear protective gloves/protective clothing/eye protection/face protection

For professional users only

Hazardous ingredients for labelling: n-Hexane, Polychlorobiphenyls (PCB)

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0,1%.

United Kingdom (en) Page 2 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 µg/ml

article number: 1YY2

SECTION 3: Composition/information on ingredients

3.1 **Substances**

not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
n-Hexane	CAS No 110-54-3 EC No 203-777-6 Index No 601-037-00-0	99 – < 100	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361f STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Aquatic Chronic 2 / H411		GHS-HC IOELV
Polychlorobiphenyls (PCB)	CAS No 1336-36-3 EC No 215-648-1 Index No 602-039-00-4	< 0,1	STOT RE 2 / H373 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410	\$	C GHS-HC

Notes

C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

IOELV: Substance with a community indicative occupational exposure limit value

Name of sub- stance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
n-Hexane	CAS No 110-54-3 EC No 203-777-6	STOT RE 2; H373: C ≥ 5 %	-	-	
Polychlorobi- phenyls (PCB)	CAS No 1336-36-3 EC No 215-648-1	STOT RE 2; H373: C ≥ 0,005 %	-	-	

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

Description of first aid measures 4.1



General notes

Take off contaminated clothing.

United Kingdom (en) Page 3 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 µg/ml

article number: 1YY2

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

United Kingdom (en) Page 4 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

United Kingdom (en) Page 5 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

effects

PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 2 - 8 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	n-hexane	110-54-3	IOELV	20	72						2006/15/ EC
GB	n-hexane	110-54-3	WEL	20	72						EH40/ 2005
GB	polychlorinated bi- phenyls (PCB)	1336-36- 3	WEL		0,1						EH40/ 2005

Notation

Ceiling-C STFI

TWA

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture										
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time				
n-Hexane	110-54-3	DNEL	75 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects				
n-Hexane	110-54-3	DNFI	11 ma/ka	human, dermal	worker (industry)	chronic - systemic				

United Kingdom (en) Page 6 / 19

bw/day

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 µg/ml

article number: 1YY2

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

≥0,4 mm

· breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

United Kingdom (en) Page 7 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 µg/ml

article number: 1YY2

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour like: - Gasoline

Melting point/freezing point -95 °C at 1.013 hPa (ECHA)

Boiling point or initial boiling point and boiling 68 – 69 °C at 1.013 hPa

range

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 1,1 vol% (LEL) - 7,5 vol% (UEL) Flash point -22 °C at 1.013 hPa (ECHA)

Auto-ignition temperature 225 °C (ECHA)

Decomposition temperature not relevant

pH (value) not determined

Kinematic viscosity 0,5 mm²/s at 20 °C

Dynamic viscosity 0,33 mPa s at 20 °C

Solubility(ies)

Water solubility <0,1 ^g/_l at 20 °C

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 160 hPa at 20 °C

Density and/or relative density

Density $0.66 \, ^{9}/_{\text{cm}^3}$ at 20 $^{\circ}\text{C}$

Relative vapour density 2,79 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard There is no additional information. classes:

Other safety characteristics: There is no additional information.

United Kingdom (en) Page 8 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Chlorine, Iodine, Peroxides, Nitrogen oxides (NOx), => Explosive properties

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
n-Hexane	110-54-3	inhalation: va- pour	LC50	185 ^{mg} / _l /4h	rat
n-Hexane	110-54-3	oral	LD50	25.000 ^{mg} / _{kg}	rat
n-Hexane	110-54-3	dermal	LD50	>2.000 ^{mg} / _{kg}	rabbit

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

United Kingdom (en) Page 9 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).

Hazard category	Target organ	Exposure route
2	nervous system	if inhaled

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

nausea, vomiting, aspiration hazard

• If in eyes

slightly irritant but not relevant for classification

• If inhaled

irritant effects, headache, vertigo, fatigue, dizziness, narcosis

• If on skin

causes skin irritation

• Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0,1%.

11.3 Information on other hazards

There is no additional information.

United Kingdom (en) Page 10 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
n-Hexane	110-54-3	LL50	12,51 ^{mg} / _l	fish	96 h
n-Hexane	110-54-3	EL50	21,85 ^{mg} / _l	aquatic invertebrates	48 h

12.2 Persistence and degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
n-Hexane	110-54-3	oxygen deple- tion	83 %	10 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
n-Hexane	110-54-3	501,2	4 (pH value: 7, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

United Kingdom (en) Page 11 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP3 flammable

HP 5 specific target organ toxicity (STOT)/aspiration toxicity

HP 10 toxic for reproduction

HP 14 ecotoxic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

444	UN nun		TD	
141	UIN DIID	nner or	II) niii	mner

ADRRID	UN 1208
IMDG-Code	UN 1208
ICAO-TI	UN 1208

14.2 UN proper shipping name

ADRRID	HEXANES
IMDG-Code	HEXANES
ICAO-TI	Hexanes

14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

ADRRID	II
IMDG-Code	II
ICAO-TI	II

14.5 Environmental hazards hazardous to the aquatic environment

Environmenta	lly hazarc	dous substanc	e (aquatic	n-Hexane
environment):				

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

United Kingdom (en) Page 12 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)

PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2



14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information

Proper shipping name HEXANES

Particulars in the transport document UN1208, HEXANES, 3, II, (D/E), environmentally

hazardous

Classification code F1

Danger label(s) 3, "Fish and tree"





Environmental hazards yes (hazardous to the aquatic environment)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E
Hazard identification No 33
Emergency Action Code 3YE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional

intormation

Classification code F1

Danger label(s) 3
Fish and tree





Environmental hazards Yes

Hazardous to water

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Hazard identification No 33

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name HEXANES

Particulars in the shipper's declaration UN1208, HEXANES, 3, II, -22°C c.c., MARINE POL-

LUTANT

Marine pollutant yes (P) (hazardous to the aquatic environment)

Danger label(s) 3, "Fish and tree"





Special provisions (SP)

United Kingdom (en) Page 13 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-E, S-D

Stowage category E

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Hexanes

Particulars in the shipper's declaration UN1208, Hexanes, 3, II

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	2012/18/EU (Seveso III)					
No	Dangerous substance/hazard categories	Qualifying quantity (to plication of lower and quiremen		Notes		
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200	500	57)		

Notation

Deco-Paint Directive

VOC content 99,92 % 659,5 ^g / _l

Industrial Emissions Directive (IED)

VOC content	99,92 %
VOC content	659,5 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

United Kingdom (en) Page 14 / 19

⁵⁷⁾ Hazardous to the Aquatic Environment in category Chronic 2

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

Pollutant release and transfer registers (PRTR)

Name of substance	CAS No	Remarks	Threshold for releases to air (kg/year)
Polychlorobiphenyls (PCB)	1336-36-3		0,1

Water Framework Directive (WFD)

List of pollutants (WFD)

Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Polychlorobiphenyls (PCB)	Organohalogen compounds and substances which may form such compounds in the aquatic envir- onment		a)	
Polychlorobiphenyls (PCB)	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	
Polychlorobiphenyls (PCB)	Persistent hydrocarbons and per- sistent and bioaccumulable or- ganic toxic substances		a)	
n-Hexane	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)	

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

chemicals subject to the international prior informed consent (PIC) procedure (the 'PIC procedure').

United Kingdom (en) Page 15 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

Name of substance	Name acc. to inventory	CAS No	Wt%	Category / subcat- egory	Use limita- tion
Polychlorobiphenyls (PCB)	polychlorinated biphenyls (PCB)	1336-36- 3	0,08	i	
Polychlorobiphenyls (PCB)	polychlorinated biphenyls (PCB)	1336-36- 3	0,08		

Legend

Category: i - industrial chemical

Regulation on persistent organic pollutants (POP)

Name of substance	CAS No	Wt%	Type of registra- tion	Re- marks	Exemp- tions	Concen- tration limit
Polychlorobiphenyls (PCB)	1336-36-3	0,08	Annex I - A		A1-ex-08	
Polychlorobiphenyls (PCB)	1336-36-3	0,08	Annex III - A			
Polychlorobiphenyls (PCB)	1336-36-3	0,08	Annex IV			50 mg/kg

Legend

A1-ex-08

Without prejudice to Directive 96/59/EC, articles already in use at the time of the entry into force of this Regulation are allowed to be used.

Member States shall identify and remove from use equipment (e.g. transformers, capacitors or other receptacles containing liquid stocks) containing more than 0,005 % PCBs and volumes greater than 0,05 dm3, as soon as possible but no later than 31 December 2025.

annex I - A Part A - Substances listed in the Convention and in the Protocol as well as substances listed only in the Convention annex III - A List of substances subject to release reduction provisions annex IV List of substances subject to waste management provisions set out in Article 7

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list none of the ingredients are listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
PCBs Standard Solution	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3
n-Hexane	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

United Kingdom (en) Page 16 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed as "ACTIVE"

Legend

AIIC CICR CSCL-ENCS

Australian Inventory of Industrial Chemicals
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)
Korea Existing Chemicals Inventory
New Zealand Inventory of Chemicals
Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH registered substances

DSL ECSI IECSC INSQ ISHA-ENCS KECI

NZIoC

REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor

United Kingdom (en) Page 17 / 19

Safety data sheet Safety data sheet acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

Abbr.	Descriptions of used abbreviations
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Liq.	Flammable liquid
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals

United Kingdom (en) Page 18 / 19

acc. to Regulation (EC) No. 1907/2006 (REACH)



PCBs Standard Solution ROTI®Star 8 PCBs in n-hexane, 100 μg/ml

article number: 1YY2

Abbr.	Descriptions of used abbreviations
Repr.	Reproductive toxicity
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs (nervous system) through prolonged or repeated exposure (if inhaled).
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 19 / 19