

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: **2224**
Version: **GHS 2.0 en**
Replaces version of: 2016-09-23
Version: (GHS 1)

date of compilation: 2016-09-23
Revision: 2022-01-13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance **Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As**

Article number 2224

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical
Laboratory and analytical use

Uses advised against: Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone:+49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.6	Carcinogenicity	1A	Carc. 1A	H350

For full text of abbreviations: see SECTION 16

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS05, GHS08



Hazard statements

H290	May be corrosive to metals
H315	Causes skin irritation
H319	Causes serious eye irritation
H350	May cause cancer

Precautionary statements

Precautionary statements - prevention

P280 Wear protective gloves

Precautionary statements - response

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P337+P313	If eye irritation persists: Get medical advice/attention
P390	Absorb spillage to prevent material damage

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

For professional users only

Hazardous ingredients for labelling: Arsenic acid

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Nitric acid ...% [C ≤ 70 %]	CAS No 7697-37-2	2	Ox. Liq. 3 / H272 Met. Corr. 1 / H290 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 EUH071		B(a)
Arsenic acid	CAS No 7778-39-4	0.1 – < 0.25	Acute Tox. 3 / H301 Acute Tox. 3 / H331 Carc. 1A / H350		IARC: 1 RoC "Known"

Notes

B(a): The classification refers to an aqueous solution

IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)

RoC NTP-RoC: Known To Be A Human Carcinogen

"Known"

:

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Rinse mouth immediately and drink plenty of water.

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Risk of blindness, Gastric perforation, Irritation, Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

none

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO_x)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use extractor hood (laboratory). Avoid exposure.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
AU	nitric acid	7697-37-2	WES	2	5.2	4	10				WES

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur
STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Arsenic acid	7778-39-4	DNEL	6 µg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Arsenic acid	7778-39-4	DNEL	85 µg/kg	human, dermal	worker (industry)	chronic - systemic effects

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Arsenic acid	7778-39-4	PNEC	0.001 mg/l	aquatic organisms	freshwater	short-term (single instance)
Arsenic acid	7778-39-4	PNEC	0.001 mg/l	aquatic organisms	marine water	short-term (single instance)
Arsenic acid	7778-39-4	PNEC	0.42 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Arsenic acid	7778-39-4	PNEC	5 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Arsenic acid	7778-39-4	PNEC	6 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Arsenic acid	7778-39-4	PNEC	0.095 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

• material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation.

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	odourless
Melting point/freezing point	~0 °C at 1,013 hPa
Boiling point or initial boiling point and boiling range	~100 °C at 1,013 hPa (unknown)
Flammability	non-combustible
Lower and upper explosion limit	not determined
Flash point	not determined
Auto-ignition temperature	not determined
Decomposition temperature	not relevant
pH (value)	0.5 (20 °C)
Kinematic viscosity	not determined
<u>Solubility(ies)</u>	
Water solubility	miscible in any proportion
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	not relevant (inorganic)
Vapour pressure	not determined
<u>Density and/or relative density</u>	
Density	1.013 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes:

Corrosive to metals category 1: corrosive to metals

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Ammonia (NH₃), Strong alkali

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

different metals

Release of flammable materials with

Metals, Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
Nitric acid ...% [C ≤ 70 %]	7697-37-2	inhalation: vapour	>2.65 mg/l/4h
Arsenic acid	7778-39-4	oral	141.4 mg/kg
Arsenic acid	7778-39-4	inhalation: vapour	3 mg/l/4h
Arsenic acid	7778-39-4	inhalation: dust/mist	0.794 mg/l/4h

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Nitric acid ...% [C ≤ 70 %]	7697-37-2	inhalation: vapour	LC50	>2.65 mg/l/4h	rat
Arsenic acid	7778-39-4	oral	LD50	141.4 mg/kg	mouse
Arsenic acid	7778-39-4	inhalation: dust/mist	LC50	0.794 mg/l/4h	mouse
Arsenic acid	7778-39-4	dermal	LD50	2,300 mg/kg	rabbit

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

Data are not available.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

- **If in eyes**

Causes serious eye irritation

- **If inhaled**

Data are not available.

- **If on skin**

causes skin irritation. May produce an allergic reaction, localised redness, oedema, pruritis and/or pain

- **Other information**

This information is based upon the present state of our knowledge.

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Arsenic acid	7778-39-4	LC50	141 mg/l	fish	24 h
Arsenic acid	7778-39-4	EC50	159 µg/l	algae	96 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Arsenic acid	7778-39-4	LC50	141 mg/l	fish	24 h
Arsenic acid	7778-39-4	EC50	0.256 mg/l	algae	14 d

Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H8 Corrosives

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 3264
IMDG-Code	UN 3264
ICAO-TI	UN 3264

14.2 UN proper shipping name

UN RTDG	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
IMDG-Code	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
ICAO-TI	Corrosive liquid, acidic, inorganic, n.o.s.
Technical name (hazardous ingredients)	Nitric acid ...% [C ≤ 70 %], Arsenic acid

14.3 Transport hazard class(es)

UN RTDG	8
IMDG-Code	8
ICAO-TI	8

14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport information National regulations Additional information (UN RTDG)

UN number 3264

Class 8

Packing group III

Danger label(s) 8



Special provisions (SP) 223, 274
UN RTDG

Excepted quantities (EQ) E1
UN RTDG

Limited quantities (LQ) 5 L
UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

Particulars in the shipper's declaration UN3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S., (contains: Nitric acid ...% [C ≤ 70 %], Arsenic acid), 8, III

Marine pollutant -

Danger label(s) 8



Special provisions (SP) 223, 274

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-A, S-B

Stowage category A

Segregation group 1 - Acids

Safety data sheet Safety data sheet


acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Particulars in the shipper's declaration	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (contains: Nitric acid ...% [C ≤ 70 %], Arsenic acid), 8, III
Danger label(s)	8
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

Legend

ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	Supplemental hazard information		yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1	Remarks: For full text of Hazard- and EU Hazard-statements: see SECTION 16.		yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Supplemental hazard information		yes
2.2		Supplemental hazard information: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Arsenic acid		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: 2224

Abbr.	Descriptions of used abbreviations
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
NLP	No-Longer Polymer
NTP-RoC	National Toxicology Program: Report on Carcinogens
Ox. Liq.	Oxidising liquid
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H350	May cause cancer.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l As

article number: **2224**

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.