acc. to Safe Work Australia - Code of Practice

#### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225 Version: GHS 2.0 en Replaces version of: 2016-10-14 Version: (GHS 1)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### **Product identifier** 1.1

Identification of the substance

Article number

**Single-Element** AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

2225

#### Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

#### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

#### e-mail (competent person):

### sicherheit@carlroth.de

#### 1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

#### **Classification acc. to GHS**

Section	Hazard class		Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319

For full text of abbreviations: see SECTION 16

#### 2.2 Label elements



Revision: 2022-03-07

date of compilation: 2016-10-14

acc. to Safe Work Australia - Code of Practice

### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225

Labelling	
Signal word	Warning
Pictograms	
GHS05	
Hazard statemen	ts
H290	May be corrosive to metals
H315 H319	Causes skin irritation Causes serious eye irritation
Precautionary sta	atements
Precautionary sta	itements - prevention
P280	Wear protective gloves
Precautionary sta	itements - response
P302+P352 P305+P351+P338	IF ON SKIN: Wash with plenty of soap and water IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P321	Specific treatment (see on this label)
P337+P313	If eye irritation persists: Get medical advice/attention

#### P390 Absorb spillage to prevent material damage

#### 2.3 **Other hazards**

#### **Results of PBT and vPvB assessment**

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## **SECTION 3: Composition/information on ingredients**

#### 3.1 **Substances**

not relevant (mixture)

#### 3.2 Mixtures

#### **Description of the mixture**

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
barium nitrate	CAS No 10022-31-8	< 2	Ox. Sol. 2 / H272 Acute Tox. 3 / H301 Acute Tox. 4 / H332		1(a) A(a)
Nitric acid% [C ≤ 70 %]	CAS No 7697-37-2	1	Ox. Liq. 3 / H272 Met. Corr. 1 / H290 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 EUH071		B(a)

Notes

The concentration stated is the percentage by weight of the metallic element calculated with reference to the total weight of the mixture 1(a):

acc. to Safe Work Australia - Code of Practice



### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

#### article number: 2225

#### Notes

A(a): The name of substance is a general description. It is required that the correct name is stated on the labelB(a): The classification refers to an aqueous solution

For full text of abbreviations: see SECTION 16

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures



#### **General notes**

Take off contaminated clothing.

#### **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

#### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

#### **Following ingestion**

Rinse mouth. Call a doctor if you feel unwell.

- **4.2 Most important symptoms and effects, both acute and delayed** Irritation
- **4.3 Indication of any immediate medical attention and special treatment needed** none

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Non-combustible.

### Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx)

acc. to Safe Work Australia - Code of Practice



#### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

#### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

No special measures are necessary.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

#### 7.3 Specific end use(s)

No information available.

acc. to Safe Work Australia - Code of Practice



### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 **Control parameters**

#### National limit values

#### **Occupational exposure limit values (Workplace Exposure Limits)**

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	nitric acid	7697-37- 2	WES	2	5.2	4	10				WES

#### Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified) TWA

	-					
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time
barium nitrate	10022-31-8	DNEL	2.73 mg/ m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
barium nitrate	10022-31-8	DNEL	8.141 mg/ kg	human, dermal	worker (industry)	chronic - systemic effects

#### **Relevant PNECs of components of the mixture**

Name of sub- stance	CAS No	End- point	Threshol d levelOrganism organism compartment		Exposure time		
barium nitrate	10022-31-8	PNEC	115 <sup>µg</sup> / <sub>l</sub>	aquatic organ- isms	freshwater	short-term (single instance)	
barium nitrate	10022-31-8	PNEC	62.2 <sup>mg</sup> / <sub>l</sub>	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)	
barium nitrate	10022-31-8	PNEC	600 <sup>mg</sup> / <sub>kg</sub>	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)	
barium nitrate	10022-31-8	PNEC	207.7 <sup>mg</sup> / <sup>kg</sup>	terrestrial organ- isms	soil	short-term (single instance)	

#### 8.2 **Exposure controls**

#### Individual protection measures (personal protective equipment)

**Eye/face protection** 



Use safety goggle with side protection.

acc. to Safe Work Australia - Code of Practice

#### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

® §ROTH

#### article number: 2225

#### Skin protection



#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

NBR (Nitrile rubber)

#### material thickness

>0,11 mm

#### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

#### **Respiratory protection**



Respiratory protection necessary at: Aerosol or mist formation.

#### Environmental exposure controls

Keep away from drains, surface and ground water.

## **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	~0 °C at 1,013 hPa
Boiling point or initial boiling point and boiling range	~100 °C at 1,013 hPa
Flammability	non-combustible
Lower and upper explosion limit	not determined
Flash point	not determined

acc. to Safe Work Australia - Code of Practice

#### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225

Auto-ignition temperature	not determined
Decomposition temperature	not relevant
pH (value)	<2
Kinematic viscosity	not determined
Solubility(ies)	
Water solubility	miscible in any proportion
water solubility	misciple in any proportion
Partition coefficient	
Partition coefficient n-octanol/water (log value):	not relevant (inorganic)
Vapour pressure	not determined
Density and/or relative density	
Density	~1 <sup>g</sup> / <sub>cm³</sub> at 20 °C
Relative vapour density	information on this property is not available
Relative vapour density	information on this property is not available
Particle characteristics	not relevant (liquid)
	not relevant (inquity)
Other safety parameters	
Oxidising properties	none
Other information	
Information with regard to physical hazard classes:	
Corrosive to metals	category 1: corrosive to metals
Other safety characteristics:	
Miscibility	completely miscible with water

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

9.2

Substance or mixture corrosive to metals.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### **10.3** Possibility of hazardous reactions

Violent reaction with: Ammonia (NH3), Bases, Metals, Reducing agents, Strong alkali, Organic solvents

#### 10.4 Conditions to avoid

Keep away from heat.



acc. to Safe Work Australia - Code of Practice

#### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225

#### 10.5 Incompatible materials

different metals (due to the release of hydrogen in an acid/alkaline medium)

## 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### **Classification procedure**

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

#### Acute toxicity

Shall not be classified as acutely toxic.

#### Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
barium nitrate	10022-31-8	oral	>50 <sup>mg</sup> / <sub>kg</sub>
barium nitrate	10022-31-8	inhalation: dust/mist	1.5 <sup>mg</sup> / <sub>l</sub> /4h
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: vapour	>2.65 <sup>mg</sup> /ı/4h

### Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
barium nitrate	10022-31-8	oral	LD50	>50 - <300 <sup>mg</sup> / <sub>kg</sub>	rat
barium nitrate	10022-31-8	dermal	LD50	>2,000 <sup>mg</sup> / <sub>kg</sub>	rat
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: va- pour	LC50	>2.65 <sup>mg</sup> / <sub>l</sub> /4h	rat

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### **Reproductive toxicity**

Shall not be classified as a reproductive toxicant.



acc. to Safe Work Australia - Code of Practice

#### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

#### article number: 2225

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

#### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

Data are not available.

• If in eyes

Causes serious eye irritation

#### • If inhaled

Data are not available.

#### • If on skin

causes skin irritation

#### • Other information

This information is based upon the present state of our knowledge.

#### **11.2** Endocrine disrupting properties

None of the ingredients are listed.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture					
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
barium nitrate	10022-31-8	LC50	>3.5 <sup>mg</sup> / <sub>l</sub>	fish	96 h
barium nitrate	10022-31-8	EC50	≤18 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	48 h
barium nitrate	10022-31-8	ErC50	>1.15 <sup>mg</sup> / <sub>l</sub>	algae	72 h

#### Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
barium nitrate	10022-31-8	ErC50	>2.19 <sup>mg</sup> / <sub>l</sub>	algae	72 d
barium nitrate	10022-31-8	EC50	>1,000 <sup>mg</sup> / <sub>l</sub>	microorganisms	3 h

#### **Biodegradation**

The methods for determining the biological degradability are not applicable to inorganic substances.





acc. to Safe Work Australia - Code of Practice

#### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225

#### 12.2 Process of degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential	Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD	
barium nitrate	10022-31-8	68.4			

#### 12.4 Mobility in soil

Data are not available.

- **12.5 Results of PBT and vPvB assessment** Data are not available.
- 12.6 Endocrine disrupting properties

None of the ingredients are listed.

#### 12.7 Other adverse effects

Data are not available.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### **Relevant provisions relating to waste(Basel Convention)**

#### Properties of waste which render it hazardous

H8 Corrosives

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.





acc. to Safe Work Australia - Code of Practice

## Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba



article number: 2225

SEC	TION 14: Transport information			
14.1	UN number			
	UN RTDG	UN 3264		
	IMDG-Code	UN 3264		
	ICAO-TI	UN 3264		
14.2	UN proper shipping name			
	UN RTDG	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.		
	IMDG-Code	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.		
	ICAO-TI	Corrosive liquid, acidic, inorganic, n.o.s.		
	Technical name (hazardous ingredients)	Nitric acid% [C ≤ 70 %], Barium nitrate		
14.3	Transport hazard class(es)			
	UN RTDG	8		
	IMDG-Code	8		
	ICAO-TI	8		
14.4	Packing group			
	UN RTDG	III		
	IMDG-Code	III		
	ICAO-TI	III		
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations		
14.6	<b>Special precautions for user</b> There is no additional information.			
14.7	<b>Transport in bulk according to Annex II of MAR</b> The cargo is not intended to be carried in bulk.	POL and the IBC Code		
14.8	Information for each of the UN Model Regulation			
	Transport informationNational regulationsAdd			
	UN number	3264		
	Class	8		
	Packing group	III		
	Danger label(s)	8		
	Special provisions (SP) 223, 274 UN RTDG			
	Excepted quantities (EQ)	E1 UN RTDG		

acc. to Safe Work Australia - Code of Practice



#### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225

Limited quantities (LQ)	5 L
	UN RTDG
International Maritime Dangerous Goods Code	(IMDG) - Additional information
Proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Particulars in the shipper's declaration	UN3264, CORROSIVE LIQUID, ACIDIC, INORGAN- IC, N.O.S., (Nitric acid% [C ≤ 70 %], barium ni- trate, solution), 8, III
Marine pollutant	-
Danger label(s)	8
	222.274
Special provisions (SP)	223, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	A
Segregation group	1 - Acids
International Civil Aviation Organization (ICAO	-IATA/DGR) - Additional information
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Particulars in the shipper's declaration	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (Nitric acid% [C ≤ 70 %], barium nitrate, solu- tion), 8, III
Danger label(s)	8
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

## **SECTION 15: Regulatory information**

# **15.1** Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

#### National regulations(Australia)

#### Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

#### **Other information**

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

acc. to Safe Work Australia - Code of Practice

### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

article number: 2225

#### **National inventories**

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

#### Legend

Legena	
AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EÌNEĆS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chémicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## **SECTION 16: Other information**

### Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

#### Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	Supplemental hazard information		yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1	Remarks: For full text of Hazard- and EU Hazard-state- ments: see SECTION 16.		yes



acc. to Safe Work Australia - Code of Practice



## Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

#### article number: 2225

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Supplemental hazard information		yes
2.2		Supplemental hazard information: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances

acc. to Safe Work Australia - Code of Practice



## Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

#### article number: 2225

Abbr.	Descriptions of used abbreviations	
EmS	Emergency Schedule	
ErC50	= EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control	
Eye Dam.	Seriously damaging to the eye	
Eye Irrit.	Irritant to the eye	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during specified time interval	
log KOW	n-Octanol/water	
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")	
Met. Corr.	Substance or mixture corrosive to metals	
NLP	No-Longer Polymer	
Ox. Liq.	Oxidising liquid	
Ox. Sol.	Oxidising solid	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
ppm	Parts per million	
Skin Corr.	Corrosive to skin	
Skin Irrit.	Irritant to skin	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants	

#### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

acc. to Safe Work Australia - Code of Practice



### Single-Element AAS - Standard Solution ROTI®Star 1 000 mg/l Ba

#### article number: 2225

#### **Classification procedure**

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.