

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: **2277**
Version: **GHS 3.0 en**
Replaces version of: 2021-04-07
Version: (GHS 2)

date of compilation: 2019-03-27
Revision: 2024-03-04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Silicone oil M 2, 2 cSt, low viscosity
Article number	2277
CAS number	141-63-9
Alternative name(s)	Dodecamethylpentasiloxane

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory and analytical use Laboratory chemical
Uses advised against:	Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

2.2 Label elements

Labelling

Signal word

Warning

Not required

Pictograms

Hazard statements

H227 Combustible liquid

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403 Store in a well-ventilated place

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

2.3 Other hazards

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Silicone oil
Molecular formula	$C_{12}H_{36}O_4Si_5$
Molar mass	384.8 g/mol
CAS No	141-63-9

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Special danger of slipping by leaking/spilling product. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

Consideration of other advice:

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	102 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	102 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	1,449 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
DNEL	1,449 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

Environmental values

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	1 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	3.77 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

• material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown). Usually no personal respiratory protection necessary.

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	230 °C at 760 mmHg
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	not determined

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

Flash point	87 °C (c.c.)
Auto-ignition temperature	350 °C at 101.3 kPa (ECHA)
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	1.8 – 2.2 mm ² /s at 25 °C
<u>Solubility(ies)</u>	
Water solubility	not determined
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	9.268 – 9.508 (ECHA)
Soil organic carbon/water (log KOC)	6.3 (ECHA)
Vapour pressure	7.8 Pa at 25 °C
<u>Density and/or relative density</u>	
Density	0.872 g/cm ³ at 20 °C
Relative vapour density	Information on this property is not available.
Relative density	0.872 (water = 1)
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none
9.2 Other information	
Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if swallowed or in contact with skin.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2,000 mg/kg	rat		ECHA
dermal	LD50	>2,000 mg/kg	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

Data are not available.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

- **If in eyes**

Data are not available.

- **If inhaled**

Data are not available.

- **If on skin**

Data are not available.

- **Other information**

Health effects are not known.

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	$>100 \text{ mg/l}$	microorganisms	ECHA	3 h

12.2 Persistence and degradability

Theoretical Oxygen Demand: 1.58 mg/mg
Theoretical Carbon Dioxide: 1.372 mg/mg

Process of degradability		
Process	Degradation rate	Time
carbon dioxide generation	0 %	28 d

12.3 Bioaccumulative potential

The substance fulfils the very bioaccumulative criterion.

n-octanol/water (log KOW)	9.268 – 9.508 (ECHA)
BCF	1,430 (ECHA)

12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	6.3 (ECHA)
------------------------------------------------------	------------

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

- | | |
|-------------------------------------------------------------------------------------------|-----------------------------------------------------------------------|
| 14.1 UN number | not subject to transport regulations |
| 14.2 UN proper shipping name | not assigned |
| 14.3 Transport hazard class(es) | not assigned |
| 14.4 Packing group | not assigned |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | There is no additional information. |
| 14.7 Transport in bulk according to IMO instruments | The cargo is not intended to be carried in bulk. |
| 14.8 <u>Information for each of the UN Model Regulations</u> | |
| Transport information National regulations Additional information (UN RTDG) | Not subject to transport regulations. UN RTDG |
| International Maritime Dangerous Goods Code (IMDG) - Additional information | Not subject to IMDG. |
| International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information | Not subject to ICAO-IATA. |

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.1	EC number: 205-492-2	CAS number: 141-63-9	yes
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Pictograms: Not required	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2		Precautionary statements - storage: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards: This material is combustible, but will not ignite readily.	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.	yes
11.1		Acute toxicity: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic): change in the listing (table)	yes
14.2	UN proper shipping name: not relevant	UN proper shipping name: not assigned	yes
14.3	Transport hazard class(es): not relevant	Transport hazard class(es): not assigned	yes
14.3	Class: -		yes
14.4	Packing group: not relevant not assigned to a packing group	Packing group: not assigned	yes

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: 2277

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
14.5	Environmental hazards: none (non-environmentally hazardous acc. to the dangerous goods regulations)	Environmental hazards: non-environmentally hazardous acc. to the dangerous goods regulations	yes
14.8	• Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN): Not subject to ADR, RID and ADN.		yes
14.8	Acute toxicity: oralLD50>2,000 mg/kg rat ECHA dermalLD50>2,000 mg/kg rat ECHA	Transport information National regulations Additional information (UN RTDG): Not subject to transport regulations. UN RTDG	yes
15.1	Safety, health and environmental regulations/legislation specific for the substance or mixture	Safety, health and environmental regulations/legislation specific for the substance or mixture: There is no additional information.	yes
15.1	National inventories: Substance is listed in the following national inventories:		yes
15.1		National regulations (Australia)	yes
15.1		Australian Inventory of Chemical Substances (AICS): Substance is listed.	yes
15.1		Other information: Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	yes
15.1		National inventories	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Silicone oil M 2, 2 cSt, low viscosity

article number: **2277**

Abbr.	Descriptions of used abbreviations
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.