

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: **2441**
Version: **GHS 3.0 en**
Replaces version of: 2019-08-27
Version: (GHS 2)

date of compilation: 2018-08-10
Revision: 2022-06-09

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Ethylene glycol ≥98 %, technical
Article number	2441
CAS number	107-21-1
Alternative name(s)	Ethanediol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use Formulation [mixing] of preparations and/or re-packaging (excluding alloys) Industrial uses Professional uses
---------------------------	---

Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).
-----------------------	---

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone:+49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

e-mail (competent person): **sicherheit@carlroth.de**

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol $\geq 98\%$, technical

article number: 2441

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure.

2.2 Label elements

Labelling

Signal word

Warning

Pictograms

GHS07, GHS08



Hazard statements

H302 Harmful if swallowed
H373 May cause damage to organs (kidney) through prolonged or repeated exposure (if swallowed)

Precautionary statements

Precautionary statements - prevention

P260 Do not breathe dust/fume/gas/mist/vapours/spray
P264 Wash thoroughly after handling
P270 Do not eat, drink or smoke when using this product

Precautionary statements - response

P314 Get medical advice/attention if you feel unwell
P330 Rinse mouth

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Ethylene glycol
Molecular formula	C ₂ H ₆ O ₂
Molar mass	62.07 g/mol
CAS No	107-21-1

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth with water (only if the person is conscious). Call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Fatigue, Vertigo, Agitation, Diarrhoea, Vomiting, Nausea, Unconsciousness

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol $\geq 98\%$, technical

article number: 2441

5.2 Special hazards arising from the substance or mixture

Combustible. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a dry place. Hygroscopic.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

humidity

Consideration of other advice:

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
AU	ethylene glycol (ethanediol)	107-21-1	WES		10						WES
AU	ethylene glycol (ethanediol)	107-21-1	WES	20	52	40	104			vap	WES

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

vap As vapours

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	35 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
DNEL	106 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Environmental values

Relevant PNECs and other threshold levels				
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	10 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	1 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	199.5 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	37 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	3.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	1.53 mg/kg	terrestrial organisms	soil	short-term (single instance)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol $\geq 98\%$, technical

article number: 2441

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

• material thickness

>0,3 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless - light yellow
Odour	odourless
Melting point/freezing point	-14 – -12 °C at 1,013 hPa
Boiling point or initial boiling point and boiling range	197 – 198 °C at 1,013 hPa
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	3.2 vol% (LEL) - 43 vol% (UEL)
Flash point	111 °C at 1,013 hPa (ECHA)
Auto-ignition temperature	412 °C at 1,013 hPa (ECHA)
Decomposition temperature	not relevant
pH (value)	6 – 7.5 (in aqueous solution: 100 g/l, 20 °C)
Kinematic viscosity	not determined
Dynamic viscosity	16 – 18 mPa s at 25 °C
<u>Solubility(ies)</u>	
Water solubility	1,000 g/l at 20 °C (ECHA)
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	-1.36 (ECHA)
Soil organic carbon/water (log KOC)	0 (ECHA)
Vapour pressure	0.12 hPa at 25 °C
<u>Density and/or relative density</u>	
Density	1.11 g/cm ³ at 20 °C (ECHA)
Relative vapour density	2.14 (air = 1)
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

9.2 Other information

Information with regard to physical hazard classes:	hazard classes acc. to GHS (physical hazards): not relevant
---	---

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

Other safety characteristics:

There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Exothermic reaction with: Sulphuric acid, Alkali hydroxide (caustic alkali), Aluminium, Nitric acid,
Risk of ignition: Chlorates, Permanganates, Peroxides, strong oxidiser

10.4 Conditions to avoid

Protect from moisture. Keep away from heat.

10.5 Incompatible materials

aluminium, zinc

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful if swallowed.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
dermal	LD50	>3,500 mg/kg	mouse		ECHA
oral	LD50	4,700 mg/kg	rat		TOXNET

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure (if swallowed).

Hazard category	Target organ	Exposure route
2	kidney	if swallowed

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

diarrhoea, vomiting, nausea, Liver and kidney damage

• If in eyes

essentially non-irritating

• If inhaled

Data are not available.

• If on skin

essentially non-irritating

• Other information

Other adverse effects: Loss of righting reflex, and ataxia, Unconsciousness, Drowsiness, Agitation

11.2 Endocrine disrupting properties

Not listed.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	>72,860 mg/l	fish	ECHA	96 h
EC50	>100 mg/l	daphnia magna	ECHA	48 h
ErC50	<13,000 mg/l	algae	ECHA	96 h

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
LC50	>1,500 mg/l	fish	ECHA	28 d
EC50	>15,000 mg/l	aquatic invertebrates	ECHA	21 d

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: 1.29 g/g
Theoretical Carbon Dioxide: 1.418 mg/mg
Biochemical Oxygen Demand: 0.78 g/g

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	83 – 96 %	14 d
DOC removal	90 – 100 %	10 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	-1.36 (ECHA)
---------------------------	--------------

12.4 Mobility in soil

Henry's law constant	0.013 Pa m ³ /mol at 25 °C (ECHA)
The Organic Carbon normalised adsorption coefficient	0 (ECHA)

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

Do not empty into drains.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

- | | |
|---|---|
| 14.1 UN number | not subject to transport regulations |
| 14.2 UN proper shipping name | not assigned |
| 14.3 Transport hazard class(es) | not assigned |
| 14.4 Packing group | not assigned |
| 14.5 Environmental hazards | non-environmentally hazardous acc. to the dangerous goods regulations |
| 14.6 Special precautions for user | There is no additional information. |
| 14.7 Transport in bulk according to IMO instruments | The cargo is not intended to be carried in bulk. |
| 14.8 Information for each of the UN Model Regulations | |
| Transport informationNational regulationsAdditional information(UN RTDG) | Not subject to transport regulations. UN RTDG |
| International Maritime Dangerous Goods Code (IMDG) - Additional information | Not subject to IMDG. |
| International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information | Not subject to ICAO-IATA. |

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
There is no additional information.
- National regulations(Australia)**
Australian Inventory of Chemical Substances(AICS)
Substance is listed.
- Other information**
Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure.	yes
2.2		Pictograms: change in the listing (table)	yes

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Ethylene glycol ≥98 %, technical

article number: 2441

Abbr.	Descriptions of used abbreviations
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H373	May cause damage to organs (kidney) through prolonged or repeated exposure (if swallowed).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.