

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: **2530**
Version: **3.0 en**
Replaces version of: 11.12.2020
Version: (2)

date of compilation: 07.02.2017
Revision: 04.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Epoxy systems Araldit® B 1 adhesive
Article number	2530
Registration number (REACH)	not relevant (mixture)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use Adhesive
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone:+49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

e-mail (competent person): **sicherheit@carlroth.de**

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.4S	Skin sensitisation	1	Skin Sens. 1	H317
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

Supplemental hazard information

Code	Supplemental hazard information
EUH205	contains epoxy constituents. May produce an allergic reaction

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Warning

Pictograms

GHS07, GHS09



Hazard statements

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P273	Avoid release to the environment
P280	Wear protective gloves/eye protection

Precautionary statements - response

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312	Call a POISON CENTRE/doctor if you feel unwell

Supplemental hazard information

EUH205	Contains epoxy constituents. May produce an allergic reaction.
--------	--

Hazardous ingredients for labelling:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxy-methylene)]bisoxirane

Labelling of packages where the contents do not exceed 125 ml

Signal word: **Warning**

Symbol(s)



H317	May cause an allergic skin reaction.
P280	Wear protective gloves/eye protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
EUH205	Contains epoxy constituents. May produce an allergic reaction.
contains:	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	CAS No 1675-54-3 EC No 216-823-5 Index No 603-073-00-2 REACH Reg. No 01-2119456619-26-xxxx	70 – < 90	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Skin Sens. 1 / H317 Aquatic Chronic 2 / H411		GHS-HC
Bis(isopropyl)naphthalene	CAS No 38640-62-9 EC No 254-052-6 REACH Reg. No 01-2119565150-48-xxxx	10 – < 20	Asp. Tox. 1 / H304 Aquatic Acute 1 / H400 Aquatic Chronic 1 / H410		

Notes

GHS-HC: Harmonised classification (the classification of the substance corresponds to the entry in the list according to 1272/2008/EC, Annex VI)

Name of substance	Identifier	Specific Conc. Limits	M-Factors	ATE	Exposure route
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	CAS No 1675-54-3 EC No 216-823-5 Index No 603-073-00-2	Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	-	-	

For full text of abbreviations: see SECTION 16

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. After contact with skin, wash immediately with plenty of water. In case of skin reactions, consult a physician. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	DNEL	4,93 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	DNEL	0,75 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Bis(isopropyl)naphthalene	38640-62-9	DNEL	8,4 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Bis(isopropyl)naphthalene	38640-62-9	DNEL	2,38 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,006 mg/l	aquatic organisms	freshwater	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,001 mg/l	aquatic organisms	marine water	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,341 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	PNEC	0,034 mg/kg	aquatic organisms	marine sediment	short-term (single instance)

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxy-methylene)]bisoxirane	1675-54-3	PNEC	0,065 mg/kg	terrestrial organisms	soil	short-term (single instance)
Bis(isopropyl)naphthalene	38640-62-9	PNEC	0 mg/l	aquatic organisms	freshwater	short-term (single instance)
Bis(isopropyl)naphthalene	38640-62-9	PNEC	0 mg/l	aquatic organisms	marine water	short-term (single instance)
Bis(isopropyl)naphthalene	38640-62-9	PNEC	0,15 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Bis(isopropyl)naphthalene	38640-62-9	PNEC	0,853 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Bis(isopropyl)naphthalene	38640-62-9	PNEC	0,085 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Bis(isopropyl)naphthalene	38640-62-9	PNEC	0,171 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

• material thickness

≥0,5 mm

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530


- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	light yellow - transparent
Odour	faintly perceptible
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	>200 °C
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined
Flash point	>140 °C (c.c.)
Auto-ignition temperature	not determined
Decomposition temperature	>200 °C
pH (value)	not determined
Kinematic viscosity	1.473 mm ² /s at 25 °C
Dynamic viscosity	1.400 – 1.650 mPa s at 25 °C
<u>Solubility(ies)</u>	
Water solubility	(practically insoluble)
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	this information is not available
Vapour pressure	<0,0001 hPa at 20 °C

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Density and/or relative density

Density	1,12 g/cm ³ at 25 °C
Relative vapour density	information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes: hazard classes acc. to GHS (physical hazards): not relevant

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat. Decomposition takes place from temperatures above: >200 °C.

10.5 Incompatible materials

Strong alkali, Strong acid

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	oral	LD50	>2.000 mg/kg	rat
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	dermal	LD50	>2.000 mg/kg	rat
Bis(isopropyl)naphthalene	38640-62-9	oral	LD50	4.130 mg/kg	rat
Bis(isopropyl)naphthalene	38640-62-9	inhalation: dust/mist	LC50	>5,64 mg/l/4h	rat
Bis(isopropyl)naphthalene	38640-62-9	dermal	LD50	>4.500 mg/kg	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

Data are not available.

• If in eyes

Causes serious eye irritation

• If inhaled

Data are not available.

• If on skin

causes skin irritation, May produce an allergic reaction, pruritis, localised redness

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

• Other information

none

11.2 Endocrine disrupting properties

Endocrine disrupting chemicals (EDC)				
Name of substance	CAS No	Combined category	Human health category	Wildlife category
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	CAT2	CAT2	CAT3

Legend

CAT2 Category 2 - at least some in vitro evidence of biological activity related to endocrine disruption
CAT3 Category 3 - no evidence of endocrine disruption or no data available

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	LC50	1,75 mg/l	fish	96 h
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	EC50	1,7 mg/l	aquatic invertebrates	48 h
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	ErC50	>11 mg/l	algae	72 h
Bis(isopropyl)naphthalene	38640-62-9	LC50	>0,5 mg/l	fish	96 h
Bis(isopropyl)naphthalene	38640-62-9	EC50	>0,16 mg/l	aquatic invertebrates	48 h

Biodegradation

Data are not available.

12.2 Process of degradability

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Degradability of components of the mixture						
Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	oxygen depletion	5 %	28 d		ECHA
Bis(isopropyl)naphthalene	38640-62-9	carbon dioxide generation	≤0,1 %	56 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	31	≥2,64 – ≤3,78 (pH value: ~7, 25 °C)	
Bis(isopropyl)naphthalene	38640-62-9	1.800	6,081	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Endocrine disrupting chemicals (EDC)				
Name of substance	CAS No	Combined category	Human health category	Wildlife category
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	CAT2	CAT2	CAT3

Legend

CAT2 Category 2 - at least some in vitro evidence of biological activity related to endocrine disruption
CAT3 Category 3 - no evidence of endocrine disruption or no data available

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	UN 3082
IMDG-Code	UN 3082
ICAO-TI	UN 3082

14.2 UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.
Technical name (hazardous ingredients)	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane, Bis(isopropyl)naphthalene

14.3 Transport hazard class(es)

ADR	9
IMDG-Code	9
ICAO-TI	9

14.4 Packing group

ADR	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment):	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane, Bis(isopropyl)naphthalene

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)





Epoxy systems Araldit® B 1 adhesive



article number: 2530

14.8 Information for each of the UN Model Regulations

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Particulars in the transport document	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (contains: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane, Bis(isopropyl)naphthalene), 9, III, (-)
Classification code	M6
Danger label(s)	9, "Fish and tree"
 	
Environmental hazards	YES (hazardous to the aquatic environment)
Special provisions (SP)	274, 335, 375, 601
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	-
Hazard identification No	90

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Particulars in the shipper's declaration	UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S., (contains: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane, Bis(isopropyl)naphthalene), 9, III
Marine pollutant	YES (hazardous to the aquatic environment), (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane)
Danger label(s)	9, "Fish and tree"
 	
Special provisions (SP)	274, 335, 969
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-F
Stowage category	A

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Environmentally hazardous substance, liquid, n.o.s.
Particulars in the shipper's declaration	UN3082, Environmentally hazardous substance, liquid, n.o.s., (contains: 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane, Bis(isopropyl)naphthalene), 9, III
Environmental hazards	yes (hazardous to the aquatic environment)
Danger label(s)	9, "Fish and tree"
Special provisions (SP)	A97, A158, A197, A215
Exempted quantities (EQ)	E1
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Epoxy systems Araldit® B 1 adhesive	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3

Legend

- R3
1. Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 2. Articles not complying with paragraph 1 shall not be placed on the market.
 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and
 - present an aspiration hazard and are labelled with H304.
 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
 - (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter fluid may lead to life threatening lung damage";
 - (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

None of the ingredients are listed.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
E2	environmental hazards (hazardous to the aquatic environment, cat. 2)	200 500	57)

Notation

57) Hazardous to the Aquatic Environment in category Chronic 2

Deco-Paint Directive

VOC content	60 – 90 % 1.008 g/l
-------------	------------------------

Industrial Emissions Directive (IED)

VOC content	60 – 90 %
VOC content	1.008 g/l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

none of the ingredients are listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

none of the ingredients are listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
2,2'-[[1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	

Legend

A) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

none of the ingredients are listed

Regulation on drug precursors

none of the ingredients are listed

Regulation on substances that deplete the ozone layer (ODS)

none of the ingredients are listed

Regulation concerning the export and import of hazardous chemicals (PIC)

none of the ingredients are listed

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Regulation on persistent organic pollutants (POP)

none of the ingredients are listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: Spillage and fire water can cause pollution of watercourses.	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
Aquatic Acute	Hazardous to the aquatic environment - acute hazard
Aquatic Chronic	Hazardous to the aquatic environment - chronic hazard
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

Abbr.	Descriptions of used abbreviations
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
SVHC	Substance of Very High Concern
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Araldit® B 1 adhesive

article number: 2530

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.