

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: **2551**
Version: **3.0 en**
Replaces version of: 04.05.2022
Version: (2)

date of compilation: 11.12.2020
Revision: 02.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Epoxy systems Aradur® H 2 hardener
Article number	2551
Registration number (REACH)	01-2119487919-13-xxxx
EC number	292-588-2
CAS number	90640-67-8
Alternative name(s)	Amines, polyethylenepoly-, triethylenetetramine fraction

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use Adhesive
Uses advised against:	Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.1D	Acute toxicity (dermal)	4	Acute Tox. 4	H312
3.2	Skin corrosion/irritation	1	Skin Corr. 1	H314

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.4S	Skin sensitisation	1	Skin Sens. 1	H317
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms

GHS05, GHS07



Hazard statements

H302+H312 Harmful if swallowed or in contact with skin
H314 Causes severe skin burns and eye damage
H317 May cause an allergic skin reaction
H412 Harmful to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P273 Avoid release to the environment
P280 Wear protective gloves/eye protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 Immediately call a POISON CENTER/doctor

Hazardous ingredients for labelling:

Amines, polyethylenepoly-, triethylenetetramine fraction

Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)



H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

P280	Wear protective gloves/eye protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
contains:	Amines, polyethylenepoly-, triethylenetetramine fraction

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Amines, polyethylenepoly-, triethylenetetramine fraction
Molecular formula	$C_6H_{18}N_4$
Molar mass	146,2 g/mol
REACH Reg. No	01-2119487919-13-xxxx
CAS No	90640-67-8
EC No	292-588-2

Substance, Specific Conc. Limits, M-factors, ATE

Specific Conc. Limits	M-Factors	ATE	Exposure route
-	-	1.862 mg/kg 1.465 mg/kg	oral dermal

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure. In case of skin reactions, consult a physician.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes hold eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Following ingestion

Rinse mouth immediately and drink plenty of water. Rinse mouth with water (only if the person is conscious). Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Vomiting, Risk of blindness, Gastric perforation, Risk of serious damage to eyes, Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Handle and open container with care. Clear contaminated areas thoroughly.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	0,54 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects

Environmental values

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0,027 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,003 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	0,13 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	8,572 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,857 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	1,25 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection. Wear face protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

• material thickness

≥0,5 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless - whitish
Odour	faintly perceptible
Melting point/freezing point	<-70 °C at 1.013 hPa
Boiling point or initial boiling point and boiling range	274,6 °C at 1.013 hPa (ECHA)
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	1 vol% (LEL) - 3,6 vol% (UEL)
Flash point	118 °C (c.c.) (ECHA)
Auto-ignition temperature	325 °C at 1.025 hPa
Decomposition temperature	>240 °C
pH (value)	~13 (in aqueous solution: 1.000 g/l, 20 °C)
Kinematic viscosity	28,6 mm ² /s at 20 °C 10,8 mm ² /s at 40 °C
Dynamic viscosity	13,9 mPa s at 40 °C
<u>Solubility(ies)</u>	
Water solubility	>1.000 g/l at 20 °C (ECHA)
Solubility in methanol	partially soluble
Solubility in organic solvents	partially soluble
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	-2,65 (TETA)
Soil organic carbon/water (log KOC)	3,2 (ECHA)
Vapour pressure	0,346 Pa at 20 °C

Density and/or relative density

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Density	0,971 g/cm ³ at 25 °C
Relative vapour density	5,04 (air = 1)

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

Other safety parameters

Oxidising properties	none
----------------------	------

9.2 Other information

Information with regard to physical hazard classes:	hazard classes acc. to GHS (physical hazards): not relevant
---	---

Other safety characteristics:

Temperature class (EU, acc. to ATEX)	T2 Maximum permissible surface temperature on the equipment: 300°C
--------------------------------------	---

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Strong acid

10.4 Conditions to avoid

Keep away from heat. Decomposition takes place from temperatures above: >240 °C.

10.5 Incompatible materials

acids, copper, nickel, cobalt

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Harmful if swallowed. Harmful in contact with skin.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	1.862 mg/kg	rat		ECHA
dermal	LD50	1.465 mg/kg	rabbit		ECHA

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

irritant effects, cough, Dyspnoea

• If on skin

causes severe burns, causes poorly healing wounds, May produce an allergic reaction, pruritis, localised redness

• Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

11.3 Information on other hazards

There is no additional information.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	330 mg/l	fish	ECHA	96 h
EC50	31,1 mg/l	aquatic invertebrates	ECHA	48 h
ErC50	20 mg/l	algae	ECHA	72 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	<10 mg/l	aquatic invertebrates	ECHA	21 d

12.2 Persistence and degradability

Theoretical Oxygen Demand (without nitrification): 1,641 mg/mg

Theoretical Oxygen Demand (with nitrification): 2,366 mg/mg

Theoretical Carbon Dioxide: 1,806 mg/mg

Biodegradation

Not readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	0 %	28 d
oxygen depletion	0 %	162 d
DOC removal	20 %	84 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	-2,65 (TETA)
---------------------------	--------------

12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	3,2 (ECHA)
--	------------

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP 4 irritant - skin irritation and eye damage
HP 6 acute toxicity
HP 8 corrosive
HP 13 sensitising
HP 14 ecotoxic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	UN 2259
IMDG-Code	UN 2259
ICAO-TI	UN 2259

14.2 UN proper shipping name

ADR	TRIETHYLENETETRAMINE
IMDG-Code	TRIETHYLENETETRAMINE
ICAO-TI	Triethylenetetramine

14.3 Transport hazard class(es)

ADR	8
IMDG-Code	8



Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

ICAO-TI	8
14.4 Packing group	
ADR	II
IMDG-Code	II
ICAO-TI	II
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7 Maritime transport in bulk according to IMO instruments	
The cargo is not intended to be carried in bulk.	
14.8 Information for each of the UN Model Regulations	
Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) Additional information	
Proper shipping name	TRIETHYLENETETRAMINE
Particulars in the transport document	UN2259, TRIETHYLENETETRAMINE, 8, II, (E)
Classification code	C7
Danger label(s)	8
	
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	E
Hazard identification No	80
International Maritime Dangerous Goods Code (IMDG) - Additional information	
Proper shipping name	TRIETHYLENETETRAMINE
Particulars in the shipper's declaration	UN2259, TRIETHYLENETETRAMINE, 8, II
Marine pollutant	-
Danger label(s)	8
	
Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-A, S-B
Stowage category	B


Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Segregation group	18 - Alkalis
International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information	
Proper shipping name	Triethylenetetramine
Particulars in the shipper's declaration	UN2259, Triethylenetetramine, 8, II
Danger label(s)	8
	
Excepted quantities (EQ)	E2
Limited quantities (LQ)	0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Amines, polyethylenepoly-, triethylenetetramine fraction	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
Amines, polyethylenepoly-, triethylenetetramine fraction	substances in tattoo inks and permanent make-up		R75	75

Legend

- R3
1. Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 2. Articles not complying with paragraph 1 shall not be placed on the market.
 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and
 - present an aspiration hazard and are labelled with H304.
 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
 - (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter fluid may lead to life threatening lung damage";
 - (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;

Epoxy systems Aradur® H 2 hardener

article number: 2551

Legend

- R75 1. Shall not be placed on the market in mixtures for use for tattooing purposes, and mixtures containing any such substances shall not be used for tattooing purposes, after 4 January 2022 if the substance or substances in question is or are present in the following circumstances:
- (a) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as carcinogen category 1A, 1B or 2, or germ cell mutagen category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - (b) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as reproductive toxicant category 1A, 1B or 2, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - (c) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin sensitiser category 1, 1A or 1B, the substance is present in the mixture in a concentration equal to or greater than 0,001 % by weight;
 - (d) in the case of a substance classified in Part 3 of Annex VI to Regulation (EC) No 1272/2008 as skin corrosive category 1, 1A, 1B or 1C or skin irritant category 2, or as serious eye damage category 1 or eye irritant category 2, the substance is present in the mixture in a concentration equal to or greater than:
 - (i) 0,1 % by weight, if the substance is used solely as a pH regulator;
 - (ii) 0,01 % by weight, in all other cases;
 - (e) in the case of a substance listed in Annex II to Regulation (EC) No 1223/2009 (*1), the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight;
 - (f) in the case of a substance for which a condition of one or more of the following kinds is specified in column g (Product type, Body parts) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration equal to or greater than 0,00005 % by weight:
 - (i) "Rinse-off products";
 - (ii) "Not to be used in products applied on mucous membranes";
 - (iii) "Not to be used in eye products";
 - (g) in the case of a substance for which a condition is specified in column h (Maximum concentration in ready for use preparation) or column i (Other) of the table in Annex IV to Regulation (EC) No 1223/2009, the substance is present in the mixture in a concentration, or in some other way, that does not accord with the condition specified in that column;
 - (h) in the case of a substance listed in Appendix 13 to this Annex, the substance is present in the mixture in a concentration equal to or greater than the concentration limit specified for that substance in that Appendix.
2. For the purposes of this entry use of a mixture "for tattooing purposes" means injection or introduction of the mixture into a person's skin, mucous membrane or eyeball, by any process or procedure (including procedures commonly referred to as permanent make-up, cosmetic tattooing, micro-blading and micro-pigmentation), with the aim of making a mark or design on his or her body.
3. If a substance not listed in Appendix 13 falls within more than one of points (a) to (g) of paragraph 1, the strictest concentration limit laid down in the points in question shall apply to that substance. If a substance listed in Appendix 13 also falls within one or more of points (a) to (g) of paragraph 1, the concentration limit laid down in point (h) of paragraph 1 shall apply to that substance.
4. By way of derogation, paragraph 1 shall not apply to the following substances until 4 January 2023:
(a) Pigment Blue 15:3 (CI 74160, EC No 205-685-1, CAS No 147-14-8);
(b) Pigment Green 7 (CI 74260, EC No 215-524-7, CAS No 1328-53-6).
5. If Part 3 of Annex VI to Regulation (EC) No 1272/2008 is amended after 4 January 2021 to classify or re-classify a substance such that the substance then becomes caught by point (a), (b), (c) or (d) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the date of application of that new or revised classification is after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect on the date of application of that new or revised classification.
6. If Annex II or Annex IV to Regulation (EC) No 1223/2009 is amended after 4 January 2021 to list or change the listing of a substance such that the substance then becomes caught by point (e), (f) or (g) of paragraph 1 of this entry, or such that it then falls within a different one of those points from the one within which it fell previously, and the amendment takes effect after the date referred to in paragraph 1 or, as the case may be, paragraph 4 of this entry, that amendment shall, for the purposes of applying this entry to that substance, be treated as taking effect from the date falling 18 months after entry into force of the act by which that amendment was made.
7. Suppliers placing a mixture on the market for use for tattooing purposes shall ensure that, after 4 January 2022, the mixture is marked with the following information:
(a) the statement "Mixture for use in tattoos or permanent make-up";
(b) a reference number to uniquely identify the batch;
(c) the list of ingredients in accordance with the nomenclature established in the glossary of common ingredient names pursuant to Article 33 of Regulation (EC) No 1223/2009, or in the absence of a common ingredient name, the IUPAC name. In the absence of a common ingredient name or IUPAC name, the CAS and EC number. Ingredients shall be listed in descending order by weight or volume of the ingredients at the time of formulation. "Ingredient" means any substance added during the process of formulation and present in the mixture for use for tattooing purposes. Impurities shall not be regarded as ingredients. If the name of a substance, used as ingredient within the meaning of this entry, is already required to be stated on the label in accordance with Regulation (EC) No 1272/2008, that ingredient does not need to be marked in accordance with this Regulation;
(d) the additional statement "pH regulator" for substances falling under point (d)(i) of paragraph 1;
(e) the statement "Contains nickel. Can cause allergic reactions." if the mixture contains nickel below the concentration limit specified in Appendix 13;
(f) the statement "Contains chromium (VI). Can cause allergic reactions." if the mixture contains chromium (VI) below the concentration limit specified in Appendix 13;
(g) safety instructions for use insofar as they are not already required to be stated on the label by Regulation (EC) No 1272/2008.
- The information shall be clearly visible, easily legible and marked in a way that is indelible.
The information shall be written in the official language(s) of the Member State(s) where the mixture is placed on the market, unless the Member State(s) concerned provide(s) otherwise.
Where necessary because of the size of the package, the information listed in the first subparagraph, except for point (a), shall be included instead in the instructions for use.
Before using a mixture for tattooing purposes, the person using the mixture shall provide the person undergoing the procedure with the information marked on the package or included in the instructions for use pursuant to this paragraph.
8. Mixtures that do not contain the statement "Mixture for use in tattoos or permanent make-up" shall not be used for tattooing purposes.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Legend

9. This entry does not apply to substances that are gases at temperature of 20 °C and pressure of 101,3 kPa, or generate a vapour pressure of more than 300 kPa at temperature of 50 °C, with the exception of formaldehyde (CAS No 50-00-0, EC No 200-001-8).

10. This entry does not apply to the placing on the market of a mixture for use for tattooing purposes, or to the use of a mixture for tattooing purposes, when placed on the market exclusively as a medical device or an accessory to a medical device, within the meaning of Regulation (EU) 2017/745, or when used exclusively as a medical device or an accessory to a medical device, within the same meaning. Where the placing on the market or use may not be exclusively as a medical device or an accessory to a medical device, the requirements of Regulation (EU) 2017/745 and of this Regulation shall apply cumulatively.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
	not assigned		

Deco-Paint Directive

VOC content	0 %
VOC content	0 g/l

Industrial Emissions Directive (IED)

VOC content	0 %
VOC content	0 g/l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

not listed

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
KR	KECI	substance is listed
NZ	NZIoC	substance is listed
VN	NCI	substance is listed

Legend

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC Inventory of Existing Chemical Substances Produced or Imported in China
KECI Korea Existing Chemicals Inventory
NCI National Chemical Inventory
NZIoC New Zealand Inventory of Chemicals
REACH Reg. REACH registered substances

15.2 Chemical safety assessment

According to REACH, Article 14 (1) a chemical safety assessment has been carried out for this substance or components of this mixture when the substance has been registered in quantities of 10 tonnes or more per year per registrant.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.	yes
15.1	VOC content: 0 % 0 ⁹ / ₁	VOC content: 0 %	yes
15.1		VOC content: 0 ⁹ / ₁	yes
15.1		National inventories: change in the listing (table)	yes
15.2	Chemical Safety Assessment: No Chemical Safety Assessment has been carried out for this substance.	Chemical safety assessment: According to REACH, Article 14 (1) a chemical safety assessment has been carried out for this substance or components of this mixture when the substance has been registered in quantities of 10 tonnes or more per year per registrant.	yes

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
SVHC	Substance of Very High Concern
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Epoxy systems Aradur® H 2 hardener

article number: 2551

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.