

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: **2641**
Version: **3.0 en**
Replaces version of: 2021-11-17
Version: (2)

date of compilation: 2016-08-29
Revision: 2024-03-03

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Styrene $\geq 99,5$ %, for synthesis, stabilized
Article number	2641
Index No (GB CLP)	601-026-00-0
EC number	202-851-5
CAS number	100-42-5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-stuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.7	Reproductive toxicity	2	Repr. 2	H361d
3.9	Specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
3.10	Aspiration hazard	1	Asp. Tox. 1	H304
4.1C	Hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08



Hazard statements

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H361d	Suspected of damaging the unborn child
H372	Causes damage to organs (hearing organs) through prolonged or repeated exposure
H412	Harmful to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P280	Wear protective gloves/eye protection

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene ≥99,5 %, for synthesis, stabilized

article number: 2641

Precautionary statements - response

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention

For professional users only

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

The substance has an endocrine disrupting potential.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Styrene
Molecular formula	C ₈ H ₈
Molar mass	104,2 g/mol
CAS No	100-42-5
EC No	202-851-5
Index No (GB CLP)	601-026-00-0

To stabilise:

Name of substance	Identifier	Wt%
4-tert-butylpyrocatechol	CAS No 98-29-3 EC No 202-653-9	0,001 – 0,0015

Substance, Specific Conc. Limits, M-factors, ATE

Specific Conc. Limits	M-Factors	ATE	Exposure route
-	-	11 mg/4h	inhalation: vapour

Remarks

For full text of abbreviations: see SECTION 16

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Localised redness, Pruritis, Malaise, Headache, Nausea, Vomiting, Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

high temperatures, direct light irradiation, UV-radiation/sunlight, contact with air/oxygen

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
GB	styrene	100-42-5	WEL	100	430	250	1.080				EH40/2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	85 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	289 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	306 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
DNEL	406 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

Environmental values

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0,028 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,014 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	5 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0,614 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,307 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0,2 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM (fluoro rubber)

• material thickness

>0,4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• Splash protection - Protective gloves

• type of material: NBR (Nitrile rubber)

• material thickness: 0,4 mm

• breakthrough times of the glove material: >30 minutes (permeation: level 2)

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	mild sweet
Melting point/freezing point	-31 °C (ECHA)
Boiling point or initial boiling point and boiling range	145 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	45 g/m ³ (LEL) - 350 g/m ³ (UEL) / 1,2 vol% (LEL) - 8,9 vol% (UEL)
Flash point	31 °C at 1.013 hPa (ECHA)
Auto-ignition temperature	490 °C at 1.013 hPa (ECHA) (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	0,77 mm ² /s at 25 °C
Dynamic viscosity	0,696 mPa s at 25 °C
<u>Solubility(ies)</u>	
Water solubility	0,32 g/l at 25 °C (ECHA)
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	2,96 (25 °C) (ECHA)
Soil organic carbon/water (log KOC)	2,55 (ECHA)
Vapour pressure	6,67 hPa at 20 °C

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

Density and/or relative density

Density 0,9 g/cm³ at 20 °C

Relative vapour density 3,6 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Maximum explosion pressure 6,6 bar

Refractive index 1,546

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Can polymerise exothermically if heated, exposed to air, sunlight or by addition of free radical initiators. May form explosive peroxides.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

Reactivity if exposed to air => May form explosive peroxides

Reactivity if exposed to light, Reactivity if heated => Danger of polymerisation

10.3 Possibility of hazardous reactions

Danger of explosion: Peroxides, Strong acid, Peroxide formation possible with air oxygen,

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Direct light irradiation. UV-radiation/sunlight. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

copper

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Release of: Peroxides.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful if inhaled.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
dermal	LD50	>2.000 mg/kg	rat		ECHA

Acute toxicity of components					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
4-tert-butylpyrocatechol	98-29-3	oral	LD50	815 mg/kg	rat
4-tert-butylpyrocatechol	98-29-3	dermal	LD50	1.331 mg/kg	rat

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs (hearing organs) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
1	hearing organs	if exposed

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

- **If swallowed**

vomiting, aspiration hazard

- **If in eyes**

Causes serious eye irritation

- **If inhaled**

vertigo, headache

- **If on skin**

causes skin irritation, pruritis, localised redness

- **Other information**

none

11.2 Endocrine disrupting properties

This substance is known as an "endocrine disruptor".

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
EC50	4,7 mg/l	aquatic invertebrates	ECHA	48 h
ErC50	4,9 mg/l	algae	ECHA	72 h

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
4-tert-butylpyrocatechol	98-29-3	LC50	0,12 mg/l	fish	96 h
4-tert-butylpyrocatechol	98-29-3	EC50	0,48 mg/l	aquatic invertebrates	48 h
4-tert-butylpyrocatechol	98-29-3	ErC50	10,17 mg/l	algae	72 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	1,88 mg/l	aquatic invertebrates	ECHA	21 d

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene ≥99,5 %, for synthesis, stabilized

article number: 2641

Aquatic toxicity (chronic) of components

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
4-tert-butylpyrocatechol	98-29-3	EC50	0,94 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Theoretical Oxygen Demand: 3,072 mg/mg

Theoretical Carbon Dioxide: 3,38 mg/mg

Process of degradability

Process	Degradation rate	Time
biotic/abiotic	80 %	20 d

Degradability of components

Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
4-tert-butylpyrocatechol	98-29-3	DOC removal	91 %	28 d		ECHA
4-tert-butylpyrocatechol	98-29-3	carbon dioxide generation	24,7 %	28 d		ECHA

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	2,96 (25 °C) (ECHA)
BCF	74 (ECHA)

Bioaccumulative potential of components

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
4-tert-butylpyrocatechol	98-29-3		1,98 (pH value: 5,9, 25 °C)	

12.4 Mobility in soil

Henry's law constant	231,6 Pa m ³ /mol (ECHA)
The Organic Carbon normalised adsorption coefficient	2,55 (ECHA)

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

This substance is known as an "endocrine disruptor".

12.7 Other adverse effects

Data are not available.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

- HP 3** flammable
- HP 4** irritant - skin irritation and eye damage
- HP 5** specific target organ toxicity (STOT)/aspiration toxicity
- HP 6** acute toxicity
- HP 10** toxic for reproduction
- HP 14** ecotoxic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

ADRRID	UN 2055
IMDG-Code	UN 2055
ICAO-TI	UN 2055

14.2 UN proper shipping name

ADRRID	STYRENE MONOMER, STABILIZED
IMDG-Code	STYRENE MONOMER, STABILIZED
ICAO-TI	Styrene monomer, stabilized

14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

14.4 Packing group

ADRRID	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user


Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments


The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) Additional information

Proper shipping name	STYRENE MONOMER, STABILIZED
Particulars in the transport document	UN2055, STYRENE MONOMER, STABILIZED, 3, III, (D/E)
Classification code	F1
Danger label(s)	3
	
Special provisions (SP)	386, 676
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E
Hazard identification No	39
Emergency Action Code	3Y

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) Additional information

Classification code	F1
Danger label(s)	3
	
Special provisions (SP)	386, 676
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Hazard identification No	39

Safety data sheet Safety data sheet


acc. to Regulation (EC) No. 1907/2006 (REACH)




Styrene ≥99,5 %, for synthesis, stabilized

article number: 2641

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	STYRENE MONOMER, STABILIZED
Particulars in the shipper's declaration	UN2055, STYRENE MONOMER, STABILIZED, 3, III, 31°C c.c.
Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	386
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	C

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Styrene monomer, stabilized
Particulars in the shipper's declaration	UN2055, Styrene monomer, stabilized, 3, III
Danger label(s)	3
	
Special provisions (SP)	A209
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P5c	flammable liquids (cat. 2, 3)	5.000 50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

VOC content	100 %
VOC content	900 g/l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	900 g/l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
Styrene	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

not listed

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
Styrene	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3
Styrene	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
14.8	Special provisions (SP): 386	Special provisions (SP): 386, 676	yes
14.8		Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional information	yes
14.8		Classification code: F1	yes
14.8		Danger label(s): 3	yes
14.8		Danger label(s): change in the listing (table)	yes
14.8		Special provisions (SP): 386, 676	yes
14.8		Excepted quantities (EQ): E1	yes
14.8		Limited quantities (LQ): 5 L	yes
14.8		Transport category (TC): 3	yes
14.8		Hazard identification No: 39	yes
15.1	Restrictions according to REACH, Annex XVII		yes
15.1		Dangerous substances with restrictions (REACH, Annex XVII): change in the listing (table)	yes
15.1	List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list: Not listed.		yes
15.1		VOC content: 900 ^g / _l	yes
15.1		VOC content: 900 ^g / _l	yes
15.1		National regulations(GB)	yes

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
15.1		List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list: not listed	yes
15.1		Restrictions according to GB REACH, Annex 17	yes
15.1		Dangerous substances with restrictions (GB REACH, Annex 17): change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	\equiv EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: 2641

Abbr.	Descriptions of used abbreviations
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs (hearing organs) through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



Styrene $\geq 99,5$ %, for synthesis, stabilized

article number: **2641**

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.