acc. to Safe Work Australia - Code of Practice



date of compilation: 2016-09-08

Revision: 2022-10-10

Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: **2650** Version: **GHS 2.0 en** Replaces version of: 2021-01-27 Version: (GHS 1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % HNO₃ - 100 mg/l

Article number

2650

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	1B	Skin Corr. 1B	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

acc. to Safe Work Australia - Code of Practice

Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l



Suppleme	ental hazard information
Code	Supplemental hazard information
EUH071	corrosive to the respiratory tract

For full text of abbreviations: see SECTION 16

. .

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling

Signal word Danger
Pictograms
GHS05

Hazard statements

H290	May be corrosive to metals
H314	Causes severe skin burns and eye damage

Precautionary statements

Precautionary statements - prevention

P260	Do not breathe dusts or mists
P280	Wear eye protection/face protection

Precautionary statements - response

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin
	with water or shower
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing
P390	Absorb spillage to prevent material damage

Nitric acid ...% [C ≤ 70 %]

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Hazardous ingredients for labelling:

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.



acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % HNO_3 - 100 mg/l

article number: 2650

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Nitric acid% [C ≤ 70 %]	CAS No 7697-37-2	5 - < 10	Ox. Liq. 3 / H272 Met. Corr. 1 / H290 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 EUH071		B(a)

Notes

B(a): The classification refers to an aqueous solution

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Cough, Risk of blindness, Gastric perforation, Risk of serious damage to eyes, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % HNO $_3$ - 100 mg/l

article number: 2650

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

acc. to Safe Work Australia - Code of Practice

Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % HNO_3 - 100 mg/l



article number: 2650

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use extractor hood (laboratory). Handle and open container with care. Clear contaminated areas thoroughly.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	lead, inorganic com- pounds		WES		0.05					Pb, df	WES
AU	nickel dinitrate	13138- 45-9	WES		0.1						WES
AU	manganese	7439-96- 5	WES		1					dust	WES
AU	manganese	7439-96- 5	WES		1		3			Mn, fume	WES
AU	antimony	7440-36- 0	WES		0.5						WES
AU	arsenic	7440-38- 2	WES		0.05						WES
AU	cadmium	7440-43- 9	WES		0.01						WES
AU	nitric acid	7697-37- 2	WES	2	5.2	4	10				WES

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

As dust and fumes As dust

dust As dust fume As fume

df

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: 2650

	Calculated as Mn (manganese)
	Calculated as Pb (lead) Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-
TWA	minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection. Wear face protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. P1 (filters at least 80 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

acc. to Safe Work Australia - Code of Practice

Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: 2650

SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties Physical state liquid Colour colourless - light yellow Odour stinging 0 °C Melting point/freezing point Boiling point or initial boiling point and boiling 100 °C (unknown) range Flammability non-combustible Lower and upper explosion limit not determined Flash point not determined not determined Auto-ignition temperature Decomposition temperature not relevant pH (value) <2 (20 °C) not determined Kinematic viscosity Solubility(ies) Water solubility miscible in any proportion Partition coefficient Partition coefficient n-octanol/water (log value): not relevant (inorganic) 23 hPa at 20 °C Vapour pressure Density and/or relative density Density ~ 1 ^g/_{cm³} at 20 °C Relative vapour density information on this property is not available Particle characteristics not relevant (liquid) Other safety parameters Oxidising properties none 9.2 Other information Information with regard to physical hazard classes: Corrosive to metals category 1: corrosive to metals Other safety characteristics:



acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: **2650**

Miscibility

completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: Alkali metals, Ammonia (NH3), Bases, Alkaline earth metal, Metals, Acids

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

different metals

Release of flammable materials with

Metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATI	i) of compone	nts of the mixt	ure			
Name of substance		CAS No	Exposure rout	:e	ATE	
Nitric acid% [C ≤ 70 %]	7	697-37-2	inhalation: vapo	ur	>2.65 ^{mg} / _l /4h	
Acute toxicity of componen	ts of the mixtu	ıre				
Name of substance	CAS No	Exposure	Endpoint	Value	Species	

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: va- pour	LC50	>2.65 ^{mg} / _l /4h	rat

Skin corrosion/irritation

Causes severe skin burns and eye damage.

acc. to Safe Work Australia - Code of Practice

Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: 2650

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

corrosive to the respiratory tract, cough, Dyspnoea

• If on skin

causes severe burns, causes poorly healing wounds

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.



acc. to Safe Work Australia - Code of Practice

Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % HNO₃ -100 mg/l

article number: 2650

12.3 Bioaccumulative potential

Data are not available.

- 12.4 Mobility in soil Data are not available.
- 12.5 **Results of PBT and vPvB assessment** Data are not available.
- 12.6 Endocrine disrupting properties None of the ingredients are listed.
- 12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous H8

Corrosives

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 2031
IMDG-Code	UN 2031
ICAO-TI	UN 2031
UN proper shipping name	
UN RTDG	NITRIC ACID
IMDG-Code	NITRIC ACID
ICAO-TI	Nitric acid

14.2



acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: 2650

14.3	Transport hazard class(es)		
	UN RTDG	8	
	IMDG-Code	8	
	ICAO-TI	8	
14.4	Packing group		
	UN RTDG	II	
	IMDG-Code	II	
	ICAO-TI	II	
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations	
14.6	Special precautions for user		
	There is no additional information.		
14.7	Transport in bulk according to IMO instruments		
	The cargo is not intended to be carried in bulk.		
14.8	Information for each of the UN Model Regulation	ons	
	Transport informationNational regulationsAdditional information(UN RTDG)		
	UN number	2031	
	Class	8	
	Packing group	II	
	Danger label(s)	8	



Special provisions (SP)	- UN RTDG
Excepted quantities (EQ)	E2 UN RTDG
Limited quantities (LQ)	1 L UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	NITRIC ACID
Particulars in the shipper's declaration	UN2031, NITRIC ACID, 8, II
Marine pollutant	-
Danger label(s)	8
Excepted quantities (EQ) E2	
Limited quantities (LQ)	1 L

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % HNO₃ -100 mg/l

article number: 2650

EmS	F-A, S-B
Stowage category	D
Segregation group	1 - Acids
International Civil Aviation Organization (ICAO-I	ATA/DGR) - Additional information
Proper shipping name	Nitric acid
Particulars in the shipper's declaration	UN2031, Nitric acid, 8, II
Danger label(s)	8
\checkmark	
Excepted quantities (EQ)	E2
Limited quantities (LQ)	0,5 L

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1 There is no additional information.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	not all ingredients are listed

Legend AIIC

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) CICR CSCL-ENCS DSL Domestic Substances List (DSL)

acc. to Safe Work Australia - Code of Practice

Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: 2650

Legend	
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chémicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg	. REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: s	section 9,	section 14
------------------	------------	------------

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1	Remarks: For full text of Hazard- and EU Hazard-state- ments: see SECTION 16.		yes
2.1		The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible dam- age to the skin; namely, visible necrosis through the epidermis and into the dermis.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Supplemental hazard information		yes
2.2		Supplemental hazard information: change in the listing (table)	yes
2.2	Hazardous ingredients for labelling: Nitric acid	Hazardous ingredients for labelling: Nitric acid% [C ≤ 70 %]	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes



acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: 2650

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Nitric acid		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
Met. Corr.	Substance or mixture corrosive to metals

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution ROTI®Star 28 elements in 5 % $\rm HNO_3$ - 100 mg/l

article number: 2650

Abbr.	Descriptions of used abbreviations
NLP	No-Longer Polymer
Ox. Liq.	Oxidising liquid
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.