

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

Version 1.13	Revision Date: 20.02.2024	SDS Number: R11243	Date of last issue: 17.02.2023 Date of first issue: 03.06.2014
-----------------	------------------------------	-----------------------	---

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Manufacturer or supplier's details

Manufacturer : BODE Chemie GmbH  
Melanchthonstraße 27  
22525 Hamburg (Germany)  
Tel.: +49 (0)40 / 54 00 60

Supplier :

Responsible Department : Scientific Affairs  
sds@bode-chemie.de

Emergency telephone number : Poison Center Göttingen  
24h-Phone +49 (0)551 / 1 92 40

#### Recommended use of the chemical and restrictions on use

Recommended use : In-door use  
For further information, refer to the product technical data sheet

Restrictions on use : Restricted to professional users.

Lieferant/Supplier:  
Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
76185 Karlsruhe, Germany  
+49 721 5606 0  
sicherheit@carlroth.de

### 2. HAZARDS IDENTIFICATION



#### GHS Classification

Flammable liquids : Category 2

Serious eye damage/eye irritation : Category 2A

Specific target organ toxicity -  
single exposure : Category 3

#### GHS label elements

Hazard pictograms :  

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and  
other ignition sources. No smoking.  
P261 Avoid breathing vapours.

**Response:**

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.

### Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Ethanol	64-17-5	$\geq 50$ - $< 70$
Propan-2-ol	67-63-0	$\geq 20$ - $< 30$
propane-1,2-diol	57-55-6	$\geq 1$ - $< 10$

## 4. FIRST AID MEASURES

General advice : If you feel unwell, seek medical advice (show the label where possible).  
In case of skin contact : No skin irritation  
In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
If swallowed : Do NOT induce vomiting.  
Rinse mouth.  
Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.  
May cause drowsiness or dizziness.  
Notes to physician : For specialist advice physicians should contact the Poisons Information Service.

## 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.  
Hazardous combustion products : No hazardous combustion products are known  
Specific extinguishing methods : Standard procedure for chemical fires.  
Special protective equipment for firefighters : Use personal protective equipment.

## 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions : Should not be released into the environment.  
Methods and materials for containment and cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).

## 7. HANDLING AND STORAGE

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

Advice on protection against fire and explosion : Keep away from sources of ignition - No smoking.

Advice on safe handling : Avoid contact with eyes.

Conditions for safe storage : Store in original container.  
Keep tightly closed.

Materials to avoid : Keep away from food and drink.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	STEL	1.000 ppm	ACGIH
Propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH

#### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Propan-2-ol	67-63-0	Acetone	Urine	End of shift at end of workweek	40 mg/l	ACGIH BEI

#### Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Protective measures : Not required because of small size of the container.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : green

Odour : alcohol-like

pH : 7,5

Melting point/range : not determined

Boiling point/boiling range : > 80 °C

Flash point : 20 °C

Method: DIN 51755 Part 1

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

Flammability (solid, gas)	:	not auto-flammable
Lower explosion limit / Lower flammability limit	:	3,5 %(V)
Vapour pressure	:	No data available
Density	:	0,9 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	:	completely miscible

---

### 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	None reasonably foreseeable.
Conditions to avoid	:	Heat, flames and sparks. Strong sunlight for prolonged periods.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

---

### 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute dermal toxicity	:	Acute toxicity estimate: > 5.000 mg/kg Method: Calculation method
-----------------------	---	--

#### Components:

##### **Ethanol (CAS: 64-17-5):**

Acute oral toxicity	:	LD50 Oral (Rat): 10.470 mg/kg Method: OECD Test Guideline 401
---------------------	---	--

Acute inhalation toxicity	:	LC50 (Rat): 51 mg/l Exposure time: 4 h Test atmosphere: vapour Method: OECD Test Guideline 403
---------------------------	---	---

##### **Propan-2-ol (CAS: 67-63-0):**

Acute oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg
Acute dermal toxicity	:	LD50 Dermal (Rabbit): > 5.000 mg/kg

##### **propane-1,2-diol (CAS: 57-55-6):**

Acute oral toxicity	:	LD50 Oral (Rat): 22.000 mg/kg Method: Calculation method
---------------------	---	---

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

### Skin corrosion/irritation

Not classified based on available information.

#### Components:

##### **Ethanol (CAS: 64-17-5):**

Species : human skin  
Result : Mild skin irritation  
Remarks : Based on available data, the classification criteria are not met.

##### **Propan-2-ol (CAS: 67-63-0):**

Species : Rabbit  
Result : No skin irritation

##### **propane-1,2-diol (CAS: 57-55-6):**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : No skin irritation

### Serious eye damage/eye irritation

### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Components:

##### **Ethanol (CAS: 64-17-5):**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : Irritating to eyes.

##### **Propan-2-ol (CAS: 67-63-0):**

Species : Rabbit  
Result : Eye irritation

##### **propane-1,2-diol (CAS: 57-55-6):**

Species : Rabbit  
Method : OECD Test Guideline 405  
Result : No eye irritation

### Respiratory or skin sensitisation

### Skin sensitisation

Not classified based on available information.

### Respiratory sensitisation

Not classified based on available information.

#### Components:

##### **Ethanol (CAS: 64-17-5):**

Species : Mouse  
Method : OECD Test Guideline 429  
Result : Does not cause skin sensitisation.

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

### Propan-2-ol (CAS: 67-63-0):

Test Type : Buehler Test  
Species : Guinea pig  
Result : Did not cause sensitisation on laboratory animals.

### propane-1,2-diol (CAS: 57-55-6):

Test Type : Maximisation Test  
Species : Guinea pig  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

### Germ cell mutagenicity

Not classified based on available information.

### Components:

#### Propan-2-ol (CAS: 67-63-0):

Genotoxicity in vitro : Test Type: Ames test  
Metabolic activation: with and without metabolic activation  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Reproductive toxicity

Not classified based on available information.

### STOT - single exposure

May cause drowsiness or dizziness.

### STOT - repeated exposure

Not classified based on available information.

### Repeated dose toxicity

No data available

### Aspiration toxicity

Not classified based on available information.

### Experience with human exposure

No data available

### Experience with human exposure

No data available

### Neurological effects

No data available

---

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### Ethanol (CAS: 64-17-5):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 11.200 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 9.268 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

Toxicity to algae/aquatic plants : EC50 ( Chlorella vulgaris (Fresh water algae)): 275 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC ( Chlorella vulgaris (Fresh water algae)): 9,6 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

### Propan-2-ol (CAS: 67-63-0):

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 8.692 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.285 mg/l  
Exposure time: 48 h

NOEC (Daphnia magna (Water flea)): 141 mg/l  
Exposure time: 16 d

Toxicity to algae/aquatic plants : EC50 ( Pseudokirchneriella subcapitata (green algae)): 10.500 mg/l  
Exposure time: 72 h

### propane-1,2-diol (CAS: 57-55-6):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 40.613 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia (water flea)): 18.340 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 ( Pseudokirchneriella subcapitata (green algae)): 19.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

## Persistence and degradability

### Components:

#### Ethanol (CAS: 64-17-5):

Biodegradability : Result: Readily biodegradable.

#### Propan-2-ol (CAS: 67-63-0):

Biodegradability : Result: rapidly biodegradable

#### propane-1,2-diol (CAS: 57-55-6):

Biodegradability : Biodegradation: > 70 %

## Bioaccumulative potential

### Components:

#### Ethanol (CAS: 64-17-5):

Partition coefficient: n-octanol/water : log Pow: -0,35

#### Propan-2-ol (CAS: 67-63-0):

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

Partition coefficient: n-octanol/water : log Pow: 0,05

### propane-1,2-diol (CAS: 57-55-6):

Partition coefficient: n-octanol/water : log Pow: -1,07

### Mobility in soil

#### Components:

### Propan-2-ol (CAS: 67-63-0):

Distribution among environmental compartments : Remarks: Mobile in soils

### Other adverse effects

No data available

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Dispose of as hazardous waste in compliance with local and national regulations.  
Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

Contaminated packaging : Empty remaining contents.  
Store containers and offer for recycling of material when in accordance with the local regulations.

---

## 14. TRANSPORT INFORMATION

### ADR

UN number : UN 1987  
Proper shipping name : ALCOHOLS, N.O.S.  
(ethanol, propan-2-ol)  
Class : 3  
Packing group : II  
Labels : 3  
Hazard Identification Number : 33  
Tunnel restriction code : (D/E)  
Limited quantity (LQ) : 1,00 L  
Environmentally hazardous : no

### UNRTDG

UN number : UN 1987  
Proper shipping name : ALCOHOLS, N.O.S.  
(ethanol, propan-2-ol)  
Class : 3  
Packing group : II  
Labels : 3  
Environmentally hazardous : no

### IATA-DGR

UN/ID No. : UN 1987  
Proper shipping name : Alcohols, n.o.s.  
(ethanol, propan-2-ol)  
Class : 3



# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

Packing group : II  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

### IMDG-Code

UN number : UN 1987  
Proper shipping name : ALCOHOLS, N.O.S.  
(ethanol, propan-2-ol)  
Class : 3  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-D  
Limited quantity (LQ) : 1,00 L  
Marine pollutant : no

### Transport in bulk according to IMO instruments

Not applicable for product as supplied.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## 15. REGULATORY INFORMATION

### Safety, health and environmental regulations/legislation specific for the substance or mixture

### Other international regulations

#### The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

---

## 16. OTHER INFORMATION

Revision Date : 20.02.2024  
Date format : yyyy/mm/dd

### Safety datasheet sections which have been updated:

- 5. Firefighting measures
- 6. Accidental release measures
- 15. Regulatory information


### Further information

# SAFETY DATA SHEET

according to the Globally Harmonized System

## Visirub conc.

### NFPA:



### HMIS® IV:

HEALTH	/	1
FLAMMABILITY		4
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

### Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit

AIIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or

# **SAFETY DATA SHEET**

according to the Globally Harmonized System

## **Visirub conc.**

quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

TC / EN