

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: **3106**  
Version: **GHS 2.0 en**  
Replaces version of: 2019-09-27  
Version: (GHS 1)

date of compilation: 2019-09-26  
Revision: 2022-09-19

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance **Refractive index standard ROTI®Calipure 1,44468 (20 °C)**

Article number 3106

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use  
Laboratory chemical

Uses advised against: Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0  
**Telefax:** +49 (0) 721 - 56 06 149  
**e-mail:** sicherheit@carlroth.de  
**Website:** www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** **sicherheit@carlroth.de**

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.7	Reproductive toxicity	2	Repr. 2	H361d
3.7L	Effects on or via lactation	L	Lact.	H362
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI® Calipure 1,44468 (20 °C)

article number: 3106

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

### The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labelling

#### Signal word

**Danger**

#### Pictograms

GHS02, GHS07,  
GHS08



#### Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H336	May cause drowsiness or dizziness
H361d	Suspected of damaging the unborn child
H362	May cause harm to breast-fed children
H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled)

#### Precautionary statements

##### Precautionary statements - prevention

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P260	Do not breathe dusts or mists
P263	Avoid contact during pregnancy/while nursing

##### Precautionary statements - response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of soap and water
P331	Do NOT induce vomiting
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

##### Precautionary statements - storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed
P403+P235	Store in a well-ventilated place. Keep cool

For professional users only

#### Hazardous ingredients for labelling:

Toluene, n-Heptane

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Refractive index standard ROTI® Calipure 1,44468 (20 °C)

article number: 3106

## 2.3 Other hazards

### Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

not relevant (mixture)

### 3.2 Mixtures

#### Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Toluene	CAS No 108-88-3	25 - 50	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304		
n-Heptane	CAS No 142-82-5	25 - 50	Flam. Liq. 2 / H225 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304		C(a)

#### Notes

C(a): Mixture of isomers

For full text of abbreviations: see SECTION 16

## SECTION 4: First aid measures

### 4.1 Description of first aid measures



#### General notes

Take off contaminated clothing.

#### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

#### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: 3106

## 4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Dizziness, Drowsiness, Narcosis, Headache, Vertigo

## 4.3 Indication of any immediate medical attention and special treatment needed

none

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), May produce toxic fumes of carbon monoxide if burning.

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: 3106

## Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

## 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep in a cool place.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### Ventilation requirements

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 2 – 8 °C

### 7.3 Specific end use(s)

No information available.

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Refractive index standard ROTI® Calipure 1,44468 (20 °C)

article number: 3106

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

#### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
AU	toluene	108-88-3	WES	50	191	150	574				WES
AU	n-heptane	142-82-5	WES	400	1,640	500	2,050				WES

#### Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur  
 STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
n-Heptane	142-82-5	DNEL	2,085 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
n-Heptane	142-82-5	DNEL	300 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Toluene	108-88-3	DNEL	192 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Toluene	108-88-3	DNEL	384 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
Toluene	108-88-3	DNEL	192 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
Toluene	108-88-3	DNEL	384 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
Toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
Toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	freshwater	short-term (single instance)
Toluene	108-88-3	PNEC	0.68 mg/l	aquatic organisms	marine water	short-term (single instance)
Toluene	108-88-3	PNEC	13.61 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI® Calipure 1,44468 (20 °C)

article number: 3106

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Toluene	108-88-3	PNEC	16.39 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Toluene	108-88-3	PNEC	2.89 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

#### Individual protection measures (personal protective equipment)

##### Eye/face protection



Use safety goggle with side protection.

##### Skin protection



##### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

##### • type of material

FKM (fluoro rubber)

##### • material thickness

0,4 mm

##### • breakthrough times of the glove material


>480 minutes (permeation: level 6)

##### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

##### Respiratory protection



# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: **3106**

Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

### Environmental exposure controls

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	acc. to product description
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	~98 °C at 1,013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	35 g/m <sup>3</sup> (LEL) - 300 g/m <sup>3</sup> (UEL) / 1.1 vol% (LEL) - 7 vol% (UEL)
Flash point	-4 °C
Auto-ignition temperature	215 °C
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
<u>Solubility(ies)</u>	
Water solubility	not determined
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	this information is not available
Vapour pressure	48 hPa at 20 °C
<u>Density and/or relative density</u>	
Density	0.794 g/cm <sup>3</sup> at 20 °C
Relative vapour density	information on this property is not available
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none



# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: 3106

### 9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Refractive index 1.44 – 1.45 (20 °C)

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition. Vapours may form explosive mixtures with air.

#### If heated

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Strong acid, Chlorine, Phosphorus, Nitric acid, Acetic acid, Nitro compound, Halogenated hydrocarbons, Perchlorates, Nitrogen oxides (NOx)

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

There is no additional information.

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

#### Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

#### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
n-Heptane	142-82-5	oral	LD50	>5,000 mg/kg	rat
n-Heptane	142-82-5	inhalation: vapour	LC50	>29.29 mg/l/4h	rat
n-Heptane	142-82-5	dermal	LD50	>2,000 mg/kg	rabbit

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI® Calipure 1,44468 (20 °C)

article number: 3106

Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Toluene	108-88-3	oral	LD50	5,580 mg/kg	rat
Toluene	108-88-3	inhalation: vapour	LC50	28.1 mg/l/4h	rat
Toluene	108-88-3	dermal	LD50	>5,000 mg/kg	rabbit

### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Suspected of damaging the unborn child. May cause harm to breast-fed children.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).

Hazard category	Target organ	Exposure route
2	central nervous system	if inhaled

### Aspiration hazard

May be fatal if swallowed and enters airways.

### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

vomiting, aspiration hazard

#### • If in eyes

causes slight to moderate irritation

#### • If inhaled

vertigo, headache, fatigue, narcosis

#### • If on skin

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation)

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Refractive index standard ROTI® Calipure 1,44468 (20 °C)

article number: 3106

## • Other information

none

## 11.2 Endocrine disrupting properties

None of the ingredients are listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

#### Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
n-Heptane	142-82-5	EC50	0.64 mg/l	aquatic invertebrates	48 h
Toluene	108-88-3	LC50	5.5 mg/l	fish	96 h
Toluene	108-88-3	EC50	84 mg/l	microorganisms	24 h

#### Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
n-Heptane	142-82-5	EC50	0.23 mg/l	aquatic invertebrates	21 d
Toluene	108-88-3	LC50	3.78 mg/l	aquatic invertebrates	2 d
Toluene	108-88-3	EC50	3.23 mg/l	aquatic invertebrates	7 d

### Biodegradation

Data are not available.

### 12.2 Process of degradability

#### Degradability of components of the mixture

Name of substance	CAS No	Process	Degradation rate	Time	Method	Source
n-Heptane	142-82-5	oxygen depletion	28.2 %	2 d		ECHA
Toluene	108-88-3	biotic/abiotic	86 %	20 d		IUCLID

### 12.3 Bioaccumulative potential

Data are not available.

#### Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
n-Heptane	142-82-5	552	4.5	
Toluene	108-88-3	90	2.73 (pH value: 7, 20 °C)	

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: 3106

## 12.4 Mobility in soil

Data are not available.

## 12.5 Results of PBT and vPvB assessment

Data are not available.

## 12.6 Endocrine disrupting properties

None of the ingredients are listed.

## 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

#### Relevant provisions relating to waste(Basel Convention)

#### Properties of waste which render it hazardous

**H3** Flammable liquids  
**H11** Toxic (Delayed or chronic)

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## SECTION 14: Transport information

### 14.1 UN number

<b>UN RTDG</b>	UN 3295
IMDG-Code	UN 3295
ICAO-TI	UN 3295

### 14.2 UN proper shipping name

<b>UN RTDG</b>	HYDROCARBONS, LIQUID, N.O.S.
IMDG-Code	HYDROCARBONS, LIQUID, N.O.S.
ICAO-TI	Hydrocarbons, liquid, n.o.s.

### 14.3 Transport hazard class(es)

<b>UN RTDG</b>	3
IMDG-Code	3





# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: 3106

ICAO-TI	3
<b>14.4 Packing group</b>	
<b>UN RTDG</b>	II
IMDG-Code	II
ICAO-TI	II
<b>14.5 Environmental hazards</b>	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment):	n-Heptane
<b>14.6 Special precautions for user</b>	
There is no additional information.	
<b>14.7 Transport in bulk according to IMO instruments</b>	
The cargo is not intended to be carried in bulk.	
<b>14.8 Information for each of the UN Model Regulations</b>	
<b>Transport information National regulations Additional information (UN RTDG)</b>	
<b>UN number</b>	3295
<b>Class</b>	3
<b>Environmental hazards</b>	Yes Hazardous to the aquatic environment
<b>Packing group</b>	II
<b>Danger label(s)</b>	3 Fish and tree
	
	
<b>Special provisions (SP)</b>	- UN RTDG
<b>Excepted quantities (EQ)</b>	E2 UN RTDG
<b>Limited quantities (LQ)</b>	1 L UN RTDG
<b>International Maritime Dangerous Goods Code (IMDG) - Additional information</b>	
Proper shipping name	HYDROCARBONS, LIQUID, N.O.S.
Particulars in the shipper's declaration	UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II, -4°C c.c., MARINE POLLUTANT
Marine pollutant	yes (hazardous to the aquatic environment)
Danger label(s)	3, "Fish and tree"
	
	
<b>Special provisions (SP)</b>	-
<b>Excepted quantities (EQ)</b>	E2

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: **3106**

Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	B

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Hydrocarbons, liquid, n.o.s.
Particulars in the shipper's declaration	UN3295, Hydrocarbons, liquid, n.o.s., 3, II
Environmental hazards	YES (hazardous to the aquatic environment)
Danger label(s)	3



## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

#### National regulations(Australia)

##### Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

#### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Toluene	108-88-3	Table II	2902.30

#### National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI® Calipure 1,44468 (20 °C)

article number: 3106

Country	Inventory	Status
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	The most important adverse physicochemical, human health and environmental effects: Narcotic effects.	The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI® Calipure 1,44468 (20 °C)

article number: 3106

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Toluene, n-Heptane		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval



# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



## Refractive index standard ROTI®Calipure 1,44468 (20 °C)

article number: 3106

Abbr.	Descriptions of used abbreviations
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties. The classification is based on tested mixture.

Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H362	May cause harm to breast-fed children.
H373	May cause damage to organs (central nervous system) through prolonged or repeated exposure (if inhaled).

# Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



**Refractive index standard ROTI®Calipure 1,44468 (20 °C)**

article number: **3106**

---

## **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.