acc. to Safe Work Australia - Code of Practice

Musk oil artificial





SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance Musk oil artificial

Article number 3364

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

•

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.45	Skin sensitisation	1	Skin Sens. 1	H317

For full text of abbreviations: see SECTION 16

2.2 Label elements

Labelling

Signal word Warning

Australia (en) Page 1 / 14

acc. to Safe Work Australia - Code of Practice



Musk oil artificial

article number: 3364

Pictograms

GHS07



Hazard statements

H317 May cause an allergic skin reaction

Precautionary statements

Precautionary statements - prevention

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P321 Specific treatment (see on this label)

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Hazardous ingredients for labelling: 2-Aceto-2,3,8,8,-tetramethyloctahydronaph-

thalene

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Benzyl alcohol	CAS No 100-51-6	2.5 - 5	Acute Tox. 4 / H302 Acute Tox. 4 / H332	<u>(1)</u>	
Benzoic acid benzyl ester	CAS No 120-51-4	2.5 - 5	Acute Tox. 4 / H302	(!)	
2-Aceto-2,3,8,8,-tetra- methyloctahy- dronaphthalene	CAS No 54464-57-2	2.5 - 5	Skin Sens. 1 / H317	<u>(1)</u>	
Ambrette Oil	CAS No 84455-19-6	2.5 - 5	Flam. Liq. 4 / H227		

For full text of abbreviations: see SECTION 16

Australia (en) Page 2 / 14

acc. to Safe Work Australia - Code of Practice



Musk oil artificial

article number: 3364

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air.

Following skin contact

After contact with skin, wash immediately with plenty of water. In case of skin reactions, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Vomiting, Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

None.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

Australia (en) Page 3 / 14

acc. to Safe Work Australia - Code of Practice

Musk oil artificial

article number: 3364



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

Australia (en) Page 4 / 14

acc. to Safe Work Australia - Code of Practice



article number: 3364



SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Data are not available.

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time
Benzoic acid benzyl ester	120-51-4	DNEL	5.1 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects
Benzoic acid benzyl ester	120-51-4	DNEL	102 mg/m³	human, inhalat- ory	worker (industry)	acute - systemic effects
Benzoic acid benzyl ester	120-51-4	DNEL	2.6 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Benzoic acid benzyl ester	120-51-4	PNEC	0.017 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
Benzoic acid benzyl ester	120-51-4	PNEC	0.002 ^{mg} / _l	aquatic organ- isms marine water		short-term (single instance)
Benzoic acid benzyl ester	120-51-4	PNEC	100 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Benzoic acid benzyl ester	120-51-4	PNEC	10.66 ^{mg} /	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Benzoic acid benzyl ester	120-51-4	PNEC	1.07 ^{mg} / _{kg}	aquatic organ- isms	•	
Benzoic acid benzyl ester	120-51-4	PNEC	2.12 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
Ambrette Oil	84455-19-6	PNEC	100 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Australia (en) Page 5 / 14

acc. to Safe Work Australia - Code of Practice

ROTH

Musk oil artificial

article number: 3364

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

· breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection necessary at: Aerosol or mist formation.

Respiratory protection





Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless - light yellow

Odour characteristic

Melting point/freezing point <-20 °C at 101.3 kPa (data apply to the main com-

ponent)

Boiling point or initial boiling point and boiling

range

(unknown) not determined

Flammability this material is combustible, but will not ignite

readily

Lower and upper explosion limit $38.7 \text{ g/m}^3 - 387 \text{ g/m}^3$ /

1.3 võl% - 13 vol%

Australia (en) Page 6 / 14

acc. to Safe Work Australia - Code of Practice

ROTH

Musk oil artificial

article number: 3364

Flash point >100 °C

Auto-ignition temperature 310 °C auto-ignition temperature (liquids and

gases)

Decomposition temperature not relevant pH (value) not determined

Kinematic viscosity not determined

Solubility(ies)

Water solubility not determined

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Vapour pressure 1.3 hPa at 25 °C

Density $1.05 \, {}^{9}/_{cm^3}$ at 20 ${}^{\circ}\text{C}$

Particle characteristics No data available.

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard hazard classes acc. to GHS

classes: (physical hazards): not relevant

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

Australia (en) Page 7 / 14

acc. to Safe Work Australia - Code of Practice

Musk oil artificial

article number: 3364



10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Benzyl alcohol	100-51-6	oral	1,580 ^{mg} / _{kg}
Benzyl alcohol	100-51-6	inhalation: vapour	11 ^{mg} / _l /4h
Benzyl alcohol	100-51-6	inhalation: dust/mist	>4.178 ^{mg} / _l /4h

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Benzyl alcohol	100-51-6	oral	LD50	1,580 ^{mg} / _{kg}	mouse
Benzyl alcohol	100-51-6	inhalation: dust/mist	LC50	>4,178 ^{mg} / _{m³} / 4h	rat
Benzoic acid benzyl ester	120-51-4	oral	LD50	>2,000 ^{mg} / _{kg}	rat
Ambrette Oil	84455-19-6	dermal	LD50	5,000 ^{mg} / _{kg}	rabbit
Ambrette Oil	84455-19-6	oral	LD50	>2,000 ^{mg} / _{kg}	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Australia (en) Page 8 / 14

acc. to Safe Work Australia - Code of Practice

ROTH

Musk oil artificial

article number: 3364

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

Data are not available.

• If in eyes

Data are not available.

If inhaled

Data are not available.

• If on skin

May produce an allergic reaction, pruritis, localised redness

Other information

This information is based upon the present state of our knowledge.

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture								
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time			
Benzyl alcohol	100-51-6	LC50	460 ^{mg} / _l	fish	96 h			
Benzyl alcohol	100-51-6	EC50	230 ^{mg} / _l	aquatic invertebrates	48 h			
Benzyl alcohol	100-51-6	ErC50	770 ^{mg} / _l	algae	72 h			
Benzoic acid benzyl ester	120-51-4	LC50	0.29 ^{mg} / _l	striped brill	96 h			
Benzoic acid benzyl ester	120-51-4	EC50	3.09 ^{mg} / _l	aquatic invertebrates	48 h			
Benzoic acid benzyl ester	120-51-4	ErC50	0.475 ^{mg} / _l	algae	72 h			
Ambrette Oil	84455-19-6	EL50	>100 ^{mg} / _l	aquatic invertebrates	48 h			
Ambrette Oil	84455-19-6	ErC50	262 ^{mg} / _l	algae	72 h			
Ambrette Oil	84455-19-6	EC50	25.2 ^{mg} / _l	algae	72 h			

Australia (en) Page 9 / 14

acc. to Safe Work Australia - Code of Practice



Musk oil artificial

article number: 3364

Aquatic toxicity (chronic) of components of the mixtur	Aquatic toxicit	(chronic) of	components of	of the mixture
--	------------------------	--------------	---------------	----------------

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Benzyl alcohol	100-51-6	LC50	770 ^{mg} / _l	fish	1 h
Benzyl alcohol	100-51-6	EC50	66 ^{mg} / _l	aquatic invertebrates	21 d
Benzoic acid benzyl ester	120-51-4	LC50	11 ^{mg} / _l	aquatic invertebrates	24 h
Benzoic acid benzyl ester	120-51-4	EC50	>10,000 ^{mg} / _l	microorganisms	3 h

Biodegradation

Data are not available.

12.2 Process of degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Benzyl alcohol	100-51-6	oxygen deple- tion	92 - 96 %	14 d		ECHA
Benzyl alcohol	100-51-6	DOC removal	95 %	21 d		ECHA
Benzoic acid benzyl ester	120-51-4	biotic/abiotic	94 %	28 d		
Benzoic acid benzyl ester	120-51-4	oxygen deple- tion	94 %	28 d		ECHA
Ambrette Oil	84455-19-6	carbon dioxide generation	80 – 90 %	28 d		ECHA

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Benzyl alcohol	100-51-6		1 (20 °C)	
Benzoic acid benzyl ester	120-51-4	193.4	3.97 (25 °C)	
2-Aceto-2,3,8,8,-tetramethyloc- tahydronaphthalene	54464-57-2		5.65 (30 °C)	
Ambrette Oil	84455-19-6		<0.3 (pH value: 5.4, 20 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

Australia (en) Page 10 / 14

acc. to Safe Work Australia - Code of Practice

Musk oil artificial

article number: 3364

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1	UN number	not subject to transport regulations

14.2 UN proper shipping name not assigned
 14.3 Transport hazard class(es) not assigned
 14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

Not subject to transport regulations. UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

Australia (en) Page 11 / 14

acc. to Safe Work Australia - Code of Practice

Musk oil artificial

article number: 3364



SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AICS CICR CSCL-ENCS DSL ECSI IECSC Australian Inventory of Chemical Substances Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS)

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS) INSQ

ISHA-ENCS

KECI NZIoC

Korea Existing Chemicals Inventory New Zealand Inventory of Chemicals Philippine Inventory of Chemicals and Chemical Substances (PICCS) PICCS Philippine Inventory of Chemicals and REACH Reg. REACH registered substances TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Australia (en) Page 12 / 14

acc. to Safe Work Australia - Code of Practice

Musk oil artificial

article number: 3364



SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Skin Sens.	Skin sensitisation
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

Australia (en) Page 13 / 14

acc. to Safe Work Australia - Code of Practice



Musk oil artificial

article number: 3364

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H332	Harmful if inhaled.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 14 / 14