

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

Version: GHS 1.0 en

date of compilation: 2024-08-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material
Article number	33PT
CAS number	928771-01-1
Alternative name(s)	Renewable hydrocarbons (diesel type fraction)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory and analytical use Laboratory chemical
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-stuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

Supplemental hazard information

Code	Supplemental hazard information
AUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

2.2 Label elements

Labelling

Signal word **Danger**

Pictograms

GHS08



Hazard statements

H304 May be fatal if swallowed and enters airways

Precautionary statements

Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTRE/doctor
P331 Do NOT induce vomiting

Precautionary statements - storage

P405 Store locked up

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Supplemental hazard information

AUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

"UVCB substance" (substance of unknown or variable composition).

Name of substance	Renewable hydrocarbons (diesel type fraction)
CAS No	928771-01-1

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage. Incompatible materials: see section 10.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM (fluoro rubber), Butyl caoutchouc (butyl rubber)

• material thickness

≥0,4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 ° C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	<-20 °C at 1,013 hPa (ECHA)

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

Boiling point or initial boiling point and boiling range	260 °C at 1,013 hPa
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	0.6 vol% (LEL) - 7 vol% (UEL)
Flash point	>100 °C at 1,013 hPa
Auto-ignition temperature	>201 °C at 1,013 hPa
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	2.9 mm ² /s at 40 °C

Solubility(ies)

Water solubility <0 g/l at 20 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): >6.5 (pH value: ~7, 30 °C) (ECHA)

Soil organic carbon/water (log KOC) >5.63 (ECHA)

Vapour pressure 87.1 Pa at 25 °C

Density and/or relative density

Density 0.779 g/cm³ at 15 °C

Relative vapour density Information on this property is not available.

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes: hazard classes acc. to GHS (physical hazards): not relevant

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if swallowed or in contact with skin.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2,000 mg/kg	rat		ECHA
dermal	LD50	>2,000 mg/kg	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

- **If swallowed**

aspiration hazard

- **If in eyes**

Data are not available.

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

• If inhaled

Data are not available.

• If on skin

Data are not available.

• Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LL50	$>100 \text{ mg/l}$	fish	ECHA	24 h
EL50	$>100 \text{ mg/l}$	aquatic invertebrates	ECHA	48 h
EC50	$>100 \text{ mg/l}$	aquatic invertebrates	ECHA	48 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
LL50	$>100 \text{ mg/l}$	fish	ECHA	3.25 h
EL50	$>100 \text{ mg/l}$	aquatic invertebrates	ECHA	21 d
EC50	$>1,000 \text{ mg/l}$	microorganisms	ECHA	30 min
NOELR	$\geq 100 \text{ mg/l}$	fish	ECHA	33 d
LOEC	$3,2 \text{ mg/l}$	aquatic invertebrates	ECHA	21 d
NOEC	1 mg/l	aquatic invertebrates	ECHA	21 d

12.2 Persistence and degradability

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
carbon dioxide generation	82 %	28 d
DOC removal	44 %	7 d

12.3 Bioaccumulative potential

The substance fulfils the very bioaccumulative criterion.

n-octanol/water (log KOW)	>6.5 (pH value: ~ 7 , $30 \text{ }^\circ\text{C}$) (ECHA)
BCF	$>3.2 - \leq 1,950$ (ECHA)

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	>5.63 (ECHA)
--	--------------

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number	not subject to transport regulations
14.2 UN proper shipping name	not assigned
14.3 Transport hazard class(es)	not assigned
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	There is no additional information.
14.7 Transport in bulk according to IMO instruments	The cargo is not intended to be carried in bulk.

Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

14.8 Information for each of the UN Model Regulations

Transport information National regulations Additional information (UN RTDG)

Not subject to transport regulations. UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations (Australia)

Australian Inventory of Chemical Substances (AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
JP	CSCL-ENCS	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)

Legend

AIIC	Australian Inventory of Industrial Chemicals
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval

Safety data sheet

acc. to Safe Work Australia - Code of Practice



Isoparaffin 255-290 SOLVAGREEN® for synthesis, recycled material

article number: 33PT

Abbr.	Descriptions of used abbreviations
ED	Endocrine disruptor
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
LOEC	Lowest Observed Effect Concentration
NOEC	No Observed Effect Concentration
NOELR	No Observed Effect Loading Rate
PBT	Persistent, Bioaccumulative and Toxic
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H304	May be fatal if swallowed and enters airways.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.