

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7\%$, for synthesis

article number: **3559**
Version: **GHS 4.0 en**
Replaces version of: 2022-03-15
Version: (GHS 3)

date of compilation: 2016-08-23
Revision: 2024-03-02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	Butylated hydroxytoluene $\geq 99,7\%$, for synthesis
Article number	3559
CAS number	128-37-0

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

This substance does not meet the criteria for classification.

2.2 Label elements

Labelling

not required

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7\%$, for synthesis

article number: 3559

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Butylated hydroxytoluene
Molecular formula	$C_{15}H_{24}O$
Molar mass	220.4 g/mol
CAS No	128-37-0

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

In case of respiratory tract irritation, consult a physician.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Irrigate copiously with clean, fresh water, holding the eyelids apart. Protect uninjured eye.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

Butylated hydroxytoluene $\geq 99,7$ %, for synthesis

article number: 3559

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water, foam, dry extinguishing powder, ABC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

No special measures are necessary.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains. Take up mechanically.

Advice on how to clean up a spill

Take up mechanically.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Butylated hydroxytoluene ≥99,7 %, for synthesis

article number: 3559

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [mg/m ³]	STEL [mg/m ³]	Ceiling-C [mg/m ³]	Notation	Source
AU	2,6-di-tert-butyl-p-cresol	128-37-0	WES	10				WES

Notation

Ceiling-C
STEL

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	19 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
DNEL	18 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	3.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	0.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7$ %, for synthesis

article number: 3559

Environmental values

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	8.33 mg/kg	aquatic organisms	water	short-term (single instance)
PNEC	1.99 $\mu\text{g/l}$	aquatic organisms	water	intermittent release
PNEC	0.199 $\mu\text{g/l}$	aquatic organisms	freshwater	short-term (single instance)
PNEC	0.02 $\mu\text{g/l}$	aquatic organisms	marine water	short-term (single instance)
PNEC	0.17 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	99.6 $\mu\text{g/kg}$	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	9.96 $\mu\text{g/kg}$	aquatic organisms	marine sediment	short-term (single instance)
PNEC	47.69 $\mu\text{g/kg}$	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



- **hand protection**

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

- **type of material**

Butyl caoutchouc (butyl rubber)

- **material thickness**

0,5 mm

- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection


Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7$ %, for synthesis

article number: 3559



Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P1 (filters at least 80 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	solid
Form	crystals
Colour	white
Odour	odourless
Melting point/freezing point	69 – 71 °C
Boiling point or initial boiling point and boiling range	265 °C at 1,013 hPa
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined
Flash point	127 °C (c.c.)
Auto-ignition temperature	not determined
Decomposition temperature	320 °C
pH (value)	not applicable
Kinematic viscosity	not relevant

Solubility(ies)

Water solubility 0.4 g/l at 20 °C (practically insoluble)

Partition coefficient

Partition coefficient n-octanol/water (log value): 5.1 (ECHA)

Soil organic carbon/water (log KOC) 4.169 (ECHA)

Vapour pressure 0.011 hPa at 20 °C

Density and/or relative density

Density 1.03 g/cm³ at 20 °C (ECHA)

Relative vapour density 7.61 (air = 1)

Bulk density ~450 kg/m³

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7\%$, for synthesis

article number: 3559

Particle characteristics No data available.

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes: hazard classes acc. to GHS (physical hazards): not relevant

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product in the delivered form is not dust explosion capable; the enrichment of fine dust however leads to the danger of dust explosion.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat. Decomposition takes place from temperatures above: 320 °C.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

This substance does not meet the criteria for classification.

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>6,000 mg/kg	rat		ECHA
dermal	LD50	>2,000 mg/kg	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7$ %, for synthesis

article number: 3559

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

Data are not available.

• If in eyes

slightly irritant but not relevant for classification

• If inhaled

Inhalation of dust may cause irritation of the respiratory system

• If on skin

Frequently or prolonged contact with skin may cause dermal irritation

• Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	$>0.57 \text{ mg/l}$	fish	ECHA	96 h
EC50	0.48 mg/l	aquatic invertebrates	ECHA	48 h

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene ≥99,7 %, for synthesis

article number: 3559

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
ErC50	>0.4 mg/l	algae	ECHA	72 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	0.096 mg/l	aquatic invertebrates	ECHA	21 d

12.2 Persistence and degradability

Theoretical Oxygen Demand: 2.977 mg/mg
Theoretical Carbon Dioxide: 2.996 mg/mg

Biodegradation

Not readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	<10 %	20 d

12.3 Bioaccumulative potential

The substance fulfils the very bioaccumulative criterion.

n-octanol/water (log KOW)	5.1 (ECHA)
BCF	598.4

12.4 Mobility in soil

Henry's law constant	318.9 Pa m ³ /mol at 25 °C (ECHA)
The Organic Carbon normalised adsorption coefficient	4.169 (ECHA)

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

12.7 Other adverse effects

Data are not available.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7$ %, for synthesis

article number: **3559**

SECTION 13: Disposal considerations

13.1 Waste treatment methods



Consult the appropriate local waste disposal expert about waste disposal.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 3077
IMDG-Code	UN 3077
ICAO-TI	UN 3077

14.2 UN proper shipping name

UN RTDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
ICAO-TI	Environmentally hazardous substance, solid, n.o.s.
Technical name	Butylated hydroxytoluene

14.3 Transport hazard class(es)

UN RTDG	9
IMDG-Code	9
ICAO-TI	9

14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

hazardous to the aquatic environment

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7\%$, for synthesis

article number: 3559

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport information National regulations Additional information (UN RTDG)

UN number	3077
Class	9
Environmental hazards	Yes Hazardous to the aquatic environment
Packing group	III
Danger label(s)	9 Fish and tree



Special provisions (SP)	274, 331, 335, 375 UN RTDG
Excepted quantities (EQ)	E1 UN RTDG
Limited quantities (LQ)	5 kg UN RTDG
Emergency Action Code	2Z

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Particulars in the shipper's declaration	UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., (Butylated hydroxytoluene), 9, III
Marine pollutant	yes (hazardous to the aquatic environment), (Butylated hydroxytoluene)
Danger label(s)	9, "Fish and tree"

Special provisions (SP)	274, 335, 966, 967, 969
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 kg
EmS	F-A, S-F
Stowage category	A



Safety data sheet Safety data sheet



acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene ≥99,7 %, for synthesis

article number: 3559

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Environmentally hazardous substance, solid, n.o.s.
Particulars in the shipper's declaration	UN3077, Environmentally hazardous substance, solid, n.o.s., (Butylated hydroxytoluene), 9, III
Environmental hazards	YES (hazardous to the aquatic environment)
Danger label(s)	9, "Fish and tree"
 	
Special provisions (SP)	A97, A158, A179, A197, A215
Excepted quantities (EQ)	E1
Limited quantities (LQ)	30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene ≥99,7 %, for synthesis

article number: 3559

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 2Z	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Butylated hydroxytoluene $\geq 99,7$ %, for synthesis

article number: 3559

Abbr.	Descriptions of used abbreviations
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.