

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane $\geq 99\%$, for synthesis

article number: **3927**
Version: **4.0 en**
Replaces version of: 19.01.2022
Version: (3)

date of compilation: 27.02.2017
Revision: 02.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	2-Methylbutane $\geq 99\%$, for synthesis
Article number	3927
Registration number (REACH)	01-2119475602-38-xxxx
Index number in CLP Annex VI	601-085-00-2
EC number	201-142-8
CAS number	78-78-4
Alternative name(s)	isopentane

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-stuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	1	Flam. Liq. 1	H224
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
4.1C	Hazardous to the aquatic environment - chronic hazard	2	Aquatic Chronic 2	H411

Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP)

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08, GHS09



Hazard statements

H224 Extremely flammable liquid and vapour
H304 May be fatal if swallowed and enters airways
H336 May cause drowsiness or dizziness
H411 Toxic to aquatic life with long lasting effects

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P240 Ground and bond container and receiving equipment
P273 Avoid release to the environment

Precautionary statements - response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane $\geq 99\%$, for synthesis

article number: 3927

Symbol(s)



H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P403+P235	Store in a well-ventilated place. Keep cool.
EUH066	Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	2-Methylbutane
Molecular formula	C_5H_{12}
Molar mass	72,15 g/mol
REACH Reg. No	01-2119475602-38-xxxx
CAS No	78-78-4
EC No	201-142-8
Index No	601-085-00-2

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Nausea, Vomiting, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Do not allow firefighting water to enter drains or water courses. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane $\geq 99\%$, for synthesis

article number: 3927

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Measures to protect the environment

Avoid release to the environment.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

high temperatures, static discharges

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	isopentane	78-78-4	IOELV	1.000	3.000						2006/15/EC
MT	isopentane	78-78-4	OELV	1.000	3.000						CAP. 424

Notation

Ceiling-C
STEL
TWA

Ceiling value is a limit value above which exposure should not occur
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	3.000 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	432 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane $\geq 99\%$, for synthesis

article number: 3927

only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

- **type of material**

NBR (Nitrile rubber)

- **material thickness**

0,4 mm

- **breakthrough times of the glove material**


>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: AX (gas filters and combined filters against low-boiling point organic compounds, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless - clear
Odour	characteristic
Melting point/freezing point	-159,8 °C (ECHA)
Boiling point or initial boiling point and boiling range	27,8 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1,4 vol% (LEL) - 7,6 vol% (UEL)
Flash point	-51 °C at 1.013 hPa (ECHA)
Auto-ignition temperature	420 °C at 1.013 hPa (ECHA)
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Dynamic viscosity	0,214 mPa s at 25 °C
<u>Solubility(ies)</u>	
Water solubility	0,049 g/l at 25 °C (practically insoluble) (ECHA)

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane $\geq 99\%$, for synthesis

article number: 3927

Partition coefficient

Partition coefficient n-octanol/water (log value): 4 (pH value: 6,6, 25 °C) (ECHA)

Soil organic carbon/water (log KOC) 2,895 (ECHA)

Vapour pressure 100 kPa at 27,5 °C

Density and/or relative density

Density 0,62 g/cm³ at 20 °C (ECHA)

Relative vapour density 2,49 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Gas group (explosion group) IIA
Maximum Experimental Safe Gap value; MESG > 0,9 mm

Maximum explosion pressure 9,1 bar

Surface tension 15,49 mN/m (25 °C) (ECHA)

Temperature class (EU, acc. to ATEX) T2
Maximum permissible surface temperature on the equipment: 300°C

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Nitric acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2.000 mg/kg	rat		ECHA
inhalation: vapour	LC50	>25,3 mg/l/4h	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, nausea, aspiration hazard

• If in eyes

Data are not available.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane $\geq 99\%$, for synthesis

article number: 3927

• If inhaled

vertigo, dizziness, fatigue, narcosis

• If on skin

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation)

• Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Theoretical Oxygen Demand: $3,548 \text{ mg/mg}$
Theoretical Carbon Dioxide: $3,05 \text{ mg/mg}$

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	100 %	12 d
oxygen depletion	71,43 %	28 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	4 (pH value: 6,6, 25 °C) (ECHA)
BCF	171 (ECHA)

12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	2,895 (ECHA)
--	--------------

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane $\geq 99\%$, for synthesis

article number: 3927

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP 3 flammable
HP 5 specific target organ toxicity (STOT)/aspiration toxicity
HP 14 ecotoxic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	UN 1265
IMDG-Code	UN 1265
ICAO-TI	UN 1265

14.2 UN proper shipping name

ADR	PENTANES
IMDG-Code	PENTANES
ICAO-TI	Pentanes

14.3 Transport hazard class(es)

ADR	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

ADR	I
-----	---

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU





2-Methylbutane $\geq 99\%$, for synthesis

article number: 3927



IMDG-Code	I
ICAO-TI	I
14.5 Environmental hazards	hazardous to the aquatic environment
14.6 Special precautions for user	
Provisions for dangerous goods (ADR) should be complied within the premises.	
14.7 Maritime transport in bulk according to IMO instruments	
The cargo is not intended to be carried in bulk.	

14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) Additional information

Proper shipping name	PENTANES
Particulars in the transport document	UN1265, PENTANES, 3, I, (D/E), environmentally hazardous
Classification code	F1
Danger label(s)	3, "Fish and tree"
 	
Environmental hazards	yes (hazardous to the aquatic environment)
Excepted quantities (EQ)	E3
Limited quantities (LQ)	0
Transport category (TC)	1
Tunnel restriction code (TRC)	D/E
Hazard identification No	33

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	PENTANES
Particulars in the shipper's declaration	UN1265, PENTANES, 3, I, -51°C c.c., MARINE POLLUTANT
Marine pollutant	yes (hazardous to the aquatic environment)
Danger label(s)	3, "Fish and tree"
 	
Special provisions (SP)	-
Excepted quantities (EQ)	E3
Limited quantities (LQ)	0
EmS	F-E, S-D
Stowage category	E

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Pentanes
Particulars in the shipper's declaration	UN1265, Pentanes, 3, I
Environmental hazards	YES (hazardous to the aquatic environment)
Danger label(s)	3



Excepted quantities (EQ) E3

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
2-Methylbutane	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
2-Methylbutane	flammable / pyrophoric		R40	40

Legend

- R3
1. Shall not be used in:
 - ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects,
 2. Articles not complying with paragraph 1 shall not be placed on the market.
 3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:
 - can be used as fuel in decorative oil lamps for supply to the general public, and
 - present an aspiration hazard and are labelled with H304.
 4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).
 5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:
 - (a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";
 - (b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';
 - (c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

Legend

- R40
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:
 - metallic glitter intended mainly for decoration,
 - artificial snow and frost,
 - 'whoopie' cushions,
 - silly string aerosols,
 - imitation excrement,
 - horns for parties,
 - decorative flakes and foams,
 - artificial cobwebs,
 - stink bombs.
 2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:
'For professional users only'.
 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).
 4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P5a	flammable liquids (cat. 1)	10 50	49)

Notation

- 49) - Flammable liquids, category 1, or
- flammable liquids category 2 or 3 maintained at a temperature above their boiling point, or
- other liquids with a flash point ≤ 60 °C, maintained at a temperature above their boiling point

Deco-Paint Directive

VOC content	100 %
VOC content	620 g/l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	620 g/l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

not listed

Regulation on the marketing and use of explosives precursors

not listed

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

Regulation on drug precursors

not listed

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical safety assessment

According to REACH, Article 14 (1) a chemical safety assessment has been carried out for this substance or components of this mixture when the substance has been registered in quantities of 10 tonnes or more per year per registrant.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.		yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1	VOC content: 100 % , 620 g/l	VOC content: 100 %	yes
15.1		VOC content: 620 g/l	yes
15.1		National inventories: change in the listing (table)	yes
15.2	Chemical Safety Assessment: No Chemical Safety Assessment has been carried out for this substance.	Chemical safety assessment: According to REACH, Article 14 (1) a chemical safety assessment has been carried out for this substance or components of this mixture when the substance has been registered in quantities of 10 tonnes or more per year per registrant.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2006/15/EC	Commission Directive establishing a second list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC and amending Directives 91/322/EEC and 2000/39/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
BCF	Bioconcentration factor
CAP. 424	Occupational Health and Safety Authority Act (CAP. 424)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥99 %, for synthesis

article number: 3927

Abbr.	Descriptions of used abbreviations
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU



2-Methylbutane ≥ 99 %, for synthesis

article number: **3927**

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.