acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997 date of compilation: 2018-06-11 Version: GHS 3.0 en

Replaces version of: 2021-08-03

Version: (GHS 2)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Lithium hydroxide monohydrate** ≥56,5 % LiOH

Article number 3997

CAS number 1310-66-3

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for squirting or spraying. Do not use

for products which come into direct contact with the skin. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment

sheet:

sicherheit@carlroth.de e-mail (competent person):

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.2	Skin corrosion/irritation	1B	Skin Corr. 1B	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

For full text of abbreviations: see SECTION 16

Australia (en) Page 1 / 14



Revision: 2024-03-02

acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS05, GHS07



Hazard statements

H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage

Precautionary statements

Precautionary statements - prevention

P260 Do not breathe dusts or mists P280 Wear eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P321 Specific treatment (see on this label)

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Lithium hydroxide monohydrate

Molecular formula HLiO

Molar mass $41.96 \, ^{\mathrm{g}} /_{\mathrm{mol}}$ CAS No 1310-66-3

Australia (en) Page 2 / 14

acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Rinse mouth with water (only if the person is conscious). Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Vomiting, Risk of blindness, Gastric perforation, Risk of serious damage to eyes

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water, foam, alcohol resistant foam, dry extinguishing powder, ABC-powder

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

Australia (en) Page 3 / 14

acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe dust.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains. Take up mechanically.

Advice on how to clean up a spill

Take up mechanically. Control of dust.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handle and open container with care. Avoid dust formation. Clear contaminated areas thoroughly.

Measures to prevent fire as well as aerosol and dust generation

Removal of dust deposits.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place. Keep container tightly closed. Hygroscopic solid.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

humidity, UV-radiation/sunlight, contact with air/oxygen

Consideration of other advice:

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

Australia (en) Page 4 / 14

acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	nuisance dusts		WES	10			i	WES

Notation

Ceiling value is a limit value above which exposure should not occur Inhalable fraction Ceiling-C

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 TWA

hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels

Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	10 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	30 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	41.35 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
DNEL	100 mg/kg bw/ day	human, dermal	worker (industry)	acute - systemic effects

Environmental values

Relevant PNECs and other threshold levels

End- point	Threshold level	Organism	Environmental com- partment	Exposure time
PNEC	2.3 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0.23 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)
PNEC	79.2 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	9 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0.9 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0.45 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)

Australia (en) Page 5 / 14



acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection. Wear face protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

≥0,3 mm

· breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P2 (filters at least 94 % of airborne particles, colour code: White).

Environmental exposure controls

Keep away from drains, surface and ground water.

Australia (en) Page 6 / 14

acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties 9.1

Physical state solid

Form crystalline Colour white

Odour odourless

Melting point/freezing point 424 °C (anhydrous) not determined

Boiling point or initial boiling point and boiling

range

Flammability non-combustible Lower and upper explosion limit not determined Flash point not applicable Auto-ignition temperature not determined

not relevant Decomposition temperature

12 (in aqueous solution: $50 \,^{9}/_{l}$, $50 \,^{\circ}$ C) pH (value)

Kinematic viscosity not relevant

Solubility(ies)

216 ^g/_l at 20 °C Water solubility

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure not determined

Density and/or relative density

1.51 ^g/_{cm³} at 20 °C Density

Relative vapour density Information on this property is not available.

~800 kg/m³ **Bulk density**

No data available. Particle characteristics

Other safety parameters

Oxidising properties none

9.2 Other information

> Information with regard to physical hazard hazard classes acc. to GHS (physical hazards): not relevant classes:

There is no additional information. Other safety characteristics:

Australia (en) Page 7 / 14

acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

10.2 Chemical stability

Hygroscopic solid.

10.3 Possibility of hazardous reactions

Violent reaction with: Ammonia (NH3), Ammonium compounds, Strong acid

10.4 Conditions to avoid

UV-radiation/sunlight. Humidity.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4. May be harmful in contact with skin or if inhaled.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	363 ^{mg} / _{kg}	rat		ECHA
dermal	LD50	>2,000 ^{mg} / _{kg}	rat		ECHA

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Australia (en) Page 8 / 14

acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

Data are not available.

• If on skin

causes severe burns, causes poorly healing wounds

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	109 ^{mg} / _l	zebra fish (Danio rerio)	ECHA	96 h
EC50	33.5 ^{mg} / _l	daphnia magna	ECHA	48 h
ErC50	153.4 ^{mg} / _l	algae	ECHA	72 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	316.8 ^{mg} / _l	microorganisms	ECHA	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Australia (en) Page 9 / 14

acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H8 Corrosives

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

UN RTDGUN 2680IMDG-CodeUN 2680ICAO-TIUN 2680

14.2 UN proper shipping name

UN RTDGLITHIUM HYDROXIDEIMDG-CodeLITHIUM HYDROXIDEICAO-TILithium hydroxide

14.3 Transport hazard class(es)

UN RTDG 8

Australia (en) Page 10 / 14



acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997

IMDG-Code 8
ICAO-TI 8

14.4 Packing group

UN RTDG II
IMDG-Code II
ICAO-TI II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 2680
Class 8
Packing group II
Danger label(s) 8

Special provisions (SP)

UN RTDG

Excepted quantities (EQ)

UN RTDG

Limited quantities (LQ) 1 kg

1 kg UN RTDG

Emergency Action Code 2X

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name LITHIUM HYDROXIDE

Particulars in the shipper's declaration UN2680, LITHIUM HYDROXIDE, 8, II

Marine pollutant Danger label(s) 8

Special provisions (SP)

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 kg

EmS F-A, S-B

Australia (en) Page 11 / 14



acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997

Stowage category Α

Segregation group 18 - Alkalis

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Lithium hydroxide

Particulars in the shipper's declaration UN2680, Lithium hydroxide, 8, II

Danger label(s)



Excepted quantities (EQ) E2 Limited quantities (LQ) 5 kg

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
VN	NCI	substance is listed

Legend

Australian Inventory of Industrial Chemicals

CICR CSCL-ENCS ECSI

Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
Korea Existing Chemicals Inventory

National Chemical Inventory New Zealand Inventory of Chemicals Philippine Inventory of Chemicals and Chemical Substances (PICCS)

Taiwan Chemical Substance Inventory

Australia (en) Page 12 / 14



acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 2X	yes
15.1		Other information: Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval

Australia (en) Page 13 / 14



acc. to Safe Work Australia - Code of Practice

Lithium hydroxide monohydrate ≥56,5 % LiOH

article number: 3997



Abbr.	Descriptions of used abbreviations
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 14 / 14