Special danger of slipping by leaking/spilling product.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt

article number: 4030 Version: GHS 5.0 en Replaces version of: 2022-10-24 Version: (GHS 4)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

4030

63148-62-9

Polydimethylsiloxane

Product identifier 1.1

Identification of the substance

- Article number
- CAS number

Alternative name(s)

Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

Do not use for private purposes (household). Food, drink and animal feedingstuffs.

Silicone oil M 200, medium viscous, 200 cSt

Details of the supplier of the safety data sheet 1.3

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification acc. to GHS

This substance does not meet the criteria for classification.

2.2 Label elements

Labelling

not required

2.3 Other hazards

Australia (en)



date of compilation: 2016-03-17 Revision: 2024-03-03

Silicone oil M 200, medium viscous, 200 cSt

acc. to Safe Work Australia - Code of Practice



article number: **4030**

Results of PBT and vPvB assessment

The substance was identified as a PBT (persistent, bioaccumulative and toxic). The substance was identified as a vPvB (very persistent and very bioaccumulative). Non-classified PBT substance. Non-classified vPvB substance.

Endocrine disrupting properties

The substance has an endocrine disrupting potential.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Silicone oil
Molecular formula	(C₂H₀OSi)n
CAS No	63148-62-9

Impurities/additives/constituents:

Name of substance	Identifier	Wt%
Dodecamethylcyclohexasiloxane	CAS No 540-97-6	0.1 – 3

Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

No special measures are necessary.

Following inhalation

Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Rinse cautiously with water for several minutes.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

- **4.2 Most important symptoms and effects, both acute and delayed** Symptoms and effects are not known to date.
- **4.3** Indication of any immediate medical attention and special treatment needed none

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt



article number: 4030

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Special danger of slipping by leaking/spilling product.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

acc. to Safe Work Australia - Code of Practice

® §ROTH

Silicone oil M 200, medium viscous, 200 cSt

article number: 4030

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Advice on general occupational hygiene

Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

Relevant DNELs of components								
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time		
Dodecamethylcyclo- hexasiloxane	540-97-6	DNEL	11 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects		
Dodecamethylcyclo- hexasiloxane	540-97-6	DNEL	1.22 mg/ m ³	human, inhalat- ory	worker (industry)	chronic - local ef- fects		
Dodecamethylcyclo- hexasiloxane	540-97-6	DNEL	6.1 mg/m ³	human, inhalat- ory	worker (industry)	acute - local ef- fects		

Relevant PNECs of components

	•					
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Dodecamethylcyclo- hexasiloxane	540-97-6	PNEC	1 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Dodecamethylcyclo- hexasiloxane	540-97-6	PNEC	13 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Dodecamethylcyclo- hexasiloxane	540-97-6	PNEC	1.3 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
Dodecamethylcyclo- hexasiloxane	540-97-6	PNEC	3.77 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt

® §ROTH

article number: 4030

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374.

• type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 $^{\circ}$ C, colour code: Brown). Usually no personal respirative protection necessary.

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Form	viscous
Colour	colourless
Odour	odourless
Melting point/freezing point	-50 °C

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt



article number: 4030

Boiling point or initial boiling point and boiling range	not determined
Flammability	this material is combustible, but will not ignite readily
Lower and upper explosion limit	not determined
Flash point	310 °C
Auto-ignition temperature	not determined
Decomposition temperature	>150 °C
pH (value)	not determined
Kinematic viscosity	190 – 210 ^{mm²} / _s at 25 °C
Solubility(ies)	
Water solubility	(The study does not need to be conducted be- cause the substance is known to be insoluble in water)
Solubility in hydrocarbons, aliphatic	soluble
Solubility in hydrocarbons, aromatic	soluble
Solubility in ethylene glycol	practically insoluble
Solubility in ethyl acetate	soluble
Solubility in n-butyl acetate	soluble
Solubility in toluene	soluble
Solubility in trichloroethylene	soluble
Solubility in methanol	practically insoluble
Solubility in trichloromethane (chloroform)	soluble
Partition coefficient	
Partition coefficient n-octanol/water (log value):	this information is not available
Vapour pressure	not determined
Density and/or relative density	
Density	0.967 – 0.975 ^g / _{cm³} at 25 °C
Relative vapour density	Information on this property is not available.
Particle characteristics	not relevant (liquid)
Other safety parameters	
Oxidising properties	none

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt

article number: 4030

9.2 Other information

Information with regard to physical hazard classes:

Other safety characteristics:

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is not reactive under normal ambient conditions.

If heated

Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat. Decompostion takes place from temperatures above: >150 °C.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

This substance does not meet the criteria for classification.

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>5,000 ^{mg} / _{kg}	rat		TOXNET
dermal	LD50	>2,000 ^{mg} / _{kg}	rabbit		TOXNET

Acute toxicity of components

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Dodecamethylcyclohexasiloxane	540-97-6	oral	LD50	>2,000 ^{mg} / _{kg}	rat
Dodecamethylcyclohexasiloxane	540-97-6	dermal	LD50	>2,000 ^{mg} / _{kg}	rat





hazard classes acc. to GHS (physical hazards): not relevant

There is no additional information.

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt



article number: 4030

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

Data are not available.

• If in eyes

Data are not available.

• If inhaled

Data are not available.

• If on skin

Data are not available.

• Other information

Health effects are not known. This information is based upon the present state of our knowledge.

11.2 Endocrine disrupting properties

Not listed.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt



article number: 4030

Aquatic toxicity (acute) of components								
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time			
Dodecamethylcyclo- hexasiloxane	540-97-6	ErC50	>2 ^{µg} /I	algae	72 h			
Aquatic toxicity (chronic) of components								
Name of sub- stance CAS No Endpoint Value Species Exposu time								
Dodecamethylcyclo- hexasiloxane	540-97-6	EC50	>100 ^{mg} /l	microorganisms	3 h			

12.2 Persistence and degradability

Biodegradation

Not readily biodegradable.

Degradability of components

Degradabilit	Degradability of components									
Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source				
Dodecamethyl- cyclohexasilox- ane	540-97-6	carbon dioxide generation	4.47 %	28 d		ECHA				

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components				
Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Dodecamethylcyclohexasiloxane	540-97-6	1,160	8.87 (23.6 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

The substance was identified as a PBT (persistent, bioaccumulative and toxic). The substance was identified as a vPvB (very persistent and very bioaccumulative).

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt



article number: **4030**

SECTION 13: Disposal considerations

13.1 Waste treatment methods



Consult the appropriate local waste disposal expert about waste disposal.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

- 14.2 UN proper shipping name
- 14.3 Transport hazard class(es)
- 14.4 Packing group
- 14.5 Environmental hazards

not subject to transport regulations

not assigned

not assigned

not assigned

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG) Not subject to transport regulations. UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

acc. to Safe Work Australia - Code of Practice



Silicone oil M 200, medium viscous, 200 cSt

article number: 4030

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
VN	NCI	all ingredients are listed

National inventories

Legend

AIIC Australian Inventory of Industrial Chemicals CICR Chemical Inventory and Control Regulation CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS) DSL Domestic Substances List (DSL) ECSI EC Substance Inventory (EINECS, ELINCS, NLP) IECSC Inventory of Existing Chemical Substances Produced or Imported in China INSQ National Inventory of Chemical Substances KECI Korea Existing Chemicals Inventory NCI National Chemical Inventory NCI National Chemical Inventory NZIOC New Zealand Inventory of Chemicals PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS) REACH Reg. REACH registered substances TCSI Taiwan Chemical Substance Inventory TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt



article number: 4030

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3	Results of PBT and vPvB assessment: Containing a PBT-/vPvB-substance in a concen- tration of $\ge 0,1\%$.	Results of PBT and vPvB assessment: The substance was identified as a PBT (persist- ent, bioaccumulative and toxic). The substance was identified as a vPvB (very persistent and very bioaccumulative). Non-classified PBT sub- stance. Non-classified vPvB substance.	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations		
BCF	Bioconcentration factor		
BOD	Biochemical Oxygen Demand		
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances		
COD	Chemical oxygen demand		
DGR	Dangerous Goods Regulations (see IATA/DGR)		
DNEL	Derived No-Effect Level		
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval		
EINECS	European Inventory of Existing Commercial Chemical Substances		
ELINCS	European List of Notified Chemical Substances		
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control		
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions		
ΙΑΤΑ	International Air Transport Association		
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)		
ICAO	International Civil Aviation Organization		
IMDG	International Maritime Dangerous Goods Code		
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval		
log KOW	n-Octanol/water		
NLP	No-Longer Polymer		
PBT	Persistent, Bioaccumulative and Toxic		
PNEC	Predicted No-Effect Concentration		
UN RTDG	UN Recommendations on the Transport of Dangerous Good		
vPvB	Very Persistent and very Bioaccumulative		

acc. to Safe Work Australia - Code of Practice

Silicone oil M 200, medium viscous, 200 cSt



article number: 4030

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.