acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318 date of compilation: 2021-08-25 Version: GHS 1.0 en



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Sulphuric acid 50 %, pure

Article number 4318

CAS number [7664-93-9]

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for squirting or spraying. Do not use

for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private

purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification acc. to GHS

Section	Hazard class		Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation		Skin Corr. 1	H314
3.3	Serious eye damage/eye irritation		Eye Dam. 1	H318

For full text of abbreviations: see SECTION 16

Australia (en) Page 1 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS05



Hazard statements

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

Precautionary statements

Precautionary statements - prevention

P260 Do not breathe dusts or mists P280 Wear eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P390 Absorb spillage to prevent material damage

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Hazardous ingredients for labelling: Sulphuric acid ...%

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

Molecular formula H₂O₄S

Molar mass $98.07 \, ^{9}/_{mol} + H_{2}O$

3.2 Mixtures

Australia (en) Page 2 / 15

acc. to Safe Work Australia - Code of Practice



article number: 4318



Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Sulphuric acid%	CAS No 7664-93-9	50 - < 55	Met. Corr. 1 / H290 Skin Corr. 1 / H314 Eye Dam. 1 / H318		B(a) IARC: 1 RoC "Known"

Notes

B(a): The classification refers to an aqueous solution
IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)
ROC NTP-RoC: Known To Be A Human Carcinogen

"Known"

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 **Description of first aid measures**



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Remove mechanically (e.g. dab away using wadding or cellulose material) then thoroughly wash the affected skin with a mild cleansing agent and water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Gastric perforation, Risk of serious damage to eyes, Risk of blindness

4.3 Indication of any immediate medical attention and special treatment needed

none

Page 3 / 15 Australia (en)

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

Hazardous combustion products

In case of fire may be liberated: Sulphur oxides (SOx)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Australia (en) Page 4 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



SECTION 7: Handling and storage

7.1 Precautions for safe handling

Handle and open container with care. Clear contaminated areas thoroughly.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Store in a dry place. Hygroscopic.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

humidity

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	sulfuric acid	7664-93- 9	WES		1		3				WES

Notation

Ceiling-C STEL Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

	•					
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time
Sulphuric acid%	7664-93-9	DNEL	0.05 mg/ m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects
Sulphuric acid%	7664-93-9	DNEL	0.1 mg/m ³	human, inhalat- ory	worker (industry)	acute - local ef- fects

Australia (en) Page 5 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Sulphuric acid%	7664-93-9	PNEC	0.003 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
Sulphuric acid%	7664-93-9	PNEC	0 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
Sulphuric acid%	7664-93-9	PNEC	8.8 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Sulphuric acid%	7664-93-9	PNEC	0.002 ^{mg} / kg	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Sulphuric acid%	7664-93-9	PNEC	0.002 ^{mg} / kg	aquatic organ- isms	marine sediment	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection. Wear face protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

FKM (fluoro rubber)

material thickness

≥0,4 mm

breakthrough times of the glove material

>480 minutes (permeation: level 6)

Splash protection - Protective gloves

• type of material: Butyl caoutchouc (butyl rubber)

• material thickness: 0,7mm

• breakthrough times of the glove material: >120 minutes (permeation: level 4)

Australia (en) Page 6 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: E (against acidic gases like sulphur dioxide or hydrogen chloride, colour code: Yellow). Type: B-P2 (combined filters for acidic gases and particles, colour code: Grey/White).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless
Odour odourless

Melting point/freezing point not determined Boiling point or initial boiling point and boiling not determined

range

Flammability non-combustible
Lower and upper explosion limit not determined
Flash point not determined
Auto-ignition temperature not determined
Decomposition temperature not relevant
pH (value) <1 (20 °C)

Kinematic viscosity not determined

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure not determined

Density $\sim 1.4 \, \mathrm{g}/\mathrm{cm}^3$ at 20 °C

Relative vapour density information on this property is not available

Australia (en) Page 7 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Corrosive to metals category 1: corrosive to metals

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: Aldehydes, Alkali (lye), Alkali metals, Ammonia (NH3), Bromates, Carbide, Chlorates, Alkaline earth metal, Halogenated hydrocarbons, Metals, Metal powder, Nitrate, Nitriles, Nitro compound, Organic substances, Perchlorates, Permanganates, Peroxides, Phosphorus, Phosphorus oxides (e.g. P2O5), Acids, Strong alkali, Water, Hydrogen peroxide

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

different metals

Release of flammable materials with

Metals, Light metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Australia (en) Page 8 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



Acute toxicity of components of the mixture					
Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Sulphuric acid%	7664-93-9	oral	LD50	2,140 ^{mg} / _{kg}	rat

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

cough, pain, choking, and breathing difficulties

• If on skin

causes severe burns, causes poorly healing wounds

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

Australia (en) Page 9 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Sulphuric acid%	7664-93-9	EC50	>100 ^{mg} / _l	aquatic invertebrates	48 h
Sulphuric acid%	7664-93-9	ErC50	>100 ^{mg} / _l	algae	72 h

Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H8 Corrosives

Australia (en) Page 10 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318

ROTH

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG UN 2796

IMDG-Code UN 2796 ICAO-TI UN 2796

14.2 UN proper shipping name

UN RTDGSULPHURIC ACIDIMDG-CodeSULPHURIC ACIDICAO-TISulphuric acid

14.3 Transport hazard class(es)

UN RTDG 8
IMDG-Code 8
ICAO-TI 8

14.4 Packing group

UN RTDG II
IMDG-Code II
ICAO-TI II

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 2796
Class 8
Packing group II
Danger label(s) 8



Special provisions (SP)

UN RTDG

Australia (en) Page 11 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318

Excepted quantities (EQ) E2

UN RTDG

Limited quantities (LQ) 1 L

UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name SULPHURIC ACID

Particulars in the shipper's declaration UN2796, SULPHURIC ACID, 8, II

Marine pollutant Danger label(s) 8



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

EmS F-A, S-B

Stowage category B

Segregation group 1 - Acids

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Sulphuric acid

Particulars in the shipper's declaration UN2796, Sulphuric acid, 8, II

Danger label(s) 8



Excepted quantities (EQ) E2
Limited quantities (LQ) 0,5 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

UN Convention against Illicit Traffic in Narcotic Drugs and Psychotropic Substances

Name of substance	CAS No	Listed in	HS code
Sulphuric acid%	7664-93-9	Table II	2807.00

Australia (en) Page 12 / 15



acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS CICR CSCL-ENCS DSL ECSI IECSC

Australian Inventory of Chemical Substances
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Korea Existing Chemicals Inventory

INSQ KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule

Australia (en) Page 13 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



Abbr.	Descriptions of used abbreviations
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HS	Harmonized Commodity Description and Coding System (Harmonized System, drawn up by the World Customs Organisation)
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
NLP	No-Longer Polymer
NTP-RoC	National Toxicology Program: Report on Carcinogens
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne conatminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Australia (en) Page 14 / 15

acc. to Safe Work Australia - Code of Practice

Sulphuric acid 50 %, pure

article number: 4318



Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H290	May be corrosive to metals.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 15 / 15