

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester ≥99 %, for synthesis

article number: **4370**  
Version: **2.0 en**  
Replaces version of: 2016-04-25  
Version: (1)

date of compilation: 2016-04-25  
Revision: 2021-12-17

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Identification of the substance	<b>Acetic acid isobutyl ester</b> ≥99 %, for synthesis
Article number	4370
Registration number (REACH)	01-2119488971-22-xxxx
Index number in CLP Annex VI	607-026-00-7
EC number	203-745-1
CAS number	110-19-0

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

### 1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG  
Schoemperlenstr. 3-5  
D-76185 Karlsruhe  
Germany

**Telephone:**+49 (0) 721 - 56 06 0

**Telefax:** +49 (0) 721 - 56 06 149

**e-mail:** sicherheit@carlroth.de

**Website:** www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

**e-mail (competent person):** **sicherheit@carlroth.de**

### 1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Centre Beaumont Hospital	Beaumont Road	Dublin 9	01 809 2166	<a href="https://www.poisons.ie/">https://www.poisons.ie/</a>

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

### Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

### Supplemental hazard information

Code	Supplemental hazard information
EUH066	repeated exposure may cause skin dryness or cracking

For full text of abbreviations: see SECTION 16

### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

## 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008 (CLP)

**Signal word**                      **Danger**

### Pictograms

GHS02, GHS07



### Hazard statements

H225                      Highly flammable liquid and vapour  
H336                      May cause drowsiness or dizziness

### Precautionary statements

#### Precautionary statements - prevention

P210                      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P280                      Wear protective gloves/eye protection

#### Precautionary statements - response

P303+P361+P353      IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]  
P304+P340              IF INHALED: Remove person to fresh air and keep comfortable for breathing

### Supplemental hazard information

EUH066                      Repeated exposure may cause skin dryness or cracking.

### Labelling of packages where the contents do not exceed 125 ml

Signal word: **Danger**

Symbol(s)



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

EUH066 Repeated exposure may cause skin dryness or cracking.

### 2.3 Other hazards

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Name of substance	Acetic acid isobutyl ester
Molecular formula	$C_6H_{12}O_2$
Molar mass	116,2 $g/mol$
REACH Reg. No	01-2119488971-22-xxxx
CAS No	110-19-0
EC No	203-745-1
Index No	607-026-00-7

## SECTION 4: First aid measures

### 4.1 Description of first aid measures



#### General notes

Take off contaminated clothing.

#### Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following skin contact

Rinse skin with water/shower.

#### Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

#### Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

### 4.2 Most important symptoms and effects, both acute and delayed

Dizziness, Drowsiness, Narcosis

### 4.3 Indication of any immediate medical attention and special treatment needed

none

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



**Acetic acid isobutyl ester  $\geq 99\%$ , for synthesis**

article number: **4370**

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings  
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Provision of sufficient ventilation.

#### Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

#### Incompatible substances or mixtures

Observe hints for combined storage.

#### Consideration of other advice:

Ground/bond container and receiving equipment.

#### Ventilation requirements

Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

### 7.3 Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### National limit values

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester ≥99 %, for synthesis

article number: 4370

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
EU	isobutyl acetate	110-19-0	IOELV	50	241	150	723				2019/1831/EU
IE	isobutyl acetate	110-19-0	OELV	150	700						S.I. No. 619 of 2001

#### Notation

Ceiling-C  
STEL Ceiling value is a limit value above which exposure should not occur  
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	300 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	300 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects
DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
DNEL	10 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
DNEL	10 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

### Environmental values

Relevant PNECs and other threshold levels				
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0,34 mg/l	aquatic organisms	water	intermittent release
PNEC	0,17 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0,017 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0,877 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0,088 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0,075 mg/kg	terrestrial organisms	soil	short-term (single instance)

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

### 8.2 Exposure controls

#### Individual protection measures (personal protective equipment)

##### Eye/face protection



Use safety goggle with side protection.

##### Skin protection



##### • hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

##### • type of material

PE: polyethylene

##### • material thickness

0,5 mm

##### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

##### • Splash protection - Protective gloves

• type of material: NBR (Nitrile rubber)

• material thickness: 0,4 mm

• breakthrough times of the glove material: >30 minutes (permeation: level 2)

##### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

##### Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 ° C , colour code: Brown).

##### Environmental exposure controls

Keep away from drains, surface and ground water.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	fruity
Odour threshold	4,05 ppm
Melting point/freezing point	-90 °C (ECHA)
Boiling point or initial boiling point and boiling range	117 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	60 g/m <sup>3</sup> (LEL) - 510 g/m <sup>3</sup> (UEL) / 1,3 vol% (LEL) - 10,5 vol% (UEL)
Flash point	22 °C at 1.013 hPa (ECHA)
Auto-ignition temperature	430 °C at 1.019 hPa (ECHA)
Decomposition temperature	not relevant
pH (value)	5 (in aqueous solution: 4 g/l, 20 °C)
Kinematic viscosity	0,8025 mm <sup>2</sup> /s at 20 °C
<u>Solubility(ies)</u>	
Water solubility	5,6 g/l at 20 °C (ECHA)
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	2,3 (pH value: 7, 25 °C) (ECHA)
Vapour pressure	21 hPa at 20 °C
<u>Density and/or relative density</u>	
Density	0,871 g/cm <sup>3</sup> at 20 °C
Relative vapour density	4,01 at 20 °C (air = 1)
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

#### 9.2 Other information

Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

Surface tension	62,5 mN/m (20 °C) (ECHA)
Temperature class (EU, acc. to ATEX)	T2 Maximum permissible surface temperature on the equipment: 300°C

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

#### If heated

Risk of ignition.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Bases

### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### 10.5 Incompatible materials

There is no additional information.

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Classification according to GHS (1272/2008/EC, CLP)

#### Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	13.413 mg/kg	rat		ECHA
dermal	LD50	>17.400 mg/kg	rabbit		ECHA

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

#### Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

Data are not available.

#### • If in eyes

Data are not available.

#### • If inhaled

fatigue, narcosis

#### • If on skin

repeated exposure may cause skin dryness or cracking

#### • Other information

none

### 11.2 Endocrine disrupting properties

Not listed.

### 11.3 Information on other hazards

There is no additional information.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	16,6 mg/l	fish	ECHA	96 h
EC50	26,8 mg/l	aquatic invertebrates	ECHA	24 h
ErC50	335 mg/l	algae	ECHA	24 h

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester ≥99 %, for synthesis

article number: 4370

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
ErC50	335 mg/l	algae	ECHA	24 h
EC50	34,2 mg/l	aquatic invertebrates	ECHA	21 d
LC50	43,5 mg/l	aquatic invertebrates	ECHA	21 d

### Biodegradation

The substance is readily biodegradable.

#### 12.2 Process of degradability

Theoretical Oxygen Demand: 2,204 mg/mg  
Theoretical Carbon Dioxide: 2,273 mg/mg

Process of degradability		
Process	Degradation rate	Time
oxygen depletion	60 %	5 d

#### 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	2,3 (pH value: 7, 25 °C) (ECHA)
---------------------------	---------------------------------

#### 12.4 Mobility in soil

Data are not available.

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

Not listed.

#### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used.

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

### 13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste catalogue ordinance (Germany).

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADR/RID/ADN	UN 1213
IMDG-Code	UN 1213
ICAO-TI	UN 1213

### 14.2 UN proper shipping name

ADR/RID/ADN	ISOBUTYL ACETATE
IMDG-Code	ISOBUTYL ACETATE
ICAO-TI	Isobutyl acetate

### 14.3 Transport hazard class(es)

ADR/RID/ADN	3
IMDG-Code	3
ICAO-TI	3

### 14.4 Packing group

ADR/RID/ADN	II
IMDG-Code	II
ICAO-TI	II

### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

### 14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

### 14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

#### Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information

Proper shipping name	ISOBUTYL ACETATE
Particulars in the transport document	UN1213, ISOBUTYL ACETATE, 3, II, (D/E)
Classification code	F1
Danger label(s)	3



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: **4370**

Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
Transport category (TC)	2
Tunnel restriction code (TRC)	D/E
Hazard identification No	33

### International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	ISOBUTYL ACETATE
Particulars in the shipper's declaration	UN1213, ISOBUTYL ACETATE, 3, II, 22°C c.c.
Marine pollutant	-
Danger label(s)	3



### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Isobutyl acetate
Particulars in the shipper's declaration	UN1213, Isobutyl acetate, 3, II
Danger label(s)	3



## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Relevant provisions of the European Union (EU)

#### Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)				
Name of substance	Name acc. to inventory	CAS No	Restriction	No
Acetic acid isobutyl ester	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		R3	3
Acetic acid isobutyl ester	flammable / pyrophoric		R40	40

#### Legend

- R3 1. Shall not be used in:  
- ornamental articles intended to produce light or colour effects by means of different phases, for example in orna-

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester ≥99 %, for synthesis

article number: 4370

### Legend

- mental lamps and ashtrays,  
- tricks and jokes,  
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects,  
2. Articles not complying with paragraph 1 shall not be placed on the market.  
3. Shall not be placed on the market if they contain a colouring agent, unless required for fiscal reasons, or perfume, or both, if they:  
— can be used as fuel in decorative oil lamps for supply to the general public, and  
— present an aspiration hazard and are labelled with H304.  
4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).  
5. Without prejudice to the implementation of other Union provisions relating to the classification, labelling and packaging of substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met:  
(a) lamp oils, labelled with H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil – or even sucking the wick of lamps – may lead to life-threatening lung damage";  
(b) grill lighter fluids, labelled with H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: 'Just a sip of grill lighter fluid may lead to life threatening lung damage';  
(c) lamps oils and grill lighters, labelled with H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.;
- R40
1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:  
- metallic glitter intended mainly for decoration,  
- artificial snow and frost,  
- 'whoopie' cushions,  
- silly string aerosols,  
- imitation excrement,  
- horns for parties,  
- decorative flakes and foams,  
- artificial cobwebs,  
- stink bombs.  
2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:  
'For professional users only'.  
3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/324/EEC (2).  
4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

### List of substances subject to authorisation (REACH, Annex XIV)/SVHC - candidate list

Not listed.

### Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P5c	flammable liquids (cat. 2, 3)	5.000 50.000	51)

#### Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

### Deco-Paint Directive

VOC content	100 % , 871 <sup>g</sup> /l
-------------	--------------------------------

### Industrial Emissions Directive (IED)

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: 4370

VOC content	100 %
VOC content	871 g/l

### Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

### Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

### Water Framework Directive (WFD)

not listed

### Regulation on the marketing and use of explosives precursors

not listed

### Regulation on drug precursors

not listed

### Regulation on substances that deplete the ozone layer (ODS)

not listed

### Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

### Regulation on persistent organic pollutants (POP)

not listed

### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

### National inventories

Country	Inventory	Status
AU	AICS	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester ≥99 %, for synthesis

article number: 4370

Country	Inventory	Status
US	TSCA	substance is listed

### Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

## SECTION 16: Other information

### Indication of changes (revised safety data sheet)

Alignment to regulation: Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification according to Regulation (EC) No 1272/2008 (CLP): change in the listing (table)	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1	Remarks: For full text of Hazard- and EU Hazard-statements: see SECTION 16.		yes
2.1	The most important adverse physicochemical, human health and environmental effects: Narcotic effects.	The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes



# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester ≥99 %, for synthesis

article number: 4370

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2019/1831/EU	Commission Directive establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ADR/RID/ADN	Agreements concerning the International Carriage of Dangerous Goods by Road/Rail/Inland Waterways (ADR/RID/ADN)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic

# Safety data sheet

according to Regulation (EC) No. 1907/2006 (REACH)



## Acetic acid isobutyl ester $\geq 99\%$ , for synthesis

article number: **4370**

Abbr.	Descriptions of used abbreviations
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
S.I. No. 619 of 2001	Safety, Health and Welfare at Work (Chemical Agents) Regulations 2001
STEL	Short-term exposure limit
SVHC	Substance of Very High Concern
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H336	May cause drowsiness or dizziness.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.