acc. to Safe Work Australia - Code of Practice



date of compilation: 2017-01-02

Revision: 2024-03-02

Ethanolamine ≥99 %, for synthesis

article number: **4376** Version: **GHS 4.0 en** Replaces version of: 2022-07-21 Version: (GHS 3)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance	Ethanolamine ≥99 %, for synthesis
Article number	4376
CAS number	141-43-5
Alternative name(s)	2-Aminoethanol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Laboratory chemical Laboratory and analytical use Formulation [mixing] of preparations and/or repackaging (excluding alloys) Intermediate Industrial uses Professional uses

Uses advised against:

Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

acc. to Safe Work Australia - Code of Practice



Ethanolamine ≥99 %, for synthesis

article number: 4376

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	4	Flam. Liq. 4	H227
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.1D	Acute toxicity (dermal)	4	Acute Tox. 4	H312
3.1I	.1I Acute toxicity (inhal.)		Acute Tox. 4	H332
3.2	3.2 Skin corrosion/irritation		Skin Corr. 1	H314
3.3	3.3 Serious eye damage/eye irritation		Eye Dam. 1	H318
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)	3	STOT SE 3	H335

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS05, GHS07



Hazard statements

H227	Combustible liquid
H302+H312+H332	Harmful if swallowed, in contact with skin or if inhaled
H314	Causes severe skin burns and eye damage
H335	May cause respiratory irritation

Precautionary statements

Precautionary statements - prevention

P260	Do not breathe dusts or mists
P280	Wear protective gloves/protective clothing

acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis

.



article number: 4376

_

Precautionary sta	Precautionary statements - response				
P302+P352	IF ON SKIN: Wash with plenty of soap and water				
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower				
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing				
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction				
Precautionary statements - storage					

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed

2.3 Other hazards

This material is combustible, but will not ignite readily.

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Ethanolamine
Molecular formula	C ₂ H ₇ NO
Molar mass	61.08 ^g / _{mol}
CAS No	141-43-5

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Rinse mouth with water (only if the person is conscious). Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis

article number: 4376

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Nausea, Vomiting, Gastric perforation, Risk of serious damage to eyes, Risk of blindness, Dizziness, Irritation, Cough, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

acc. to Safe Work Australia - Code of Practice



Ethanolamine ≥99 %, for synthesis

article number: 4376

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Handle and open container with care. Clear contaminated areas thoroughly.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Hygroscopic.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

humidity, contact with air/oxygen

Consideration of other advice:

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

acc. to Safe Work Australia - Code of Practice



Ethanolamine ≥99 %, for synthesis

article number: 4376

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	ethanolamine (2- aminoethanol)	141-43-5	WES	3	7.5	6	15				WES

Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

TWA

Human health values

Relevant DNELs and other threshold levels					
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time	
DNEL	3.3 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects	
DNEL	1 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects	

Environmental values

Relevant PNECs and other threshold levels							
End- point	Threshold level	Organism	Environmental com- partment	Exposure time			
PNEC	0.085 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)			
PNEC	0.009 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)			
PNEC	100 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)			
PNEC	0.434 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)			
PNEC	0.043 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)			
PNEC	0.037 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)			

8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection. Wear face protection.

acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis

article number: 4376

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NR: natural rubber, latex, Butyl caoutchouc (butyl rubber)

• material thickness

0,6 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• Splash protection - Protective gloves

- type of material: NBR (Nitrile rubber)
- material thickness: >0,11 mm
- breakthrough times of the glove material:

>10 minutes (permeation: level 1)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	clear
Odour	like ammonia
Melting point/freezing point	10.5 °C
Boiling point or initial boiling point and boiling range	167 °C at 101 kPa (ECHA)



acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis

article number: 4376



articl	e number: 4376		
	Flammability	flammable liquid in accordance with GHS criteria	
	Lower and upper explosion limit	3.4 vol% (LEL) - 27 vol% (UEL)	
	Flash point	91 °C at 101.3 kPa (ECHA)	
	Auto-ignition temperature	424 °C at 101.3 kPa (ECHA)	
	Decomposition temperature	not relevant	
	pH (value)	12.1 (in aqueous solution: 100 ^g / _l , 20 °C)	
	Kinematic viscosity	23.5 ^{mm²} / _s at 20 °C	
	Dynamic viscosity	23.86 mPa s at 20 °C	
	Solubility(ies)		
	Water solubility	>1,000 ^g / _l at 20 °C (ECHA)	
	Partition coefficient		
	Partition coefficient n-octanol/water (log value):	-2.3 (25 °C) (ECHA)	
	Vapour pressure	0.5 hPa at 20 °C	
	Density and/or relative density		
	Density	1.02 ^g / _{cm³} at 20 °C (ECHA)	
	Relative vapour density	2.1 (air = 1)	
	Particle characteristics	not relevant (liquid)	
	Other safety parameters		
	Oxidising properties	none	
9.2	Other information		
	Information with regard to physical hazard classes:	There is no additional information.	
	Other safety characteristics:		
	Gas group (explosion group)	IIA Maximum Experimental Safe Gap value; MESG > 0,9 mm	

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

Moisture-sensitive.

acc. to Safe Work Australia - Code of Practice



Ethanolamine ≥99 %, for synthesis

article number: 4376

10.3 Possibility of hazardous reactions

Exothermic reaction with: strong oxidiser, Acetic acid, Acetic anhydride, Mineral acids, Nitric acid, Sulphuric acid

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Humidity. Keep away from heat.

10.5 Incompatible materials

different plastics, copper

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	1,089 ^{mg} / _{kg}	rat		ECHA
dermal	LD50	2,504 ^{mg} / _{kg}	rabbit		ECHA

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis

article number: 4376



Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea

• If on skin

causes severe burns, causes poorly healing wounds

• Other information

Other adverse effects: Liver and kidney damage, Nausea, Dizziness

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	349 ^{mg} / _l	fish	ECHA	96 h
EC50	65 ^{mg} / _l	aquatic invertebrates	ECHA	48 h
ErC50	2.8 ^{mg} / _l	algae	ECHA	72 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
EC50	2.5 ^{mg} / _l	aquatic invertebrates	ECHA	21 d

12.2 Persistence and degradability

Theoretical Oxygen Demand (without nitrification): 1.31 $^{mg}/_{mg}$ Theoretical Oxygen Demand (with nitrification): 2.357 $^{mg}/_{mg}$ Theoretical Carbon Dioxide: 1.441 $^{mg}/_{mg}$

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
DOC removal	>90 %	21 d

acc. to Safe Work Australia - Code of Practice



Ethanolamine ≥99 %, for synthesis

article number: 4376

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	-2.3 (25 °C) (ECHA)
BCF	2.3 (ECHA)

12.4 Mobility in soil

Henry's law constant	0 ^{Pa m³} / _{mol} at 25 °C (ECHA)
----------------------	---

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

- H8 Corrosives
- H11 Toxic (Delayed or chronic)


13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis

article number: 4376





acc. to Safe Work Australia - Code of Practice



Ethanolamine ≥99 %, for synthesis

article number: 4376

Emergency Action Code	2X
International Maritime Dangerous Goods C	ode (IMDG) - Additional information
Proper shipping name	ETHANOLAMINE
Particulars in the shipper's declaration	UN2491, ETHANOLAMINE, 8, III
Marine pollutant	-
Danger label(s)	8
Special provisions (SP)	223
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	А
Segregation group	18 - Alkalis
International Civil Aviation Organization (I	CAO-IATA/DGR) - Additional information
Proper shipping name	Ethanolamine
Particulars in the shipper's declaration	UN2491, Ethanolamine, 8, III
Danger label(s)	8
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis

article number: 4376

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 2X	yes
15.1		National inventories: change in the listing (table)	yes

Page 14 / 16



acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis



article number: 4376

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
BCF	Bioconcentration factor	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
ED	Endocrine disruptor	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
LEL	Lower explosion limit (LEL)	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
ppm	Parts per million	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
UEL	Upper explosion limit (UEL)	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants	

acc. to Safe Work Australia - Code of Practice

Ethanolamine ≥99 %, for synthesis



article number: 4376

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.