acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745 Version: 11.0 en

Replaces version of: 2022-12-21

Version: (10)



SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Tetrahydrofuran** ≥99,5 %, stabilized, for synthes-

Article number 4745

Index No (GB CLP) 603-025-00-0 EC number 203-726-8 CAS number 109-99-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-

stuffs.

1.3 Details of the supplier of the safety data sheet

> Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

United Kingdom (en) Page 1 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.6	Carcinogenicity	2	Carc. 2	H351
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)	3	STOT SE 3	H335
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

Supplemental hazard information

Code	Supplemental hazard information
EUH019	may form explosive peroxides

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS02, GHS07, GHS08







Hazard statements

Highly flammable liquid and vapour
Harmful if swallowed
Causes serious eye irritation
May cause respiratory irritation
May cause drowsiness or dizziness
Suspected of causing cancer

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking

P280 Wear protective clothing/eye protection/face protection

United Kingdom (en) Page 2 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed

For professional users only

Supplemental hazard information

EUH019 May form explosive peroxides.

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 **Substances**

Name of substance Tetrahydrofuran

Molecular formula C_4H_8O

Molar mass 72,11 ^g/_{mol}

CAS No 109-99-9

EC No 203-726-8

Index No (GB CLP) 603-025-00-0

To stabilise:

Name of substance	Identifier	Wt%
Butylated hydroxytoluene	CAS No 128-37-0 EC No 204-881-4	< 0,1

Substance, Specific Conc. Limits, M-factors, ATE

Specific Conc. Limits	M-Factors	ATE	Exposure route
Eye Irrit. 2; H319: C ≥ 25 % STOT SE 3; H335: C ≥ 25 %	-	1.650 ^{mg} / _{kg}	oral

Remarks

For full text of abbreviations: see SECTION 16

United Kingdom (en) Page 3 / 20



Precautionary statements - response

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth with water (only if the person is conscious). In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Cough, Dyspnoea, Headache, Vertigo, Drowsiness, Dizziness, Narcosis, Following skin contact: Localised redness, oedema, pruritis and/or pain,

After eye contact: Irritation,

Following ingestion: Nausea, Vomiting

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO_2)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

United Kingdom (en) Page 4 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

United Kingdom (en) Page 5 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

Conditions for safe storage, including any incompatibilities 7.2

Store in a well-ventilated place. Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Protect against external exposure, such as

high temperatures, UV-radiation/sunlight, contact with air/oxygen

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
EU	tetrahydrofuran	109-99-9	IOELV	50	150	100	300			Н	2000/39/ EC
GB	tetrahydrofuran	109-99-9	WEL	50	150	100	300				EH40/ 2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

Absorbed through the skin

STEL

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 **TWA**

hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels Threshold **Endpoint** Protection goal, **Used in Exposure time** level route of exposure DNEL 72,4 mg/m³ human, inhalatory worker (industry) chronic - systemic effects DNFI 96 mg/m³ human, inhalatory worker (industry) acute - systemic effects

United Kingdom (en) Page 6 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Relevant DNELs and other threshold levels **Threshold** Protection goal, **Endpoint Used** in **Exposure time** route of exposure level 150 mg/m³ chronic - local effects DNEL human, inhalatory worker (industry) DNEL 300 mg/m³ acute - local effects human, inhalatory worker (industry) **DNEL** 12,6 mg/kg bw/ human, dermal worker (industry) chronic - systemic effects day

Relevant DNELs of components Name of sub-**CAS No** End-**Threshol Protection Used in Exposure time** goal, route of exposure stance point d level Butylated hydroxy-19 mg/kg 128-37-0 DNEL human, dermal worker (industry) acute - systemic bw/day effects toluene DNEL Butylated hydroxy-128-37-0 18 mg/m³ human, inhalatworker (industry) acute - systemic toluene ory effects human, inhalatworker (industry) Butylated hydroxy-128-37-0 **DNEL** 3,5 mg/m³ chronic - systemic effects toluene orv Butylated hydroxy-128-37-0 DNEL 0,5 mg/kg human, dermal worker (industry) chronic - systemic toluene bw/day effects

Environmental values

Relevant PNECs and other threshold levels									
End- point	Threshold level	Organism	Organism Environmental compartment						
PNEC	4,32 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)					
PNEC	0,432 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)					
PNEC	4,6 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)					
PNEC	23,3 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)					
PNEC	2,33 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)					
PNEC	2,13 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)					

Relevant PNECs of components Name of sub-**CAS No** End-**Threshol Organism Environmental Exposure time** stance point d level compartment 8,33 ^{mg}/_{kg} Butylated hydroxy-128-37-0 **PNEC** short-term (single aquatic organwater toluene isms instance) Butylated hydroxy-128-37-0 **PNEC** 1,99 ^{µg}/_I aquatic organwater intermittent retoluene isms lease **PNEC** 0,199 ^{µg}/_I Butylated hydroxy-128-37-0 freshwater short-term (single aquatic organtoluene isms instance) 128-37-0 **PNEC** $0.02 \, \mu g/I$ Butylated hydroxyaquatic organmarine water short-term (single toluene isms instance)

United Kingdom (en) Page 7 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Relevant PNECs of components

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Butylated hydroxy- toluene	128-37-0	PNEC	0,17 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	99,6 ^{µg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	9,96 ^{µg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
Butylated hydroxy- toluene	128-37-0	PNEC	47,69 ^{µg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• Splash protection - Protective gloves

• type of material: Butyl caoutchouc (butyl rubber)

material thickness: 0,7mm

• breakthrough times of the glove material: >10 minutes (permeation: level 1)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection





United Kingdom (en) Page 8 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless
Odour like ether
Melting point/freezing point -108,5 °C

Boiling point or initial boiling point and boiling

range

65 °C at 1.013 hPa (ECHA)

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 1,5 vol% (LEL) - 12,4 vol% (UEL) Flash point -21,2 °C at 1.013 hPa (ECHA)

Auto-ignition temperature 215 °C (DIN 51794)

Decomposition temperature not relevant
pH (value) 7 – 8 (20 °C)
Kinematic viscosity not determined

Dynamic viscosity 0,48 mPa s at 20 °C

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): 0,45 (pH value: 7, 25 °C) (ECHA)

Vapour pressure 170 hPa at 20 °C

Density and/or relative density

Density $0,883 \, {}^{9}/_{cm^3}$ at 25 ${}^{\circ}$ C (ECHA)

Relative vapour density 2,49 (air = 1)

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

United Kingdom (en) Page 9 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Miscibility

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air. May form explosive peroxides.

There is no additional information.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Alkali hydroxide (caustic alkali), Acids

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. UVradiation/sunlight.

10.5 Incompatible materials

Rubber articles, different plastics, tin

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5. Peroxides.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity Exposure route Method **Source Endpoint Value Species** 1.650 ^{mg}/_{kg} LD50 **ECHA** oral rat >2.000 ^{mg}/_{kg} LD50 **ECHA** dermal rat

United Kingdom (en) Page 10 / 20



Information with regard to physical hazard

classes:

Other safety characteristics:

completely miscible with water

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Acute toxicity of components								
Name of substance	CAS No	Exposure route	Endpoint	Value	Species			
Butylated hydroxytoluene	128-37-0	oral	LD50	>6.000 ^{mg} / _{kg}	rat			
Butylated hydroxytoluene	128-37-0	dermal	LD50	>2.000 ^{mg} / _{kg}	rat			

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

vomiting, nausea

• If in eyes

Causes serious eye irritation

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea, headache, vertigo, drowsiness, dizziness, narcosis

• If on skin

Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

11.3 Information on other hazards

United Kingdom (en) Page 11 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745

There is no additional information.



SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	2.160 ^{mg} / _l	fish	ECHA	96 h
EC50	1.930 ^{mg} / _l	fish	ECHA	96 h

Aquatic toxicity (acute) of components

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Butylated hydroxy- toluene	128-37-0	LC50	>0,57 ^{mg} / _l	fish	96 h
Butylated hydroxy- toluene	128-37-0	EC50	0,48 ^{mg} / _l	aquatic invertebrates	48 h
Butylated hydroxy- toluene	128-37-0	ErC50	>0,4 ^{mg} / _l	algae	72 h

Aquatic toxicity (chronic) of components

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Butylated hydroxy- toluene	128-37-0	EC50	0,096 ^{mg} / _l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Theoretical Oxygen Demand: $2,441 \frac{mg}{mg}$ Theoretical Carbon Dioxide: $2,441 \frac{mg}{mg}$

Process of degradability

Process	Degradation rate	Time
biotic/abiotic	39 %	28 d
oxygen depletion	39 %	28 d

Degradability of components


Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Butylated hy- droxytoluene	128-37-0	biotic/abiotic	<10 %	20 d		

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

United Kingdom (en) Page 12 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)



article number: 4745



n-octan	ol/water (log KOW)	0,45 (pH value: 7, 25 °C) (ECHA)
	, 3	

Bioaccumulative potential of components

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Butylated hydroxytoluene	128-37-0	598,4	5,1	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

HP 3 flammable

HP 15 waste capable of exhibiting a hazardous property listed above not directly displayed by the original waste

HP 4 irritant - skin irritation and eye damage

HP 5 specific target organ toxicity (STOT)/aspiration toxicity

HP 6 acute toxicity

HP 7 carcinogenic

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

United Kingdom (en) Page 13 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



SECTION 14: Transport information

14.1 UN number or ID number

ADRRID UN 2056
IMDG-Code UN 2056
ICAO-TI UN 2056

14.2 UN proper shipping name

ADRRID TETRAHYDROFURAN IMDG-Code TETRAHYDROFURAN ICAO-TI Tetrahydrofuran

14.3 Transport hazard class(es)

ADRRID 3
IMDG-Code 3
ICAO-TI 3

14.4 Packing group

ADRRID II
IMDG-Code II
ICAO-TI II

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR)Additional information

Proper shipping name TETRAHYDROFURAN

Particulars in the transport document UN2056, TETRAHYDROFURAN, 3, II, (D/E)

Classification code F1
Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Tunnel restriction code (TRC) D/E

United Kingdom (en) Page 14 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745

Hazard identification No 33

Emergency Action Code 2YE

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID)Additional

information

Classification code F1

Danger label(s) 3

3

Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
Transport category (TC) 2
Hazard identification No 33

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name TETRAHYDROFURAN

Particulars in the shipper's declaration UN2056, TETRAHYDROFURAN, 3, II, -21,2°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP) - Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L
EmS F-E, S-D

Stowage category B

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Tetrahydrofuran

Particulars in the shipper's declaration UN2056, Tetrahydrofuran, 3, II

Danger label(s) 3



Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

United Kingdom (en) Page 15 / 20



acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU)

Seveso Directive

2012/	2012/18/EU (Seveso III)						
No	Dangerous substance/hazard categories	Qualifying quantity plication of lower a quiren		Notes			
P5c	flammable liquids (cat. 2, 3)	5.000	50.000	51)			

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	100 %
VOC content	883 ^g / _l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	883 ^g / _l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)						
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks		
Tetrahydrofuran	Substances and preparations, or the breakdown products of such, which have been proved to pos- sess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine- related functions in or via the aquatic environment		a)			

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

United Kingdom (en) Page 16 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list not listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)					
Name of substance	Name acc. to inventory	CAS No	No		
Tetrahydrofuran	this product meets the criteria for classi- fication in accordance with Regulation No 1272/2008/EC		3		
Tetrahydrofuran	flammable / pyrophoric		40		

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC Australian Inventory of Industrial Chemicals CICR

Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)

CSCL-ENCS DSL ECSI

United Kingdom (en) Page 17 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



IECSC INSQ Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances Korea Existing Chemicals Inventory

NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1	VOC content: 100 % 883 ⁹ / _I	VOC content: 100 %	yes
15.1		VOC content: 883 ⁹ / _I	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor

United Kingdom (en) Page 18 / 20



acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Abbr.	Descriptions of used abbreviations
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-li- cence/)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regula- tions concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

United Kingdom (en) Page 19 / 20

acc. to Regulation (EC) No. 1907/2006 (REACH)

Tetrahydrofuran ≥99,5 %, stabilized, for synthesis

article number: 4745



Abbr.	Descriptions of used abbreviations
WEL	Workplace exposure limit

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United Kingdom (en) Page 20 / 20