acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078 date of compilation: 2016-10-04 Version: GHS 4.0 en Revision: 2024-03-04

Replaces version of: 2022-06-01

Version: (GHS 3)

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

#### **Product identifier** 1.1

Identification of the substance **Strontium nitrate** ROTI®METIC 99,999 % (5N)

Article number 5078

CAS number 10042-76-9

#### Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for private purposes (household).

Food, drink and animal feedingstuffs.

#### Details of the supplier of the safety data sheet 1.3

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

sheet:

e-mail (competent person): sicherheit@carlroth.de

#### 1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

### **SECTION 2: Hazards identification**

#### Classification of the substance or mixture

#### Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.14	Oxidising solid	1	Ox. Sol. 1	H271
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

For full text of abbreviations: see SECTION 16

#### 2.2 **Label elements**

Page 1 / 14 Australia (en)



acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078

### Labelling

Signal word **Danger** 

### **Pictograms**

GHS03, GHS05



### **Hazard statements**

H271 May cause fire or explosion; strong oxidiser

H318 Causes serious eye damage

### **Precautionary statements**

### **Precautionary statements - prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P280 Wear eye protection/face protection

P283 Wear fire/flame resistant/retardant clothing

### **Precautionary statements - response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P306+P360 IF ON CLOTHING: Rinse immediately contaminated clothing and skin with plenty

of water before removing clothes

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction P371+P380+P375 In case of major fire and large quantities: Evacuate area. Fight fire remotely due

to the risk of explosion

#### 2.3 Other hazards

### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

## SECTION 3: Composition/information on ingredients

#### **Substances** 3.1

Name of substance Strontium nitrate

Molecular formula  $Sr(NO_3)_2$ 211.6 g/mol Molar mass 10042-76-9 CAS No

Australia (en) Page 2 / 14



acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078



### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures



#### **General notes**

Take off contaminated clothing.

### **Following inhalation**

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

### **Following skin contact**

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

### Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

### Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

### 4.2 Most important symptoms and effects, both acute and delayed

Risk of blindness, Risk of serious damage to eyes

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media



### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water, foam, alcohol resistant foam, dry extinguishing powder, ABC-powder

### Unsuitable extinguishing media

water jet

### 5.2 Special hazards arising from the substance or mixture

Explosive when mixed with combustible material. Oxidising property. Non-combustible.

### **Hazardous combustion products**

In case of fire may be liberated: Nitrogen oxides (NOx)

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

Australia (en) Page 3 / 14

acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078



### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures



### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe dust.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

### Advice on how to contain a spill

Covering of drains. Take up mechanically.

### Advice on how to clean up a spill

Take up mechanically. Control of dust.

### Other information relating to spills and releases

Place in appropriate containers for disposal.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## **SECTION 7: Handling and storage**

### 7.1 Precautions for safe handling

Avoid dust formation.

#### Measures to prevent fire as well as aerosol and dust generation

Removal of dust deposits. Keep away from combustible material.

### Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a dry place.

### **Incompatible substances or mixtures**

Observe hints for combined storage. Keep/store away from clothing/combustible materials. Take any precaution to avoid mixing with combustibles.

### Consideration of other advice:

#### **Ventilation requirements**

Use local and general ventilation.

### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

### 7.3 Specific end use(s)

No information available.

Australia (en) Page 4 / 14

acc. to Safe Work Australia - Code of Practice



article number: 5078



### **SECTION 8: Exposure controls/personal protection**

### **Control parameters**

### **National limit values**

### **Occupational exposure limit values (Workplace Exposure Limits)**

Coun try	Name of agent	CAS No	Identifi- er	TWA [mg/ m³]	STEL [mg/ m³]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	nuisance dusts		WES	10			i	WES

Notation

Ceiling value is a limit value above which exposure should not occur Inhalable fraction Ceiling-C

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 **STEL** 

**TWA** 

hours time-weighted average (unless otherwise specified)

### **Human health values**

Relevant DNELs and other threshold levels						
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time		
DNEL	7.9 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects		
DNEL	40.1 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects		

### **Environmental values**

Relevant PNECs and other threshold levels						
End- point	Threshold level	Organism	Environmental com- partment	Exposure time		
PNEC	2.1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)		
PNEC	4.2 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)		
PNEC	1,811 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single instance)		
PNEC	332 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)		

#### 8.2 **Exposure controls**

Individual protection measures (personal protective equipment)

### Eye/face protection



Use safety goggle with side protection.

Australia (en) Page 5 / 14

acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078

### Skin protection



### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a quide.

### type of material

NBR (Nitrile rubber)

#### material thickness

>0,3 mm

### breakthrough times of the glove material

>480 minutes (permeation: level 6)

### other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

### **Respiratory protection**





Respiratory protection necessary at: Dust formation. Particulate filter device (EN 143). P1 (filters at least 80 % of airborne particles, colour code: White).

#### **Environmental exposure controls**

Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state solid

Form powder, crystalline

Colour white

Odour odourless

Melting point/freezing point 570°C

Boiling point or initial boiling point and boiling

range

**Flammability** non-combustible Lower and upper explosion limit not determined

Page 6 / 14 Australia (en)

645 °C at 1,013 hPa



acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078

Flash point not applicable
Auto-ignition temperature not determined

Decomposition temperature not relevant

pH (value) 6.7 (in aqueous solution:  $10^{9}/_{l}$ ,  $20^{\circ}$ C) (ECHA)

Kinematic viscosity not relevant

Solubility(ies)

Water solubility ~660 <sup>g</sup>/<sub>l</sub> at 20 °C

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure not determined

Density and/or relative density

Density 2.986 <sup>g</sup>/<sub>cm³</sub> at 20 °C

Relative vapour density Information on this property is not available.

Bulk density  $\sim 1,000 \text{ kg/m}^3$ 

Particle characteristics No data available.

Other safety parameters

Oxidising properties

9.2 Other information

Information with regard to physical hazard

classes:

Other safety characteristics: There is no additional information.

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

It's a reactive substance. Oxidising property.

### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

There is no additional information.

### 10.3 Possibility of hazardous reactions

**Violent reaction with:** Magnesium-Powder, Metal powder, PVC: polyvinyl chloride, Sulphur, **Danger of explosion:** Combustible materials, Reducing agents, Acetic anhydride, Heat, Hydrides

### 10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

Australia (en) Page 7 / 14



acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078



combustible materials, PVC: polyvinyl chloride

### 10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

## **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

#### Classification acc. to GHS

#### **Acute toxicity**

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if swallowed.

#### **Acute toxicity Exposure route Endpoint Value Species** Method **Source** >2,000 <sup>mg</sup>/<sub>kg</sub> LD50 **ECHA** oral rat inhalation: dust/ LC50 >4.5 <sup>mg</sup>/<sub>I</sub>/4h ECHA rat mist

### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

### Serious eye damage/eye irritation

Causes serious eye damage.

### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

### **Germ cell mutagenicity**

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### **Aspiration hazard**

Shall not be classified as presenting an aspiration hazard.

### Symptoms related to the physical, chemical and toxicological characteristics

#### If swallowed

Data are not available.

### If in eyes

Causes serious eye damage, risk of blindness

Australia (en) Page 8 / 14



acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078



Inhalation of dust may cause irritation of the respiratory system

• If on skin

Irritating to skin

Other information

none

### 11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq 0.1\%$ .

## **SECTION 12: Ecological information**

### 12.1 Toxicity

Harmful to aquatic life.

# Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	>92.8 <sup>mg</sup> / <sub>l</sub>	fish	ECHA	96 h
ErC50	>43.3 <sup>mg</sup> / <sub>I</sub>	algae	ECHA	72 h
EC50	>43.3 <sup>mg</sup> / <sub>l</sub>	algae	ECHA	72 h

### **Aquatic toxicity (chronic)**

Endpoint	Value	Species	Source	Exposure time
EC50	>100 <sup>mg</sup> / <sub>I</sub>	microorganisms	ECHA	3 h

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

Data are not available.

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\geq$  0,1%.

### 12.7 Other adverse effects

Data are not available.

Australia (en) Page 9 / 14



acc. to Safe Work Australia - Code of Practice

#### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078



### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

### Sewage disposal-relevant information

Do not empty into drains.

### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

### Relevant provisions relating to waste(Basel Convention)

### Properties of waste which render it hazardous

**H5.1** Oxidizing

### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

## **SECTION 14: Transport information**

14.1	UN	num	ber

UN RTDG	UN 1507
IMDG-Code	UN 1507
ICAO-TI	UN 1507

#### 14.2 UN proper shipping name

UN RTDG	STRONTIUM NITRATE
IMDG-Code	STRONTIUM NITRATE
ICAO-TI	Strontium nitrate

### 14.3 Transport hazard class(es)

UN RTDG	5.1
IMDG-Code	5.1
ICAO-TI	5.1

### 14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

# **14.5 Environmental hazards**non-environmentally hazardous acc. to the dangerous goods regulations

Australia (en) Page 10 / 14

acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078



There is no additional information.

### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

### 14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

**UN number** 1507 Class 5.1 **Packing group** Ш Danger label(s) 5.1

**Special provisions (SP)** 

**UN RTDG** 

E1 UN RTDG **Excepted quantities (EQ)** 

Limited quantities (LQ)

5 kg UN RTDG

**Emergency Action Code** 17

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name STRONTIUM NITRATE

Particulars in the shipper's declaration UN1507, STRONTIUM NITRATE, 5.1, III

Marine pollutant 5.1 Danger label(s)



Special provisions (SP) Excepted quantities (EQ) E1 Limited quantities (LQ) 5 kg **EmS** F-A, S-Q

Stowage category

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Strontium nitrate

Particulars in the shipper's declaration UN1507, Strontium nitrate, 5.1, III

Danger label(s) 5.1



Excepted quantities (EQ) E1

Australia (en) Page 11 / 14



acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078

Limited quantities (LQ) 10 kg



## **SECTION 15: Regulatory information**

### Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

### National regulations(Australia)

### Australian Inventory of Chemical Substances(AICS)

Substance is listed.

#### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### **National inventories**

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

#### Legend

AIIC CSCL-ENCS

DSL ECSI

Australian Inventory of Industrial Chemicals
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Yorga Existing Chemical Substances **IECSC** 

KECI Korea Existing Chemicals Inventory
NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory

**Toxic Substance Control Act** 

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

Australia (en) Page 12 / 14

acc. to Safe Work Australia - Code of Practice

Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078



## **SECTION 16: Other information**

### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 1Z	yes
15.1		National inventories: change in the listing (table)	yes

### **Abbreviations and acronyms**

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration

Australia (en) Page 13 / 14

acc. to Safe Work Australia - Code of Practice

### Strontium nitrate ROTI®METIC 99,999 % (5N)

article number: 5078



Abbr.	Descriptions of used abbreviations
STEL	Short-term exposure limit
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H271	May cause fire or explosion; strong oxidiser.
H318	Causes serious eye damage.

#### **Disclaimer**

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 14 / 14