

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: **5146**

Version: **GHS 2.0 en**

Replaces version of: 2016-10-18

Version: (GHS 1)

date of compilation: 2016-10-18

Revision: 2022-04-11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance

Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

Article number

5146

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Laboratory chemical
Laboratory and analytical use

Uses advised against:

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.4R	Respiratory sensitisation	1	Resp. Sens. 1	H334
3.4S	Skin sensitisation	1	Skin Sens. 1	H317

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: 5146

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.5	Germ cell mutagenicity	2	Muta. 2	H341
3.6	Carcinogenicity	1A	Carc. 1A	H350
3.7	Reproductive toxicity	1A	Repr. 1A	H360D
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS05, GHS08



Hazard statements

H290	May be corrosive to metals
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H360D	May damage the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

Precautionary statements

Precautionary statements - prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray
P280	Wear protective gloves

Precautionary statements - response

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician

For professional users only

Hazardous ingredients for labelling:

Nickel dinitrate

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: 5146

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub-stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
nickel dinitrate	CAS No 13138-45-9	1	Ox. Sol. 2 / H272 Acute Tox. 4 / H302 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Muta. 2 / H341 Carc. 1A / H350 Repr. 1A / H360D STOT RE 1 / H372		
Nitric acid ...% [C ≤ 70 %]	CAS No 7697-37-2	1	Ox. Liq. 3 / H272 Met. Corr. 1 / H290 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 EUH071		B(a)

Notes

B(a): The classification refers to an aqueous solution

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. After contact with skin, wash immediately with plenty of water. In case of skin reactions, consult a physician. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: **5146**

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Allergic reactions, Cough, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NO_x)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: 5146

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m ³]	STE L [pp m]	STEL [mg/ m ³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m ³]	Nota- tion	Source
AU	nickel dinitrate	13138-45-9	WES		0.1						WES
AU	nitric acid	7697-37-2	WES	2	5.2	4	10				WES

Notation

Ceiling-C
STEL
TWA

Ceiling value is a limit value above which exposure should not occur
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: **5146**

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggles with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

• material thickness

>0,11 mm


• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation.

Environmental exposure controls

Keep away from drains, surface and ground water.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: **5146**

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	~0 °C
Boiling point or initial boiling point and boiling range	~100 °C (unknown)
Flammability	non-combustible
Lower and upper explosion limit	not determined
Flash point	not determined
Auto-ignition temperature	not determined
Decomposition temperature	not relevant
pH (value)	<2
Kinematic viscosity	not determined
<u>Solubility(ies)</u>	
Water solubility	miscible in any proportion
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	not relevant (inorganic)
Vapour pressure	23 hPa at 20 °C
<u>Density and/or relative density</u>	
Density	1.016 g/cm ³ at 20 °C
Relative vapour density	information on this property is not available
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

9.2 Other information

Information with regard to physical hazard classes:	
Corrosive to metals	category 1: corrosive to metals
Other safety characteristics:	
Miscibility	completely miscible with water

Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃article number: **5146****SECTION 10: Stability and reactivity****10.1 Reactivity**

Substance or mixture corrosive to metals.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions**Violent reaction with:** Ammonia (NH₃), Bases, Metals, Reducing agents, Strong alkali, Organic solvents**10.4 Conditions to avoid**

Keep away from heat.

10.5 Incompatible materials

different metals (due to the release of hydrogen in an acid/alkaline medium)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS**Acute toxicity**

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
nickel dinitrate	13138-45-9	oral	1,620 mg/kg
nickel dinitrate	13138-45-9	inhalation: dust/mist	1.5 mg/l/4h
Nitric acid ...% [C ≤ 70 %]	7697-37-2	inhalation: vapour	>2.65 mg/l/4h

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
nickel dinitrate	13138-45-9	oral	LD50	1,620 mg/kg	rat
Nitric acid ...% [C ≤ 70 %]	7697-37-2	inhalation: vapour	LC50	>2.65 mg/l/4h	rat

Skin corrosion/irritation

Causes skin irritation.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: **5146**

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity

Suspected of causing genetic defects.

Carcinogenicity

May cause cancer.

Reproductive toxicity

May damage the unborn child.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

Data are not available.

• If in eyes

Causes serious eye irritation

• If inhaled

May produce an allergic reaction, cough, Dyspnoea

• If on skin

causes skin irritation, May produce an allergic reaction, pruritis, localised redness

• Other information

This information is based upon the present state of our knowledge.

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: **5146**

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H8 Corrosives
H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG

UN
3264

IMDG-Code

UN 3264

ICAO-TI

UN 3264

14.2 UN proper shipping name

UN RTDG

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

IMDG-Code

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

ICAO-TI

Corrosive liquid, acidic, inorganic, n.o.s.

Technical name (hazardous ingredients)

Nitric acid ...% [C ≤ 70 %], Nickel dinitrate

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: 5146

14.3 Transport hazard class(es)

UN RTDG	8
IMDG-Code	8
ICAO-TI	8

14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number	3264
Class	8
Packing group	III
Danger label(s)	8



Special provisions (SP)	223, 274 UN RTDG
-------------------------	---------------------

Excepted quantities (EQ)	E1 UN RTDG
--------------------------	---------------

Limited quantities (LQ)	5 L UN RTDG
-------------------------	----------------

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
Particulars in the shipper's declaration	UN3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S., (Nitric acid ...% [C ≤ 70 %], nickel dintrate, solution), 8, III
Marine pollutant	-
Danger label(s)	8



Special provisions (SP)	223, 274
Excepted quantities (EQ)	E1


Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: **5146**

Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	A
Segregation group	1 - Acids
International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information	
Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s.
Particulars in the shipper's declaration	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (Nitric acid ...% [C ≤ 70 %], nickel dinitrate, solution), 8, III
Danger label(s)	8
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: 5146

Country	Inventory	Status
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1	Remarks: For full text of Hazard- and EU Hazard-statements: see SECTION 16.		yes
2.1		The most important adverse physicochemical, human health and environmental effects: Delayed or immediate effects can be expected after short or long-term exposure.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: 5146

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Nickel dinitrate		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
Muta.	Germ cell mutagenicity

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: 5146

Abbr.	Descriptions of used abbreviations
NLP	No-Longer Polymer
Ox. Liq.	Oxidising liquid
Ox. Sol.	Oxidising solid
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
Repr.	Reproductive toxicity
Resp. Sens.	Respiratory sensitisation
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Nickel nitrate matrix modifier solution 10 g/l Ni(NO₃)₂ (99,999 %) in 1 % HNO₃

article number: **5146**

Code	Text
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.