acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.

article number: 6837 Version: GHS 6.0 en Replaces version of: 2023-06-16 Version: (GHS 5)

### SECTION 1: Identification of the substance/mixture and of the company/ undertaking

**Product identifier** 1.1

Identification of the substance

- Article number
- CAS number

Alternative name(s)

#### Relevant identified uses of the substance or mixture and uses advised against 1.2

Relevant identified uses:

Uses advised against:

Isolated intermediate

sicherheit@carlroth.de

Ethylene dichloride

6837

107-06-2

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

**1,2-Dichloroethane** ROTIPURAN® ≥99,5 %, p.a.

#### Details of the supplier of the safety data sheet 1.3

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

#### e-mail (competent person):

#### 1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

### **SECTION 2: Hazards identification**

#### Classification of the substance or mixture 2.1

#### **Classification acc. to GHS**

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	2	Flam. Liq. 2	H225
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.1I	Acute toxicity (inhal.)	3	Acute Tox. 3	H331
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315

date of compilation: 2017-03-02 Revision: 2024-03-02

acc. to Safe Work Australia - Code of Practice

### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



#### article number: 6837

Section	Hazard class		Hazard class and category	Hazard statement
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.6	Carcinogenicity	1B	Carc. 1B	H350
3.8R	Specific target organ toxicity - single exposure (respirat- ory tract irritation)	3	STOT SE 3	H335
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

### The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

#### Labelling

Signal word Danger

#### Pictograms



#### Hazard statements

H225	Highly flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H331	Toxic if inhaled
H335	May cause respiratory irritation
H335	May cause respiratory irritation
H350	May cause cancer
	-

#### **Precautionary statements**

#### **Precautionary statements - prevention**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

#### **Precautionary statements - response**

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of soap and water
	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P331	Do NOT induce vomiting
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

#### **Precautionary statements - storage**

P403+P233	Store in a well-ventilated place. Keep container tightly closed
P403+P235	Store in a well-ventilated place. Keep cool

For professional users only

acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



#### article number: 6837

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### **Endocrine disrupting properties**

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Name of substance1,2-DichloroethaneMolecular formula $C_2H_4Cl_2$ Molar mass98.97  $^{g}/_{mol}$ CAS No107-06-2

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures



#### **General notes**

Self-protection of the first aider.

#### **Following inhalation**

Call a physician immediately. If breathing is irregular or stopped, administer artificial respiration.

#### Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

#### Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

#### **Following ingestion**

Rinse mouth with water (only if the person is conscious). In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

#### 4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Vomiting, Irritation, Cough, Dyspnoea

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



article number: 6837

### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media



#### Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

water jet

#### 5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Hydrogen chloride (HCl), Hydrogen halides (HX)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures



#### For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

#### Advice on how to contain a spill

Covering of drains.

#### Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

#### Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



article number: 6837

#### 6.4 Reference to other sections


Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Provision of sufficient ventilation. Use extractor hood (laboratory). Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

#### Advice on general occupational hygiene

Wash hands before breaks and after work. When using do not smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

#### Protect against external exposure, such as

light, humidity, contact with air/oxygen

#### Consideration of other advice:

Store locked up. Ground/bond container and receiving equipment.

#### **Ventilation requirements**

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

#### Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

#### 7.3 Specific end use(s)

No information available.

acc. to Safe Work Australia - Code of Practice

### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



article number: 6837

# **SECTION 8: Exposure controls/personal protection**

#### 8.1 **Control parameters**

#### National limit values

#### **Occupational exposure limit values (Workplace Exposure Limits)**

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	ethylene dichloride (1,2-dichloroethane)	107-06-2	WES	10	40						WES

#### Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

TWA

#### **Environmental values**

Relevant PNECs and other threshold levels								
End- point	Threshold level	Exposure time						
PNEC	1.1 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)				
PNEC	0.11 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)				
PNEC	27.8 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)				
PNEC	11.1 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single instance)				
PNEC	1.11 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)				
PNEC	1.8 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)				

#### 8.2 **Exposure controls**

#### Individual protection measures (personal protective equipment)

#### **Eye/face protection**



Use safety goggle with side protection.

### **Skin protection**



acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



#### article number: 6837

#### hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

#### • type of material

FKM (fluoro rubber)

material thickness

0,4 mm

#### • breakthrough times of the glove material

>480 minutes (permeation: level 6)

#### • other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

#### **Respiratory protection**



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

#### **Environmental exposure controls**

Keep away from drains, surface and ground water.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

liquid
colourless
schwach Lösungsmittel
3 ppm
-36 °C
83.6 °C at 1,013 hPa (ECHA)
flammable liquid in accordance with GHS criteria
250 g/m³ (LEL) - 660 g/m³ (UEL) / 6 vol% (LEL) - 15.9 vol% (UEL)
13 °C at 1,013 hPa (ECHA)
440 °C at 1,013 hPa (ECHA)

acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.

#### article number: 6837



Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	0.6632 <sup>mm²</sup> / <sub>s</sub> at 20 °C
Dynamic viscosity	0.829 mPa s at 20 °C
Solubility(ies)	
Water solubility	7.9 <sup>g</sup> / <sub>l</sub> at 25 °C (ECHA)
Partition coefficient	
Partition coefficient n-octanol/water (log value):	1.45 (pH value: ~7.4, 20 °C) (ECHA)
Vapour pressure	102 hPa at 25 °C 87 hPa at 20 °C
Density and/or relative density	
Density	1.25 <sup>g</sup> / <sub>cm³</sub> at 20 °C
Relative vapour density	3.4 (air = 1)
Particle characteristics	not relevant (liquid)
Other safety parameters	
Oxidising properties	none
Other information	
Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	
Surface tension	32.45 <sup>dyn</sup> / <sub>cm</sub> (20 °C) (ECHA)

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

9.2

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

#### If heated

Risk of ignition.

#### 10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

#### 10.3 Possibility of hazardous reactions

**Violent reaction with:** strong oxidiser, Alkali metals, Alkaline earth metal, Metal powder, Nitric acid, Nitrogen oxides (NOx)

acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



#### article number: 6837

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from moisture. Direct light irradiation. Contact with air/oxygen.

#### 10.5 Incompatible materials

aluminium, iron, Light metals, different plastics

#### **10.6** Hazardous decomposition products

Hazardous combustion products: see section 5.

### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

#### **Classification acc. to GHS**

#### Acute toxicity

Harmful if swallowed. Toxic if inhaled.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity							
Exposure route	Endpoint	Value	Species	Method	Source		
inhalation: vapour	LC50	7,758 <sup>mg</sup> / <sub>m³</sub> /4h	rat		ECHA		
oral	LD50	670 <sup>mg</sup> / <sub>kg</sub>	rat		TOXNET		
dermal	LD50	2,800 <sup>mg</sup> / <sub>kg</sub>	rabbit		TOXNET		

### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

May cause cancer.

#### **Reproductive toxicity**

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

May cause respiratory irritation.

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### **Aspiration hazard**

May be fatal if swallowed and enters airways.

acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



article number: 6837

#### Symptoms related to the physical, chemical and toxicological characteristics

#### • If swallowed

vomiting, aspiration hazard

#### • If in eyes

Causes serious eye irritation

#### • If inhaled

vertigo, headache, Irritation to respiratory tract, cough, Dyspnoea

#### • If on skin

causes skin irritation

#### • Other information

Other adverse effects: Liver and kidney damage, Cardiovascular system, Central nervous system

#### **11.2** Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)							
Endpoint	Value	Species	Source	Exposure time			
LC50	136 <sup>mg</sup> / <sub>l</sub>	fish	ECHA	96 h			
EC50	160 <sup>mg</sup> / <sub>l</sub>	aquatic invertebrates	ECHA	48 h			

#### 12.2 Persistence and degradability

Theoretical Oxygen Demand: 0.8083 <sup>mg</sup>/<sub>mg</sub> Theoretical Carbon Dioxide: 0.8893 <sup>mg</sup>/<sub>mg</sub>

#### 12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	1.45 (pH value: ~7.4, 20 °C) (ECHA)
BCF	2 (ECHA)

#### 12.4 Mobility in soil

Henry's law constant	149 <sup>Pa m³</sup> / <sub>mol</sub>
----------------------	---------------------------------------

#### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

#### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of  $\ge 0,1\%$ .

acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



article number: 6837

#### 12.7 Other adverse effects

Data are not available.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Sewage disposal-relevant information

Do not empty into drains.

#### Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

#### Relevant provisions relating to waste(Basel Convention)

#### Properties of waste which render it hazardous

H3 Flammable liquids

H11 Toxic (Delayed or chronic)

#### 13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

### **SECTION 14: Transport information**

14.1	UN number		
	UN RTDG	UN 1184	
	IMDG-Code	UN 1184	
	ICAO-TI	UN 1184	
14.2	UN proper shipping name		
	UN RTDG	ETHYLENE DICHLORIDE	
	IMDG-Code	ETHYLENE DICHLORIDE	
	ICAO-TI	Ethylene dichloride	
14.3 Transport hazard class(es)			
	UN RTDG	3 (6.1)	
	IMDG-Code	3 (6.1)	
	ICAO-TI	3 (6.1)	
14.4	Packing group		
	UN RTDG	II	

acc. to Safe Work Australia - Code of Practice

® FOTH

1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a	a.
--	----

1,2-0	$\frac{1}{2}$		
article	e number: <b>6837</b>		
	IMDG-Code	П	
	ICAO-TI	II	
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations	
14.6	Special precautions for user		
	There is no additional information.		
14.7	Transport in bulk according to IMO instruments		
	The cargo is not intended to be carried in bulk.		
14.8	Information for each of the UN Model Regulations		
	Transport informationNational regulations	Additional information(UN RTDG)	
	UN number	1184	
	Class	3	
	Subsidiary risk(s)	6.1	
	Packing group	П	
	Danger label(s)	3+6.1	
	Special provisions (SP)	- UN RTDG	
	Excepted quantities (EQ)	E2 UN RTDG	
	Limited quantities (LQ)	1 L UN RTDG	
	Emergency Action Code	2YE	
	International Maritime Dangerous Goods Code (IMDG) - Additional information		
	Proper shipping name	ETHYLENE DICHLORIDE	
	Particulars in the shipper's declaration	UN1184, ETHYLENE DICHLORIDE, 3 (6.1), II, 13°C c.c.	
	Marine pollutant	-	
	Danger label(s)	3+6.1	
	Special provisions (SP)	-	
	Excepted quantities (EQ)	E2	
	Limited quantities (LQ)	1 L	
	EmS	F-E, S-D	
	Stowage category	В	
	Common actions and an		

Segregation group

10 - Liquid halogenated hydrocarbons

acc. to Safe Work Australia - Code of Practice

#### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



article number: 6837

International Civil Aviation Organization (	(ICAO-IATA/DGR) - Additional information
Proper shipping name	Ethylene dichloride
Particulars in the shipper's declaration	UN1184, Ethylene dichloride, 3 (6.1), II
Danger label(s)	3+6.1
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

### **SECTION 15: Regulatory information**

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1 There is no additional information.

National regulations(Australia)

#### Australian Inventory of Chemical Substances(AICS)

Substance is listed.

#### Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

#### National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC

Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) Domestic Substances List (DSL) CICR CSCL-ENCS DSL

acc. to Safe Work Australia - Code of Practice

### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



#### article number: 6837

Legend	
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC INSQ	Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI NCI	Korea Existing Chemicals Inventory National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
TCSI	. REACH registered substances Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

### **SECTION 16: Other information**

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0,1%.	Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1		National inventories: change in the listing (table)	yes

#### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code

acc. to Safe Work Australia - Code of Practice

### 1,2-Dichloroethane ROTIPURAN® ≥99,5 %, p.a.



#### article number: 6837

Abbr.	Descriptions of used abbreviations	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
LEL	Lower explosion limit (LEL)	
NLP	No-Longer Polymer	
РВТ	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
ppm	Parts per million	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
UEL	Upper explosion limit (UEL)	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants	

#### Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H350	May cause cancer.

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.