

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥94 % pure

article number: **7653**
Version: **GHS 3.0 en**
Replaces version of: 2019-06-21
Version: (GHS 2)

date of compilation: 2019-06-19
Revision: 2022-08-01

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance	Diisobutyl ketone ≥94 % pure
Article number	7653
CAS number	108-83-8
Alternative name(s)	2,6-dimethylheptan-4-one

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use Industrial uses Professional uses Formulation [mixing] of preparations and/or re-packaging (excluding alloys) Feedstock use Intermediate Use in cleaning agents
---------------------------	--

Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household).
-----------------------	---

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥ 94 % pure

article number: 7653

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word

Warning

Pictograms

GHS02, GHS07



Hazard statements

H226 Flammable liquid and vapour
H335 May cause respiratory irritation

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
P261 Avoid breathing dust/fume/gas/mist/vapours/spray

Precautionary statements - response

P312 Call a POISON CENTER or doctor/physician if you feel unwell
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed
P403+P235 Store in a well-ventilated place. Keep cool

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥ 94 % pure

article number: 7653

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Diisobutyl ketone
Molecular formula	$C_9H_{18}O$
Molar mass	142.2 g/mol
CAS No	108-83-8

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Cough, Dyspnoea, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
dry extinguishing powder, BC-powder, carbon dioxide (CO_2)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥ 94 % pure

article number: 7653

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥ 94 % pure

article number: 7653

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
AU	diisobutyl ketone (2,6-dimethylheptan-4-one)	108-83-8	WES	25	145						WES

Notation

Ceiling-C
STEL

Ceiling value is a limit value above which exposure should not occur
Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥ 94 % pure

article number: 7653

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	53 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	7.7 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Environmental values

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0.03 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0.003 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	2.55 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0.46 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0.046 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0.075 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR (Nitrile rubber)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥ 94 % pure

article number: 7653

- **material thickness**

>0,3 mm

- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	like esters
Melting point/freezing point	-46 °C at 1,013 hPa (ECHA)
Boiling point or initial boiling point and boiling range	168 °C at 1,013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	47 g/m ³ (LEL) - 365 g/m ³ (UEL) / 0.8 vol% (LEL) - 6.2 vol% (UEL)
Flash point	49 °C at 1,013 hPa (c.c.) (ECHA)
Auto-ignition temperature	345 °C at 1,013 hPa (ECHA)
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	1.292 mm ² /s at 20 °C
Dynamic viscosity	1.05 mPa s at 20 °C
<u>Solubility(ies)</u>	
Water solubility	0.5 g/l at 20 °C
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	3.71 (25 °C) (ECHA)
Soil organic carbon/water (log KOC)	2.07 (ECHA)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥ 94 % pure

article number: **7653**

Vapour pressure	1.6 hPa at 20 °C 9.8 hPa at 50 °C
<u>Density and/or relative density</u>	
Density	0.804 – 0.813 g/cm ³
Relative vapour density	4.91 (air = 1)
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

9.2 Other information

Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	
Surface tension	22.8 dyn/cm (25 °C) (ECHA)
Refractive index	1.414

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

aluminium, plastics, rubber, natural, Butyl caoutchouc (butyl rubber)

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Diisobutyl ketone ≥94 % pure

article number: 7653

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2,000 mg/kg	rat		ECHA
inhalation: vapour	LC50	>14.5 mg/l/4h	rat		ECHA
dermal	LD50	>2,000 mg/kg	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, nausea

• If in eyes

slightly irritant

• If inhaled

Irritation to respiratory tract, cough, Dyspnoea

• If on skin

has degreasing effect on the skin

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥94 % pure

article number: 7653

• Other information

Liver and kidney damage, Headache, Abdominal pain, Narcosis, Nausea, Vertigo, Dizziness, Drowsiness, Vomiting

11.2 Endocrine disrupting properties

Not listed.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	30 mg/l	fish	ECHA	24 h
EC50	55.6 mg/l	aquatic invertebrates	ECHA	24 h
ErC50	46.9 mg/l	algae	ECHA	72 h

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: 2.924 mg/mg
Theoretical Carbon Dioxide: 2.785 mg/mg

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	88 %	20 d
oxygen depletion	4 %	5 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	3.71 (25 °C) (ECHA)
BCF	130 (ECHA)

12.4 Mobility in soil

The Organic Carbon normalised adsorption coefficient	2.07 (ECHA)
--	-------------

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥ 94 % pure

article number: 7653

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids
H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 1157
IMDG-Code	UN 1157
ICAO-TI	UN 1157

14.2 UN proper shipping name

UN RTDG	DIISOBUTYL KETONE
IMDG-Code	DIISOBUTYL KETONE
ICAO-TI	Diisobutyl ketone

14.3 Transport hazard class(es)

UN RTDG	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥94 % pure

article number: 7653

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments


The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations


Transport information National regulations Additional information (UN RTDG)

UN number	1157
Class	3
Packing group	III
Danger label(s)	3
	
Special provisions (SP)	- UN RTDG
Excepted quantities (EQ)	E1 UN RTDG
Limited quantities (LQ)	5 L UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	DIISOBUTYL KETONE
Particulars in the shipper's declaration	UN1157, DIISOBUTYL KETONE, 3, III, 49°C c.c.
Marine pollutant	-
Danger label(s)	3
	
Special provisions (SP)	-
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Diisobutyl ketone
Particulars in the shipper's declaration	UN1157, Diisobutyl ketone, 3, III
Danger label(s)	3
	
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

Diisobutyl ketone ≥94 % pure

article number: 7653

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥94 % pure

article number: 7653

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Diisobutyl ketone ≥94 % pure

article number: 7653

Abbr.	Descriptions of used abbreviations
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H335	May cause respiratory irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.