

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: **7724**
Version: **GHS 4.1 en**
Replaces version of: 2024-03-02
Version: (GHS 4)

date of compilation: 2019-10-10
Revision: 2024-03-04

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	1-Butanol ≥99,5 %, for synthesis
Article number	7724
CAS number	71-36-3
Alternative name(s)	n-Butanol

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone:+49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 Westmead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.10	Acute toxicity (oral)	4	Acute Tox. 4	H302
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol $\geq 99,5\%$, for synthesis

article number: 7724

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
3.8D	Specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS02, GHS05,
GHS07



Hazard statements

H226	Flammable liquid and vapour
H302	Harmful if swallowed
H315	Causes skin irritation
H318	Causes serious eye damage
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary statements - response

P302+P352	IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed
P403+P235	Store in a well-ventilated place. Keep cool

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol $\geq 99,5\%$, for synthesis

article number: 7724

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	1-Butanol
Molecular formula	$C_4H_{10}O$
Molar mass	74.12 g/mol
CAS No	71-36-3

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion

Rinse mouth with water (only if the person is conscious). Call a doctor.

4.2 Most important symptoms and effects, both acute and delayed

Following inhalation: Cough, Dyspnoea, Irritant effects, Vertigo, Headache, Drowsiness, Dizziness, Narcosis,

Following skin contact: Irritation,

After eye contact: Irritation, Risk of serious damage to eyes, Risk of blindness,

Following ingestion: Vomiting, Nausea

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!

water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol $\geq 99,5$ %, for synthesis

article number: 7724

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol $\geq 99,5\%$, for synthesis

article number: 7724

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
AU	n-butyl alcohol (butan-1-ol)	71-36-3	WES					50	152	H	WES

Notation

Ceiling-C

H

STEL

TWA

Ceiling value is a limit value above which exposure should not occur

Absorbed through the skin

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol $\geq 99,5\%$, for synthesis

article number: 7724

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	310 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects

Environmental values

Relevant PNECs and other threshold levels				
End-point	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0.082 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0.008 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	2,476 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	0.324 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0.032 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0.017 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

Butyl caoutchouc (butyl rubber)

• material thickness

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol $\geq 99,5$ %, for synthesis

article number: 7724

0,5 mm


- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	like: - alcohol
Odour threshold	0.004 – 48.7 ppm
Melting point/freezing point	<-90 °C (ECHA)
Boiling point or initial boiling point and boiling range	119 °C at 1,013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1.4 vol% (LEL) - 11.3 vol% (UEL)
Flash point	35 °C at 1,013 hPa (ECHA)
Auto-ignition temperature	355 °C at 1,019 hPa (ECHA)
Decomposition temperature	not relevant
pH (value)	7 (in aqueous solution: 70 g/l, 20 °C)
Kinematic viscosity	3.638 mm ² /s at 20 °C
Dynamic viscosity	2.947 mPa s at 20 °C
<u>Solubility(ies)</u>	
Water solubility	66 g/l at 20 °C (ECHA)
<u>Partition coefficient</u>	
Partition coefficient n-octanol/water (log value):	1 (pH value: 7, 25 °C) (ECHA)
Soil organic carbon/water (log KOC)	0.54 (ECHA)

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: 7724

Vapour pressure	<10 hPa at 20 °C
<u>Density and/or relative density</u>	
Density	0.81 g/cm ³ at 20 °C (ECHA)
Relative vapour density	2.6 at 20 °C (air = 1)
Particle characteristics	not relevant (liquid)
<u>Other safety parameters</u>	
Oxidising properties	none

9.2 Other information

Information with regard to physical hazard classes:	There is no additional information.
Other safety characteristics:	
Gas group (explosion group)	IIB Maximum Experimental Safe Gap value; 0,5 mm ≤ MESG ≤ 0,9 mm
Maximum explosion pressure	8.4 bar
Surface tension	69.9 mN/m (20 °C) (ECHA)
Refractive index	1.399 (20 °C)

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Exothermic reaction with: Alkali metals, Aluminium, Alkaline earth metal, Reducing agents, Acid chlorides, inorganic, Strong oxidisers

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

aluminium, Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: 7724

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful if swallowed.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	2,292 mg/kg	rat		ECHA
dermal	LD50	3,430 mg/kg	rabbit		ECHA

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• **If swallowed**

vomiting, nausea

• **If in eyes**

Causes serious eye damage, risk of blindness

• **If inhaled**

Irritation to respiratory tract, cough, Dyspnoea, headache, vertigo, fatigue, dizziness, narcosis

• **If on skin**

causes skin irritation

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: 7724

• Other information

Other adverse effects: Liver and kidney damage, Cardiovascular system

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	1,376 mg/l	fish	ECHA	96 h
EC50	1,328 mg/l	aquatic invertebrates	ECHA	48 h
ErC50	225 mg/l	algae	ECHA	96 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EC50	18 mg/l	aquatic invertebrates	ECHA	21 d

12.2 Persistence and degradability

Theoretical Oxygen Demand: 2.59 mg/mg
Theoretical Carbon Dioxide: 2.375 mg/mg

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
biotic/abiotic	98 %	28 d
oxygen depletion	68 %	5 d

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	1 (pH value: 7, 25 °C) (ECHA)
---------------------------	-------------------------------

12.4 Mobility in soil

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: 7724

Henry's law constant	0.054 Pa m ³ /mol (ECHA)
The Organic Carbon normalised adsorption coefficient	0.54 (ECHA)

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids
H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 1120
IMDG-Code	UN 1120
ICAO-TI	UN 1120

14.2 UN proper shipping name

UN RTDG	BUTANOLS
IMDG-Code	BUTANOLS
ICAO-TI	Butanols

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: 7724

14.3 Transport hazard class(es)

UN RTDG	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport information National regulations Additional information (UN RTDG)

UN number	1120
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	223 UN RTDG
-------------------------	----------------

Excepted quantities (EQ)	E1 UN RTDG
--------------------------	---------------

Limited quantities (LQ)	5 L UN RTDG
-------------------------	----------------

Emergency Action Code	2Y
-----------------------	----

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name	BUTANOLS
Particulars in the shipper's declaration	UN1120, BUTANOLS, 3, III, 35°C c.c.
Marine pollutant	-
Danger label(s)	3



Special provisions (SP)	223
Excepted quantities (EQ)	E1

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: 7724

Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name	Butanols
Particulars in the shipper's declaration	UN1120, Butanols, 3, III
Danger label(s)	3



Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: 7724

Country	Inventory	Status
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



1-Butanol ≥99,5 %, for synthesis

article number: 7724

Abbr.	Descriptions of used abbreviations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.