
acc. to Safe Work Australia - Code of Practice



article number: **7912** Version: **GHS 6.0 en** Replaces version of: 2022-12-05 Version: (GHS 5)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Identification of the substance

Article number

CAS number

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:

Uses advised against:

Laboratory chemical Laboratory and analytical use

Benzene D6 99,8 Atom%D

7912

1076-43-3

Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de **Website:** www.carlroth.de

Competent person responsible for the safety data Department Health, Safety and Environment sheet:

e-mail (competent person):

sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class		Hazard class and category	Hazard statement
2.6	2.6 Flammable liquid		Flam. Liq. 2	H225
3.2	3.2 Skin corrosion/irritation		Skin Irrit. 2	H315
3.3	3.3 Serious eye damage/eye irritation		Eye Irrit. 2A	H319
3.5	Germ cell mutagenicity	1B	Muta. 1B	H340



date of compilation: 2019-06-26 Revision: 2024-03-01

acc. to Safe Work Australia - Code of Practice



Benzene D6 99,8 Atom%D

article number: 7912

Section	Hazard class		Hazard class and category	Hazard statement
3.6	6 Carcinogenicity		Carc. 1A	H350
3.9	3.9 Specific target organ toxicity - repeated exposure		STOT RE 1	H372
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word Danger

Pictograms



Hazard statements

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H340	May cause genetic defects
H350	May cause cancer
H372	Causes damage to organs (haematopoietic system) through prolonged or repeated exposure

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking
P260	Do not breathe dust/fume/gas/mist/vapours/spray

Precautionary statements - response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313	IF exposed or concerned: Get medical advice/attention
P331	Do NOT induce vomiting
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

For professional users only

acc. to Safe Work Australia - Code of Practice

Benzene D6 99,8 Atom%D

article number: **7912**

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Benzene D6
Molecular formula	C_6D_6
Molar mass	84.16 ^g / _{mol}
CAS No	1076-43-3

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Call a physician immediately. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Headache, Vertigo, Nausea, Fatigue

4.3 Indication of any immediate medical attention and special treatment needed

none



acc. to Safe Work Australia - Code of Practice



Benzene D6 99,8 Atom%D

article number: 7912

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapourair mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

acc. to Safe Work Australia - Code of Practice



Benzene D6 99,8 Atom%D

article number: 7912

6.4 Reference to other sections


Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

This information is not available.

acc. to Safe Work Australia - Code of Practice



Benzene D6 99,8 Atom%D

article number: 7912

invironmental values					
Relevant PNECs and other threshold levels					
End- point	Threshold level	Organism	Environmental com- partment	Exposure time	
PNEC	1.9 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)	
PNEC	1.9 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)	
PNEC	39 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)	
PNEC	33 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)	
PNEC	33 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)	
PNEC	4.8 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)	

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a consider-able reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM (fluoro rubber)

material thickness

0,4 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

acc. to Safe Work Australia - Code of Practice

Benzene D6 99,8 Atom%D

article number: 7912

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 $^{\circ}$ C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	6.8 °C at 1,013 hPa
Boiling point or initial boiling point and boiling range	79.1 °C at 1,013 hPa
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	1.3 vol% (LEL) - 8 vol% (UEL)
Flash point	-11 °C at 1,013 hPa
Auto-ignition temperature	498 °C at 1,013 hPa
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	not determined
Solubility(ies)	
Water solubility	~2 ^g / _l at 25 °C
Partition coefficient	
Partition coefficient n-octanol/water (log value):	2.13 (pH value: 7, 25 °C) (ECHA)
Vapour pressure	99.5 hPa at 20 °C
Density and/or relative density	
Density	0.95 ^g / _{cm³} at 25 °C
Relative vapour density	2.91 (air = 1)
Particle characteristics	not relevant (liquid)



acc. to Safe Work Australia - Code of Practice

Benzene D6 99,8 Atom%D

article number: 7912



	Other safety parameters	
	Oxidising properties	none
9.2	Other information	
	Information with regard to physical hazard classes:	There is no additional information.
	Other safety characteristics:	There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser, Mineral acids, Sulphur, Exothermic reaction with: Halogenated hydrocarbons, Danger of explosion: Halogens, Nitric acid, Perchlorates, Peroxides

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful if swallowed or if inhaled.

Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	>2,000 ^{mg} / _{kg}	rat		ECHA
inhalation: vapour	LC50	43,767 ^{mg} / _{m³} /4h	rat		ECHA

Skin corrosion/irritation

Causes skin irritation.

acc. to Safe Work Australia - Code of Practice

Benzene D6 99,8 Atom%D

article number: 7912

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs (haematopoietic system) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
1	haematopoietic system	if exposed

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

vomiting, nausea, aspiration hazard

• If in eyes

Causes serious eye irritation

• If inhaled

cough, pain, choking, and breathing difficulties, deficits in perception and coordination, reaction time, or sleepiness, poisoning effect on central nervous system can cause convulsions, laboured breathing and loss of consciousness

• If on skin

pruritis, causes skin irritation

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\ge 0,1\%$.



acc. to Safe Work Australia - Code of Practice

Benzene D6 99,8 Atom%D

article number: 7912

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)

1 21	-			
Endpoint	Value	Species	Source	Exposure time
LC50	5.3 ^{mg} / _l	fish	ECHA	96 h
EC50	10 ^{mg} / _l	aquatic invertebrates	ECHA	48 h
ErC50	100 ^{mg} / _l	algae	ECHA	72 h

12.2 Persistence and degradability

Theoretical Oxygen Demand: 2.281 ^{mg}/_{mg} Theoretical Carbon Dioxide: 3.138 ^{mg}/_{mg}

Biodegradation

The substance is readily biodegradable.

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	2.13 (pH value: 7, 25 °C) (ECHA)
---------------------------	----------------------------------

12.4 Mobility in soil

Henry's law constant	415 ^{Pa m³} / _{mol} (ECHA)
----------------------	--

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.



acc. to Safe Work Australia - Code of Practice

Benzene D6 99,8 Atom%D



article number: 7912

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1 UN number

	UN RTDG	UN 1114
	IMDG-Code	UN 1114
	ICAO-TI	UN 1114
14.2	UN proper shipping name	
	UN RTDG	BENZENE
	IMDG-Code	BENZENE
	ICAO-TI	Benzene
14.3	Transport hazard class(es)	
	UN RTDG	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	UN RTDG	II
	IMDG-Code	II
	ICAO-TI	II
14.5	Environmental hazards	non-environ

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

acc. to Safe Work Australia - Code of Practice

Benzene D6 99,8 Atom%D

article number: 7912



Transport informationNational regulationsAd	ditional information(UN RTDG)
UN number	1114
Class	3
Packing group	II
Danger label(s)	3
Special provisions (SP)	- UN RTDG
Excepted quantities (EQ)	E2 UN RTDG
Limited quantities (LQ)	1 L UN RTDG
Emergency Action Code	3WE
International Maritime Dangerous Goods Cod	e (IMDG) - Additional information
Proper shipping name	BENZENE
Particulars in the shipper's declaration	UN1114, BENZENE, 3, II, -11°C c.c.
Marine pollutant	-
Danger label(s)	3
Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	В
International Civil Aviation Organization (ICA	D-IATA/DGR) - Additional information
Proper shipping name	Benzene
Particulars in the shipper's declaration	UN1114, Benzene, 3, II
Danger label(s)	3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

acc. to Safe Work Australia - Code of Practice



Benzene D6 99,8 Atom%D

article number: 7912

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture 15.1

There is no additional information.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
CA	NDSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
JP	CSCL-ENCS	substance is listed
NZ	NZIoC	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

CSCL-ENCS

- ECSI IECSC
- List of Existing and New Chemical Substances (CSCL-ENCS) EC Substance Inventory (EINECS, ELINCS, NLP) Inventory of Existing Chemical Substances Produced or Imported in China National Chemical Inventory Non-domestic Substances List (NDSL) New Zealand Inventory of Chemicals Taiwan Chemical Substance Inventory Toxic Substance Control Act NCI
- NDSL

NZIoC TCSI

Toxic Substance Control Act TSCA

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		Hazard statements: change in the listing (table)	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 3WE	yes
15.1		National inventories: change in the listing (table)	yes

acc. to Safe Work Australia - Code of Practice



Benzene D6 99,8 Atom%D

article number: 7912

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Na- tions
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
UEL	Upper explosion limit (UEL)
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

acc. to Safe Work Australia - Code of Practice



Benzene D6 99,8 Atom%D

article number: 7912

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H340	May cause genetic defects.
H350	May cause cancer.
H372	Causes damage to organs (haematopoietic system) through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.