acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966 date of compilation: 2019-02-08 Version: GHS 3.0 en Revision: 2024-02-23

Replaces version of: 2022-06-27

Version: (GHS 2)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Propylene glycol methyl ether acetate** ≥99 %,

pure

Article number 7966

CAS number 108-65-6

Alternative name(s) 1-Methoxy-2-propyl acetate

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for private purposes (household).

Food, drink and animal feedingstuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 **Telefax:** +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

sheet:

1.4

e-mail (competent person):

sicherheit@carlroth.de

Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

Australia (en) Page 1 / 15



acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966



Labelling

Signal word Warning

Pictograms

GHS02



Hazard statements

H226 Flammable liquid and vapour

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

P233 Keep container tightly closed

P241 Use explosion-proof electrical/ventilating/lighting equipment

P280 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance Propylene glycol methyl ether acetate

Molecular formula $C_6H_{12}O_3$ Molar mass $132.2 \, {}^g/_{mol}$ CAS No 108-65-6

Australia (en) Page 2 / 15



acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966



SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Dizziness, Unconsciousness, Narcotic effects

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings! water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

Australia (en) Page 3 / 15

acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966



5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Australia (en) Page 4 / 15

acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966



Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

Control parameters 8.1

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	1-methoxy-2-pro- panol acetate	108-65-6	WES	50	274	100	548			Н	WES

Notation

Ceiling value is a limit value above which exposure should not occur Absorbed through the skin Ceiling-C

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels Endpoint Threshold Protection goal, **Used in Exposure time** route of exposure level DNEL 275 mg/m³ human, inhalatory worker (industry) chronic - systemic effects 550 mg/m³ DNEL human, inhalatory acute - local effects worker (industry) **DNEL** 796 mg/kg bw/ human, dermal worker (industry) chronic - systemic effects

Environmental values

Relevant PNECs and other threshold levels					
End- point	Threshold level	Organism	Environmental com- partment	Exposure time	
PNEC	0.329 ^{mg} / _{cm³}	unknown	marine sediment	intermittent release	
PNEC	0.0635 ^{mg} / _{cm³}	unknown	marine water	intermittent release	

Australia (en) Page 5 / 15



acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966



Relevant	Relevant PNECs and other threshold levels					
End- point	Threshold level	Organism	Environmental com- partment	Exposure time		
PNEC	6.35 ^{mg} / _{cm³}	unknown	air	intermittent release		
PNEC	3.29 ^{mg} / _{cm³}	unknown	freshwater sediment	intermittent release		
PNEC	0.635 ^{mg} / _{cm³}	unknown	freshwater	intermittent release		
PNEC	100 ^{mg} / _{cm³}	unknown	sewage treatment plant (STP)	intermittent release		
PNEC	0.29 ^{mg} / _{cm³}	unknown	soil	intermittent release		
PNEC	0.635 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)		
PNEC	0.064 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)		
PNEC	100 ^{mg} / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)		
PNEC	3.29 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)		
PNEC	0.329 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)		
PNEC	0.29 ^{mg} / _{kg}	terrestrial organisms	soil	short-term (single instance)		

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,7mm

Australia (en) Page 6 / 15

acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966



>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour greenish yellow

Melting point/freezing point -66 °C at 1,013 hPa (ECHA)

Boiling point or initial boiling point and boiling

range

145.8 °C at 1,013 hPa (ECHA)

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit 1.5 vol% (LEL) - 7 vol% (UEL)

Flash point 45.5 °C at 1,013 hPa

Auto-ignition temperature 333 °C at 1,013 hPa (ECHA) (auto-ignition temper-

ature (liquids and gases))

Decomposition temperature not relevant

pH (value) 4 (in aqueous solution: 200 ^g/_l, 20 °C)

Kinematic viscosity $1.13 \, ^{\text{mm}^2} /_{\text{s}}$ at 25 °C

Dynamic viscosity 1.2 mPa s at 20 °C

Solubility(ies)

Water solubility 198 ^g/_l at 20 °C (ECHA)

Partition coefficient

Partition coefficient n-octanol/water (log value): 1.2 (pH value: 6.8, 20 °C) (ECHA)

Vapour pressure 3.599 hPa at 20 °C

Australia (en) Page 7 / 15



acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966

Density and/or relative density

Density $0.965 - 0.97 \, {\rm g}/{\rm cm}^3$ at 20 °C

Relative vapour density Information on this property is not available.

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Other safety characteristics: There is no additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

There is no additional information.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4. May be harmful in contact with skin.

Australia (en) Page 8 / 15



acc. to Safe Work Australia - Code of Practice



Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
oral	LD50	6,190 – 10,000 ^{mg} / kg	rat		ECHA
dermal	LD50	>2,000 ^{mg} / _{kg}	rat		ECHA

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

nausea, gastrointestinal complaints

• If in eyes

Data are not available.

• If inhaled

headache, dizziness

• If on skin

irritant effects

Other information

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0.1\%$.

Australia (en) Page 9 / 15

acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966



SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Endpoint	Value	Species	Source	Exposure time
LC50	180 ^{mg} / _l	fish	ECHA	96 h
EC50	>500 ^{mg} / _l	aquatic invertebrates	ECHA	48 h
ErC50	>1,000 ^{mg} / _l	algae	ECHA	96 h

Aquatic toxicity (chronic)

Endpoint	Value	Species	Source	Exposure time
LC50	63.5 ^{mg} / _l	fish	ECHA	14 d
EC50	>100 ^{mg} / _l	aquatic invertebrates	ECHA	21 d

12.2 Persistence and degradability

Theoretical Oxygen Demand: 1.816 $^{\rm mg}/_{\rm mg}$ Theoretical Carbon Dioxide: 1.998 $^{\rm mg}/_{\rm mg}$

Biodegradation

The substance is readily biodegradable.

Process of degradability

Process	Degradation rate	Time		
biotic/abiotic	100 %	8 d		
carbon dioxide generation	90 %	28 d		
oxygen depletion	60 %	5.9 d		
DOC removal	99 %	28 d		

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	1.2 (pH value: 6.8, 20 °C) (ECHA)
---------------------------	-----------------------------------

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of \geq 0,1%.

Australia (en) Page 10 / 15

acc. to Safe Work Australia - Code of Practice

Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966



Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

SECTION 14: Transport information

14.1	UN number	
	UN RTDG	UN 3272
	IMDG-Code	UN 3272
	ICAO-TI	UN 3272
14.2	UN proper shipping name	
	UN RTDG	ESTERS, N.O.S.
	IMDG-Code	ESTERS, N.O.S.
	ICAO-TI	Esters, n.o.s.
	Technical name	Propylene glycol methyl ether acetate
14.3	Transport hazard class(es)	
	UN RTDG	3
	IMDG-Code	3
	ICAO-TI	3
14.4	Packing group	
	UN RTDG	III
	IMDG-Code	III

Australia (en) Page 11 / 15



acc. to Safe Work Australia - Code of Practice



Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966

ICAO-TI III

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations 14.8

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 3272 Class 3 **Packing group** III 3 Danger label(s)

Special provisions (SP) 223, 274

UN RTDG

Excepted quantities (EQ)

UN RTDG

Limited quantities (LQ)

ŬÑ RTDG

Emergency Action Code 3Y

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name ESTERS, N.O.S.

UN3272, ESTERS, N.O.S., (Propylene glycol methyl ether acetate), 3, III, 45.5°C c.c. Particulars in the shipper's declaration

Marine pollutant

Danger label(s) 3



Special provisions (SP) 223, 274

Excepted quantities (EQ) E1 Limited quantities (LQ) 5 L

EmS F-E, S-D

Stowage category Α

Australia (en) Page 12 / 15

acc. to Safe Work Australia - Code of Practice



Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Esters, n.o.s.

Particulars in the shipper's declaration UN3272, Esters, n.o.s., (Propylene glycol methyl ether acetate), 3, III

Danger label(s) 3



Special provisions (SP) А3 Excepted quantities (EQ) E1 Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Australia (en) Page 13 / 15

acc. to Safe Work Australia - Code of Practice



Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966

Legend

AIIC CICR CSCL-ENCS Australian Inventory of Industrial Chemicals

Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Inventory of Existing and New Chemical Substances (ISHA-ENCS)
Korea Existing Chemicals Inventory DSL ECSI IECSC

INSQ

ISHA-ENCS KECI

NCI National Chemical Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
14.8		Emergency Action Code: 3Y	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations	
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)	
Ceiling-C	Ceiling value	
DGR	Dangerous Goods Regulations (see IATA/DGR)	
DNEL	Derived No-Effect Level	
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval	
ED	Endocrine disruptor	
EINECS	European Inventory of Existing Commercial Chemical Substances	
ELINCS	European List of Notified Chemical Substances	
EmS	Emergency Schedule	
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control	
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations	
IATA	International Air Transport Association	
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)	

Australia (en) Page 14 / 15

acc. to Safe Work Australia - Code of Practice



Propylene glycol methyl ether acetate ≥99 %, pure

article number: 7966

Abbr.	Descriptions of used abbreviations	
ICAO	International Civil Aviation Organization	
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air	
IMDG	International Maritime Dangerous Goods Code	
IMDG-Code	International Maritime Dangerous Goods Code	
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval	
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval	
LEL	Lower explosion limit (LEL)	
NLP	No-Longer Polymer	
PBT	Persistent, Bioaccumulative and Toxic	
PNEC	Predicted No-Effect Concentration	
ppm	Parts per million	
STEL	Short-term exposure limit	
TWA	Time-weighted average	
UEL	Upper explosion limit (UEL)	
UN RTDG	UN Recommendations on the Transport of Dangerous Good	
vPvB	Very Persistent and very Bioaccumulative	
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants	

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 15 / 15