acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

date of compilation: 2016-06-09 article number: 8248 Version: GHS 2.0 en Revision: 2022-01-31

Replaces version of: 2016-06-09

Version: (GHS 1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance Multi-Element ICP - Standard Solution A

ROTI®Star 24 Elemente in 5 % HNO₃

Article number

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory chemical

Laboratory and analytical use

Uses advised against: Do not use for squirting or spraying. Do not use

> for products which come into direct contact with the skin. Do not use for products which come into contact with foodstuffs. Do not use for private

purposes (household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone: +49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

2.1

e-mail (competent person): sicherheit@carlroth.de

Emergency telephone number 1.4

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.16	Substance or mixture corrosive to metals	1	Met. Corr. 1	H290
3.2	Skin corrosion/irritation	1B	Skin Corr. 1B	H314
3.3	Serious eye damage/eye irritation	1	Eye Dam. 1	H318
3.6	Carcinogenicity	1A	Carc. 1A	H350

Page 1 / 18 Australia (en)

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Supplemental hazard information

Code	Supplemental hazard information
EUH071	corrosive to the respiratory tract

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis.

2.2 Label elements

Labelling

Signal word Danger

Pictograms

GHS05, GHS08



Hazard statements

H290 May be corrosive to metals

H314 Causes severe skin burns and eye damage

H350 May cause cancer

Precautionary statements

Precautionary statements - prevention

P260 Do not breathe dusts or mists P280 Wear eye protection/face protection

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing

P390 Absorb spillage to prevent material damage

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

For professional users only

Hazardous ingredients for labelling: Nitric acid ...% [C ≤ 70 %], Nickel dinitrate, Cobalt

dinitrate

Australia (en) Page 2 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

Substances

not relevant (mixture)

3.2 **Mixtures**

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Nitric acid% [C ≤ 70 %]	CAS No 7697-37-2	5	Ox. Liq. 3 / H272 Met. Corr. 1 / H290 Acute Tox. 3 / H331 Skin Corr. 1A / H314 Eye Dam. 1 / H318 EUH071		B(a)
Boric acid	CAS No 10043-35-3	0.28	Repr. 1B / H360FD	\$	
nickel dinitrate	CAS No 13138-45-9	0.16	Ox. Sol. 2 / H272 Acute Tox. 4 / H302 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Dam. 1 / H318 Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Muta. 2 / H341 Carc. 1A / H350 Repr. 1A / H360D STOT RE 1 / H372		
cobalt dinitrate	CAS No 10141-05-6	0.155	Resp. Sens. 1 / H334 Skin Sens. 1 / H317 Muta. 2 / H341 Carc. 1A / H350 Repr. 1A / H360F	\$	1(a)
Ammonium monovanadate	CAS No 7803-55-6	0.11	Acute Tox. 3 / H301 Acute Tox. 4 / H332 Eye Irrit. 2A / H319 Repr. 2 / H361fd STOT RE 1 / H372		

Notes

The concentration stated is the percentage by weight of the metallic element calculated with reference to the total weight of the mixture

The classification refers to an aqueous solution 1(a):

B(a):

For full text of abbreviations: see SECTION 16

Australia (en) Page 3 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off immediately all contaminated clothing. Self-protection of the first aider.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

After contact with skin, wash immediately with plenty of water. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Following eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

Following ingestion

Rinse mouth immediately and drink plenty of water. Call a physician immediately. If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects).

4.2 Most important symptoms and effects, both acute and delayed

Corrosion, Risk of blindness, Gastric perforation, Risk of serious damage to eyes, Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Non-combustible.

Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus. Wear full chemical protective clothing.

Australia (en) Page 4 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray.

6.2 Environmental precautions

Keep away from drains, surface and ground water. The product is an acid. Before discharge into sewage plants the product normally needs to be neutralised.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use extractor hood (laboratory). Handle and open container with care. Avoid exposure. Clear contaminated areas thoroughly.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

Australia (en) Page 5 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

SECTION 8: Exposure controls/personal protection

Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	nickel dinitrate	13138- 45-9	WES		0.1						WES
AU	nitric acid	7697-37- 2	WES	2	5.2	4	10				WES

Notation

Ceiling-C

Ceiling value is a limit value above which exposure should not occur

Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified) STEL

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time
Boric acid	10043-35-3	DNEL	8.3 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects
Boric acid	10043-35-3	DNEL	392 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Ammonium monovanadate	7803-55-6	DNEL	0.64 mg/ m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
Ammonium monovanadate	7803-55-6	DNEL	0.18 mg/ m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects
Ammonium monovanadate	7803-55-6	DNEL	0.92 mg/ m³	human, inhalat- ory	worker (industry)	acute - local ef- fects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Boric acid	10043-35-3	PNEC	2.9 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
Boric acid	10043-35-3	PNEC	2.9 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
Boric acid	10043-35-3	PNEC	10 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Boric acid	10043-35-3	PNEC	5.7 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
Ammonium monovanadate	7803-55-6	PNEC	6.93 ^{µg} / _l	aquatic organ- isms	water	intermittent re- lease

Australia (en) Page 6 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time
Ammonium monovanadate	7803-55-6	PNEC	7.6 ^{µg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
Ammonium monovanadate	7803-55-6	PNEC	2.5 ^{µg} / _l	aquatic organ- isms	marine water	short-term (single instance)
Ammonium monovanadate	7803-55-6	PNEC	450 ^{µg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
Ammonium monovanadate	7803-55-6	PNEC	240 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
Ammonium monovanadate	7803-55-6	PNEC	79 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
Ammonium monovanadate	7803-55-6	PNEC	7.2 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection. Wear face protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

Australia (en) Page 7 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation.

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless - light yellow

Odour stinging

Melting point/freezing point ~0 °C at 1,013 hPa

Boiling point or initial boiling point and boiling ~100 °C at 1,013 hPa

range

Flammability non-combustible
Lower and upper explosion limit not determined
Flash point not determined
Auto-ignition temperature not determined
Decomposition temperature not relevant

pH (value) <2

Kinematic viscosity not determined

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): not relevant (inorganic)

Vapour pressure not determined

Density and/or relative density

Density $\sim 1 \, {}^{9}/_{cm^3}$ at 20 $^{\circ}$ C

Relative vapour density information on this property is not available

Australia (en) Page 8 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

Corrosive to metals category 1: corrosive to metals

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

Substance or mixture corrosive to metals.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: Ammonia (NH3), Metals, Strong alkali, strong oxidiser

10.4 Conditions to avoid

Keep away from heat.

10.5 Incompatible materials

different metals

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Australia (en) Page 9 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: vapour	>2.65 ^{mg} / _l /4h
nickel dinitrate	13138-45-9	oral	1,620 ^{mg} / _{kg}
nickel dinitrate	13138-45-9	inhalation: dust/mist	1.5 ^{mg} / _l /4h
Ammonium monovanadate	7803-55-6	oral	218.1 ^{mg} / _{kg}
Ammonium monovanadate	7803-55-6	inhalation: dust/mist	2.61 ^{mg} / _l /4h

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Nitric acid% [C ≤ 70 %]	7697-37-2	inhalation: va- pour	LC50	>2.65 ^{mg} / _l /4h	rat
Boric acid	10043-35-3	oral	LD50	3,450 ^{mg} / _{kg}	rat
Boric acid	10043-35-3	dermal	LD50	>2,000 ^{mg} / _{kg}	rabbit
nickel dinitrate	13138-45-9	oral	LD50	1,620 ^{mg} / _{kg}	rat
Ammonium monovanadate	7803-55-6	oral	LD50	218.1 ^{mg} / _{kg}	rat
Ammonium monovanadate	7803-55-6	inhalation: dust/mist	LC50	2.61 ^{mg} / _l /4h	rat
Ammonium monovanadate	7803-55-6	dermal	LD50	>2,500 ^{mg} / _{kg}	rat

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Australia (en) Page 10 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

If swallowed danger of perforation of the esophagus and the stomach (strong corrosive effects)

• If in eyes

causes burns, Causes serious eye damage, risk of blindness

If inhaled

corrosive to the respiratory tract, cough, Dyspnoea

• If on skin

causes severe burns, May produce an allergic reaction, localised redness, oedema, pruritis and/or pain

Other information

This information is based upon the present state of our knowledge.

11.2 Endocrine disrupting properties

Information on this property is not available.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture											
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time						
Ammonium monovanadate	7803-55-6	LC50	9,005 ^{µg} / _l	fish	24 h						
Ammonium monovanadate	7803-55-6	ErC50	2,907 ^{µg} / _l	algae	72 h						
Ammonium monovanadate	7803-55-6	EC50	989.4 ^{µg} / _l	algae	72 h						

Aquatic toxicity (chronic) of components of the mixture **CAS No Exposure** Name of sub-**Endpoint Value Species** stance time 44,000 ^{µg}/_I Ammonium 7803-55-6 LC50 fish 24 h monovanadate EC50 >100 mg/_I 3 h Ammonium 7803-55-6 microorganisms monovanadate

Biodegradation

The methods for determining the biological degradability are not applicable to inorganic substances.

12.2 Process of degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

Australia (en) Page 11 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Boric acid	10043-35-3		-1.09 (pH value: 7.5, 22 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Information on this property is not available.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H8 Corrosives

H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

UN RTDG UN 3264

IMDG-Code UN 3264 ICAO-TI UN 3264

14.2 UN proper shipping name

UN RTDG CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

IMDG-Code CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

Australia (en) Page 12 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article	num	ber:	8248
---------	-----	------	------

	ICAO-TI	Corrosive liquid, acidic, inorganic, n.o.s.
	Technical name (hazardous ingredients)	Nitric acid% [C ≤ 70 %], Ammonium monovanadate
14.3	Transport hazard class(es)	
	UN RTDG	8
	IMDG-Code	8
	ICAO-TI	8
14.4	Packing group	
	UN RTDG	II
	IMDG-Code	II
	ICAO-TI	II

14.6 Special precautions for user

14.5 Environmental hazards

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number	3264
Class	8
Packing group	II
Danger label(s)	8
.	



Special provisions (SP) 274

UN RTDG

Excepted quantities (EQ)

UN RTDG

Limited quantities (LQ) 1 L

UN RTDG

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

Particulars in the shipper's declaration UN3264, CORROSIVE LIQUID, ACIDIC, INORGAN-

IC, N.O.S., (contains: Nitric acid ...% [$C \le 70 \%$],

non-environmentally hazardous acc. to the dangerous goods regulations

Ammonium monovanadate), 8, II

Marine pollutant Danger label(s) 8

Australia (en) Page 13 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248



Special provisions (SP) 274 Excepted quantities (EQ) E2 Limited quantities (LQ) 1 L **EmS** F-A, S-B Stowage category В

1 - Acids Segregation group

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Corrosive liquid, acidic, inorganic, n.o.s.

UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (contains: Nitric acid ...% [C \leq 70 %], Ammonium Particulars in the shipper's declaration

monovanadate), 8, II

Danger label(s) 8



Special provisions (SP) А3 Excepted quantities (EQ) E2 Limited quantities (LQ) 0,5 L

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AICS	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
KR	KECI	all ingredients are listed

Australia (en) Page 14 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Country	Inventory	Status
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed

Legend

Australian Inventory of Chemical Substances
Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS)
Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China
National Inventory of Chemical Substances
Koraa Existing Chemicals Inventory AICS CICR CSCL-ENCS DSL ECSI

IECSC

INSQ KECI Korea Existing Chemicals Inventory
NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory

Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		Supplemental hazard information: change in the listing (table)	yes
2.1	Remarks: For full text of Hazard- and EU Hazard-state- ments: see SECTION 16.		yes
2.1		The most important adverse physicochemical, human health and environmental effects: Skin corrosion produces an irreversible dam- age to the skin; namely, visible necrosis through the epidermis and into the dermis.	yes
2.2		Pictograms: change in the listing (table)	yes
2.2		Hazard statements: change in the listing (table)	yes
2.2		Precautionary statements - prevention: change in the listing (table)	yes
2.2		Precautionary statements - response: change in the listing (table)	yes

Australia (en) Page 15 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2	Supplemental hazard information		yes
2.2		Supplemental hazard information: change in the listing (table)	yes
2.2	Hazardous ingredients for labelling: nickel dinitrate, Ammonium monovanadate, Nitric acid	Hazardous ingredients for labelling: Nitric acid% [C ≤ 70 %], Nickel dinitrate, Co- balt dinitrate	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Danger		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2	contains: Nickel dinitrate, Ammonium monovanadate, Nitric acid		yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances

Australia (en) Page 16 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Abbr.	Descriptions of used abbreviations
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during specified time interval
log KOW	n-Octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
Met. Corr.	Substance or mixture corrosive to metals
Muta.	Germ cell mutagenicity
NLP	No-Longer Polymer
Ox. Liq.	Oxidising liquid
Ox. Sol.	Oxidising solid
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
Resp. Sens.	Respiratory sensitisation
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitisation
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good

Australia (en) Page 17 / 18

acc. to Safe Work Australia - Code of Practice



Multi-Element ICP - Standard Solution A ROTI®Star 24 Elemente in 5 % HNO₃

article number: 8248

Abbr.	Descriptions of used abbreviations
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H272	May intensify fire; oxidiser.
H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H360D	May damage the unborn child.
H360F	May damage fertility.
H360FD	May damage fertility. May damage the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 18 / 18