

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Version: **4.0 en**

Replaces version of: 2022-12-20

Version: (3)

date of compilation: 2016-06-30

Revision: 2024-03-02

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	o-Xylene ≥98 %, for synthesis
Article number	8749
Index No (GB CLP)	601-022-00-9
EC number	202-422-2
CAS number	95-47-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses:	Laboratory chemical Laboratory and analytical use
Uses advised against:	Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). Food, drink and animal feeding-stuffs.

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co. KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone: +49 (0) 721 - 56 06 0

Telefax: +49 (0) 721 - 56 06 149

e-mail: sicherheit@carlroth.de

Website: www.carlroth.de

Competent person responsible for the safety data sheet: Department Health, Safety and Environment

e-mail (competent person): sicherheit@carlroth.de

1.4 Emergency telephone number

Name	Street	Postal code/city	Telephone	Website
National Poisons Information Service City Hospital	Dudley Rd	B187QH Birmingham	844 892 0111	

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Classification acc. to GHS

Section	Hazard class	Cat-egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.1D	Acute toxicity (dermal)	4	Acute Tox. 4	H312
3.1I	Acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	Skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	Serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8R	Specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
3.9	Specific target organ toxicity - repeated exposure	2	STOT RE 2	H373
3.10	Aspiration hazard	1	Asp. Tox. 1	H304

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08



Hazard statements

H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H312+H332	Harmful in contact with skin or if inhaled
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H373	May cause damage to organs (respiratory tract) through prolonged or repeated exposure

Precautionary statements

Precautionary statements - prevention

P210	Keep away from heat, sparks, open flames, hot surfaces. No smoking
P260	Do not breathe mist/vapours/spray
P280	Wear protective gloves/protective clothing

Precautionary statements - response

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor
P302+P352 IF ON SKIN: Wash with plenty of water
P331 Do NOT induce vomiting

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	o-Xylene
Molecular formula	C ₈ H ₁₀
Molar mass	106,2 g/mol
CAS No	95-47-6
EC No	202-422-2
Index No (GB CLP)	601-022-00-9

Substance, Specific Conc. Limits, M-factors, ATE			
Specific Conc. Limits	M-Factors	ATE	Exposure route
-	-	1.100 mg/kg >11 mg/l/4h	dermal inhalation: vapour

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Call a physician immediately. Observe aspiration hazard if vomiting occurs.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

4.2 Most important symptoms and effects, both acute and delayed

Aspiration hazard, Irritation, Cough, Dyspnoea

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings!
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
EU	o-xylene	95-47-6	IOELV	50	221	100	442			H	2000/39/EC
GB	o-xylene	95-47-6	WEL	50	220	100	441				EH40/2005

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur
H Absorbed through the skin
STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values

Country	Name of agent	CAS No	Parameter	Notation	Identifier	Value	Material	Source
GB	xylene, mixture of isomers	95-47-6	methylhippuric acids	crea	BMGV	650 mmol/mol	urine	EH40/2005

Notation

crea Creatinine

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 °C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

FKM (fluoro rubber)

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

- **material thickness**

>0,11 mm

- **breakthrough times of the glove material**

>480 minutes (permeation: level 6)

- **Splash protection - Protective gloves**

- type of material: NBR (Nitrile rubber)


- material thickness: >0,4 mm

- breakthrough times of the glove material: >30 minutes (permeation: level 2)

- **other protection measures**

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C, colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-25,2 °C at 1.013 hPa (ECHA)
Boiling point or initial boiling point and boiling range	139,1 °C at 1.013 hPa (ECHA)
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	0,9 vol% (LEL) - 7 vol% (UEL)
Flash point	27 °C at 1.013 hPa (ECHA)
Auto-ignition temperature	528 °C at 1.013 hPa (ECHA) (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Kinematic viscosity	0,6602 mm ² /s at 25 °C
Dynamic viscosity	0,581 mPa s at 25 °C
<u>Solubility(ies)</u>	
Water solubility	0,146 g/l at 25 °C (ECHA)

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Partition coefficient

Partition coefficient n-octanol/water (log value): 3,15 (pH value: 7, 20 °C) (ECHA)

Soil organic carbon/water (log KOC) 2,73 (ECHA)

Vapour pressure 8,812 hPa at 25 °C

Density and/or relative density

Density 0,88 g/cm³ at 25 °C (ECHA)

Relative vapour density Information on this property is not available.

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard classes: There is no additional information.

Other safety characteristics:

Surface tension 28,01 mN/m (25 °C) (ECHA)

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition.

If heated

Risk of ignition. Vapours may form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Harmful in contact with skin. Harmful if inhaled.

GHS of the United Nations, annex 4. May be harmful if swallowed.

Acute toxicity					
Exposure route	Endpoint	Value	Species	Method	Source
inhalation: vapour	LC50	21,7 mg/l/4h	rat		GESTIS
oral	LD50	3.523 mg/kg	rat		ECHA
dermal	LD50	12.126 mg/kg	rabbit		ECHA

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

May cause damage to organs (respiratory tract) through prolonged or repeated exposure.

Hazard category	Target organ	Exposure route
2	respiratory tract	if exposed

Aspiration hazard

May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

aspiration hazard

• If in eyes

Causes serious eye irritation

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

- **If inhaled**

Irritation to respiratory tract, cough, Dyspnoea

- **If on skin**

causes skin irritation

- **Other information**

none

11.2 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of $\geq 0,1\%$.

11.3 Information on other hazards

There is no additional information.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)				
Endpoint	Value	Species	Source	Exposure time
LC50	2,6 mg/l	fish	ECHA	96 h
LL50	5,549 mg/l	fish	ECHA	72 h
ErC50	4,7 mg/l	algae	ECHA	72 h
EL50	5,744 mg/l	algae	ECHA	72 h

Aquatic toxicity (chronic)				
Endpoint	Value	Species	Source	Exposure time
EL50	2,9 mg/l	aquatic invertebrates	ECHA	21 d
ErC50	4,36 mg/l	algae	ECHA	73 h
EC50	2,2 mg/l	algae	ECHA	73 h

12.2 Persistence and degradability

Theoretical Oxygen Demand: 3,165 mg/mg
Theoretical Carbon Dioxide: 3,316 mg/mg

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
carbon dioxide generation	50 %	23 d
oxygen depletion	90 %	28 d

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

12.3 Bioaccumulative potential

Does not significantly accumulate in organisms.

n-octanol/water (log KOW)	3,15 (pH value: 7, 20 °C) (ECHA)
BCF	>5,5 - <12,2 (ECHA)

12.4 Mobility in soil

Henry's law constant	623 Pa m ³ /mol at 25 °C (ECHA)
The Organic Carbon normalised adsorption coefficient	2,73 (ECHA)

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Handle contaminated packages in the same way as the substance itself. Completely emptied packages can be recycled.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Properties of waste which render it hazardous

- HP 3** flammable
- HP 4** irritant - skin irritation and eye damage
- HP 5** specific target organ toxicity (STOT)/aspiration toxicity
- HP 6** acute toxicity

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions. Non-contaminated packages may be recycled.

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

SECTION 14: Transport information

14.1 UN number or ID number

ADRRID	UN 1307
IMDG-Code	UN 1307
ICAO-TI	UN 1307

14.2 UN proper shipping name

ADRRID	XYLENES
IMDG-Code	XYLENES
ICAO-TI	Xylenes

14.3 Transport hazard class(es)

ADRRID	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

ADRRID	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Provisions for dangerous goods (ADR) should be complied within the premises.

14.7 Maritime transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR) Additional information

Proper shipping name	XYLENES
Particulars in the transport document	UN1307, XYLENES, 3, III, (D/E)
Classification code	F1
Danger label(s)	3



Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
Transport category (TC)	3
Tunnel restriction code (TRC)	D/E

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Hazard identification No 30

Emergency Action Code 3Y

Regulations concerning the International Carriage of Dangerous Goods by Rail (RID) Additional information

Classification code F1

Danger label(s) 3



Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

Transport category (TC) 3

Hazard identification No 30

International Maritime Dangerous Goods Code (IMDG) - Additional information

Proper shipping name XYLENES

Particulars in the shipper's declaration UN1307, XYLENES, 3, III, 27°C c.c.

Marine pollutant -

Danger label(s) 3



Special provisions (SP) 223

Excepted quantities (EQ) E1

Limited quantities (LQ) 5 L

EmS F-E, S-D

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Xylenes

Particulars in the shipper's declaration UN1307, Xylenes, 3, III

Danger label(s) 3



Special provisions (SP) A3

Excepted quantities (EQ) E1

Limited quantities (LQ) 10 L

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant provisions of the European Union (EU)

Seveso Directive

2012/18/EU (Seveso III)			
No	Dangerous substance/hazard categories	Qualifying quantity (tonnes) for the application of lower and upper-tier requirements	Notes
P5c	flammable liquids (cat. 2, 3)	5.000 50.000	51)

Notation

51) Flammable liquids, categories 2 or 3 not covered by P5a and P5b

Deco-Paint Directive

VOC content	100 %
VOC content	880 g/l

Industrial Emissions Directive (IED)

VOC content	100 %
VOC content	880 g/l

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed

Water Framework Directive (WFD)

List of pollutants (WFD)				
Name of substance	Name acc. to inventory	CAS No	Listed in	Remarks
o-Xylene	Substances and preparations, or the breakdown products of such, which have been proved to possess carcinogenic or mutagenic properties or properties which may affect steroidogenic, thyroid, reproduction or other endocrine-related functions in or via the aquatic environment		a)	

Legend

a) Indicative list of the main pollutants

Regulation on the marketing and use of explosives precursors

not listed

Regulation on drug precursors

not listed

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Regulation on substances that deplete the ozone layer (ODS)

not listed

Regulation concerning the export and import of hazardous chemicals (PIC)

not listed

Regulation on persistent organic pollutants (POP)

not listed

National regulations(GB)

List of substances subject to authorisation (GB REACH, Annex 14) / SVHC - candidate list

not listed

Restrictions according to GB REACH, Annex 17

Dangerous substances with restrictions (GB REACH, Annex 17)			
Name of substance	Name acc. to inventory	CAS No	No
o-Xylene	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3
o-Xylene	flammable / pyrophoric		40

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
JP	ISHA-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)
VN	NCI	substance is listed

Legend

AIIC Australian Inventory of Industrial Chemicals
CICR Chemical Inventory and Control Regulation

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Legend

CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (ED) at a concentration of ≥ 0,1%.	yes
15.1	VOC content: 100 % 880 g/l	VOC content: 100 %	yes
15.1		VOC content: 880 g/l	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
2000/39/EC	Commission Directive establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC
ADR	Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
ED	Endocrine disruptor
EH40/2005	EH40/2005 Workplace exposure limits (http://www.nationalarchives.gov.uk/doc/open-government-licence/)

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Abbr.	Descriptions of used abbreviations
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
GB CLP	The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended)
GB REACH	The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended)
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
index No	The Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
IOELV	Indicative occupational exposure limit value
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
LEL	Lower explosion limit (LEL)
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
STEL	Short-term exposure limit
TWA	Time-weighted average
UEL	Upper explosion limit (UEL)
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
WEL	Workplace exposure limit

Safety data sheet Safety data sheet

acc. to Regulation (EC) No. 1907/2006 (REACH)



o-Xylene ≥98 %, for synthesis

article number: **8749**

Key literature references and sources for data

Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). Regulations concerning the International Carriage of Dangerous Goods by Rail (RID). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs (respiratory tract) through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.