acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284 date of compilation: 2020-05-08 Version: GHS 2.0 en Revision: 2022-10-07

Replaces version of: 2020-05-08

Version: (GHS 1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

Product identifier 1.1

Identification of the substance **Roti® Elution Tubes MINI**

Article number 9284

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Laboratory and analytical use

Laboratory chemical

Uses advised against: Do not use for products which come into contact

with foodstuffs. Do not use for private purposes

(household).

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany

Telephone:+49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 **e-mail:** sicherheit@carlroth.de Website: www.carlroth.de

Competent person responsible for the safety data :Department Health, Safety and Environment

sheet:

e-mail (competent person): sicherheit@carlroth.de

1.4 **Emergency telephone number**

Name	Street	Postal code/city	Telephone	Website
NSW Poisons Information Centre Childrens Hospital	Hawkesbury Road	2145 West- mead, NSW	131126	

SECTION 2: Hazards identification

Classification of the substance or mixture 2.1

Classification acc. to GHS

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
2.6	Flammable liquid	3	Flam. Liq. 3	H226
3.3	3.3 Serious eye damage/eye irritation		Eye Irrit. 2A	H319

For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

Australia (en) Page 1 / 16



acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284

2.2 Label elements

Labelling

Signal word Warning

Pictograms

GHS02, GHS07



Hazard statements

H226 Flammable liquid and vapour H319 Causes serious eye irritation

Precautionary statements

Precautionary statements - prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Precautionary statements - response

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower

P337+P313 If eye irritation persists: Get medical advice/attention

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction

Precautionary statements - storage

P403+P235 Store in a well-ventilated place. Keep cool

Precautionary statements - disposal

P501 Dispose of contents/container to industrial combustion plant

2.3 Other hazards

Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of sub- stance	Identifier	Wt%	Classification acc. to GHS	Pictograms	Notes
Ethanol	CAS No 64-17-5	≥ 25	Flam. Liq. 2 / H225 Eye Irrit. 2A / H319	(1)	IARC: 1
Ethylenediamine tet- raacetic acid disodi- um salt dihydrate	CAS No 6381-92-6	<1	Acute Tox. 4 / H332 STOT RE 2 / H373	(!)	

Australia (en) Page 2 / 16



acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



IARC: 1: IARC group 1: carcinogenic to humans (International Agency for Research on Cancer)

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart. In case of eye irritation consult an ophthalmologist.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Vomiting, Irritation

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings water spray, alcohol resistant foam, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours may form explosive mixtures with air.

Australia (en) Page 3 / 16



acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



Hazardous combustion products

In case of fire may be liberated: Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO₂), May produce toxic fumes of carbon monoxide if burning.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

Australia (en) Page 4 / 16

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



7.2 Conditions for safe storage, including any incompatibilities

Keep in a cool place.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 2 - 8 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 **Control parameters**

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Cou ntr y	Name of agent	CAS No	Identi- fier	TW A [pp m]	TWA [mg/ m³]	STE L [pp m]	STEL [mg/ m³]	Ceil ing- C [pp m]	Ceil- ing-C [mg/ m³]	Nota- tion	Source
AU	ethyl alcohol (ethan- ol)	64-17-5	WES	1,00 0	1,880						WES

Notation

Ceiling-C STEL

Ceiling value is a limit value above which exposure should not occur Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-

minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8

hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture Name of sub-**CAS No Used** in **Exposure time** End-**Threshol Protection** goal, route of stance point d level exposure **Ethanol** 64-17-5 DNEL 1,900 mg/ human, inhalatworker (industry) acute - systemic m^3 effects Ethanol 64-17-5 **DNEL** chronic - systemic 343 mg/kg human, dermal worker (industry) effects Ethanol 64-17-5 DNEL 950 mg/m³ human, inhalatworker (industry) chronic - systemic ory effects Ethylenediamine 6381-92-6 **DNEL** 1.5 mg/m³ human, inhalatchronic - local efworker (industry) tetraacetic acid disory fects odium salt dihydrate Ethylenediamine 6381-92-6 **DNEL** 3 mg/m³ human, inhalatacute - local efworker (industry) tetraacetic acid disfects ory odium salt dihydrate

Page 5 / 16 Australia (en)

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



Relevant PNECs	Relevant PNECs of components of the mixture							
Name of sub- stance	CAS No	End- point	Threshol d level	Organism	Environmental compartment	Exposure time		
Ethanol	64-17-5	PNEC	0.79 ^{mg} / _{cm³}	unknown	marine water	intermittent re- lease		
Ethanol	64-17-5	PNEC	2.75 ^{mg} / _{cm³}	unknown	air	intermittent re- lease		
Ethanol	64-17-5	PNEC	3.6 ^{mg} / _{cm³}	unknown	freshwater sedi- ment	intermittent re- lease		
Ethanol	64-17-5	PNEC	580 ^{mg} / _{cm³}	unknown	sewage treatment plant (STP)	intermittent re- lease		
Ethanol	64-17-5	PNEC	0.63 ^{mg} / _{cm³}	unknown	soil	intermittent re- lease		
Ethanol	64-17-5	PNEC	0.96 ^{mg} / _{cm³}	unknown	freshwater	intermittent re- lease		
Ethylenediamine tetraacetic acid dis- odium salt di- hydrate	6381-92-6	PNEC	2.2 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)		
Ethylenediamine tetraacetic acid dis- odium salt di- hydrate	6381-92-6	PNEC	0.22 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)		
Ethylenediamine tetraacetic acid dis- odium salt di- hydrate	6381-92-6	PNEC	43 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)		

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection





Use safety goggle with side protection.

Skin protection





hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

Australia (en) Page 6 / 16

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284

type of material

Butyl caoutchouc (butyl rubber)

material thickness

0,5 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection





Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state liquid

Colour colourless

Odour like: - alcohol

Melting point/freezing point not determined

Boiling point or initial boiling point and boiling

range

78 °C at 1,013 hPa

Flammability flammable liquid in accordance with GHS criteria

Lower and upper explosion limit not determined Flash point not determined

Auto-ignition temperature 455 °C

Decomposition temperature not relevant pH (value) 7 (20 °C)

Kinematic viscosity not determined

Solubility(ies)

Water solubility miscible in any proportion

Partition coefficient

Partition coefficient n-octanol/water (log value): this information is not available

Australia (en) Page 7 / 16



acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



Vapour pressure 59 hPa at 20 °C

Density and/or relative density

Density ~1 g/_{cm³}

Relative vapour density information on this property is not available

Particle characteristics not relevant (liquid)

Other safety parameters

Oxidising properties none

9.2 Other information

Information with regard to physical hazard

classes:

There is no additional information.

Other safety characteristics:

Miscibility completely miscible with water

SECTION 10: Stability and reactivity

10.1 Reactivity

The mixture contains reactive substance(s). Risk of ignition.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

Australia (en) Page 8 / 16

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Ethylenediamine tetraacetic acid disodium salt dihydrate	6381-92-6	inhalation: dust/mist	>1 ^{mg} / _l /4h

Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	Endpoint	Value	Species
Ethanol	64-17-5	inhalation: va- pour	LC50	95.6 ^{mg} / _l /4h	rat
Ethanol	64-17-5	oral	LD50	7,060 ^{mg} / _{kg}	rat
Ethylenediamine tetraacetic acid dis- odium salt dihydrate	6381-92-6	oral	LD50	2,800 ^{mg} / _{kg}	rat

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Australia (en) Page 9 / 16

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



Symptoms related to the physical, chemical and toxicological characteristics

If swallowed

Data are not available.

• If in eyes

Causes serious eye irritation

• If inhaled

Data are not available.

• If on skin

Data are not available.

Other information

none

11.2 Endocrine disrupting properties

None of the ingredients are listed.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute) of components of the mixture								
Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time			
Ethanol	64-17-5	LC50	8,140 ^{mg} / _l	orfe (Leuciscus idus)	96 h			
Ethanol	64-17-5	EC50	9,000 – 14,000 ^{mg} / _l	daphnia magna	48 h			
Ethylenediamine tet- raacetic acid disodi- um salt dihydrate	6381-92-6	LC50	41 ^{mg} / _l	bluegill (Lepomis mac- rochirus)	96 h			
Ethylenediamine tet- raacetic acid disodi-	6381-92-6	EC50	610 ^{mg} / _l	daphnia magna	24 h			

Aquatic toxicity (chronic) of components of the mixture

Name of sub- stance	CAS No	Endpoint	Value	Species	Exposure time
Ethylenediamine tet- raacetic acid disodi- um salt dihydrate	6381-92-6	EC50	56 ^{mg} / _l	Pseudomonas putida	8 h

Biodegradation

Data are not available.

um salt dihydrate

Australia (en) Page 10 / 16

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



12.2 Process of degradability

Degradability of components of the mixture

Name of substance	CAS No	Process	Degrada- tion rate	Time	Method	Source
Ethanol	64-17-5	biotic/abiotic	94 %	d		

12.3 Bioaccumulative potential

Data are not available.

Bioaccumulative potential of components of the mixture

Name of substance	CAS No	BCF	Log KOW	BOD5/COD
Ethanol	64-17-5		-0.31	
Ethylenediamine tetraacetic acid disodium salt dihydrate	6381-92-6	1.8		

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

Australia (en) Page 11 / 16

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



SECTION 14: Transport information

14.1 UN number

UN RTDG UN 1170

IMDG-Code UN 1170 ICAO-TI UN 1170

14.2 UN proper shipping name

UN RTDGETHANOL SOLUTIONIMDG-CodeETHANOL SOLUTION

14.3 Transport hazard class(es)

UN RTDG 3
IMDG-Code 3
ICAO-TI 3

14.4 Packing group

ICAO-TI

UN RTDG III
IMDG-Code III
ICAO-TI III

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

Ethanol solution

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

14.8 Information for each of the UN Model Regulations

Transport informationNational regulationsAdditional information(UN RTDG)

UN number 1170
Class 3
Packing group III
Danger label(s) 3



Special provisions (SP)144, 233
UN RTDG

Excepted quantities (EQ) E1

UN RTDG

Limited quantities (LQ) 5 L

5 L UN RTDG

Australia (en) Page 12 / 16

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



Proper shipping name ETHANOL SOLUTION

Particulars in the shipper's declaration UN1170, ETHANOL SOLUTION, 3, III, >23°C c.c.

Marine pollutant Danger label(s) 3



Special provisions (SP) 144, 223

Excepted quantities (EQ) E1
Limited quantities (LQ) 5 L
EmS F-E, S-D

Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Proper shipping name Ethanol solution

Particulars in the shipper's declaration UN1170, Ethanol solution, 3, III

Danger label(s) 3



Special provisions (SP) A3, A58, A180

Excepted quantities (EQ) E1
Limited quantities (LQ) 10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

All ingredients are listed or exempt from listing.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed

Australia (en) Page 13 / 16



acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



Country	Inventory	Status
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) CICR CSCL-ENCS DSL ECSI IECSC

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances
Korea Existing Chemicals Inventory
New Zooland Experience Chemicals INSQ

NZIOC New Zealand Inventory of Chemicals
PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.1		Classification acc. to GHS: change in the listing (table)	yes
2.1		The most important adverse physicochemical, human health and environmental effects: The product is combustible and can be ignited by potential ignition sources.	yes
2.2		Precautionary statements - response: change in the listing (table)	yes
2.2	Labelling of packages where the contents do not exceed 125 ml: Signal word: Warning		yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes

Australia (en) Page 14 / 16

Safety data sheet Safety data sheet acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.2		Labelling of packages where the contents do not exceed 125 ml: change in the listing (table)	yes
2.3	Other hazards: There is no additional information.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: This mixture does not contain any substances that are assessed to be a PBT or a vPvB.	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substance
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causin 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United N tions
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code

Page 15 / 16 Australia (en)

acc. to Safe Work Australia - Code of Practice

Roti® Elution Tubes MINI

article number: 9284



Abbr.	Descriptions of used abbreviations
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LD50	Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval
log KOW	n-Octanol/water
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
vPvB	Very Persistent and very Bioaccumulative
WES	Safe Work Australia: Workplace exposure standards for airborne contaminants

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties. The classification is based on tested mixture. Health hazards. Environmental hazards. The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

Australia (en) Page 16 / 16