

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzine 60-70 , extra pure

article number: **9735**
Version: **GHS 1.1 en**
Replaces version of: 2021-05-18
Version: (GHS 1)

date of compilation: 2021-05-18
Revision: 2021-10-25

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

| | |
|---------------------------------|--|
| Identification of the substance | Petroleum benzine 60-70 , extra pure |
| Article number | 9735 |
| CAS number | 64742-49-0 |
| Alternative name(s) | Hydrocarbons, C ₆ , n-alkanes, iso-alkanes, cyclics, 5-60% n-hexane |

1.2 Relevant identified uses of the substance or mixture and uses advised against

| | |
|---------------------------|---|
| Relevant identified uses: | Laboratory chemical Laboratory and analytical use |
| Uses advised against: | Do not use for products which come into contact with foodstuffs. Do not use for private purposes (household). |

1.3 Details of the supplier of the safety data sheet

Carl Roth GmbH + Co KG
Schoemperlenstr. 3-5
D-76185 Karlsruhe
Germany

Telephone:+49 (0) 721 - 56 06 0
Telefax: +49 (0) 721 - 56 06 149
e-mail: sicherheit@carlroth.de
Website: www.carlroth.de

Competent person responsible for the safety data sheet: :Department Health, Safety and Environment

e-mail (competent person): **sicherheit@carlroth.de**

1.4 Emergency telephone number

| Name | Street | Postal code/city | Telephone | Website |
|--|-----------------|--------------------|-----------|---------|
| NSW Poisons Information Centre Childrens Hospital | Hawkesbury Road | 2145 Westmead, NSW | 131126 | |

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

| Section | Hazard class | Cat-egory | Hazard class and category | Hazard statement |
|---------|---------------------------|-----------|---------------------------|------------------|
| 2.6 | Flammable liquid | 2 | Flam. Liq. 2 | H225 |
| 3.2 | Skin corrosion/irritation | 2 | Skin Irrit. 2 | H315 |
| 3.7 | Reproductive toxicity | 2 | Repr. 2 | H361fd |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

| Section | Hazard class | Cat-egory | Hazard class and category | Hazard statement |
|---------|---|-----------|---------------------------|------------------|
| 3.8D | Specific target organ toxicity - single exposure (narcotic effects, drowsiness) | 3 | STOT SE 3 | H336 |
| 3.9 | Specific target organ toxicity - repeated exposure | 2 | STOT RE 2 | H373 |
| 3.10 | Aspiration hazard | 1 | Asp. Tox. 1 | H304 |

The classification as a carcinogen or mutagen is not required. The substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7). For full text of abbreviations: see SECTION 16

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling

Signal word

Danger

Pictograms

GHS02, GHS07,
GHS08



Hazard statements

| | |
|--------|--|
| H225 | Highly flammable liquid and vapour |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H336 | May cause drowsiness or dizziness |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child (if inhaled) |
| H373 | May cause damage to organs (nervous system) through prolonged or repeated exposure |

Precautionary statements

Precautionary statements - prevention

| | |
|------|---|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking |
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray |

Precautionary statements - response

| | |
|-----------|---|
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water |
| P331 | Do NOT induce vomiting |
| P370+P378 | In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction |

Precautionary statements - storage

| | |
|-----------|---|
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed |
| P403+P235 | Store in a well-ventilated place. Keep cool |

For professional users only

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical identity of the main constituent

"UVCB substance" (substance of unknown or variable composition).

| | |
|-------------------|--------------------------------|
| Name of substance | Petroleum benzene 60-70 |
| Molecular formula | C ₆ H ₁₄ |
| Molar mass | 86.18 g/mol |
| CAS No | 64742-49-0 |

Impurities/additives/constituents:

| Name of substance | Identifier | Wt% |
|-------------------|-------------------|------|
| Benzene | CAS No 71-43-2 | <0.1 |

For full text of abbreviations: see SECTION 16

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In case of skin irritation, consult a physician.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Observe aspiration hazard if vomiting occurs.

4.2 Most important symptoms and effects, both acute and delayed

Irritation, Cough, Vertigo, Dyspnoea, Aspiration hazard, Loss of righting reflex, and ataxia, Dizziness, Drowsiness, Narcosis

4.3 Indication of any immediate medical attention and special treatment needed

none

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

co-ordinate firefighting measures to the fire surroundings
water spray, dry extinguishing powder, BC-powder, carbon dioxide (CO₂)

Unsuitable extinguishing media

water jet

5.2 Special hazards arising from the substance or mixture

Combustible. In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Use personal protective equipment as required. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Danger of explosion.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains.

Advice on how to clean up a spill

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation. Avoid exposure.

Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge. Due to danger of explosion, prevent leakage

of vapours into cellars, flues and ditches.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice:

Ground/bond container and receiving equipment.

Ventilation requirements

Use local and general ventilation.

Specific designs for storage rooms or vessels

Recommended storage temperature: 15 - 25 °C

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

Occupational exposure limit values (Workplace Exposure Limits)

| Cou ntr y | Name of agent | CAS No | Identifi er | TW A [pp m] | TWA [mg/ m ³] | STE L [pp m] | STEL [mg/ m ³] | Ceil ing- C [pp m] | Ceil ing- C [mg/ m ³] | Nota tion | Source |
|-----------|---------------|----------|-------------|-------------|---------------------------|--------------|----------------------------|--------------------|-----------------------------------|-----------|--------|
| AU | n-hexane | 110-54-3 | WES | 20 | 72 | | | | | | WES |

Notation

Ceiling-C Ceiling value is a limit value above which exposure should not occur

STEL Short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA Time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Human health values

| Relevant DNELs and other threshold levels | | | | |
|---|----------------------|------------------------------------|-------------------|----------------------------|
| Endpoint | Threshold level | Protection goal, route of exposure | Used in | Exposure time |
| DNEL | 93 mg/m ³ | human, inhalatory | worker (industry) | chronic - systemic effects |
| DNEL | 13 mg/kg bw/day | human, dermal | worker (industry) | chronic - systemic effects |

| Relevant PNECs of components of the mixture | | | | | | |
|---|---------|-----------|------------------|------------------------|------------------------------|------------------------------|
| Name of sub-stance | CAS No | End-point | Threshol d level | Organism | Environmental compartment | Exposure time |
| Benzene | 71-43-2 | PNEC | 1.9 mg/l | aquatic organ-isms | freshwater | short-term (single instance) |
| Benzene | 71-43-2 | PNEC | 1.9 mg/l | aquatic organ-isms | marine water | short-term (single instance) |
| Benzene | 71-43-2 | PNEC | 39 mg/l | aquatic organ-isms | sewage treatment plant (STP) | short-term (single instance) |
| Benzene | 71-43-2 | PNEC | 33 mg/kg | aquatic organ-isms | freshwater sedi-ment | short-term (single instance) |
| Benzene | 71-43-2 | PNEC | 33 mg/kg | aquatic organ-isms | marine sediment | short-term (single instance) |
| Benzene | 71-43-2 | PNEC | 4.8 mg/kg | terrestrial organ-isms | soil | short-term (single instance) |

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection



Use safety goggle with side protection.

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

Skin protection



• hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. The times are approximate values from measurements at 22 ° C and permanent contact. Increased temperatures due to heated substances, body heat etc. and a reduction of the effective layer thickness by stretching can lead to a considerable reduction of the breakthrough time. If in doubt, contact manufacturer. At an approx. 1.5 times larger / smaller layer thickness, the respective breakthrough time is doubled / halved. The data apply only to the pure substance. When transferred to substance mixtures, they may only be considered as a guide.

• type of material

NBR: acrylonitrile-butadiene rubber

• material thickness

0,4 mm

• breakthrough times of the glove material


>480 minutes (permeation: level 6)

• other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Flame-retardant protective clothing.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 ° C , colour code: Brown).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|--|
| Physical state | liquid |
| Colour | clear - colourless |
| Odour | mild sweet |
| Melting point/freezing point | <-20 °C |
| Boiling point or initial boiling point and boiling range | 65 – 70 °C at 100 kPa (ECHA) |
| Flammability | flammable liquid in accordance with GHS criteria |
| Lower and upper explosion limit | 1.2 vol% (LEL) - 7.3 vol% (UEL) |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

| | |
|---------------------------|-----------------------------------|
| Flash point | -26 °C at 1 atm |
| Auto-ignition temperature | 300 °C at 1 atm (ECHA) |
| Decomposition temperature | not relevant |
| pH (value) | not determined |
| Kinematic viscosity | 0.474 mm ² /s at 20 °C |

Solubility(ies)

| | |
|------------------|--------------------------|
| Water solubility | 0.01 g/l at 25 °C (ECHA) |
|------------------|--------------------------|

Partition coefficient

| | |
|--|-------------|
| Partition coefficient n-octanol/water (log value): | 4 |
| Soil organic carbon/water (log KOC) | 3.34 (ECHA) |

| | |
|-----------------|-----------------|
| Vapour pressure | 47 kPa at 25 °C |
|-----------------|-----------------|

| | |
|---------|----------------------------------|
| Density | 0.675 g/cm ³ at 15 °C |
|---------|----------------------------------|

| | |
|-------------------------|---------------|
| Relative vapour density | 2.8 (air = 1) |
|-------------------------|---------------|

| | |
|--------------------------|-----------------------|
| Particle characteristics | not relevant (liquid) |
|--------------------------|-----------------------|

Other safety parameters

| | |
|----------------------|------|
| Oxidising properties | none |
|----------------------|------|

9.2 Other information

| | |
|---|-------------------------------------|
| Information with regard to physical hazard classes: | There is no additional information. |
|---|-------------------------------------|

Other safety characteristics:

| | |
|------------------|--------|
| Refractive index | ≥1.377 |
|------------------|--------|

SECTION 10: Stability and reactivity

10.1 Reactivity

It's a reactive substance. Risk of ignition. Vapours may form explosive mixtures with air.

If heated

Risk of ignition.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions

Violent reaction with: strong oxidiser

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials

Rubber articles, different plastics

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

| Acute toxicity of components of the mixture | | | | | |
|---|---------|--------------------|----------|------------------------------|---------|
| Name of substance | CAS No | Exposure route | Endpoint | Value | Species |
| Benzene | 71-43-2 | oral | LD50 | >2,000 mg/kg | rat |
| Benzene | 71-43-2 | inhalation: vapour | LC50 | 43,767 mg/m ³ /4h | rat |

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Suspected of damaging the unborn child (if inhaled). Suspected of damaging fertility (if inhaled).

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs (nervous system) through prolonged or repeated exposure.

| Hazard category | Target organ | Exposure route |
|-----------------|----------------|----------------|
| 2 | nervous system | if exposed |

Aspiration hazard

May be fatal if swallowed and enters airways.

Petroleum benzene 60-70 , extra pure

article number: 9735

Symptoms related to the physical, chemical and toxicological characteristics

• **If swallowed**

aspiration hazard

• **If in eyes**

slightly irritant but not relevant for classification

• **If inhaled**

vertigo, headache, cough, Dyspnoea, fatigue, narcosis

• **If on skin**

has degreasing effect on the skin, causes skin irritation, risk of absorption via the skin

• **Other information**

Other adverse effects: Loss of righting reflex, and ataxia

11.2 Endocrine disrupting properties

Not listed.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

| Aquatic toxicity (acute) of components of the mixture | | | | | |
|---|---------|----------|----------|-----------------------|---------------|
| Name of substance | CAS No | Endpoint | Value | Species | Exposure time |
| Benzene | 71-43-2 | LC50 | 5.3 mg/l | fish | 96 h |
| Benzene | 71-43-2 | EC50 | 10 mg/l | aquatic invertebrates | 48 h |
| Benzene | 71-43-2 | ErC50 | 100 mg/l | algae | 72 h |

Biodegradation

The substance is readily biodegradable.

12.2 Process of degradability

Theoretical Oxygen Demand: 3.527 mg/mg
 Theoretical Carbon Dioxide: 3.064 mg/mg

12.3 Bioaccumulative potential

The substance fulfils the very bioaccumulative criterion.

| | |
|---------------------------|--------------|
| n-octanol/water (log KOW) | 4 |
| BCF | 501.2 (ECHA) |

| Bioaccumulative potential of components of the mixture | | | | |
|--|---------|-----|---------------------------|----------|
| Name of substance | CAS No | BCF | Log KOW | BOD5/COD |
| Benzene | 71-43-2 | | 2.13 (pH value: 7, 25 °C) | |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

12.4 Mobility in soil

| | |
|--|-------------|
| The Organic Carbon normalised adsorption coefficient | 3.34 (ECHA) |
|--|-------------|

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

Relevant provisions relating to waste(Basel Convention)

Properties of waste which render it hazardous

H3 Flammable liquids
H11 Toxic (Delayed or chronic)

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information

14.1 UN number

| | |
|----------------|------------|
| UN RTDG | UN 1208 |
| IMDG-Code | UN 1208 |
| ICAO-TI | UN 1208 |

14.2 UN proper shipping name

| | |
|----------------|---------|
| UN RTDG | HEXANES |
| IMDG-Code | HEXANES |
| ICAO-TI | Hexanes |

14.3 Transport hazard class(es)

| | |
|----------------|---|
| UN RTDG | 3 |
|----------------|---|





Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

| | |
|---|--|
| IMDG-Code | 3 |
| ICAO-TI | 3 |
| 14.4 Packing group | |
| UN RTDG | II |
| IMDG-Code | II |
| ICAO-TI | II |
| 14.5 Environmental hazards | hazardous to the aquatic environment |
| 14.6 Special precautions for user | |
| There is no additional information. | |
| 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code | |
| The cargo is not intended to be carried in bulk. | |
| 14.8 Information for each of the UN Model Regulations | |
| Transport informationNational regulationsAdditional information(UN RTDG) | |
| UN number | 1208 |
| Class | 3 |
| Environmental hazards | Yes Hazardous to the aquatic environment |
| Packing group | II |
| Danger label(s) | 3 Fish and tree |
|  | |
|  | |
| Special provisions (SP) | - UN RTDG |
| Excepted quantities (EQ) | E2 UN RTDG |
| Limited quantities (LQ) | 1 L UN RTDG |
| International Maritime Dangerous Goods Code (IMDG) - Additional information | |
| Proper shipping name | HEXANES |
| Particulars in the shipper's declaration | UN1208, HEXANES, 3, II, -26°C c.c., MARINE POLLUTANT |
| Marine pollutant | yes (P) (hazardous to the aquatic environment) |
| Danger label(s) | 3, "Fish and tree" |
|  | |
|  | |
| Special provisions (SP) | - |
| Excepted quantities (EQ) | E2 |
| Limited quantities (LQ) | 1 L |


Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

| | |
|---|--|
| EmS | F-E, S-D |
| Stowage category | E |
| International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information | |
| Proper shipping name | Hexanes |
| Particulars in the shipper's declaration | UN1208, Hexanes, 3, II |
| Environmental hazards | yes (hazardous to the aquatic environment) |
| Danger label(s) | 3 |
|  | |
| Excepted quantities (EQ) | E2 |
| Limited quantities (LQ) | 1 L |

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National regulations(Australia)

Australian Inventory of Chemical Substances(AICS)

Substance is listed.

Other information

Directive 94/33/EC on the protection of young people at work. Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

National inventories

| Country | Inventory | Status |
|---------|------------|---------------------|
| AU | AICS | substance is listed |
| CA | DSL | substance is listed |
| CN | IECSC | substance is listed |
| EU | ECSI | substance is listed |
| EU | REACH Reg. | substance is listed |
| KR | KECI | substance is listed |
| MX | INSQ | substance is listed |
| NZ | NZIoC | substance is listed |
| PH | PICCS | substance is listed |
| TR | CICR | substance is listed |
| TW | TCSI | substance is listed |
| US | TSCA | substance is listed |

Legend

| | |
|------|--|
| AICS | Australian Inventory of Chemical Substances |
| CICR | Chemical Inventory and Control Regulation |
| DSL | Domestic Substances List (DSL) |
| ECSI | EC Substance Inventory (EINECS, ELINCS, NLP) |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

Legend

| | |
|------------|---|
| IECSC | Inventory of Existing Chemical Substances Produced or Imported in China |
| INSQ | National Inventory of Chemical Substances |
| KECI | Korea Existing Chemicals Inventory |
| NZIoC | New Zealand Inventory of Chemicals |
| PICCS | Philippine Inventory of Chemicals and Chemical Substances (PICCS) |
| REACH Reg. | REACH registered substances |
| TCSI | Taiwan Chemical Substance Inventory |
| TSCA | Toxic Substance Control Act |

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book").

Restructuring: section 9, section 14

Abbreviations and acronyms

| Abbr. | Descriptions of used abbreviations |
|-----------|--|
| BCF | Bioconcentration factor |
| BOD | Biochemical Oxygen Demand |
| CAS | Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances) |
| Ceiling-C | Ceiling value |
| COD | Chemical oxygen demand |
| DGR | Dangerous Goods Regulations (see IATA/DGR) |
| DNEL | Derived No-Effect Level |
| EC50 | Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval |
| EINECS | European Inventory of Existing Commercial Chemical Substances |
| ELINCS | European List of Notified Chemical Substances |
| EmS | Emergency Schedule |
| ErC50 | ≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control |
| GHS | "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations |
| IATA | International Air Transport Association |
| IATA/DGR | Dangerous Goods Regulations (DGR) for the air transport (IATA) |
| ICAO | International Civil Aviation Organization |
| ICAO-TI | Technical instructions for the safe transport of dangerous goods by air |
| IMDG | International Maritime Dangerous Goods Code |
| IMDG-Code | International Maritime Dangerous Goods Code |
| LC50 | Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval |

Safety data sheet Safety data sheet

acc. to Safe Work Australia - Code of Practice



Petroleum benzene 60-70 , extra pure

article number: 9735

| Abbr. | Descriptions of used abbreviations |
|---------|--|
| LD50 | Lethal Dose 50 %: the LD50 corresponds to the dose of a tested substance causing 50 % lethality during a specified time interval |
| LEL | Lower explosion limit (LEL) |
| log KOW | n-Octanol/water |
| MARPOL | International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant") |
| NLP | No-Longer Polymer |
| PBT | Persistent, Bioaccumulative and Toxic |
| PNEC | Predicted No-Effect Concentration |
| ppm | Parts per million |
| STEL | Short-term exposure limit |
| TWA | Time-weighted average |
| UEL | Upper explosion limit (UEL) |
| UN RTDG | UN Recommendations on the Transport of Dangerous Good |
| vPvB | Very Persistent and very Bioaccumulative |
| WES | Safe Work Australia: Workplace exposure standards for airborne contaminants |

Key literature references and sources for data

Safe Work Australia's Code of Practice for Labelling of Workplace Hazardous Chemicals (under WHS Regulations).

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

| Code | Text |
|--------|---|
| H225 | Highly flammable liquid and vapour. |
| H304 | May be fatal if swallowed and enters airways. |
| H315 | Causes skin irritation. |
| H336 | May cause drowsiness or dizziness. |
| H361fd | Suspected of damaging fertility. Suspected of damaging the unborn child (if inhaled). |
| H373 | May cause damage to organs (nervous system) through prolonged or repeated exposure. |

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.